




NOTE:

WHEN RECONNECTING THIS HOIST FOR 230 VOLT THE BRAKE, MOTOR & TRANSFORMER NEED TO BE REWIRED AS ILLUSTRATED ON DRAWING 333211 SHEET 2.

DANGER:

UNLESS HOOK RAISES WHEN "UP" BUTTON IS PRESSED SEVERE HOIST DAMAGE AND A DROPPED LOAD MAY RESULT.

CORRECT IMPROPER HOOK DIRECTION BY INTERCHANGING MOTOR LEADS ORANGE (5) AND RED (8).

DO NOT CHANGE PUSHBUTTON WIRING.

WARNING

THIS EQUIPMENT MUST BE EFFECTIVELY GROUNDED ACCORDING TO APPLICABLE CODES.

AVERTISSEMENT

CET EQUIPEMENT DOIT ETRE MIS A LA TERRE EN ACCORDANCE AVEC LES NORMES EN VIGUEUR.

NO.	CHANGE	DATE	ITL.	WIRING DIAGRAM	115 VOLT
				1 PHASE RECONNECTABLE	
				A.C. SOLENOID BRAKE, STEARNS REVERSING SWITCH	
				BUDGET ELECTRIC HOIST	
				SC. -----	
				DA. 8/29/06	
				DR. RITTER	
				CK.	
				YALE • LIFT-TECH division of Columbus McKinnon Corporation Muskegon, Michigan 49443	
				SHEET 1 OF 4 SHEETS	
				333211	