

# 

# LR Motor Shop Repairs

# **Job Number 102262**

Prepared for 3M-Main Plant (10001)

310 Walter Road Little Rock AR 72216

## **Table of Contents**

AC Inspection as Found - MOTOR SHOP LR

AC Inspection - Rev. 2: Z 12 20181161-0001 R 0001

1.0





### **AC Inspection as Found** 3M-Main Plant (10001)

310 Walter Road Little Rock, AR 72216

FolderID: 102262 FormID: 18842449

### AC Inspection - Rev. 2

Location: MOTOR SHOP LR Serial Number: Z 12 20181161-0001 R 0001

Description: 300HP US MOTORS 720RPM

5811S

Hi-Speed Job Number:	102262
Manufacturer:	US Motors/Nidec
Serial Number:	Z 12 20181161-0001 R 0001
HP/kW:	300 (HP)
RPM:	713 (RPM)
Frame:	5811S
Voltage:	460
Current:	358
Phase:	Three
Hz:	60 (Hz)
Service Factor:	1.15
Enclosure:	TEFC
J-box Included:	Complete
Bearing RTDs:	No
Stator RTDs:	No
Repair Stage:	Final
Heaters:	No
Winding Type :	Random Wound
Bearing Type:	Rolling Element

Priorities Found: 4 - High

4 - Good

### **Overall Condition**

- Report Date
- 2. Nameplate Picture
- Photos of all six sides of the machine.





Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.











































4.	Describe the Overall Condition of the	Equipment as Received		
	Broken drive end shaft, very dirty			
5.	Distance from the end of the shaft to t	he Coupling/Sheave		
Initial	Mechanical/Electrical			
<ul><li>6.</li></ul>	Does Shaft Turn Freely?			(Yes) Yes
7.	Does Shaft Have Visible Damage?			(Yes) Yes
-	Broken shaft			
8.	Assembled Shaft Runout			
9.	Assembled Shaft End Play			
10.	Air Gap Variation <10%			
11.	Lead Condition			(P) Pass
12.	Lead Length			30 Inches
13.	Lead Numbers			112233
14.	Frame Condition			
15.	Fan Condition			(P) Pass
16.	Broken or Missing Components		driv	e end shaft
Initial	Electrical Inspection			
17.	Insulation Resistance/Megger		200	00 Megohms
18.	Winding Resistance			
	1-2	1-3	2-3	
	.0172	.0172	.0171	
19.	Perform Surge Test			(P) Pass

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

28. Drive End Lubrication Type 29. Drive End Bearing Insulation or Grounding Device? 30. Drive End Wavy Washer/Snap-Ring Other Retention Device? 31. Drive End Bearing Condition 32. Opposite Drive End Bearing Brand 33. Opposite Drive End Bearing Number- 34. Opposite Drive End Bearing Qty. 35. Opposite Drive End Bearing Type (Ball) 36. Opposite Drive End Lubrication Type (Grease) Grease 37. Opposite Drive End Bearing Insulation or Grounding Device? 38. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? snap ring 39. Opposite Drive End Bearing Condition	no worn ntn 6226c3 1
22. Stator Thermistors/Ohms  23. Stator Overloads/Ohms  Mechanical Inspection  24. Drive End Bearing Brand  25. Drive End Bearing Number-  26. Drive End Bearing Type  27. Drive End Bearing Type  28. Drive End Lubrication Type  29. Drive End Bearing Insulation or Grounding Device?  30. Drive End Wavy Washer/Snap-Ring Other Retention Device?  31. Drive End Bearing Condition  32. Opposite Drive End Bearing Brand  33. Opposite Drive End Bearing Number-  34. Opposite Drive End Bearing Qty.  35. Opposite Drive End Bearing Type  (Grease) Grease	6226c3  1 ) Ball Bearing se Lubricated  no worn ntn 6226c3 1 ) Ball Bearing
23. Stator Overloads/Ohms  Mechanical Inspection  24. Drive End Bearing Brand  25. Drive End Bearing Number-  26. Drive End Bearing Type  27. Drive End Bearing Type  28. Drive End Lubrication Type  29. Drive End Bearing Insulation or Grounding Device?  30. Drive End Wavy Washer/Snap-Ring Other Retention Device?  31. Drive End Bearing Condition  32. Opposite Drive End Bearing Brand  33. Opposite Drive End Bearing Number-  34. Opposite Drive End Bearing Qty.  35. Opposite Drive End Bearing Type  (Ball)  36. Opposite Drive End Bearing Insulation or Grounding Device?  37. Opposite Drive End Bearing Insulation or Grounding Device?  38. Opposite Drive End Bearing Insulation or Grounding Device?  39. Opposite Drive End Bearing Condition	6226c3 1 ) Ball Bearing se Lubricated no worn ntn 6226c3 1 ) Ball Bearing
Mechanical Inspection  24. Drive End Bearing Brand  25. Drive End Bearing Number-  26. Drive End Bearing Type  27. Drive End Bearing Type  28. Drive End Lubrication Type  29. Drive End Bearing Insulation or Grounding Device?  30. Drive End Bearing Insulation or Grounding Device?  31. Drive End Bearing Condition  32. Opposite Drive End Bearing Brand  33. Opposite Drive End Bearing Number-  34. Opposite Drive End Bearing Qty.  35. Opposite Drive End Bearing Type  (Grease) Grease  (Grease) Grease	6226c3 1 ) Ball Bearing se Lubricated no worn ntn 6226c3 1 ) Ball Bearing
24. Drive End Bearing Brand 25. Drive End Bearing Number- 26. Drive End Bearing Qty. 27. Drive End Bearing Type (Grease) Grease 29. Drive End Bearing Insulation or Grounding Device? 30. Drive End Bearing Insulation or Grounding Device? 31. Drive End Bearing Condition 32. Opposite Drive End Bearing Brand 33. Opposite Drive End Bearing Number- 34. Opposite Drive End Bearing Qty. 35. Opposite Drive End Bearing Type (Ball) 36. Opposite Drive End Lubrication Type (Grease) Grease 37. Opposite Drive End Bearing Insulation or Grounding Device? 38. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? 39. Opposite Drive End Bearing Condition	6226c3 1 ) Ball Bearing se Lubricated no worn ntn 6226c3 1 ) Ball Bearing
25. Drive End Bearing Number- 26. Drive End Bearing Qty.  27. Drive End Bearing Type  (Ball)  28. Drive End Lubrication Type  (Grease) Grease  29. Drive End Bearing Insulation or Grounding Device?  30. Drive End Wavy Washer/Snap-Ring Other Retention Device?  31. Drive End Bearing Condition  32. Opposite Drive End Bearing Brand  33. Opposite Drive End Bearing Number-  34. Opposite Drive End Bearing Qty.  35. Opposite Drive End Bearing Type  (Ball)  36. Opposite Drive End Lubrication Type  (Grease) Grease  37. Opposite Drive End Bearing Insulation or Grounding Device?  38. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device?  snap ring  39. Opposite Drive End Bearing Condition	6226c3 1 ) Ball Bearing se Lubricated no worn ntn 6226c3 1 ) Ball Bearing
26. Drive End Bearing Qty.  27. Drive End Bearing Type  (Ball)  28. Drive End Lubrication Type  (Grease) Grease  29. Drive End Bearing Insulation or Grounding Device?  30. Drive End Wavy Washer/Snap-Ring Other Retention Device?  31. Drive End Bearing Condition  32. Opposite Drive End Bearing Brand  33. Opposite Drive End Bearing Number-  34. Opposite Drive End Bearing Qty.  35. Opposite Drive End Bearing Type  (Ball)  36. Opposite Drive End Lubrication Type  (Grease) Grease  37. Opposite Drive End Bearing Insulation or Grounding Device?  38. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device?  snap ring  39. Opposite Drive End Bearing Condition	1 ) Ball Bearing se Lubricated  no worn ntn 6226c3 1 ) Ball Bearing
27. Drive End Bearing Type (Ball) 28. Drive End Lubrication Type (Grease) Grease 29. Drive End Bearing Insulation or Grounding Device? 30. Drive End Wavy Washer/Snap-Ring Other Retention Device? 31. Drive End Bearing Condition 32. Opposite Drive End Bearing Brand 33. Opposite Drive End Bearing Number- 34. Opposite Drive End Bearing Qty. 35. Opposite Drive End Bearing Type (Ball) 36. Opposite Drive End Lubrication Type (Grease) Grease 37. Opposite Drive End Bearing Insulation or Grounding Device? 38. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? snap ring 39. Opposite Drive End Bearing Condition	no worn ntn 6226c3 1 Ball Bearing
28. Drive End Lubrication Type  29. Drive End Bearing Insulation or Grounding Device?  30. Drive End Wavy Washer/Snap-Ring Other Retention Device?  31. Drive End Bearing Condition  32. Opposite Drive End Bearing Brand  33. Opposite Drive End Bearing Number-  34. Opposite Drive End Bearing Qty.  35. Opposite Drive End Bearing Type  (Ball)  36. Opposite Drive End Lubrication Type  (Grease) Grease  37. Opposite Drive End Bearing Insulation or Grounding Device?  38. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device?  snap ring  39. Opposite Drive End Bearing Condition	no worn ntn 6226c3 1 Ball Bearing
29. Drive End Bearing Insulation or Grounding Device? 30. Drive End Wavy Washer/Snap-Ring Other Retention Device? 31. Drive End Bearing Condition 32. Opposite Drive End Bearing Brand 33. Opposite Drive End Bearing Number- 34. Opposite Drive End Bearing Qty. 35. Opposite Drive End Bearing Type  (Ball) 36. Opposite Drive End Lubrication Type  (Grease) Grease 37. Opposite Drive End Bearing Insulation or Grounding Device? 38. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device?  snap ring 39. Opposite Drive End Bearing Condition	no worn ntn 6226c3 1
30. Drive End Wavy Washer/Snap-Ring Other Retention Device?  31. Drive End Bearing Condition  32. Opposite Drive End Bearing Brand  33. Opposite Drive End Bearing Number-  34. Opposite Drive End Bearing Qty.  35. Opposite Drive End Bearing Type  (Ball)  36. Opposite Drive End Lubrication Type  (Grease) Grease  37. Opposite Drive End Bearing Insulation or Grounding Device?  38. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device?  39. Opposite Drive End Bearing Condition	worn ntn 6226c3 1 ) Ball Bearing
31. Drive End Bearing Condition 32. Opposite Drive End Bearing Brand 33. Opposite Drive End Bearing Number- 34. Opposite Drive End Bearing Qty. 35. Opposite Drive End Bearing Type (Ball) 36. Opposite Drive End Lubrication Type (Grease) Grease 37. Opposite Drive End Bearing Insulation or Grounding Device? 38. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? snap ring 39. Opposite Drive End Bearing Condition	worn ntn 6226c3 1 ) Ball Bearing
32. Opposite Drive End Bearing Brand 33. Opposite Drive End Bearing Number- 34. Opposite Drive End Bearing Qty. 35. Opposite Drive End Bearing Type (Ball) 36. Opposite Drive End Lubrication Type (Grease) Grease 37. Opposite Drive End Bearing Insulation or Grounding Device? 38. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? snap ring 39. Opposite Drive End Bearing Condition	ntn 6226c3 1 ) Ball Bearing
33. Opposite Drive End Bearing Number-  34. Opposite Drive End Bearing Qty.  35. Opposite Drive End Bearing Type (Ball)  36. Opposite Drive End Lubrication Type (Grease) Grease  37. Opposite Drive End Bearing Insulation or Grounding Device?  38. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? snap ring  39. Opposite Drive End Bearing Condition	6226c3 1 ) Ball Bearing
<ul> <li>34. Opposite Drive End Bearing Qty.</li> <li>35. Opposite Drive End Bearing Type (Ball)</li> <li>36. Opposite Drive End Lubrication Type (Grease) Grease</li> <li>37. Opposite Drive End Bearing Insulation or Grounding Device?</li> <li>38. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? snap ring</li> <li>39. Opposite Drive End Bearing Condition</li> </ul>	1 ) Ball Bearing
35. Opposite Drive End Bearing Type  (Ball) 36. Opposite Drive End Lubrication Type  (Grease) Grease 37. Opposite Drive End Bearing Insulation or Grounding Device?  38. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device?  snap ring 39. Opposite Drive End Bearing Condition	) Ball Bearing
<ul> <li>36. Opposite Drive End Lubrication Type</li> <li>37. Opposite Drive End Bearing Insulation or Grounding Device?</li> <li>38. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device?</li> <li>39. Opposite Drive End Bearing Condition</li> </ul>	
<ul> <li>37. Opposite Drive End Bearing Insulation or Grounding Device?</li> <li>38. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device?</li> <li>39. Opposite Drive End Bearing Condition</li> </ul>	
<ul><li>38. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? snap ring</li><li>39. Opposite Drive End Bearing Condition</li></ul>	se Lubricated
39. Opposite Drive End Bearing Condition	Belzona
•	g and spacer
	worn
40. Drive End Seal	va120
41. Opposite Drive End Seal	va120
Rotor Inspection	
42. Rotor Type/Material (Squirrel Alumin Cage Alumin	num) Squirrel num Die Cast
43. Growler Test	(Pass) Pass
44. Number of Rotor Bars	72
45. Rotor Condition nee	ds new shaft
46. List the Parts needed for the Repair Below	
6226c3 both ends	
New shaft	Trevor Hall
47. Signature of Technician that Disassembled Motor	Trevor Hall
Mechanical Fits- Rotor	
48. Shaft Runout	
49. Rotor Runout	
Drive End Bearing Fit Rotor Body Opposite Drive En	nd Bearing
50. Coupling Fit Closest to Bearing Housing	
0 Degrees 90 Degrees 120 Degrees	
51. Coupling Fit Closest to the end of the Shaft	
0 Degrees 60 Degrees 120 Degrees	

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

10   10   10   10   10   10   10   10	=-	D: E ID : 01 ( E)			
5.5. 1198	52.				
53. Drive End Bearing Shaft Fit Condition  Figg shape  60 Degrees 60 Degrees 5.117 5.1165 5.1165 5.1165 5.15. Opposite Drive End Bearing Shaft Fit Condition  Fits Bearing Shaft Air Seal Fits  Drive End Air Seal  Mechanical Fits- Bearing Housings  57. Drive End - Endbell Bearing Fit  0 Degrees 9.05358999999999 9.0535 9.05359999999999 9.0535 9.076359999999999 9.0535 9.076359999999999 9.0535 9.07692051 9.0		-	-	-	
## Egg shape  54. Opposite Drive End Bearing Shaft Fit O Degrees			5.1193	5.1195	
54. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 5.117 5.1165 5.1165 5.117 5.5 Opposite Drive End Bearing Shaft Fit Condition (F) Fail 55. Opposite Drive End Bearing Shaft Fit Condition (F) Fail 56. Shaft Air Seal Fits Drive End Air Seal  Mechanical Fits- Bearing Housings 57. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 9.0536999999999 9.0535 9.0536999999999 9.0535 9.0536999999999 9.0535 9.05369999999999 9.0536 9.0506999999999 9.0536 9.05069999999999 9.0536 9.05069999999999 9.0536 9.05069999999999 9.0536 9.05069999999999 9.0536 9.050699999999999 9.0536 9.050699999999999 9.0536 9.050699999999999 9.0536 9.05369999999999 9.0536 9.053699999999999 9.0536 9.053699999999999 9.0536 9.053699999999999 9.0536 9.053699999999999 9.0536 9.05369999999999 9.0536 9.053699999999999 9.0536 9.053699999999999 9.0536 9.053699999999999 9.0536 9.053699999999999 9.0536 9.053699999999999 9.0536 9.053699999999999 9.0536 9.053699999999999 9.0536 9.053699999999999 9.0536 9.053699999999999 9.0536 9.053699999999999 9.0536 9.0536999999999999 9.0536 9.053699999999999 9.0536 9.053699999999999 9.0536 9.053699999999999 9.0536 9.053699999999999 9.0536 9.053699999999999 9.0536 9.053699999999999 9.0536 9.05369999999999 9.0536 9.053699999999999 9.0536 9.05369999999999 9.0536 9.05369999999999 9.0536 9.05369999999999 9.0536 9.0536999999999 9.0536 9.05369999999999 9.0536 9.05369999999999 9.0536 9.05369999999999 9.0536 9.05369999999999 9.0536 9.053699999999999 9.0536 9.05369999999999 9.0536 9.05369999999999 9.0536 9.0536999999999999 9.0536 9.05369999999999 9.0536 9.053699999999999 9.0536 9.05369999999999 9.0536 9.053699999999999 9.0536 9.053699999999999 9.0536 9.05369999999999 9.0536 9.05369999999999 9.0536 9.053699999999999 9.0536 9.05369999999999 9.0536 9.05369999999999 9.0536 9.05369999999999 9.0536 9.05369999999999 9.0536 9.0536999999999 9.0536 9.0536999999999 9.0536 9.0536999999999 9.0536 9.05369999999999999 9.0536 9.05369999999999 9.0536 9.05369999999999 9.0536 9.0536999999999999 9.0536 9.0536999999999999 9.0536 9.0536999999999	<b>5</b> 3.	· ·			(F) Fail
0 Degrees 60 Degrees 5.117 5.1165 5.1165  5.5. Opposite Drive End Bearing Shaft Fit Condition (F) Fail 5.5. Opposite Drive End Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Fits Degrees 60 Degrees 120 Degrees 9.0536999999999 9.0535 9.05359999999999 9.0535 9.0535999999999 9.0535 9.0535999999999 9.0535 9.05359999999999 9.0535 9.05359999999999 9.0535 9.05359999999999 9.0535 9.05359999999999 9.0535 9.05359999999999 9.0535 9.05359999999999 9.0535 9.05359999999999 9.0535 9.05359999999999 9.0535 9.0535999999999999 9.0535 9.053599999999999 9.0535 9.053599999999999 9.0535 9.05359999999999999999 9.0535 9.0535999999999999 9.0535 9.05359999999999999999999999999999999999					
5.117 5.1165 5.1165  55. Opposite Drive End Bearing Shaft Fit Condition (F) Fail  56. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal  Mechanical Fits-Bearing Housings  57. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 9.05369999999999 9.0536 9.05359999999999999999999999999999999999	54.	Opposite Drive End Bearing Shaft Fit			
\$55. Opposite Drive End Bearing Shaft Fit Condition		-	-	•	
Shaft Air Seal Fits   Opposite Drive End Air Seal   Opposite Drive End Air Seal				5.1165	
Mechanical Fits- Bearing Housings  57. Drive End - Endbell Bearing Fit  0 Degrees 60 Degrees 120 Degrees 9.05369999999999 9.0535 9.05359999999999999999999999999999999999		*	Condition		(F) Fail
Mechanical Fits- Bearing Housings  57. Drive End - Endbell Bearing Fit  0 Degrees 60 Degrees 9.053699999999999 9.0535 9.053699999999999  58. Drive End - Endbell Bearing Fit Condition Too tight  59. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 5.0548 5.0547 5.0548  60. Opposite Drive End - Endbell Bearing Fit Condition Too tight 61. Bearing Cap Condition Drive End Bearing Cap Degrees Pass 62. End Bell Air Seal Fits Drive End Air Seal  63. List Machine Work Needed Below New Shaft and both endbells  64. Technician  Frevor Hall  Root Cause of Failure 65. Failure locations Shaft 66. Root cause of failure Too much stress on shaft  Dynamic Balance Report 67. Rotor Weight and Balance Grade	56.	Shaft Air Seal Fits			
57. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 9.053e999999999 9.053e999999999 9.053e999999999 9.053e999999999 9.053e9999999999 9.053e9999999999 9.053e999999999999999999999999999999999999		Drive End Air Seal	Opposite Drive End Air Seal		
57. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 9.053e999999999 9.053e999999999 9.053e999999999 9.053e999999999 9.053e9999999999 9.053e9999999999 9.053e999999999999999999999999999999999999					
0 Degrees 9,0536999999999 9,0535 9,05359999999999999999999999999999999999					
9.05369999999999 9.0535 9.05359999999999999999999999999999999999	57.				
S8. Drive End - Endbell Bearing Fit Condition   (F) Fail   Too tight   Too			<u> </u>	=	
Too tight  59. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 5.0548 5.0547 5.0548  60. Opposite Drive End - Endbell Bearing Fit Condition Too tight 61. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap pass pass 62. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal  63. List Machine Work Needed Below New shaft and both endbells  64. Technician Trevor Hall  Root Cause of Failure 65. Failure locations Shaft 66. Root cause of failure Too much stress on shaft  Dynamic Balance Report 67. Rotor Weight and Balance Grade				9.05359999999999	
59. Opposite Drive End - Endbell Bearing Fit  0 Degrees 60 Degrees 5.0548  5.0547  5.0548  60. Opposite Drive End - Endbell Bearing Fit Condition Too tight  61. Bearing Cap Condition Drive End Bearing Cap pass pass  62. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal  63. List Machine Work Needed Below New shaft and both endbells  64. Technician  Frevor Hall  Root Cause of Failure  65. Failure locations Shaft  66. Root cause of failure Too much stress on shaft  Dynamic Balance Report  67. Rotor Weight and Balance Grade		· ·	ion		(F) Fail
0 Degrees 60 Degrees 5.0548 5.0547 5.0548  60. Opposite Drive End - Endbell Bearing Fit Condition (F) Fail Too tight 61. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap pass pass 62. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal  63. List Machine Work Needed Below New shaft and both endbells 64. Technician Trevor Hall  Root Cause of Failure 65. Failure locations Shaft 66. Root cause of failure Too much stress on shaft  Dynamic Balance Report 67. Rotor Weight and Balance Grade					
5.0548  5.0548  5.0548  5.0547  5.0548  60. Opposite Drive End - Endbell Bearing Fit Condition  Too tight  61. Bearing Cap Condition  Drive End Bearing Cap  pass  62. End Bell Air Seal Fits  Drive End Air Seal  Opposite Drive End Air Seal  63. List Machine Work Needed Below  New shaft and both endbells  64. Technician  Trevor Hall  Root Cause of Failure  65. Failure locations  Shaft  66. Root cause of failure  Too much stress on shaft  Dynamic Balance Report  67. Rotor Weight and Balance Grade	59.				
60. Opposite Drive End - Endbell Bearing Fit Condition  Too tight  61. Bearing Cap Condition  Drive End Bearing Cap Opposite Drive End Bearing Cap pass pass  62. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal  63. List Machine Work Needed Below New shaft and both endbells  64. Technician Trevor Hall  Root Cause of Failure  65. Failure locations Shaft  66. Root cause of failure Too much stress on shaft  Dynamic Balance Report  67. Rotor Weight and Balance Grade		•	-	120 Degrees	
Too tight  61. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap pass pass  62. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal  63. List Machine Work Needed Below New shaft and both endbells  64. Technician Trevor Hall  Root Cause of Failure  65. Failure locations Shaft  66. Root cause of failure Too much stress on shaft  Dynamic Balance Report  67. Rotor Weight and Balance Grade				5.0548	
Drive End Bearing Cap pass pass  62. End Bell Air Seal Fits Drive End Air Seal  Opposite Drive End Air Seal  Opposite Drive End Air Seal  Fix Machine Work Needed Below New shaft and both endbells  Fix Trevor Hall  Root Cause of Failure  65. Failure locations Shaft  66. Root cause of failure Too much stress on shaft  Dynamic Balance Report  67. Rotor Weight and Balance Grade		* *	Fit Condition		(F) Fail
pass 62. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal  63. List Machine Work Needed Below New shaft and both endbells  64. Technician Trevor Hall  Root Cause of Failure  65. Failure locations Shaft  66. Root cause of failure Too much stress on shaft  Dynamic Balance Report  67. Rotor Weight and Balance Grade	61.	Bearing Cap Condition			
62. End Bell Air Seal Opposite Drive End Air Seal  63. List Machine Work Needed Below New shaft and both endbells  64. Technician Trevor Hall  Root Cause of Failure  65. Failure locations Shaft  66. Root cause of failure Too much stress on shaft  Dynamic Balance Report  67. Rotor Weight and Balance Grade		Drive End Bearing Cap	Opposite Drive End Bearing Cap		
Brive End Air Seal Opposite Drive End Air Seal  63. List Machine Work Needed Below New shaft and both endbells  64. Technician Trevor Hall  Root Cause of Failure  65. Failure locations Shaft  66. Root cause of failure Too much stress on shaft  Dynamic Balance Report  67. Rotor Weight and Balance Grade		pass	pass		
63. List Machine Work Needed Below New shaft and both endbells  64. Technician  Trevor Hall  Root Cause of Failure  65. Failure locations Shaft  66. Root cause of failure Too much stress on shaft  Dynamic Balance Report  67. Rotor Weight and Balance Grade	62.	End Bell Air Seal Fits			
Root Cause of Failure  65. Failure locations Shaft  66. Root cause of failure  Too much stress on shaft  Dynamic Balance Report  67. Rotor Weight and Balance Grade		Drive End Air Seal	Opposite Drive End Air Seal		
64. Technician  Trevor Hall  Root Cause of Failure  65. Failure locations Shaft  66. Root cause of failure Too much stress on shaft  Dynamic Balance Report  67. Rotor Weight and Balance Grade	63.	List Machine Work Needed Below			
Root Cause of Failure  65. Failure locations Shaft  66. Root cause of failure Too much stress on shaft  Dynamic Balance Report  67. Rotor Weight and Balance Grade		New shaft and both endbells			
65. Failure locations Shaft  66. Root cause of failure Too much stress on shaft  Dynamic Balance Report  67. Rotor Weight and Balance Grade	64.	Technician		Tr	evor Hall
65. Failure locations Shaft  66. Root cause of failure Too much stress on shaft  Dynamic Balance Report  67. Rotor Weight and Balance Grade			11		
65. Failure locations Shaft  66. Root cause of failure Too much stress on shaft  Dynamic Balance Report  67. Rotor Weight and Balance Grade					
65. Failure locations Shaft  66. Root cause of failure Too much stress on shaft  Dynamic Balance Report  67. Rotor Weight and Balance Grade			1/		
65. Failure locations Shaft  66. Root cause of failure Too much stress on shaft  Dynamic Balance Report  67. Rotor Weight and Balance Grade					
Shaft  66. Root cause of failure Too much stress on shaft  Dynamic Balance Report  67. Rotor Weight and Balance Grade	Root	Cause of Failure			
66. Root cause of failure  Too much stress on shaft  Dynamic Balance Report  67. Rotor Weight and Balance Grade	65.	Failure locations			
Too much stress on shaft  Dynamic Balance Report  67. Rotor Weight and Balance Grade					
Dynamic Balance Report  67. Rotor Weight and Balance Grade	66.	Root cause of failure			
67. Rotor Weight and Balance Grade		Too much stress on shaft			
67. Rotor Weight and Balance Grade	Dynar	mic Balance Report			
	-				
Lote Tolgin	J		Balance Grade		

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

68.	Initial Balance Readings			
	Drive End	Opposite Drive End		
	DIVO LIIG	opposite zine zine		
69.	Final Balance Readings			
	Drive End	Opposite Drive End		
70.	Technician			
Rewin	ıd			
71.	Core Test Results - Watts loss per Po	ound		
	Pre-Burnout	Post Burnout		
70	One Hat On at Tast			
72.	Core Hot Spot Test	Deat Death		
	Pre-Burnout	Post-Burnout		
73.	Post Rewind Electrical Test- Insulation	n Resistance		
74.	Post Rewind Polarization Index			
75.	Post Rewind Winding Resistance			
	1-2	1-3	2-3	
76.	Post Rewind Surge Test			
77.	Post Rewind Hi-Pot			
	78. Technician			
	anical Fits- Rotor - Post Repair			
	Shaft Runout Post Repair			
80.	Rotor Runout Post Repair			
	Drive End Bearing Fit	Rotor Body	Opposite Drive End Bearing	
Ω1	Coupling Fit Closest to Bearing Housi	ng Poet Repair		
01.	0 Degrees	90 Degrees	120 Degrees	
	o Degrees	30 Degrees	120 Degrees	
82.	Coupling Fit Closest to the end of the	Shaft Post Repair		
	0 Degrees	60 Degrees	120 Degrees	
83.	Drive End Bearing Shaft Fit Post Rep			
	0 Degrees	60 Degrees	120 Degrees	
9.4	Opposite Drive End Bearing Shaft Fit	Doot Bonoir		
04.			120 Dograda	
	0 Degrees	60 Degrees	120 Degrees	
85.	Shaft Air Seal Fits Post Repair			
	Drive End Air Seal	Opposite Drive End Air Seal		
86.	Shaft Repair Sign-off			
Mecha	anical Fits- Bearing Housings - P	ost Repair		
87.	Drive End - Endbell Bearing Fit Post F	Repair		
	0 Degrees	60 Degrees	120 Degrees	

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

88.	Opposite Drive End - Endbell Bearing Fit Post Repair		
	0 Degrees	60 Degrees	120 Degrees
89.	9. Bearing Cap Condition Post Repair		
	Drive End Bearing Cap	Opposite Drive End Bearing Cap	
00	Find Dall Air Coal Fite Doot Danair		
90.	End Bell Air Seal Fits Post Repair	Onn saite Drive Find Air Cool	
	Drive End Air Seal	Opposite Drive End Air Seal	
91.	End Bell Repair Sign-off		
Assen	· · · · · ·		
	QC Check All Parts for Cleanliness Pr	rior to Assembly	
	Photograph All Major Components pri	•	
	Final Insulation Resistance Test	•	
95.	Assembled Shaft Endplay		
96.	Assembled Shaft Runout		
97.	Test Run Voltage		
	Volts	Volts	Volts
98.	Test Run Amperage		
	Amps	Amps	Amps
00	Drive End Vibration Readings Inches	a Dor Sacand	
99.	Drive End Vibration Readings - Inches Horizontal	Vertical	Aviol
	Horizoniai	vertical	Axial
100.	Opposite Drive End Vibration Readings - Inches Per Second		
	Horizontal	Vertical	Axial
101.	. Ambient Temperature - Fahrenheit		
102.	2. Drive End Bearing Temps - Fahrenheit		
	5 Minutes	10 Minutes	15 Minutes
		<b>-</b> 1	
103.	Opposite Drive End Bearing Temps -		45.00
	5 Minutes	10 Minutes	15 Minutes
104	Document Final Condition with Picture	es after naint	
	Final Pics and QC Review	or and paint	
100.	100 and a0 Hoviow		

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.



### STANDARD TERMS AND CONDITIONS FOR PURCHASE OF GOOD AND/OR SERVICES

- 1. APPLICABILITY. The sale of any and all goods and/or services by Mock, Inc. d/b/a Hi-Speed Industrial Service ("Hi-Speed") shall be specifically conditioned upon and subject to the following terms and conditions which are incorporated by reference into any contracts and purchase orders with Hi-Speed, and which shall form and become a part of any agreement related thereto. Buyer's acceptance of any offer or quotation made by Hi-Speed for sale of any goods or services is expressly made subject to the terms and conditions set forth herein and to be so effective, Buyer need not sign or approve these Terms and Conditions to be bound hereunder provided a copy of same is provided to Buyer through any means. None of the terms and conditions contained herein may be added to, expanded, changed, modified, superseded or otherwise altered except as revised in writing and duly executed by Hi-Speed, and all orders received by Hi-Speed shall be governed only by the terms and conditions contained herein, notwithstanding any terms, conditions or provisions of any purchase order, release order, authorization or any other form issued by the Buyer. Hi-Speed hereby objects to any additional, modified, changed, deleted, altered or other terms and conditions not contained herein and notifies Buyer that any such terms or provisions are expressly rejected by Hi-Speed.
- 2. PRICE. All quoted prices shall remain firm and binding for a period of thirty (30) days from the date of quotation or for the period specifically stated in the quotation. The price for any and all goods and/or services ordered or approved by Buyer after thirty (30) days from the date of any quotation are subject to any increase in price that may occur after the expiration of thirty (30) days from the issuance of the quotation and the date the Buyer releases any shipment.
- 3. SCOPE OF GOODS AND/OR SERVICES. The goods and/or services provided by Hi-Speed pursuant to any quotation shall be limited exclusively to those goods and/or services expressly identified therein. Hi-Speed does not assume any responsibility and/or liability for the failure to provide any other goods and/or services not identified in any quotation. Modifications, additions or deletions to or from the scope referenced in any quotation shall only bee effective if evidenced in writing and signed by Hi-Speed. The sale of any of all goods and/or services affected by such modification, addition or deletion shall be subject to these same Standard Terms and Conditions whether or not referenced therein.
- 4. <u>BILLING AND PAYMENT TERMS.</u> Hi-Speed shall invoice Buyer for all goods and/or services as same are rendered at the address listed on the quotation. Payments for all goods and/or services shall be due thirty (30) days from the date of the current invoice or as otherwise set forth in the quotation. Late payments are subject to a late fee of 5% of the total invoice amount. Recurring late payments may lead to a deposit requirement on future services or sale of goods. Buyer shall be liable to Hi-Speed for any and all fees and expenses incurred by Hi-Speed to collect any invoices or to enforce these Standard Terms and Conditions, including but not limited to, attorney's fees.
- 5. <u>DELIVERY OF GOODS AND/OR SERVICES.</u> Unless otherwise identified in the quotation, all shipments are F.O.B. Hi-Speed's warehouse and the title to and all risk of loss with respect to any goods shipped shall pass to Buyer when such goods are delivered to the carrier at Hi-Speed's warehouse. Hi-Speed will use its best efforts to affect delivery by the date or dates specified in the quotation. However, Hi-Speed shall not be liable for delay in or failure to make shipment, or to perform services, by any identified date for any reason whatsoever, including but not limited to, causes beyond its reasonable control, such as strikes, fires, floods, epidemics, quarantines, restrictions, severe weather, embargos, acts of God, or public enemy, war, riot, delays in transportation or the inability to obtain necessary labor, materials or manufacturing facilities.
- **DELIVERY SITE AND TIME FOR PERFORMANCE.** Hi-Speed and Buver agree that time is of the essence for the purchase order and that Buyer shall fully cooperate with Hi-Speed in order to allow Hi-Speed full access to prosecute its work diligently and in an orderly manner. Buyer shall assist Hi-Speed in every way possible to avoid delaying, disrupting or interfering with the progress of Hi-Speed's work at the project site. In the event Hi-Speed's work is delayed, hindered, suspended, disrupted, re-sequenced or interfered with or rendered less efficient or more costly or adversely affected in any way as a result of acts or omissions of Buyer or other contractors or employees of Buyer or by any other reason beyond Hi-Speed's control and without the fault of Hi-Speed, then, in such event, Buyer shall be liable to Hi-Speed for any damages, additional costs, expenses, labor, materials, man hours, acceleration costs, overtime, additional jobsite overhead, extended home office overhead, and any and all other direct and indirect expenses of whatsoever nature or kind, caused in whole or in part, as a result of any of the above-referenced occurrences. Hi-Speed's project records will be the basis for computing the additional costs and damages of Hi-Speed's labor, materials, expenses and overhead related to such changes. BUYER WARRANTS THAT THE SITE FOR DELIVERY OR INSTALLATION OF ANY GOODS AND/OR FOR THE PERFORMANCE OF ANY SERVICES SHALL BE READY AND ADEQUATE FOR HI-SPEED'S DELIVERY OF GOODS AND/OR PERFORMANCE OF SERVICES AND THAT HI-SPEED SHALL HAVE FULL ACCESS THERETO, FREE OF ALL OBSTRUCTIONS. BUYER SHALL ASSUME ALL EXTRA COSTS ASSOCIATED WITH HI-SPEED'S INABILITY TO INSTALL ANY GOODS OR PERFORM ANY SERVICES AS A RESULT OF BUYER'S FAILURE TO COMPLY WITH THIS PROVISION. HI-SPEED MAY NOT INSPECT THE SITE PRIOR TO DELIVERY AND/OR INSTALLATION OF GOODS AND/OR PERFORMANCE OF SERVICES AND MAKES NO WARRANTY AS TO THE SUFFICIENCY OF THE SITE FOR THE DELIVERY AND/OR INSTALLATION OF GOODS AND/OR THE PERFORMANCE OF SERVICES AT SUCH SITE.
- 7. INSPECTION/ACCEPTANCE. All goods and services ordered pursuant to any quotation shall be subject to inspection by Buyer after delivery or performance to determine conformity with the quotation and/or purchase order and Hi-Speed's advertised or published specifications. Buyer shall have a period of thirty (30) days from shipment of goods at the delivery destination specified in the quotation within which to inspect the goods for conformity with the quotation, order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. Buyer shall have a period of thirty (30) days following completion of any services within which to inspect the services for conformity with the quotation, purchase order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. If the goods delivered or services performed do not so conform, upon delivery of notice to Hi-Speed of any discrepancy, nonconformance or rejection, Hi-Speed shall have sixty (60) days to cure the alleged discrepancy and/or nonconformance. If Hi-Speed fails to cure in this time period, Buyer shall have the right to reject such goods or services. After the cure period, goods that have been delivered and rejected, in whole or in part, shall be returned to Hi-Speed. Buyer shall notify Hi-Speed and arrange for the return of the goods as required. Should such non-conforming services be rejected Hi-Speed shall, at its sole cost, re-perform the non-conforming services. Inspection or failure to inspect on any occasion shall not affect Buyer's rights under the warranty provisions herein.
- 8. WARRANTIES. Hi-Speed warrants that all goods shall conform in all material aspects to the goods identified in the quotation to Buyer and/or purchase order, and Hi-Speed makes to Buyer the manufacturer's express warranty for any goods sold to Buyer, which is offered by the manufacturer at the time of acceptance of any quotation by Buyer. This warranty is conditioned upon the installation, operation, and maintenance of the goods in accordance with the manufacturer's recommendations and/or standard industry practice and the goods at all times being operated or used under normal operating conditions for which they were designed. Hi-Speed, at its sole option, will repair or

replace any defective or non-conforming goods in accordance with the applicable manufacturer's warranty. Warranty for any defective or incorrect parts is limited to the repair or replacement of those parts. Hi-Speed warrants that all services will conform in all material respects to the description of services identified in the quotation and will be performed in a good and workmanlike manner in accordance with industry practices and standards. Should the services be reasonably rejected or not conform with the foregoing warranties, Hi-Speed shall, at its sole cost, re-perform the defective or nonconforming services. Notwithstanding the foregoing, these warranties do not extend to goods or services to the extent that such goods have been subject to misuse, neglect or abuse not caused by Hi-Speed or have been used in violation of the approved written instructions furnished to Buyer. THE FOREGOING REPRESENTS THE SOLE AND EXCLUSIVE WARRANTY GIVEN BY HI-SPEED WITH RESPECT TO ALL GOODS SOLD AND IS IN LIEU OF ALL OTHER WARRANTIES EITHER EXPRESS OR IMPLIED. HI-SPEED EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICLAR USE OR PURPOSE. BUYER WAIVES ANY CLAIM THAT THESE EXCLUSIONS OR LIMITATIONS DEPRIVE IT OF AN ADEQUATE REMEDY AT EQUITY OR LAW OR CAUSE THIS AGREEMENT TO FAIL IN ITS ESSENTIAL PURPOSE. BUYER SHALL BE ENTITLED TO NO OTHER REMEDY OTHER THAN AS SET FORTH HEREIN, REGARDLESS OF THE CLAIM OR CAUSE OF ACTION, WHETHER BASED IN CONTRACT, TORT, NEGLIGENCE, GOODS LIABILITY, STRICT LIABILITY OR OTHERWISE.

- 9. <u>LIMITATION OF DAMAGES.</u> HI-SPEED SHALL HAVE NO LIABILITY TO BUYER WITH RESPECT TO THE SALE OR DELIVERY OF ANY GOODS OR THE REPAIR THEREOF OR WITH RESPECT TO THE SALE OR PERFORMANCE OF ANY SERVICES, FOR LOST PROFITS, SPECIAL, CONSEQUENTIAL, EXEMPLARY, PUNITIVE OR INCIDENTAL DAMAGES OF ANY KIND OR NATURE WHETHER ARISING IN CONTRACT, TORT, GOODS LIABILITY OR OTHERWISE, EVEN IF HI-SPEED WAS ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGES. HI-SPEED SHALL NOT BE LIABLE FOR ANY DAMAGES OR DELAYS CAUSED BY ANY FAILURE TO MAKE ANY DELIVERY OF GOODS BY ANY EXPECTED TIME OR DATE OR THE FAILURE TO PROVIDE OR COMPLETE ANY SERVICES BY ANY EXPECTED DATE OR TIME. IN NO EVENT SHALL HI-SPEED BE LIABLE TO BUYER FOR ANY DAMAGES WHATSOEVER IN EXCESS OF THE TOTAL PRICE PAID FOR ALL GOODS AND/OR SERVICES HEREUNDER OR REFERENCED IN ANY QUOTATION OR THE PURCHASE ORDER.
- 10. <u>SEVERABILITY.</u> The partial or complete invalidity of any provision of these Standard Terms and Conditions shall not affect the enforceability of the remainder of these Standard Terms and Conditions. If any provision is found to be invalid or unenforceable, that portion shall be modified to make it enforceable or shall be stricken and the remainder of these Standard Terms and Conditions shall enforced.
- 11. **GOVERNING LAW AND JURISDICTION.** Any controversy arising out of any quotation, the purchase order, the goods sold or delivered, repair or replacement thereof, or any services provided pursuant to any quotation or any purchase order, or these Standard Terms and Conditions shall be governed by the laws of the state of Tennessee without regard to any choice of law provisions and any cause of action related in any manner thereto shall be brought only in the state or federal courts of Shelby County, Tennessee.
- 12. ABANDONED EQUIPMENT. Hi-Speed requires that Buyer promptly pick up or provide shipment instructions for Buyer equipment or other Buyer property in Hi-Speed's possession. If equipment or other Buyer property is left with Hi-Speed and not picked up within six (6) months after Hi-Speed's final action related to the applicable property (e.g. evaluation, teardown, estimate, completion of services), Hi-Speed will consider such property abandoned and may dispose of it in accordance with applicable law. Buyer agrees to hold Hi-Speed harmless for any damage or claim for such abandoned property and acknowledges that Hi-Speed may discard or recycle it at Hi-Speed's sole and absolute discretion. Specifically, Hi-Speed may sell Buyer's abandoned property at a private or public sale and retain the proceeds to offset Hi-Speed's storage, inspection and servicing costs. For the avoidance of doubt, Hi-Speed reserves its statutory and other lawful liens for unpaid charges related to abandoned property.
- 13. FORCE MAJEURE. Neither party shall be responsible for any delay or failure in performance of any party of the quotation, purchase order or these Standard Terms and Conditions to the extent that such delays or failures are caused by fire, flood, earth quake, explosion, war, embargo, government requirement, civil or military authority, acts of God, or any other circumstances beyond its reasonable control and not involving any fault or negligence on the party affected ("Condition"). If any such Condition occurs, the party delayed or unable to perform shall promptly give written notice to the other party and, if such Condition remains at the end of thirty (30) days, the party affected by the other party's delay and inability to perform may elect to (i) terminate such order or part thereof, or (ii) suspend the order for the duration of the Condition, if the Buyer is the suspending party, buy elsewhere comparable material to be sold under the order and apply to any commitment the purchase price of such purchase, and resume performance of the order once the Condition ceases, with an option in the affected party to extend the period of this order up to the length of the time the Condition endures.
- 14. <u>NONWAIVER.</u> No course of dealing or failure of either party to strictly enforce any term, right, or condition of these Standard Terms and Conditions will be construed as a waiver of such term, right or condition. Any waiver by Hi-Speed will only be in writing and will waive no succeeding breach of a term, right or condition.
- 15. **ASSIGNMENT.** The rights and obligations of the parties shall neither be assigned nor delegated without the prior written consent of the other party. However, any party may assign or delegate its respective rights and obligations, in whole or in part, (i) to any subsidiary, (ii) pursuant to other financing, merger or reorganization or (iii) pursuant to any sale or transfer of substantially all of the assets of the assigning party. These Standard Terms and Conditions shall bind the heirs, successors and assigns of the parties hereto.
- 16. NO INDIVIDUAL LIABILITY. Notwithstanding any other agreement to the contrary, the Buyer agrees that in no event will the Buyer hold and HI-Speed owner, director, officer or employee personally liable for unintentional tortious conduct or conduct that constitutes the breach of any contract between HI-Speed and the Buyer, even if the HI-Speed owner, director, officer or employee is or could be construed to be a party to such contract.