

# LR Motor Shop Repairs

# **Job Number 101121**

Prepared for Dassault Falcon Jet (11751)

3801 East 10th st. Little rock AR 72203

## **Table of Contents**

AC Recondition As Found - MOTOR SHOP LR

AC Recondition - Rev. 2: 1500961003Y15

1.0



FolderID: 101121

FormID: 16276072



### **AC Recondition As Found**

**Dassault Falcon Jet (11751)** 

3801 East 10th st. Little rock, AR 72203

AC Recondition - Rev. 2

MOTOR SHOP LR Location:

**Serial Number:** 1500961003Y15

Description: 6.6KW CEMP 1800RPM 132S PAINT BOOTH BLOWER

Hi-Speed Job Number:	101121
Manufacturer:	Other
Product Number:	AB31 132S3 4
Serial Number:	1500961003Y15
HP/kW:	6.6 (kW)
RPM:	1745 (RPM)
Frame:	132S
Voltage:	480
Current:	12
Phase:	Three
Hz:	60 (Hz)
Enclosure:	TEFC
J-box Included:	Complete
Coupling/Sheave:	Propeller
Bearing RTDs:	No
Stator RTDs:	No
Repair Stage:	Final
Heaters:	No
Winding Type :	Random Wound
Bearing Type:	Rolling Element

Priorities Found: 2 - High

6 - Good

### **Overall Condition**

1. Report Date

Nameplate Picture

























































3	3.	Photos of all six sides of the machine.		
4	4.	Describe the Overall Condition of the Equipment as Received		
		Clean		
5	5.	Distance from the end of the shaft to the Coupling/Sheave		
Initi	ial	Mechanical/Electrical		
• 6	6.	Does Shaft Turn Freely?		(Yes) Yes
7	7.	Does Shaft Have Visible Damage?		(No) No
8	8.	Assembled Shaft Runout		Inches
9	9.	Assembled Shaft End Play		
1	0.	Air Gap Variation <10%		
• 1	1.	Lead Condition		(P) Pass
1	2.	Lead Length		6 Inches
1	3.	Frame Condition		good
• 1	4.	Fan Condition		(P) Pass
1	5.	Broken or Missing Components		one
Initi	ial	Electrical Inspection		
1	6.	Insulation Resistance/Megger		
1	7.	Winding Resistance		
		1-2 1-3		2-3
		2.868 4.450		10.765
1	8.	Perform Surge Test		(F) Fail
1	9.	Number of Stator Slots		
2	20.	Stator Condition		rewind
Med	cha	anical Inspection		
2	21.	Drive End Bearing Brand		koyo
2	22.	Drive End Bearing Number-		6308RD
2	23.	Drive End Bearing Qty.		1
2	24.	Drive End Bearing Type		(Ball) Ball Bearing
2	25.	Drive End Lubrication Type		(Grease) Grease Lubricated
2	26.	Drive End Bearing Insulation or Grounding Device	e?	none
2	27.	Drive End Wavy Washer/Snap-Ring Other Reten	tion Device?	snap ring outer, snap ring inner
2	28.	Drive End Bearing Condition		ok
2	29.	Opposite Drive End Bearing Brand		koyo
3	30.	Opposite Drive End Bearing Number-		6308RD

	Opposite Drive End Bearing Qty.		1
32.	Opposite Drive End Bearing Type		(Ball) Ball Bearing
33.		(Grease) Grease Lubricated	
34.	-111	none	
35.		r/Snap-Ring Other Retention Device?	wavy
36.	3 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	lition	
37.			40 52 4
	Opposite Drive End Seal		
	Inspection		
39.	Rotor Type/Material		
40.	Growler Test		(Pass) Pass
41.	Number of Rotor Bars		28
42.			good
43.	List the Parts needed for the Repa	air Below	
	6308RD, 6308RD, 40-52-4 seal		
44.	Signature of Technician that Disas	SSETTIDIEG MOTOR	David Maclin
/lech	anical Fits- Rotor		
	Shaft Runout		
45.	Shaft Runout Rotor Runout		
45.		Rotor Body	Opposite Drive End Bearing
45. 46.	Rotor Runout Drive End Bearing Fit	·	Opposite Drive End Bearing
45. 46.	Rotor Runout Drive End Bearing Fit Coupling Fit Closest to Bearing H	ousing	
45. 46.	Rotor Runout Drive End Bearing Fit	·	Opposite Drive End Bearing  120 Degrees
45. 46.	Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing H  0 Degrees	ousing 90 Degrees	
45. 46. 47.	Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing H 0 Degrees  Coupling Fit Closest to the end of	ousing 90 Degrees the Shaft	120 Degrees
45. 46. 47.	Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing H  0 Degrees	ousing 90 Degrees	
45. 46. 47.	Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing H 0 Degrees  Coupling Fit Closest to the end of	ousing 90 Degrees the Shaft	120 Degrees
45. 46. 47.	Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing H 0 Degrees  Coupling Fit Closest to the end of 0 Degrees	ousing 90 Degrees the Shaft	120 Degrees
45. 46. 47.	Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing H 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit	ousing 90 Degrees the Shaft 60 Degrees	120 Degrees 120 Degrees
45. 46. 47. 48.	Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing H 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees	ousing 90 Degrees the Shaft 60 Degrees 60 Degrees 1.5752	120 Degrees  120 Degrees  120 Degrees
45. 46. 47. 48.	Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing H 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  1.5752	ousing 90 Degrees the Shaft 60 Degrees 60 Degrees 1.5752	120 Degrees  120 Degrees  120 Degrees  1.5752
45. 46. 47. 48.	Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing H 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  1.5752  Drive End Bearing Shaft Fit Cond	ousing 90 Degrees the Shaft 60 Degrees 60 Degrees 1.5752	120 Degrees  120 Degrees  120 Degrees  1.5752
45. 46. 47. 48.	Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing H 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  1.5752  Drive End Bearing Shaft Fit Cond Opposite Drive End Bearing Shaft	ousing 90 Degrees the Shaft 60 Degrees 60 Degrees 1.5752 ition t Fit	120 Degrees  120 Degrees  120 Degrees  1.5752  (P) Pass
45. 46. 47. 48. 49. 50. 51.	Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing H 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  1.5752  Drive End Bearing Shaft Fit Cond Opposite Drive End Bearing Shaft 0 Degrees	ousing 90 Degrees the Shaft 60 Degrees 60 Degrees 1.5752 ition t Fit 60 Degrees 1.575	120 Degrees  120 Degrees  120 Degrees  1.5752  (P) Pass
45. 46. 47. 48. 49. 50. 51.	Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing H 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  1.5752  Drive End Bearing Shaft Fit Cond Opposite Drive End Bearing Shaft 0 Degrees 1.5749	ousing 90 Degrees the Shaft 60 Degrees 60 Degrees 1.5752 ition t Fit 60 Degrees 1.575	120 Degrees  120 Degrees  120 Degrees  1.5752  (P) Pass
45. 46. 47. 48. 49. 50. 51.	Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing H 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  1.5752  Drive End Bearing Shaft Fit Cond Opposite Drive End Bearing Shaft 0 Degrees  1.5749  Opposite Drive End Bearing Shaft	ousing 90 Degrees the Shaft 60 Degrees 60 Degrees 1.5752 ition t Fit 60 Degrees 1.575	120 Degrees  120 Degrees  120 Degrees  1.5752  (P) Pass
45. 46. 47. 48. 49. 50. 51.	Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing H 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  1.5752  Drive End Bearing Shaft Fit Cond Opposite Drive End Bearing Shaft 0 Degrees  1.5749  Opposite Drive End Bearing Shaft Shaft Air Seal Fits Drive End Air Seal	ousing 90 Degrees the Shaft 60 Degrees  60 Degrees 1.5752 ition t Fit 60 Degrees 1.575 t Fit Condition  Opposite Drive End Air Seal	120 Degrees  120 Degrees  120 Degrees  1.5752  (P) Pass
45. 46. 47. 48. 49. 50. 51. 52. 53.	Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing H 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  1.5752 Drive End Bearing Shaft Fit Cond Opposite Drive End Bearing Shaft 0 Degrees  1.5749  Opposite Drive End Bearing Shaft Shaft Air Seal Fits Drive End Air Seal  anical Fits- Bearing Housings	ousing 90 Degrees the Shaft 60 Degrees  60 Degrees 1.5752 ition t Fit 60 Degrees 1.575 t Fit Condition  Opposite Drive End Air Seal	120 Degrees  120 Degrees  120 Degrees  1.5752  (P) Pass
45. 46. 47. 48. 49. 50. 51. 52. 53.	Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing H 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  1.5752  Drive End Bearing Shaft Fit Cond Opposite Drive End Bearing Shaft 0 Degrees  1.5749  Opposite Drive End Bearing Shaft Shaft Air Seal Fits Drive End Air Seal  anical Fits- Bearing Housings Drive End - Endbell Bearing Fit	ousing 90 Degrees  the Shaft 60 Degrees  60 Degrees  1.5752  ition t Fit 60 Degrees  1.575 t Fit Condition  Opposite Drive End Air Seal	120 Degrees  120 Degrees  120 Degrees  1.5752  (P) Pass  120 Degrees  1.575  (P) Pass
45. 46. 47. 48. 49. 50. 51. 52. 53.	Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing H 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  1.5752 Drive End Bearing Shaft Fit Cond Opposite Drive End Bearing Shaft 0 Degrees  1.5749  Opposite Drive End Bearing Shaft Shaft Air Seal Fits Drive End Air Seal  anical Fits- Bearing Housings	ousing 90 Degrees the Shaft 60 Degrees  60 Degrees 1.5752 ition t Fit 60 Degrees 1.575 t Fit Condition  Opposite Drive End Air Seal	120 Degrees  120 Degrees  120 Degrees  1.5752  (P) Pass

0 Degrees 60 Degrees 120 Degrees 3.5443 3.5444 3.5445 3.5444 3.5445 3.5444 3.5445 3.5444 3.5445 3.5444 3.5445 3.5444 3.5445 3.5444 3.5445 3.54	56.	Opposite Drive End - Endbell Bearing	g Fit		
3.5443 3.5443 3.5445 3.5444  57. Opposite Drive End - Endbell Bearing Fit Condition (F) Fail  58. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap  59. End Bell Air Seal Tits Drive End Air Seal Opposite Drive End Air Seal  60. List Machine Work Needed Below Siever ODE  61. Technician David Maclin				120 Degrees	
57. Opposite Drive End - Endbell Bearing Fit Condition (F) Fail 58. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap  59. End Bell Air Seal Tits Drive End Air Seal Opposite Drive End Air Seal  60. List Machine Work Needed Below Sloeve ODE  61. Technician David Maclin  Dynamic Balance Report 62. Rotor Weight Balance Grade Rotor Weight Balance Grade 63. Inhial Balance Readings Drive End Opposite Drive End 64. Final Balance Readings Drive End Opposite Drive End  65. Technician  Rewind  66. Core Test Results - Watts loss per Pound Pre-Burnout Post Burnout  67. Core Hot Spot Test Pre-Burnout Post-Burnout  68. Post Rewind Polarization Index 70. Post Rewind Vinding Resistance 1-2 1-3 2-3  71. Post Rewind Surge Test 72. Post Rewind Winding Resistance Roto Cause of Failure  74. Fallure locations 75. Roto cause of failure  Mechanical Fits- Rotor - Post Repair  Mechanical Fits- Rotor - Post Repair		_	-	_	
58. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap Opposite Drive End Air Seal Oprive End Air Seal Opposite Drive End Air Seal Opavid Maclin  David Maclin	<b>5</b> 7.				(F) Fail
Drive End Bearing Cap Opposite Drive End Bearing Cap  59. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal  60. List Machine Work Needed Below Sleeve ODE 61. Technician  David Maclin  David M	58.				
59. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal  60. List Machine Work Needed Below Sleeve ODE  61. Technician David Maclin  David			Opposite Drive End Bearing Cap		
Drive End Air Seal Opposite Drive End Air Seal  60. List Machine Work Needed Below Sleeve ODE  61. Technician David Maclin  Dynamic Balance Report  62. Rotor Weight and Balance Grade Rotor Weight Balance Grade  63. Initial Balance Readings Drive End Opposite Drive End  64. Final Balance Readings Drive End Opposite Drive End  65. Technician  Rewind  66. Core Test Results - Watts loss per Pount Pre-Burnout Post Burnout  67. Core Hot Spot Test Pre-Burnout Post-Burnout  68. Post Rewind Electrical Test- Insulation Resistance  69. Post Rewind Winding Resistance  1-2 1-3 2-3  71. Post Rewind Surge Test 72. Post Rewind Hi-Pot 73. Technician  Root Cause of Failure  74. Failure locations 75. Root cause of failure  Mechanical Fits- Rotor - Post Repair		Zine Zina Zeamig Cap	opposite 2 me 2 me 2 caming cap		
60. List Machine Work Needed Below Sleeve ODE 61. Technician David Maclin  Dynamic Balance Report 62. Rotor Weight and Balance Grade Rotor Weight and Balance Grade 63. Initial Balance Readings Drive End Opposite Drive End 64. Final Balance Readings Drive End Opposite Drive End 65. Technician  Rewind 66. Core Test Results - Watts loss per Pound Pre-Burnout Post Burnout 67. Core Hot Spot Test Pre-Burnout Post-Burnout 68. Post Rewind Electrical Test- Insulation Resistance 69. Post Rewind Polarization Index 70. Post Rewind Winding Resistance 1-2 1-3 2-3  71. Post Rewind Surge Test 72. Post Rewind Surge Test 73. Technician  Root Cause of Failure 74. Failure locations 75. Root cause of failure  Mechanical Fits- Rotor - Post Repair	59.	End Bell Air Seal Fits			
Sleeve ODE 61. Technician David Maclin  Pynamic Balance Report 62. Rotor Weight and Balance Grade Rotor Weight Balance Readings Drive End Opposite Drive End 64. Final Balance Readings Drive End Opposite Drive End 65. Technician  Rewind 66. Core Test Results - Watts loss per Pount Pre-Burnout Post Burnout 67. Core Hot Spot Test Pre-Burnout Post-Burnout 68. Post Rewind Electrical Test- Insulation Resistance 69. Post Rewind Polarization Index 70. Post Rewind Winding Resistance 1-2 1-3 2-3 71. Post Rewind Minding Resistance 73. Technician  Rot Cause of Failure 74. Failure locations 75. Root cause of failure  Mechanical Fits- Rotor - Post Repair		Drive End Air Seal	Opposite Drive End Air Seal		
Pynamic Balance Report  62. Rotor Weight and Balance Grade Rotor Weight Balance Grade  63. Initial Balance Readings Drive End Opposite Drive End  64. Final Balance Readings Drive End Opposite Drive End  65. Technician  Rewind  66. Core Test Results - Watts loss per Pound Pre-Burnout Post Burnout  67. Core Hot Spot Test Pre-Burnout Post-Burnout  68. Post Rewind Electrical Test- Insulation Resistance  69. Post Rewind Polarization Index  70. Post Rewind Winding Resistance  1-2 1-3 2-3  71. Post Rewind Surge Test  72. Post Rewind Surge Test  73. Technician  Rot Cause of Failure  74. Failure locations  75. Root cause of failure  Mechanical Fits- Rotor - Post Repair	60.	List Machine Work Needed Below			
Dynamic Balance Report  62. Rotor Weight and Balance Grade Rotor Weight Balance Grade  63. Initial Balance Readings Drive End Opposite Drive End  64. Final Balance Readings Drive End Opposite Drive End  65. Technician  Rewind  66. Core Test Results - Watts loss per Pound Pre-Burnout Post Burnout  67. Core Hot Spot Test Pre-Burnout Post-Burnout  68. Post Rewind Electrical Test- Insulation Resistance  69. Post Rewind Polarization Index  70. Post Rewind Winding Resistance  1-2 1-3 2-3  71. Post Rewind Surge Test 72. Post Rewind Hi-Pot 73. Technician  Root Cause of Failure  74. Failure locations 75. Root cause of failure  Mechanical Fits- Rotor - Post Repair		Sleeve ODE			
62. Rotor Weight and Balance Grade Rotor Weight Balance Grade  63. Initial Balance Readings Drive End Opposite Drive End  64. Final Balance Readings Drive End Opposite Drive End  65. Technician  Rewind  66. Core Test Results - Watts loss per Pound Pre-Burnout Post Burnout  67. Core Hot Spot Test Pre-Burnout Post-Burnout  68. Post Rewind Electrical Test- Insulation Resistance  69. Post Rewind Polarization Index  70. Post Rewind Winding Resistance  1-2 1-3 2-3  71. Post Rewind Surge Test 72. Post Rewind Hi-Pot 73. Technician  Rotot Cause of Failure 74. Failure locations 75. Root cause of failure  Mechanical Fits- Rotor - Post Repair	61.	Technician	7		David Maclin
Rotor Weight Balance Grade  63. Initial Balance Readings Drive End Opposite Drive End  64. Final Balance Readings Drive End Opposite Drive End  65. Technician  Rewind  66. Core Test Results - Watts loss per Pound Pre-Burnout Post Burnout  67. Core Hot Spot Test Pre-Burnout Post-Burnout  68. Post Rewind Electrical Test- Insulation Resistance  69. Post Rewind Polarization Index  70. Post Rewind Surge Test 71. Post Rewind Surge Test 72. Post Rewind Hi-Pot 73. Technician  Root Cause of Failure  74. Failure locations 75. Root cause of failure  Mechanical Fits- Rotor - Post Repair	_	•	•		
63. Initial Balance Readings Drive End Opposite Drive End  64. Final Balance Readings Drive End Opposite Drive End  65. Technician  Rewind  66. Core Test Results - Watts loss per Pound Pre-Burnout Post Burnout  67. Core Hot Spot Test Pre-Burnout Post-Burnout  68. Post Rewind Electrical Test- Insulation Resistance 69. Post Rewind Volarization Index 70. Post Rewind Winding Resistance 1-2 1-3 2-3  71. Post Rewind Surge Test 72. Post Rewind Hi-Pot 73. Technician  Root Cause of Failure  74. Failure locations 75. Root cause of failure  Mechanical Fits- Rotor - Post Repair	62.	Rotor Weight and Balance Grade			
Drive End Opposite Drive End  64. Final Balance Readings Drive End Opposite Drive End  65. Technician  Rewind  66. Core Test Results - Watts loss per Pound Pre-Burnout Post Burnout  67. Core Hot Spot Test Pre-Burnout Post-Burnout  68. Post Rewind Electrical Test- Insulation Resistance 69. Post Rewind Polarization Index  70. Post Rewind Winding Resistance 1-2 1-3 2-3  71. Post Rewind Surge Test 72. Post Rewind Surge Test 73. Technician  Root Cause of Failure  74. Failure locations 75. Root cause of failure  Mechanical Fits- Rotor - Post Repair		Rotor Weight	Balance Grade		
64. Final Balance Readings Drive End  65. Technician  Rewind  66. Core Test Results - Watts loss per Pound Pre-Burnout  67. Core Hot Spot Test Pre-Burnout  68. Post Rewind Electrical Test- Insulation Resistance 69. Post Rewind Polarization Index  70. Post Rewind Winding Resistance 1-2  1-3  2-3  71. Post Rewind Surge Test 72. Post Rewind Hi-Pot 73. Technician  Root Cause of Failure  74. Failure locations 75. Root cause of failure  Mechanical Fits- Rotor - Post Repair	63.	Initial Balance Readings			
Brive End Opposite Drive End  65. Technician  Rewind  66. Core Test Results - Watts loss per Pound Pre-Burnout Post Burnout  67. Core Hot Spot Test Pre-Burnout Post-Burnout  68. Post Rewind Electrical Test- Insulation Resistance 69. Post Rewind Polarization Index 70. Post Rewind Winding Resistance 1-2 1-3 2-3  71. Post Rewind Surge Test 72. Post Rewind Hi-Pot 73. Technician  Root Cause of Failure  74. Failure locations 75. Root cause of failure  Mechanical Fits- Rotor - Post Repair		Drive End	Opposite Drive End		
Brive End Opposite Drive End  65. Technician  Rewind  66. Core Test Results - Watts loss per Pound Pre-Burnout Post Burnout  67. Core Hot Spot Test Pre-Burnout Post-Burnout  68. Post Rewind Electrical Test- Insulation Resistance 69. Post Rewind Polarization Index 70. Post Rewind Winding Resistance 1-2 1-3 2-3  71. Post Rewind Surge Test 72. Post Rewind Hi-Pot 73. Technician  Root Cause of Failure  74. Failure locations 75. Root cause of failure  Mechanical Fits- Rotor - Post Repair	64.	Final Balance Readings			
Rewind  66. Core Test Results - Watts loss per Pound Pre-Burnout Post Burnout  67. Core Hot Spot Test Pre-Burnout Post-Burnout  68. Post Rewind Electrical Test- Insulation Resistance 69. Post Rewind Polarization Index 70. Post Rewind Winding Resistance 1-2 1-3 2-3  71. Post Rewind Surge Test 72. Post Rewind Hi-Pot 73. Technician  Root Cause of Failure  74. Failure locations 75. Root cause of failure  Mechanical Fits- Rotor - Post Repair			Opposite Drive End		
66. Core Test Results - Watts loss per Pound Pre-Burnout Post Burnout  67. Core Hot Spot Test Pre-Burnout Post-Burnout  68. Post Rewind Electrical Test- Insulation Resistance 69. Post Rewind Polarization Index 70. Post Rewind Winding Resistance 1-2 1-3 2-3  71. Post Rewind Surge Test 72. Post Rewind Hi-Pot 73. Technician  Root Cause of Failure  74. Failure locations 75. Root cause of failure  Mechanical Fits- Rotor - Post Repair	65.	Technician			
Pre-Burnout Post Burnout  67. Core Hot Spot Test Pre-Burnout Post-Burnout  68. Post Rewind Electrical Test- Insulation Resistance  69. Post Rewind Polarization Index  70. Post Rewind Winding Resistance 1-2 1-3 2-3  71. Post Rewind Surge Test 72. Post Rewind Hi-Pot 73. Technician  Root Cause of Failure  74. Failure locations 75. Root cause of failure  Mechanical Fits- Rotor - Post Repair	Rewir	nd			
67. Core Hot Spot Test Pre-Burnout Post-Burnout  68. Post Rewind Electrical Test- Insulation Resistance 69. Post Rewind Polarization Index 70. Post Rewind Winding Resistance 1-2 1-3 2-3  71. Post Rewind Surge Test 72. Post Rewind Hi-Pot 73. Technician  Root Cause of Failure 74. Failure locations 75. Root cause of failure  Mechanical Fits- Rotor - Post Repair	66.	Core Test Results - Watts loss per P	ound		
Pre-Burnout  Post-Burnout  Post-Burnout  Post Rewind Electrical Test- Insulation Resistance  Post Rewind Polarization Index  Post Rewind Winding Resistance  1-2  1-3  2-3  71. Post Rewind Surge Test  72. Post Rewind Hi-Pot  73. Technician  Root Cause of Failure  74. Failure locations  75. Root cause of failure  Mechanical Fits- Rotor - Post Repair		Pre-Burnout	Post Burnout		
68. Post Rewind Electrical Test- Insulation Resistance 69. Post Rewind Polarization Index 70. Post Rewind Winding Resistance 1-2 1-3 2-3  71. Post Rewind Surge Test 72. Post Rewind Hi-Pot 73. Technician  Root Cause of Failure 74. Failure locations 75. Root cause of failure  Mechanical Fits- Rotor - Post Repair	67.	Core Hot Spot Test			
69. Post Rewind Polarization Index 70. Post Rewind Winding Resistance 1-2 1-3 2-3  71. Post Rewind Surge Test 72. Post Rewind Hi-Pot 73. Technician  Root Cause of Failure 74. Failure locations 75. Root cause of failure  Mechanical Fits- Rotor - Post Repair		Pre-Burnout	Post-Burnout		
70. Post Rewind Winding Resistance 1-2 1-3 2-3  71. Post Rewind Surge Test 72. Post Rewind Hi-Pot 73. Technician  Root Cause of Failure 74. Failure locations 75. Root cause of failure  Mechanical Fits- Rotor - Post Repair	68.	Post Rewind Electrical Test- Insulation	on Resistance		
1-2 1-3 2-3  71. Post Rewind Surge Test  72. Post Rewind Hi-Pot  73. Technician  Root Cause of Failure  74. Failure locations  75. Root cause of failure  Mechanical Fits- Rotor - Post Repair	69.	Post Rewind Polarization Index			
71. Post Rewind Surge Test  72. Post Rewind Hi-Pot  73. Technician  Root Cause of Failure  74. Failure locations  75. Root cause of failure  Mechanical Fits- Rotor - Post Repair	70.	Post Rewind Winding Resistance			
72. Post Rewind Hi-Pot 73. Technician  Root Cause of Failure 74. Failure locations 75. Root cause of failure  Mechanical Fits- Rotor - Post Repair		1-2	1-3	2-3	
73. Technician  Root Cause of Failure  74. Failure locations  75. Root cause of failure  Mechanical Fits- Rotor - Post Repair	71.	Post Rewind Surge Test			
Root Cause of Failure  74. Failure locations  75. Root cause of failure  Mechanical Fits- Rotor - Post Repair	72.	Post Rewind Hi-Pot			
74. Failure locations 75. Root cause of failure  Mechanical Fits- Rotor - Post Repair	73.	Technician			
75. Root cause of failure  Mechanical Fits- Rotor - Post Repair	Root	Cause of Failure			
Mechanical Fits- Rotor - Post Repair	74.	Failure locations			
	75.	Root cause of failure			
	Mecha	anical Fits- Rotor - Post Repair			
		-			

77.	Rotor Runout Post Repair		
	Drive End Bearing Fit	Rotor Body	Opposite Drive End Bearing
		·	
78.	Coupling Fit Closest to Bearing Housi	ng Post Repair	
	0 Degrees	90 Degrees	120 Degrees
79.	Coupling Fit Closest to the end of the	Shaft Post Repair	
	0 Degrees	60 Degrees	120 Degrees
80.	Drive End Bearing Shaft Fit Post Repa		
	0 Degrees	60 Degrees	120 Degrees
81.	Opposite Drive End Bearing Shaft Fit	•	
	0 Degrees	60 Degrees	120 Degrees
00	Chaft Air Coal Fite Boot Beneix		
82.	Shaft Air Seal Fits Post Repair		
	Drive End Air Seal	Opposite Drive End Air Seal	
02	Shaft Repair Sign-off		
		ant Dannelin	
	anical Fits- Bearing Housings - P	•	
84.	Drive End - Endbell Bearing Fit Post F		
	0 Degrees	60 Degrees	120 Degrees
0.5		EV.D. v.D. v.	
85.	Opposite Drive End - Endbell Bearing		
	0 Degrees	60 Degrees	120 Degrees
	3.5435	3.5435	3.5435



86.	Bearing Cap Condition Post Repair	
	Drive End Bearing Cap	Opposite Drive End Bearing Cap
87.	End Bell Air Seal Fits Post Repair	
	Drive End Air Seal	Opposite Drive End Air Seal
88.	End Bell Repair Sign-off	
Assei	mbly	
89.	QC Check All Parts for Cleanliness P	rior to Assembly

90.	Photograph All Major Components prior to assembly		
91.	91. Final Insulation Resistance Test		
92.	Assembled Shaft Endplay		
93.	Assembled Shaft Runout		
94.	Test Run Voltage		
	Volts	Volts	Volts
	457	458	459



95.	Test Run Amperage		
	Amps	Amps	Amps
	5.9	6.1	6
96.	Drive End Vibration Readings - Inches	Per Second	
	Horizontal	Vertical	Axial
97.	Opposite Drive End Vibration Reading	s - Inches Per Second	
	Horizontal	Vertical	Axial
98.	Ambient Temperature - Fahrenheit		
99.	Drive End Bearing Temps - Fahrenhei	t	
	5 Minutes	10 Minutes	15 Minutes
100.	Opposite Drive End Bearing Temps -	Fahrenheit	
	5 Minutes	10 Minutes	15 Minutes
101.	Document Final Condition with Picture	es after paint	
102.	Final Pics and QC Review		

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.











#### STANDARD TERMS AND CONDITIONS FOR PURCHASE OF GOOD AND/OR SERVICES

- 1. APPLICABILITY. The sale of any and all goods and/or services by Mock, Inc. d/b/a Hi-Speed Industrial Service ("Hi-Speed") shall be specifically conditioned upon and subject to the following terms and conditions which are incorporated by reference into any contracts and purchase orders with Hi-Speed, and which shall form and become a part of any agreement related thereto. Buyer's acceptance of any offer or quotation made by Hi-Speed for sale of any goods or services is expressly made subject to the terms and conditions set forth herein and to be so effective, Buyer need not sign or approve these Terms and Conditions to be bound hereunder provided a copy of same is provided to Buyer through any means. None of the terms and conditions contained herein may be added to, expanded, changed, modified, superseded or otherwise altered except as revised in writing and duly executed by Hi-Speed, and all orders received by Hi-Speed shall be governed only by the terms and conditions contained herein, notwithstanding any terms, conditions or provisions of any purchase order, release order, authorization or any other form issued by the Buyer. Hi-Speed hereby objects to any additional, modified, changed, deleted, altered or other terms and conditions not contained herein and notifies Buyer that any such terms or provisions are expressly rejected by Hi-Speed.
- 2. PRICE. All quoted prices shall remain firm and binding for a period of thirty (30) days from the date of quotation or for the period specifically stated in the quotation. The price for any and all goods and/or services ordered or approved by Buyer after thirty (30) days from the date of any quotation are subject to any increase in price that may occur after the expiration of thirty (30) days from the issuance of the quotation and the date the Buyer releases any shipment.
- 3. SCOPE OF GOODS AND/OR SERVICES. The goods and/or services provided by Hi-Speed pursuant to any quotation shall be limited exclusively to those goods and/or services expressly identified therein. Hi-Speed does not assume any responsibility and/or liability for the failure to provide any other goods and/or services not identified in any quotation. Modifications, additions or deletions to or from the scope referenced in any quotation shall only bee effective if evidenced in writing and signed by Hi-Speed. The sale of any of all goods and/or services affected by such modification, addition or deletion shall be subject to these same Standard Terms and Conditions whether or not referenced therein.
- 4. <u>BILLING AND PAYMENT TERMS.</u> Hi-Speed shall invoice Buyer for all goods and/or services as same are rendered at the address listed on the quotation. Payments for all goods and/or services shall be due thirty (30) days from the date of the current invoice or as otherwise set forth in the quotation. Late payments are subject to a late fee of 5% of the total invoice amount. Recurring late payments may lead to a deposit requirement on future services or sale of goods. Buyer shall be liable to Hi-Speed for any and all fees and expenses incurred by Hi-Speed to collect any invoices or to enforce these Standard Terms and Conditions, including but not limited to, attorney's fees.
- 5. <u>DELIVERY OF GOODS AND/OR SERVICES.</u> Unless otherwise identified in the quotation, all shipments are F.O.B. Hi-Speed's warehouse and the title to and all risk of loss with respect to any goods shipped shall pass to Buyer when such goods are delivered to the carrier at Hi-Speed's warehouse. Hi-Speed will use its best efforts to affect delivery by the date or dates specified in the quotation. However, Hi-Speed shall not be liable for delay in or failure to make shipment, or to perform services, by any identified date for any reason whatsoever, including but not limited to, causes beyond its reasonable control, such as strikes, fires, floods, epidemics, quarantines, restrictions, severe weather, embargos, acts of God, or public enemy, war, riot, delays in transportation or the inability to obtain necessary labor, materials or manufacturing facilities.
- **DELIVERY SITE AND TIME FOR PERFORMANCE.** Hi-Speed and Buver agree that time is of the essence for the purchase order and that Buyer shall fully cooperate with Hi-Speed in order to allow Hi-Speed full access to prosecute its work diligently and in an orderly manner. Buyer shall assist Hi-Speed in every way possible to avoid delaying, disrupting or interfering with the progress of Hi-Speed's work at the project site. In the event Hi-Speed's work is delayed, hindered, suspended, disrupted, re-sequenced or interfered with or rendered less efficient or more costly or adversely affected in any way as a result of acts or omissions of Buyer or other contractors or employees of Buyer or by any other reason beyond Hi-Speed's control and without the fault of Hi-Speed, then, in such event, Buyer shall be liable to Hi-Speed for any damages, additional costs, expenses, labor, materials, man hours, acceleration costs, overtime, additional jobsite overhead, extended home office overhead, and any and all other direct and indirect expenses of whatsoever nature or kind, caused in whole or in part, as a result of any of the above-referenced occurrences. Hi-Speed's project records will be the basis for computing the additional costs and damages of Hi-Speed's labor, materials, expenses and overhead related to such changes. BUYER WARRANTS THAT THE SITE FOR DELIVERY OR INSTALLATION OF ANY GOODS AND/OR FOR THE PERFORMANCE OF ANY SERVICES SHALL BE READY AND ADEQUATE FOR HI-SPEED'S DELIVERY OF GOODS AND/OR PERFORMANCE OF SERVICES AND THAT HI-SPEED SHALL HAVE FULL ACCESS THERETO, FREE OF ALL OBSTRUCTIONS. BUYER SHALL ASSUME ALL EXTRA COSTS ASSOCIATED WITH HI-SPEED'S INABILITY TO INSTALL ANY GOODS OR PERFORM ANY SERVICES AS A RESULT OF BUYER'S FAILURE TO COMPLY WITH THIS PROVISION. HI-SPEED MAY NOT INSPECT THE SITE PRIOR TO DELIVERY AND/OR INSTALLATION OF GOODS AND/OR PERFORMANCE OF SERVICES AND MAKES NO WARRANTY AS TO THE SUFFICIENCY OF THE SITE FOR THE DELIVERY AND/OR INSTALLATION OF GOODS AND/OR THE PERFORMANCE OF SERVICES AT SUCH SITE.
- 7. INSPECTION/ACCEPTANCE. All goods and services ordered pursuant to any quotation shall be subject to inspection by Buyer after delivery or performance to determine conformity with the quotation and/or purchase order and Hi-Speed's advertised or published specifications. Buyer shall have a period of thirty (30) days from shipment of goods at the delivery destination specified in the quotation within which to inspect the goods for conformity with the quotation, order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. Buyer shall have a period of thirty (30) days following completion of any services within which to inspect the services for conformity with the quotation, purchase order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. If the goods delivered or services performed do not so conform, upon delivery of notice to Hi-Speed of any discrepancy, nonconformance or rejection, Hi-Speed shall have sixty (60) days to cure the alleged discrepancy and/or nonconformance. If Hi-Speed fails to cure in this time period, Buyer shall have the right to reject such goods or services. After the cure period, goods that have been delivered and rejected, in whole or in part, shall be returned to Hi-Speed. Buyer shall notify Hi-Speed and arrange for the return of the goods as required. Should such non-conforming services be rejected Hi-Speed shall, at its sole cost, re-perform the non-conforming services. Inspection or failure to inspect on any occasion shall not affect Buyer's rights under the warranty provisions herein.
- 8. WARRANTIES. Hi-Speed warrants that all goods shall conform in all material aspects to the goods identified in the quotation to Buyer and/or purchase order, and Hi-Speed makes to Buyer the manufacturer's express warranty for any goods sold to Buyer, which is offered by the manufacturer at the time of acceptance of any quotation by Buyer. This warranty is conditioned upon the installation, operation, and maintenance of the goods in accordance with the manufacturer's recommendations and/or standard industry practice and the goods at all times being operated or used under normal operating conditions for which they were designed. Hi-Speed, at its sole option, will repair or

replace any defective or non-conforming goods in accordance with the applicable manufacturer's warranty. Warranty for any defective or incorrect parts is limited to the repair or replacement of those parts. Hi-Speed warrants that all services will conform in all material respects to the description of services identified in the quotation and will be performed in a good and workmanlike manner in accordance with industry practices and standards. Should the services be reasonably rejected or not conform with the foregoing warranties, Hi-Speed shall, at its sole cost, re-perform the defective or nonconforming services. Notwithstanding the foregoing, these warranties do not extend to goods or services to the extent that such goods have been subject to misuse, neglect or abuse not caused by Hi-Speed or have been used in violation of the approved written instructions furnished to Buyer. THE FOREGOING REPRESENTS THE SOLE AND EXCLUSIVE WARRANTY GIVEN BY HI-SPEED WITH RESPECT TO ALL GOODS SOLD AND IS IN LIEU OF ALL OTHER WARRANTIES EITHER EXPRESS OR IMPLIED. HI-SPEED EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICLAR USE OR PURPOSE. BUYER WAIVES ANY CLAIM THAT THESE EXCLUSIONS OR LIMITATIONS DEPRIVE IT OF AN ADEQUATE REMEDY AT EQUITY OR LAW OR CAUSE THIS AGREEMENT TO FAIL IN ITS ESSENTIAL PURPOSE. BUYER SHALL BE ENTITLED TO NO OTHER REMEDY OTHER THAN AS SET FORTH HEREIN, REGARDLESS OF THE CLAIM OR CAUSE OF ACTION, WHETHER BASED IN CONTRACT, TORT, NEGLIGENCE, GOODS LIABILITY, STRICT LIABILITY OR OTHERWISE.

- 9. <u>LIMITATION OF DAMAGES.</u> HI-SPEED SHALL HAVE NO LIABILITY TO BUYER WITH RESPECT TO THE SALE OR DELIVERY OF ANY GOODS OR THE REPAIR THEREOF OR WITH RESPECT TO THE SALE OR PERFORMANCE OF ANY SERVICES, FOR LOST PROFITS, SPECIAL, CONSEQUENTIAL, EXEMPLARY, PUNITIVE OR INCIDENTAL DAMAGES OF ANY KIND OR NATURE WHETHER ARISING IN CONTRACT, TORT, GOODS LIABILITY OR OTHERWISE, EVEN IF HI-SPEED WAS ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGES. HI-SPEED SHALL NOT BE LIABLE FOR ANY DAMAGES OR DELAYS CAUSED BY ANY FAILURE TO MAKE ANY DELIVERY OF GOODS BY ANY EXPECTED TIME OR DATE OR THE FAILURE TO PROVIDE OR COMPLETE ANY SERVICES BY ANY EXPECTED DATE OR TIME. IN NO EVENT SHALL HI-SPEED BE LIABLE TO BUYER FOR ANY DAMAGES WHATSOEVER IN EXCESS OF THE TOTAL PRICE PAID FOR ALL GOODS AND/OR SERVICES HEREUNDER OR REFERENCED IN ANY QUOTATION OR THE PURCHASE ORDER.
- 10. <u>SEVERABILITY.</u> The partial or complete invalidity of any provision of these Standard Terms and Conditions shall not affect the enforceability of the remainder of these Standard Terms and Conditions. If any provision is found to be invalid or unenforceable, that portion shall be modified to make it enforceable or shall be stricken and the remainder of these Standard Terms and Conditions shall enforced.
- 11. **GOVERNING LAW AND JURISDICTION.** Any controversy arising out of any quotation, the purchase order, the goods sold or delivered, repair or replacement thereof, or any services provided pursuant to any quotation or any purchase order, or these Standard Terms and Conditions shall be governed by the laws of the state of Tennessee without regard to any choice of law provisions and any cause of action related in any manner thereto shall be brought only in the state or federal courts of Shelby County, Tennessee.
- 12. ABANDONED EQUIPMENT. Hi-Speed requires that Buyer promptly pick up or provide shipment instructions for Buyer equipment or other Buyer property in Hi-Speed's possession. If equipment or other Buyer property is left with Hi-Speed and not picked up within six (6) months after Hi-Speed's final action related to the applicable property (e.g. evaluation, teardown, estimate, completion of services), Hi-Speed will consider such property abandoned and may dispose of it in accordance with applicable law. Buyer agrees to hold Hi-Speed harmless for any damage or claim for such abandoned property and acknowledges that Hi-Speed may discard or recycle it at Hi-Speed's sole and absolute discretion. Specifically, Hi-Speed may sell Buyer's abandoned property at a private or public sale and retain the proceeds to offset Hi-Speed's storage, inspection and servicing costs. For the avoidance of doubt, Hi-Speed reserves its statutory and other lawful liens for unpaid charges related to abandoned property.
- 13. FORCE MAJEURE. Neither party shall be responsible for any delay or failure in performance of any party of the quotation, purchase order or these Standard Terms and Conditions to the extent that such delays or failures are caused by fire, flood, earth quake, explosion, war, embargo, government requirement, civil or military authority, acts of God, or any other circumstances beyond its reasonable control and not involving any fault or negligence on the party affected ("Condition"). If any such Condition occurs, the party delayed or unable to perform shall promptly give written notice to the other party and, if such Condition remains at the end of thirty (30) days, the party affected by the other party's delay and inability to perform may elect to (i) terminate such order or part thereof, or (ii) suspend the order for the duration of the Condition, if the Buyer is the suspending party, buy elsewhere comparable material to be sold under the order and apply to any commitment the purchase price of such purchase, and resume performance of the order once the Condition ceases, with an option in the affected party to extend the period of this order up to the length of the time the Condition endures.
- 14. <u>NONWAIVER.</u> No course of dealing or failure of either party to strictly enforce any term, right, or condition of these Standard Terms and Conditions will be construed as a waiver of such term, right or condition. Any waiver by Hi-Speed will only be in writing and will waive no succeeding breach of a term, right or condition.
- 15. **ASSIGNMENT.** The rights and obligations of the parties shall neither be assigned nor delegated without the prior written consent of the other party. However, any party may assign or delegate its respective rights and obligations, in whole or in part, (i) to any subsidiary, (ii) pursuant to other financing, merger or reorganization or (iii) pursuant to any sale or transfer of substantially all of the assets of the assigning party. These Standard Terms and Conditions shall bind the heirs, successors and assigns of the parties hereto.
- 16. NO INDIVIDUAL LIABILITY. Notwithstanding any other agreement to the contrary, the Buyer agrees that in no event will the Buyer hold and HI-Speed owner, director, officer or employee personally liable for unintentional tortious conduct or conduct that constitutes the breach of any contract between HI-Speed and the Buyer, even if the HI-Speed owner, director, officer or employee is or could be construed to be a party to such contract.