

LR Motor Shop Repairs

Job Number 102191

Prepared for Process & Power

1625 East 145th Street Little Rock AR 72206

Table of Contents

AC Inspection as Found - MOTOR SHOP LR

AC Inspection - Rev. 2: 6308000

1.0



FolderID: 102191

FormID: 18706640



AC Inspection as Found

Process & Power

1625 East 145th Street Little Rock, AR 72206

AC Inspection - Rev. 2

Location: MOTOR SHOP LR

Serial Number: 6308000

Description: 300HP RELIANCE 1800RPM

447TDZ

Hi-Speed Job Number:	102191
Manufacturer:	Reliance
Serial Number:	6308000
HP/kW:	300 (HP)
RPM:	1780 (RPM)
Frame:	447TDZ
Voltage:	460
Current:	344
Phase:	Three
Hz:	60 (Hz)
Service Factor:	1.15
Enclosure:	ODP
J-box Included:	None
Coupling/Sheave:	None
Bearing RTDs:	No
Stator RTDs:	No
Repair Stage:	Final
Heaters:	No
Winding Type :	Random Wound
Bearing Type:	Rolling Element

Priorities Found: **a** 2 - High

6 - Good

Overall Condition

1. Report Date 12/13/2023

Nameplate Picture





Photos of all six sides of the machine.

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.















Dirty, oily

21. Stator Thermistors/Ohms

22. Stator Overloads/Ohms

23. Drive End Bearing Brand

25. Drive End Bearing Qty.26. Drive End Bearing Type

24. Drive End Bearing Number-

27. Drive End Lubrication Type

30. Drive End Bearing Condition

31. Opposite Drive End Bearing Brand

28. Drive End Bearing Insulation or Grounding Device?

29. Drive End Wavy Washer/Snap-Ring Other Retention Device?

Mechanical Inspection



none

none

NSK

nu222

none

snap ring

normal

NSK

(Roller) Roller Bearing

(Grease) Grease Lubricated

Initia	l Mechanical/Electrical			
5 .	Does Shaft Turn Freely?			(Yes) Yes
6.	Does Shaft Have Visible Damage?			(No) No
7 .	Assembled Shaft Runout			0 Inches
8.	Assembled Shaft End Play			0 inches
9.	Air Gap Variation <10%			ok
10.	Lead Condition			(P) Pass
11.	Lead Length			60 Inches
12.	Lead Numbers			1-6
13.	Frame Condition			good
14.	Fan Condition			(N) NA
15.	Broken or Missing Components			none
Initia	itial Electrical Inspection			
16.	Insulation Resistance/Megger			2009 Megohms
17.	Winding Resistance			
	1-2	1-3	2-3	
	.349	.349	.349	
18.	Perform Surge Test			(P) Pass
19.	Number of Stator Slots			72
20.	Stator Condition			good

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

32. Opposite Drive End Bearing Number- 33. Opposite Drive End Bearing Oty- 34. Opposite Drive End Dearing Type 35. Opposite Drive End Dearing Type 36. Opposite Drive End Lubrication Type 37. Opposite Drive End Lubrication Type 38. Opposite Drive End Mavy Washer/Snap-Ring Other Retention Device? 38. Opposite Drive End Bearing Insulation or Grounding Device? 39. Opposite Drive End Bearing Insulation or Grounding Device? 39. Opposite Drive End Bearing Insulation or Grounding Device? 39. Opposite Drive End Bearing Condition 39. Drive End Seal 40. Opposite Drive End Seal 41. Rotor Type/Material 42. Growler Test 43. Number of Rotor Bars 44. Rotor Condition 45. List the Parts needed for the Repair Below 46. Signature of Technician that Disassembled Motor 47. Shaft Runout 48. Rotor Runout 48. Rotor Runout 49. Coupling Fit Closest to Bearing Housing 49. Oupping Fit Closest to Bearing Housing 50. Degrees 50. Opposite Drive End Bearing Shaft Fit 60. Degrees 60. D	00	On and Drive Ford Descine Number		0040
34. Opposite Drive End Bearing Type (Ball) Ball Bearing 35. Opposite Drive End Lubrication Type (Grease) Grease Lubricated none 36. Opposite Drive End Bearing Insulation or Grounding Device? none 37. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? spanner nut 38. Opposite Drive End Bearing Condition none 38. Opposite Drive End Bearing Condition none 40. Opposite Drive End Seal none 41. Rotor Type/Material (Squirrel Aluminum) Squirrel Cage Aluminum Die Cast (Pass) Pass 43. Number of Rotor Bars 56. Opposite Drive End Seal Number of Rotor Bars 56. Opposite Drive End Bearing Seal Number of Rotor Bars 56. Opposite Drive End Sear of the Repair Below Nu222 6378 46. Signature of Technician that Disassembled Motor David Maclin Opposite Drive End Bearing Fit Rotor Body Opposite Drive End Bearing Shaft Fit Condition (F) Fail Drive End Bearing Shaft Fit Condition (P) Pass Shaft Air Seal Fits Drive End Bearing Shaft Fit Condition (P) Pass Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal				
35. Opposite Drive End Lubrication Type (Grease) Grease Lubricated on Opposite Drive End Bearing Insulation or Grounding Device? none of Opposite Drive End May Washer/Snap-Ring Other Retention Device? spanner nut on Opposite Drive End Bearing Condition normal one opposite Drive End Bearing Condition none one opposite Drive End Bearing Condition none one opposite Drive End Seal none opposite Drive End Seal (Squirrel Aluminum) Squirrel Cage Aluminum Dia Cast Cage Aluminum		* *		,
36. Opposite Drive End Bearing Insulation or Grounding Device? 37. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? 38. Opposite Drive End Bearing Condition 39. Drive End Seal 30. Opposite Drive End Seal 31. Opposite Drive End Seal 32. Opposite Drive End Seal 33. Opposite Drive End Seal 34. Rotor Type/Material 34. Rotor Type/Material 35. Opposite Drive End Seal 36. Number of Rotor Bars 36. Cage Aluminum Die Cast 37. Number of Rotor Bars 38. Rotor Condition 39. Opposite Drive End Bearing Below 39. Wazzz 6318 39. Signature of Technician that Disassembled Motor 39. Opposite Drive End Bearing Fit 39. Rotor Runout 39. Opposite Drive End Bearing Housing 39. Opposite Drive End Bearing Fit 30. Opposite Drive End Bearing Shaft Fit 30. Opposite Drive End Bearing Shaft Fit Condition 40. Capping Fit Closest to the end of the Shaft 30. Opposite Drive End Bearing Shaft Fit 40. Opposite Drive End Bearing Shaft Fit Condition 40. Opposite Drive End Bearing Shaft Fit Condition 40. Opposite Drive End Bearing Shaft Fit Condition 40. Opposite Drive End Air Seal 40. Opposite Drive End Air Seal		* * * * * * * * * * * * * * * * * * * *		
37. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? 38. Opposite Drive End Searing Condition 39. Orive End Searing Condition 40. Opposite Drive End Searing 40. Opposite Drive End Searing 41. Rotor Type/Material 42. Growler Test 43. Number of Rotor Bars 44. Rotor Condition 45. List the Parts needed for the Repair Below Nuc222 6318 46. Signature of Technician that Disassembled Motor 47. Shaft Runout 48. Rotor Runout 49. Opposite Drive End Bearing Fit 50. Outpling Fit Closest to Bearing Housing 50. Opposite Drive End Bearing Shaft Fit 51. Drive End Bearing Shaft Fit 52. Drive End Bearing Shaft Fit Condition 53. Opposite Drive End Bearing Shaft Fit 54. A317 55. Opposite Drive End Bearing Shaft Fit Condition 56. Opposite Drive End Bearing Shaft Fit Condition 57. Opposite Drive End Bearing Shaft Fit Condition 58. Opposite Drive End Bearing Shaft Fit Condition 59. Opposite Drive End Bearing Shaft Fit Condition 69. Opposite Drive End Bearing Shaft Fit Condition 60. Opposite Drive End Air Seal 61. Opposite Drive End Air Seal		• • • • • • • • • • • • • • • • • • • •		
38. Opposite Drive End Bearing Condition			-	none
3.9. Drive End Seal none	37.		-	spanner nut
Autonomy	38.		1	normal
Actor Type/Material 41. Rotor Type/Material 42. Growler Test 43. Number of Rotor Bars 44. Rotor Condition 45. List the Parts needed for the Repair Below Nu222 6318 46. Signature of Technician that Disassembled Motor 47. Shaft Runout 48. Rotor Runout Drive End Bearing Fit O Degrees O 50. Coupling Fit Closest to Bearing Housing O Degrees A 3115 A 316 A 3116 A 3115 D Degrees O				none
41. Rotor Type/Material 42. Growler Test 43. Number of Rotor Bars 44. Rotor Condition 45. List the Paris needed for the Repair Below Nu222 6318 46. Signature of Technician that Disassembled Motor 47. Shaft Runout 47. Shaft Runout 48. Rotor Runout Drive End Bearing Fit O Degrees O Degre		• •		none
42. Growler Test (Pass) Pass 43. Number of Rotor Bars 56 44. Rotor Condition ok 45. List the Parts needed for the Repair Below Nu222 6318 46. Signature of Technician that Disassembled Motor David Maclin 47. Shaft Runout 0 inches 48. Rotor Runout Drive End Bearing Fit Rotor Body Opposite Drive End Bearing Polyers 49. Coupling Fit Closest to Bearing Housing 0 Degrees 90 Degrees 120 Degrees 0 50. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 0 51. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees	Roto	Inspection		
43. Number of Rotor Bars 56 44. Rotor Condition ok 45. List the Parts needed for the Repair Below **Nu222 6318** 46. Signature of Technician that Disassembled Motor David Maclin **Mechanical Fits- Rotor** 47. Shaft Runout 0 inches 48. Rotor Runout Drive End Bearing Fit Rotor Body Opposite Drive End Bearing 0 49. Coupling Fit Closest to Bearing Housing 0 Degrees 90 Degrees 120 Degrees 0 50. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 0 51. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 4.3115 4.3116 4.3115 52. Drive End Bearing Shaft Fit Condition (F) Fail 53. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 4.3115 4.3116 4.3115 54. Opposite Drive End Bearing Shaft Fit Condition (F) Fail 55. Shaft Air Seal Fits Drive End Bearing Shaft Fit Condition (P) Pass 55. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Bearing Shaft Fit Condition (P) Pass 55. Shaft Air Seal Fits Drive End Air Seal	41.	Rotor Type/Material		
44. Rotor Condition 45. List the Parts needed for the Repair Below Nu222 6318 46. Signature of Technician that Disassembled Motor All Pits-Rotor 47. Shaft Runout All Rotor Runout Drive End Bearing Fit Coupling Fit Closest to Bearing Housing 0 49. Coupling Fit Closest to Bearing Housing 0 49. Coupling Fit Closest to Bearing Housing 0 50. Coupling Fit Closest to the end of the Shaft 0 Degrees 0 50. Coupling Fit Closest to the end of the Shaft 0 Degrees 0 51. Drive End Bearing Shaft Fit 0 Degrees 6 Degrees 120 Degrees	42.	Growler Test		(Pass) Pass
45. List the Parts needed for the Repair Below Nu222 6318 46. Signature of Technician that Disassembled Motor David Maclin Mechanical Fits- Rotor 47. Shaft Runout 0 inches 48. Rotor Runout Drive End Bearing Fit Rotor Body Opposite Drive End Bearing 0 49. Coupling Fit Closest to Bearing Housing 0 Degrees 90 Degrees 120 Degrees 0 50. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 0 51. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 4.3115 4.3116 4.3115 52. Drive End Bearing Shaft Fit Condition (F) Fail 53. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 3.5437 3.5437 3.5438 54. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 55. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal	43.	Number of Rotor Bars		56
Ale. Signature of Technician that Disassembled Motor David Maclin Mechanical Fits- Rotor 47. Shaft Runout Drive End Bearing Fit Poupling Fit Closest to Bearing Housing O 49. Coupling Fit Closest to Bearing Housing O 50. Coupling Fit Closest to the end of the Shaft O Degrees O 50. Coupling Fit Closest to the end of the Shaft O Degrees O 51. Drive End Bearing Shaft Fit O Degrees 60 Degrees 120 Degrees O 51. Drive End Bearing Shaft Fit O Degrees 60 Degrees 120 Degrees	44.	Rotor Condition		ok
Mechanical Fits- Rotor 47. Shaft Runout Are Rotor Runout Drive End Bearing Fit O Degrees O 50. Coupling Fit Closest to Bearing Housing O Degrees A.3115 A.3116 A.3116 A.3116 CF) Fail O Degrees 3.5437 3.5437 3.5437 3.5437 3.5437 3.5438 Fits Drive End Bearing Shaft Fit Condition (P) Pass S Shaft Air Seal Fits Drive End Air Seal	45.	•	elow	
47. Shaft Runout 48. Rotor Runout Drive End Bearing Fit Rotor Body Opposite Drive End Bearing 0 49. Coupling Fit Closest to Bearing Housing 0 Degrees 90 Degrees 120 Degrees 0 50. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 0 51. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 4.3115 4.3116 4.3115 52. Drive End Bearing Shaft Fit Condition (F) Fail 53. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 3.5437 3.5437 3.5438 54. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 55. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal	46.	Signature of Technician that Disasser	nbled Motor	David Maclin
48. Rotor Runout Drive End Bearing Fit Rotor Body Opposite Drive End Bearing 0 49. Coupling Fit Closest to Bearing Housing 0 Degrees 90 Degrees 120 Degrees 0 50. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 0 51. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 4.3115 4.3116 4.3115 52. Drive End Bearing Shaft Fit Condition (F) Fail 53. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 3.5437 3.5437 3.5438 54. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 55. Shaft Air Seal Fits Drive End Air Seal	Mech	anical Fits- Rotor		
Drive End Bearing Fit Rotor Body Opposite Drive End Bearing Coupling Fit Closest to Bearing Housing Degrees 90 Degrees 120 Degrees OCUPING Fit Closest to the end of the Shaft Degrees 60 Degrees 120 Degrees OCUPING Fit Closest to the end of the Shaft Degrees 60 Degrees 120 Degrees OCUPING Fit Closest to the end of the Shaft Drive End Bearing Shaft Fit Degrees 60 Degrees 120 Degrees 4.3115 4.3116 4.3115 Drive End Bearing Shaft Fit Condition (F) Fail ODegrees 60 Degrees 120 Degrees 3.5437 3.5437 3.5438 Degrees 120 Degrees Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal	47.	Shaft Runout		0 inches
0 49. Coupling Fit Closest to Bearing Housing 0 Degrees 90 Degrees 120 Degrees 0 0 50. Coupling Fit Closest to the end of the Shaft 0 Degrees 120 Degrees 0 0 51. Drive End Bearing Shaft Fit 0 Degrees 120 Degrees 4.3115 4.3116 4.3115 52. Drive End Bearing Shaft Fit Condition (F) Fail 53. Opposite Drive End Bearing Shaft Fit (F) Fail 53. Opposite Drive End Bearing Shaft Fit (P) Pass 54. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 55. Shaft Air Seal Fits Opposite Drive End Air Seal	48.	Rotor Runout		
49. Coupling Fit Closest to Bearing Housing 0 Degrees 90 Degrees 120 Degrees 0 50. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 0 51. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 4.3115 4.3116 4.3115 52. Drive End Bearing Shaft Fit Condition (F) Fail 53. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 3.5437 3.5437 3.5438 54. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 55. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal		Drive End Bearing Fit	Rotor Body	Opposite Drive End Bearing
0 Degrees 90 Degrees 120 Degrees 0 50. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 0 51. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 4.3115 4.3116 4.3115 52. Drive End Bearing Shaft Fit Condition (F) Fail 53. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 3.5437 3.5437 3.5438 54. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 55. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal		0		
0 50. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 0 0 51. Drive End Bearing Shaft Fit 0 Degrees 120 Degrees 4.3115 4.3116 4.3115 52. Drive End Bearing Shaft Fit Condition (F) Fail 53. Opposite Drive End Bearing Shaft Fit (F) Fail 54. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 55. Shaft Air Seal Fits Opposite Drive End Air Seal	49.	Coupling Fit Closest to Bearing Housi	ng	
50. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 0 51. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 4.3115 4.3116 4.3115 52. Drive End Bearing Shaft Fit Condition (F) Fail 53. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 3.5437 3.5437 3.5437 3.5438 54. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 55. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal		0 Degrees	90 Degrees	120 Degrees
O Degrees 60 Degrees 120 Degrees O Company Company Degrees 60 Degrees 120 Degrees 4.3115 4.3116 4.3115 Drive End Bearing Shaft Fit Condition (F) Fail Degrees 60 Degrees 120 Degrees 3.5437 3.5437 3.5438 Opposite Drive End Bearing Shaft Fit Condition (P) Pass Shaft Air Seal Fits Opposite Drive End Air Seal		0		
0 51. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 4.3115 4.3116 4.3115 52. Drive End Bearing Shaft Fit Condition (F) Fail 53. Opposite Drive End Bearing Shaft Fit (F) Fail 53. Opposite Drive End Bearing Shaft Fit (F) Pail 54. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 55. Shaft Air Seal Fits Opposite Drive End Air Seal	50.	Coupling Fit Closest to the end of the	Shaft	
51. Drive End Bearing Shaft Fit 0 Degrees 120 Degrees 4.3115 4.3116 4.3115 52. Drive End Bearing Shaft Fit Condition (F) Fail 53. Opposite Drive End Bearing Shaft Fit (F) Fail 50. Degrees 60 Degrees 120 Degrees 3.5437 3.5437 3.5438 54. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 55. Shaft Air Seal Fits Drive End Air Seal Drive End Air Seal Opposite Drive End Air Seal		0 Degrees	60 Degrees	120 Degrees
0 Degrees 60 Degrees 120 Degrees 4.3115 4.3116 4.3115 52. Drive End Bearing Shaft Fit Condition (F) Fail 53. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 3.5437 3.5437 3.5437 3.5438 54. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 55. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal		0	•	•
0 Degrees 60 Degrees 120 Degrees 4.3115 4.3116 4.3115 52. Drive End Bearing Shaft Fit Condition (F) Fail 53. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 3.5437 3.5437 3.5438 54. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 55. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal	51.	Drive End Bearing Shaft Fit		
4.3115 4.3116 4.3115 4.3116 4.3115 52. Drive End Bearing Shaft Fit Condition (F) Fail 53. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 3.5437 3.5437 3.5437 3.5438 54. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 55. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal				
53. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 3.5437 3.5437 3.5438 54. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 55. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal			60 Degrees	120 Degrees
0 Degrees 60 Degrees 120 Degrees 3.5437 3.5437 3.5438 54. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 55. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal		-	-	-
0 Degrees 60 Degrees 120 Degrees 3.5437 3.5437 3.5438 54. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 55. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal	52.	4.3115	4.3116	4.3115
3.5437 3.5437 3.5437 3.5438 54. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 55. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal		4.3115 Drive End Bearing Shaft Fit Condition	4.3116	4.3115
54. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 55. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal		4.3115 Drive End Bearing Shaft Fit Condition Opposite Drive End Bearing Shaft Fit	4.3116	4.3115 (F) Fail
55. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal		4.3115Drive End Bearing Shaft Fit ConditionOpposite Drive End Bearing Shaft Fit0 Degrees	4.3116 60 Degrees	4.3115 (F) Fail
•••	53.	4.3115Drive End Bearing Shaft Fit ConditionOpposite Drive End Bearing Shaft Fit0 Degrees3.5437	4.3116 60 Degrees 3.5437	4.3115 (F) Fail 120 Degrees 3.5438
**	53. 54.	4.3115 Drive End Bearing Shaft Fit Condition Opposite Drive End Bearing Shaft Fit 0 Degrees 3.5437 Opposite Drive End Bearing Shaft Fit	4.3116 60 Degrees 3.5437	4.3115 (F) Fail 120 Degrees 3.5438
	53. 54.	4.3115 Drive End Bearing Shaft Fit Condition Opposite Drive End Bearing Shaft Fit 0 Degrees 3.5437 Opposite Drive End Bearing Shaft Fit Shaft Air Seal Fits	4.3116 60 Degrees 3.5437 Condition	4.3115 (F) Fail 120 Degrees 3.5438

Mechanical Fits- Bearing Housings

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

56	Drive End - Endbell Bearing Fit			
30.	0 Degrees	60 Degrees	120 Degrees	
	7.8761	7.876	7.8759	
5 7.			7.0759	(P) Pass
	57. Drive End - Endbell Bearing Fit Condition58. Opposite Drive End - Endbell Bearing Fit			(F) F a33
56.			120 Dograda	
	0 Degrees 7.481	60 Degrees 7.481	120 Degrees 7.4811	
5 0	Opposite Drive End - Endbell Bearing	•	7.4011	(D) Dage
59.	Bearing Cap Condition	rit Condition		(P) Pass
60.	• •	Opposite Drive Find Decrine Con		
	Drive End Bearing Cap	Opposite Drive End Bearing Cap		
04	ok End Bell Air Seal Fits	ok		
61.		Occasio Di la Fall Air Carl		
	Drive End Air Seal	Opposite Drive End Air Seal		
	ok	ok		
62.	List Machine Work Needed Below			
	Replace shaft, sleeve de			B
63.	Technician			David Mac,in
/				
Root	Cause of Failure			
64.	Failure locations			
	De bearing fit likely causing high vibrat	ions		
65.	Root cause of failure			
	Wear.			
Dynai	mic Balance Report			
66.	Rotor Weight and Balance Grade			
	Rotor Weight	Balance Grade		
67.	Initial Balance Readings			
	Drive End	Opposite Drive End		
	Final Polonos Pardinas			
68.	Final Balance Readings	Occasio Director		
	Drive End	Opposite Drive End		
60	Technician			
Rewir				
	Core Test Results - Watts loss per Po	und		
70.	Pre-Burnout	Post Burnout		
	FIE-DUITIOUL	FUSI DUITIUUI		
71.	Core Hot Spot Test			
	Pre-Burnout	Post-Burnout		
	Danioat	. cot Barriout		
72.	Post Rewind Electrical Test- Insulation	n Resistance		
73.	Post Rewind Polarization Index			

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

74.	Post Rewind Winding Resistance		
	1-2	1-3	2-3
	Post Rewind Surge Test		
	Post Rewind Hi-Pot		
	Technician		
	anical Fits- Rotor - Post Repair		
	Shaft Runout Post Repair		
79.	Rotor Runout Post Repair	Data and	Occasio Di la Fall Destina
	Drive End Bearing Fit	Rotor Body	Opposite Drive End Bearing
80.	Coupling Fit Closest to Bearing Housi	ng Post Repair	
	0 Degrees	90 Degrees	120 Degrees
	Ŭ	3	9
81.	Coupling Fit Closest to the end of the	Shaft Post Repair	
	0 Degrees	60 Degrees	120 Degrees
02	Drive End Bearing Shaft Fit Post Repa	nie.	
02.	0 Degrees	60 Degrees	120 Degrees
	0 Degrees	oo Degrees	120 Degrees
83.	Opposite Drive End Bearing Shaft Fit	Post Repair	
	0 Degrees	60 Degrees	120 Degrees
84.	Shaft Air Seal Fits Post Repair		
	Drive End Air Seal	Opposite Drive End Air Seal	
85.	Shaft Repair Sign-off		
	anical Fits- Bearing Housings - P	ost Repair	
	Drive End - Endbell Bearing Fit Post F	•	
	0 Degrees	60 Degrees	120 Degrees
			9
87.	Opposite Drive End - Endbell Bearing		
	0 Degrees	60 Degrees	120 Degrees
88.	Bearing Cap Condition Post Repair		
00.	Drive End Bearing Cap	Opposite Drive End Bearing Cap	
	Dive the Bearing Cap	Opposite Drive Line Bearing Gap	
89.	End Bell Air Seal Fits Post Repair		
	Drive End Air Seal	Opposite Drive End Air Seal	
00	E 10 110 . 0; "		
	End Bell Repair Sign-off		
Asser	QC Check All Parts for Cleanliness Pr	ior to Assembly	
91.		-	
93.		o. to dodombiy	
	Assembled Shaft Endplay		
	Assembled Shaft Runout		
50.			

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

96.	5. Test Run Voltage			
	Volts	Volts	Volts	
97.	Test Run Amperage			
	Amps	Amps	Amps	
98.	Drive End Vibration Readings - Inches	Per Second		
	Horizontal	Vertical	Axial	
99.	Opposite Drive End Vibration Readings - Inches Per Second			
	Horizontal	Vertical	Axial	
100.). Ambient Temperature - Fahrenheit			
101.	Drive End Bearing Temps - Fahrenheit			
	5 Minutes	10 Minutes	15 Minutes	
102.	Opposite Drive End Bearing Temps - I	ahrenheit		
	5 Minutes	10 Minutes	15 Minutes	
103.	Document Final Condition with Picture	es after paint		
104.	Final Pics and QC Review			

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.



STANDARD TERMS AND CONDITIONS FOR PURCHASE OF GOOD AND/OR SERVICES

- 1. APPLICABILITY. The sale of any and all goods and/or services by Mock, Inc. d/b/a Hi-Speed Industrial Service ("Hi-Speed") shall be specifically conditioned upon and subject to the following terms and conditions which are incorporated by reference into any contracts and purchase orders with Hi-Speed, and which shall form and become a part of any agreement related thereto. Buyer's acceptance of any offer or quotation made by Hi-Speed for sale of any goods or services is expressly made subject to the terms and conditions set forth herein and to be so effective, Buyer need not sign or approve these Terms and Conditions to be bound hereunder provided a copy of same is provided to Buyer through any means. None of the terms and conditions contained herein may be added to, expanded, changed, modified, superseded or otherwise altered except as revised in writing and duly executed by Hi-Speed, and all orders received by Hi-Speed shall be governed only by the terms and conditions contained herein, notwithstanding any terms, conditions or provisions of any purchase order, release order, authorization or any other form issued by the Buyer. Hi-Speed hereby objects to any additional, modified, changed, deleted, altered or other terms and conditions not contained herein and notifies Buyer that any such terms or provisions are expressly rejected by Hi-Speed.
- 2. PRICE. All quoted prices shall remain firm and binding for a period of thirty (30) days from the date of quotation or for the period specifically stated in the quotation. The price for any and all goods and/or services ordered or approved by Buyer after thirty (30) days from the date of any quotation are subject to any increase in price that may occur after the expiration of thirty (30) days from the issuance of the quotation and the date the Buyer releases any shipment.
- 3. SCOPE OF GOODS AND/OR SERVICES. The goods and/or services provided by Hi-Speed pursuant to any quotation shall be limited exclusively to those goods and/or services expressly identified therein. Hi-Speed does not assume any responsibility and/or liability for the failure to provide any other goods and/or services not identified in any quotation. Modifications, additions or deletions to or from the scope referenced in any quotation shall only bee effective if evidenced in writing and signed by Hi-Speed. The sale of any of all goods and/or services affected by such modification, addition or deletion shall be subject to these same Standard Terms and Conditions whether or not referenced therein.
- 4. <u>BILLING AND PAYMENT TERMS.</u> Hi-Speed shall invoice Buyer for all goods and/or services as same are rendered at the address listed on the quotation. Payments for all goods and/or services shall be due thirty (30) days from the date of the current invoice or as otherwise set forth in the quotation. Late payments are subject to a late fee of 5% of the total invoice amount. Recurring late payments may lead to a deposit requirement on future services or sale of goods. Buyer shall be liable to Hi-Speed for any and all fees and expenses incurred by Hi-Speed to collect any invoices or to enforce these Standard Terms and Conditions, including but not limited to, attorney's fees.
- 5. <u>DELIVERY OF GOODS AND/OR SERVICES.</u> Unless otherwise identified in the quotation, all shipments are F.O.B. Hi-Speed's warehouse and the title to and all risk of loss with respect to any goods shipped shall pass to Buyer when such goods are delivered to the carrier at Hi-Speed's warehouse. Hi-Speed will use its best efforts to affect delivery by the date or dates specified in the quotation. However, Hi-Speed shall not be liable for delay in or failure to make shipment, or to perform services, by any identified date for any reason whatsoever, including but not limited to, causes beyond its reasonable control, such as strikes, fires, floods, epidemics, quarantines, restrictions, severe weather, embargos, acts of God, or public enemy, war, riot, delays in transportation or the inability to obtain necessary labor, materials or manufacturing facilities.
- **DELIVERY SITE AND TIME FOR PERFORMANCE.** Hi-Speed and Buver agree that time is of the essence for the purchase order and that Buyer shall fully cooperate with Hi-Speed in order to allow Hi-Speed full access to prosecute its work diligently and in an orderly manner. Buyer shall assist Hi-Speed in every way possible to avoid delaying, disrupting or interfering with the progress of Hi-Speed's work at the project site. In the event Hi-Speed's work is delayed, hindered, suspended, disrupted, re-sequenced or interfered with or rendered less efficient or more costly or adversely affected in any way as a result of acts or omissions of Buyer or other contractors or employees of Buyer or by any other reason beyond Hi-Speed's control and without the fault of Hi-Speed, then, in such event, Buyer shall be liable to Hi-Speed for any damages, additional costs, expenses, labor, materials, man hours, acceleration costs, overtime, additional jobsite overhead, extended home office overhead, and any and all other direct and indirect expenses of whatsoever nature or kind, caused in whole or in part, as a result of any of the above-referenced occurrences. Hi-Speed's project records will be the basis for computing the additional costs and damages of Hi-Speed's labor, materials, expenses and overhead related to such changes. BUYER WARRANTS THAT THE SITE FOR DELIVERY OR INSTALLATION OF ANY GOODS AND/OR FOR THE PERFORMANCE OF ANY SERVICES SHALL BE READY AND ADEQUATE FOR HI-SPEED'S DELIVERY OF GOODS AND/OR PERFORMANCE OF SERVICES AND THAT HI-SPEED SHALL HAVE FULL ACCESS THERETO, FREE OF ALL OBSTRUCTIONS. BUYER SHALL ASSUME ALL EXTRA COSTS ASSOCIATED WITH HI-SPEED'S INABILITY TO INSTALL ANY GOODS OR PERFORM ANY SERVICES AS A RESULT OF BUYER'S FAILURE TO COMPLY WITH THIS PROVISION. HI-SPEED MAY NOT INSPECT THE SITE PRIOR TO DELIVERY AND/OR INSTALLATION OF GOODS AND/OR PERFORMANCE OF SERVICES AND MAKES NO WARRANTY AS TO THE SUFFICIENCY OF THE SITE FOR THE DELIVERY AND/OR INSTALLATION OF GOODS AND/OR THE PERFORMANCE OF SERVICES AT SUCH SITE.
- 7. INSPECTION/ACCEPTANCE. All goods and services ordered pursuant to any quotation shall be subject to inspection by Buyer after delivery or performance to determine conformity with the quotation and/or purchase order and Hi-Speed's advertised or published specifications. Buyer shall have a period of thirty (30) days from shipment of goods at the delivery destination specified in the quotation within which to inspect the goods for conformity with the quotation, order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. Buyer shall have a period of thirty (30) days following completion of any services within which to inspect the services for conformity with the quotation, purchase order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. If the goods delivered or services performed do not so conform, upon delivery of notice to Hi-Speed of any discrepancy, nonconformance or rejection, Hi-Speed shall have sixty (60) days to cure the alleged discrepancy and/or nonconformance. If Hi-Speed fails to cure in this time period, Buyer shall have the right to reject such goods or services. After the cure period, goods that have been delivered and rejected, in whole or in part, shall be returned to Hi-Speed. Buyer shall notify Hi-Speed and arrange for the return of the goods as required. Should such non-conforming services be rejected Hi-Speed shall, at its sole cost, re-perform the non-conforming services. Inspection or failure to inspect on any occasion shall not affect Buyer's rights under the warranty provisions herein.
- 8. WARRANTIES. Hi-Speed warrants that all goods shall conform in all material aspects to the goods identified in the quotation to Buyer and/or purchase order, and Hi-Speed makes to Buyer the manufacturer's express warranty for any goods sold to Buyer, which is offered by the manufacturer at the time of acceptance of any quotation by Buyer. This warranty is conditioned upon the installation, operation, and maintenance of the goods in accordance with the manufacturer's recommendations and/or standard industry practice and the goods at all times being operated or used under normal operating conditions for which they were designed. Hi-Speed, at its sole option, will repair or

replace any defective or non-conforming goods in accordance with the applicable manufacturer's warranty. Warranty for any defective or incorrect parts is limited to the repair or replacement of those parts. Hi-Speed warrants that all services will conform in all material respects to the description of services identified in the quotation and will be performed in a good and workmanlike manner in accordance with industry practices and standards. Should the services be reasonably rejected or not conform with the foregoing warranties, Hi-Speed shall, at its sole cost, re-perform the defective or nonconforming services. Notwithstanding the foregoing, these warranties do not extend to goods or services to the extent that such goods have been subject to misuse, neglect or abuse not caused by Hi-Speed or have been used in violation of the approved written instructions furnished to Buyer. THE FOREGOING REPRESENTS THE SOLE AND EXCLUSIVE WARRANTY GIVEN BY HI-SPEED WITH RESPECT TO ALL GOODS SOLD AND IS IN LIEU OF ALL OTHER WARRANTIES EITHER EXPRESS OR IMPLIED. HI-SPEED EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICLAR USE OR PURPOSE. BUYER WAIVES ANY CLAIM THAT THESE EXCLUSIONS OR LIMITATIONS DEPRIVE IT OF AN ADEQUATE REMEDY AT EQUITY OR LAW OR CAUSE THIS AGREEMENT TO FAIL IN ITS ESSENTIAL PURPOSE. BUYER SHALL BE ENTITLED TO NO OTHER REMEDY OTHER THAN AS SET FORTH HEREIN, REGARDLESS OF THE CLAIM OR CAUSE OF ACTION, WHETHER BASED IN CONTRACT, TORT, NEGLIGENCE, GOODS LIABILITY, STRICT LIABILITY OR OTHERWISE.

- 9. <u>LIMITATION OF DAMAGES.</u> HI-SPEED SHALL HAVE NO LIABILITY TO BUYER WITH RESPECT TO THE SALE OR DELIVERY OF ANY GOODS OR THE REPAIR THEREOF OR WITH RESPECT TO THE SALE OR PERFORMANCE OF ANY SERVICES, FOR LOST PROFITS, SPECIAL, CONSEQUENTIAL, EXEMPLARY, PUNITIVE OR INCIDENTAL DAMAGES OF ANY KIND OR NATURE WHETHER ARISING IN CONTRACT, TORT, GOODS LIABILITY OR OTHERWISE, EVEN IF HI-SPEED WAS ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGES. HI-SPEED SHALL NOT BE LIABLE FOR ANY DAMAGES OR DELAYS CAUSED BY ANY FAILURE TO MAKE ANY DELIVERY OF GOODS BY ANY EXPECTED TIME OR DATE OR THE FAILURE TO PROVIDE OR COMPLETE ANY SERVICES BY ANY EXPECTED DATE OR TIME. IN NO EVENT SHALL HI-SPEED BE LIABLE TO BUYER FOR ANY DAMAGES WHATSOEVER IN EXCESS OF THE TOTAL PRICE PAID FOR ALL GOODS AND/OR SERVICES HEREUNDER OR REFERENCED IN ANY QUOTATION OR THE PURCHASE ORDER.
- 10. <u>SEVERABILITY.</u> The partial or complete invalidity of any provision of these Standard Terms and Conditions shall not affect the enforceability of the remainder of these Standard Terms and Conditions. If any provision is found to be invalid or unenforceable, that portion shall be modified to make it enforceable or shall be stricken and the remainder of these Standard Terms and Conditions shall enforced.
- 11. **GOVERNING LAW AND JURISDICTION.** Any controversy arising out of any quotation, the purchase order, the goods sold or delivered, repair or replacement thereof, or any services provided pursuant to any quotation or any purchase order, or these Standard Terms and Conditions shall be governed by the laws of the state of Tennessee without regard to any choice of law provisions and any cause of action related in any manner thereto shall be brought only in the state or federal courts of Shelby County, Tennessee.
- 12. ABANDONED EQUIPMENT. Hi-Speed requires that Buyer promptly pick up or provide shipment instructions for Buyer equipment or other Buyer property in Hi-Speed's possession. If equipment or other Buyer property is left with Hi-Speed and not picked up within six (6) months after Hi-Speed's final action related to the applicable property (e.g. evaluation, teardown, estimate, completion of services), Hi-Speed will consider such property abandoned and may dispose of it in accordance with applicable law. Buyer agrees to hold Hi-Speed harmless for any damage or claim for such abandoned property and acknowledges that Hi-Speed may discard or recycle it at Hi-Speed's sole and absolute discretion. Specifically, Hi-Speed may sell Buyer's abandoned property at a private or public sale and retain the proceeds to offset Hi-Speed's storage, inspection and servicing costs. For the avoidance of doubt, Hi-Speed reserves its statutory and other lawful liens for unpaid charges related to abandoned property.
- 13. FORCE MAJEURE. Neither party shall be responsible for any delay or failure in performance of any party of the quotation, purchase order or these Standard Terms and Conditions to the extent that such delays or failures are caused by fire, flood, earth quake, explosion, war, embargo, government requirement, civil or military authority, acts of God, or any other circumstances beyond its reasonable control and not involving any fault or negligence on the party affected ("Condition"). If any such Condition occurs, the party delayed or unable to perform shall promptly give written notice to the other party and, if such Condition remains at the end of thirty (30) days, the party affected by the other party's delay and inability to perform may elect to (i) terminate such order or part thereof, or (ii) suspend the order for the duration of the Condition, if the Buyer is the suspending party, buy elsewhere comparable material to be sold under the order and apply to any commitment the purchase price of such purchase, and resume performance of the order once the Condition ceases, with an option in the affected party to extend the period of this order up to the length of the time the Condition endures.
- 14. <u>NONWAIVER.</u> No course of dealing or failure of either party to strictly enforce any term, right, or condition of these Standard Terms and Conditions will be construed as a waiver of such term, right or condition. Any waiver by Hi-Speed will only be in writing and will waive no succeeding breach of a term, right or condition.
- 15. **ASSIGNMENT.** The rights and obligations of the parties shall neither be assigned nor delegated without the prior written consent of the other party. However, any party may assign or delegate its respective rights and obligations, in whole or in part, (i) to any subsidiary, (ii) pursuant to other financing, merger or reorganization or (iii) pursuant to any sale or transfer of substantially all of the assets of the assigning party. These Standard Terms and Conditions shall bind the heirs, successors and assigns of the parties hereto.
- 16. NO INDIVIDUAL LIABILITY. Notwithstanding any other agreement to the contrary, the Buyer agrees that in no event will the Buyer hold and HI-Speed owner, director, officer or employee personally liable for unintentional tortious conduct or conduct that constitutes the breach of any contract between HI-Speed and the Buyer, even if the HI-Speed owner, director, officer or employee is or could be construed to be a party to such contract.