

# LR Motor Shop Repairs

## **Job Number 101130**

Prepared for Twin Rivers

1701 Jefferson Parkway White Hall AR 71602

### **Table of Contents**

AC Recondition As Found - MOTOR SHOP LR

AC Recondition - Rev. 2: R97 DRN90S4/DH

1.0



FolderID: 101130

FormID: 16285352



#### **AC Recondition As Found**

**Twin Rivers** 

1701 Jefferson Parkway White Hall, AR 71602

AC Recondition - Rev. 2

MOTOR SHOP LR Location:

Serial Number: R97 DRN90S4/DH

Description: 1.5HP SEW EURODRIVE 1800RPM

Hi-Speed Job Number:	101130
Manufacturer:	SEW Eurodrive
Product Number:	R97 DRN90S4/DH
Spec/ID #:	NO TAG
Serial Number:	N/A
HP/kW:	1.5 (HP)
RPM:	1762 (RPM)
Frame:	90S
Voltage:	230 / 460
Current:	4.6/2.3
Phase:	Three
Hz:	60 (Hz)
Service Factor:	1.15
Enclosure:	TEFC
J-box Included:	Complete
Coupling/Sheave:	Coupling
Bearing RTDs:	No
Stator RTDs:	No
Repair Stage:	Final
Heaters:	No
Winding Type :	Random Wound
Bearing Type:	Rolling Element

Priorities Found: 1 - High

7 - Good

#### **Overall Condition**

Report Date

Nameplate Picture



#### 3. Photos of all six sides of the machine.






























4.	Describe the Overall Condition of the Equipment as Received	
	Dirty, can smell burnt windings	
5.	Distance from the end of the shaft to the Coupling/Sheave	inches
Initial	Mechanical/Electrical	
<ul><li>6.</li></ul>	Does Shaft Turn Freely?	(Yes) Yes
7.	Does Shaft Have Visible Damage?	(No) No
8.	Assembled Shaft Runout	
9.	Assembled Shaft End Play	
10.	Air Gap Variation <10%	
<ul><li>11.</li></ul>	Lead Condition	(P) Pass
12.	Lead Length	8 Inches
13.	Frame Condition	
<b>1</b> 4.	Fan Condition	(P) Pass
15.	Broken or Missing Components	
Initial	Electrical Inspection	
16.	Insulation Resistance/Megger	0 Megohms
17.	Winding Resistance	
	1-2 1-3	2-3
	D ( 0 T )	( <del>-</del> ) - "
<b>18.</b>	Perform Surge Test	(F) Fail
19.	Number of Stator Slots	
	Stator Condition	rewind
	anical Inspection	
	Drive End Bearing Brand	nsk
22.	Drive End Bearing Number-	6305du
23.	- We - we - coming any	(Pall) Pall Pagging
24.		(Ball) Ball Bearing
25.	Drive End Lubrication Type	(Grease) Grease Lubricated
26.	Drive End Bearing Insulation or Grounding Device?	
27. 28.	Drive End Wavy Washer/Snap-Ring Other Retention Device?	snap rings
	3 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	worn
29. 30.	Opposite Drive End Bearing Brand	nsk 6205du
	Opposite Drive End Bearing Number-	6205du
31.	Opposite Drive End Bearing Type	•
32.	Opposite Drive End Bearing Type	(Ball) Ball Bearing

(Grease) Grease Lubricated	9	Opposite Drive End Lubrication Ty	33.
	on or Grounding Device?	Opposite Drive End Bearing Insula	34.
wavy washer	nap-Ring Other Retention Device?	Opposite Drive End Wavy Washe	35.
worn	n	Opposite Drive End Bearing Cond	36.
25x40x7		Drive End Seal	37.
18x35x7		Opposite Drive End Seal	38.
		Inspection	Rotor
(Squirrel Aluminum) Squirrel Cage Aluminum Die Cast		Rotor Type/Material	39.
(Pass) Pass		Growler Test	40.
28		Number of Rotor Bars	41.
		Rotor Condition	42.
	Below	List the Parts needed for the Repa 6305 2rsr 6205 2rsr Seals Rewind	43.
Trevor Hall	embled Motor	Signature of Technician that Disas	44.
		anical Fits- Rotor	
0.0005 inches		Shaft Runout	45.
		Shaft Runout Rotor Runout	45.
0.0005 inches Opposite Drive End Bearing	Rotor Body	Shaft Runout	45.
	·	Shaft Runout Rotor Runout Drive End Bearing Fit	45. 46.
Opposite Drive End Bearing	sing	Shaft Runout Rotor Runout Drive End Bearing Fit Coupling Fit Closest to Bearing He	45.
	·	Shaft Runout Rotor Runout Drive End Bearing Fit	45. 46.
Opposite Drive End Bearing	sing 90 Degrees	Shaft Runout Rotor Runout Drive End Bearing Fit Coupling Fit Closest to Bearing He 0 Degrees	45. 46.
Opposite Drive End Bearing	sing 90 Degrees	Shaft Runout Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing He 0 Degrees	45. 46. 47.
Opposite Drive End Bearing  120 Degrees	sing 90 Degrees e Shaft	Shaft Runout Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing He 0 Degrees  Coupling Fit Closest to the end of 0 Degrees	45. 46. 47.
Opposite Drive End Bearing  120 Degrees  120 Degrees	sing 90 Degrees e Shaft 60 Degrees	Shaft Runout Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing Ho 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit	45. 46. 47.
Opposite Drive End Bearing  120 Degrees  120 Degrees  120 Degrees	sing 90 Degrees e Shaft 60 Degrees 60 Degrees	Shaft Runout Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing He 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees	45. 46. 47.
Opposite Drive End Bearing  120 Degrees  120 Degrees  120 Degrees  0.9847	sing 90 Degrees e Shaft 60 Degrees 60 Degrees 0.9847	Shaft Runout Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing He 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  0.9847	45. 46. 47. 48.
Opposite Drive End Bearing  120 Degrees  120 Degrees  120 Degrees	sing 90 Degrees e Shaft 60 Degrees 60 Degrees 0.9847	Shaft Runout Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing He 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  0.9847  Drive End Bearing Shaft Fit Condi	45. 46. 47. 48. 49.
Opposite Drive End Bearing  120 Degrees  120 Degrees  120 Degrees  0.9847  (P) Pass	sing 90 Degrees e Shaft 60 Degrees 60 Degrees 0.9847	Shaft Runout Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing He 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  0.9847  Drive End Bearing Shaft Fit Condition Opposite Drive End Bearing Shaft	45. 46. 47. 48. 49.
Opposite Drive End Bearing  120 Degrees  120 Degrees  120 Degrees  0.9847  (P) Pass	sing 90 Degrees Shaft 60 Degrees 60 Degrees 0.9847 n t 60 Degrees	Shaft Runout Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing He 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  0.9847  Drive End Bearing Shaft Fit Condit Opposite Drive End Bearing Shaft 0 Degrees	45. 46. 47. 48. 49.
Opposite Drive End Bearing  120 Degrees  120 Degrees  120 Degrees  0.9847  (P) Pass  120 Degrees  0.9847	sing 90 Degrees Shaft 60 Degrees 60 Degrees 0.9847 60 Degrees 0.9847	Shaft Runout Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing He 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  0.9847  Drive End Bearing Shaft Fit Condit Opposite Drive End Bearing Shaft 0 Degrees  0.9847	45. 46. 47. 48. 49. 50. 51.
Opposite Drive End Bearing  120 Degrees  120 Degrees  120 Degrees  0.9847  (P) Pass	sing 90 Degrees Shaft 60 Degrees 60 Degrees 0.9847 60 Degrees 0.9847	Shaft Runout Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing He 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  0.9847  Drive End Bearing Shaft Fit Condi Opposite Drive End Bearing Shaft 0 Degrees  0.9847  Opposite Drive End Bearing Shaft 0 Degrees	45. 46. 47. 48. 49. 50. 51.
Opposite Drive End Bearing  120 Degrees  120 Degrees  120 Degrees  0.9847  (P) Pass  120 Degrees  0.9847	sing 90 Degrees  Shaft 60 Degrees  60 Degrees  0.9847  t 60 Degrees  0.9847  t Condition	Shaft Runout Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing He 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  0.9847  Drive End Bearing Shaft Fit Condit Opposite Drive End Bearing Shaft 0 Degrees  0.9847  Opposite Drive End Bearing Shaft Shaft Air Seal Fits	45. 46. 47. 48. 49. 50. 51.
Opposite Drive End Bearing  120 Degrees  120 Degrees  120 Degrees  0.9847  (P) Pass  120 Degrees  0.9847	sing 90 Degrees Shaft 60 Degrees 60 Degrees 0.9847 60 Degrees 0.9847	Shaft Runout Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing He 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  0.9847  Drive End Bearing Shaft Fit Condi Opposite Drive End Bearing Shaft 0 Degrees  0.9847  Opposite Drive End Bearing Shaft 0 Degrees	45. 46. 47. 48. 49. 50. 51.
Opposite Drive End Bearing  120 Degrees  120 Degrees  120 Degrees  0.9847  (P) Pass  120 Degrees  0.9847	sing 90 Degrees  Shaft 60 Degrees  60 Degrees  0.9847  t 60 Degrees  0.9847  t Condition	Shaft Runout Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing He 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  0.9847  Drive End Bearing Shaft Fit Condit Opposite Drive End Bearing Shaft 0 Degrees  0.9847  Opposite Drive End Bearing Shaft Shaft Air Seal Fits	45. 46. 47. 48. 49. 50. 51.
Opposite Drive End Bearing  120 Degrees  120 Degrees  120 Degrees  0.9847  (P) Pass  120 Degrees  0.9847	sing 90 Degrees  Shaft 60 Degrees  60 Degrees  0.9847  t 60 Degrees  0.9847  t Condition	Shaft Runout Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing He 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  0.9847  Drive End Bearing Shaft Fit Condi Opposite Drive End Bearing Shaft 0 Degrees  0.9847  Opposite Drive End Bearing Shaft Shaft Air Seal Fits Drive End Air Seal	45. 46. 47. 48. 49. 50. 51. 52. 53.
Opposite Drive End Bearing  120 Degrees  120 Degrees  120 Degrees  0.9847  (P) Pass  120 Degrees  0.9847	sing 90 Degrees  Shaft 60 Degrees  60 Degrees  0.9847  t 60 Degrees  0.9847  t Condition	Shaft Runout Rotor Runout Drive End Bearing Fit  Coupling Fit Closest to Bearing He 0 Degrees  Coupling Fit Closest to the end of 0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  0.9847 Drive End Bearing Shaft Fit Condit Opposite Drive End Bearing Shaft 0 Degrees  0.9847 Opposite Drive End Bearing Shaft Shaft Air Seal Fits Drive End Air Seal	45. 46. 47. 48. 49. 50. 51. 52. 53.

56	Opposite Drive End - Endbell Bearing	□i+	
50.	•		120 Degrees
	0 Degrees	60 Degrees	120 Degrees
<b>57</b>	2.0475 Opposite Drive End - Endbell Bearing	2.0475	2.0475 (P) Pass
	Bearing Cap Condition	Fit Collation	(F) Fd55
56.	· ·	Opposite Drive End Bearing Can	
	Drive End Bearing Cap	Opposite Drive End Bearing Cap	
59.	End Bell Air Seal Fits		
	Drive End Air Seal	Opposite Drive End Air Seal	
		·	
60.	List Machine Work Needed Below		
61.	Technician		
Dynar	mic Balance Report		
62.	Rotor Weight and Balance Grade		
	Rotor Weight	Balance Grade	
00	Initial Dalance Description		
63.	Initial Balance Readings	Opposite Drive Fod	
	Drive End	Opposite Drive End	
64.	Final Balance Readings		
	Drive End	Opposite Drive End	
65.	Technician		
Rewir	nd		
66.	Core Test Results - Watts loss per Po	und	
	Pre-Burnout	Post Burnout	
67	Core Hot Spot Test		
07.	Pre-Burnout	Post-Burnout	
	Fie-Buillout	rost-bulliout	
68.	Post Rewind Electrical Test- Insulation	n Resistance	
69.	Post Rewind Polarization Index		
70.	Post Rewind Winding Resistance		
	1-2	1-3	2-3
	Post Rewind Surge Test		
72.			
_	Technician		
	Cause of Failure		
	Failure locations Root cause of failure		
	anical Fits- Rotor - Post Repair		
	Shaft Runout Post Repair Rotor Runout Post Repair		
11.	Drive End Bearing Fit	Rotor Body	Opposite Drive End Bearing
	Drive Life Dearing Fit	Notor Body	Opposite Drive Life bearing
78.	Coupling Fit Closest to Bearing Housi	ng Post Repair	
	0 Degrees	90 Degrees	120 Degrees
			•

79. Coupling Fit Closest to the end of the Shaft Post Repair 0 Degrees 60 Degrees 120 Degrees	
0 Degrees 60 Degrees 120 Degrees	
	S
80. Drive End Bearing Shaft Fit Post Repair	
0 Degrees 60 Degrees 120 Degrees	S
94 Opposite Drive End Bearing Chaft Fit Deet Depair	
81. Opposite Drive End Bearing Shaft Fit Post Repair	
0 Degrees 60 Degrees 120 Degrees	S
82. Shaft Air Seal Fits Post Repair	
Drive End Air Seal Opposite Drive End Air Seal	
83. Shaft Repair Sign-off	
Mechanical Fits- Bearing Housings - Post Repair	
84. Drive End - Endbell Bearing Fit Post Repair	
0 Degrees 60 Degrees 120 Degrees	S
85. Opposite Drive End - Endbell Bearing Fit Post Repair	
0 Degrees 60 Degrees 120 Degrees	5
86. Bearing Cap Condition Post Repair	
Drive End Bearing Cap Opposite Drive End Bearing Cap	
87. End Bell Air Seal Fits Post Repair	
Drive End Air Seal Opposite Drive End Air Seal	
88. End Bell Repair Sign-off	
Assembly	
89. QC Check All Parts for Cleanliness Prior to Assembly	









91. Final Insulation Resistance Test

92. Assembled Shaft Endplay

93. Assembled Shaft Runout

94. Test Run Voltage

Volts

Volts

Volts

Volts

Volts

Volts



95.	Test Run Amperage		
	Amps	Amps	Amps
	1.8	1.7	1.8



96. Drive End Vibration Readings - Inches Per Second			
	Horizontal	Vertical	Axial
97.	97. Opposite Drive End Vibration Readings - Inches Per Second		
	Horizontal	Vertical	Axial
98.	Ambient Temperature - Fahrenheit		
99.	9. Drive End Bearing Temps - Fahrenheit		
	5 Minutes	10 Minutes	15 Minutes
100.	100. Opposite Drive End Bearing Temps - Fahrenheit		
	5 Minutes	10 Minutes	15 Minutes
101.	101. Document Final Condition with Pictures after paint		







102. Final Pics and QC Review

RW

RW



#### STANDARD TERMS AND CONDITIONS FOR PURCHASE OF GOOD AND/OR SERVICES

- 1. APPLICABILITY. The sale of any and all goods and/or services by Mock, Inc. d/b/a Hi-Speed Industrial Service ("Hi-Speed") shall be specifically conditioned upon and subject to the following terms and conditions which are incorporated by reference into any contracts and purchase orders with Hi-Speed, and which shall form and become a part of any agreement related thereto. Buyer's acceptance of any offer or quotation made by Hi-Speed for sale of any goods or services is expressly made subject to the terms and conditions set forth herein and to be so effective, Buyer need not sign or approve these Terms and Conditions to be bound hereunder provided a copy of same is provided to Buyer through any means. None of the terms and conditions contained herein may be added to, expanded, changed, modified, superseded or otherwise altered except as revised in writing and duly executed by Hi-Speed, and all orders received by Hi-Speed shall be governed only by the terms and conditions contained herein, notwithstanding any terms, conditions or provisions of any purchase order, release order, authorization or any other form issued by the Buyer. Hi-Speed hereby objects to any additional, modified, changed, deleted, altered or other terms and conditions not contained herein and notifies Buyer that any such terms or provisions are expressly rejected by Hi-Speed.
- 2. PRICE. All quoted prices shall remain firm and binding for a period of thirty (30) days from the date of quotation or for the period specifically stated in the quotation. The price for any and all goods and/or services ordered or approved by Buyer after thirty (30) days from the date of any quotation are subject to any increase in price that may occur after the expiration of thirty (30) days from the issuance of the quotation and the date the Buyer releases any shipment.
- 3. SCOPE OF GOODS AND/OR SERVICES. The goods and/or services provided by Hi-Speed pursuant to any quotation shall be limited exclusively to those goods and/or services expressly identified therein. Hi-Speed does not assume any responsibility and/or liability for the failure to provide any other goods and/or services not identified in any quotation. Modifications, additions or deletions to or from the scope referenced in any quotation shall only bee effective if evidenced in writing and signed by Hi-Speed. The sale of any of all goods and/or services affected by such modification, addition or deletion shall be subject to these same Standard Terms and Conditions whether or not referenced therein.
- 4. <u>BILLING AND PAYMENT TERMS.</u> Hi-Speed shall invoice Buyer for all goods and/or services as same are rendered at the address listed on the quotation. Payments for all goods and/or services shall be due thirty (30) days from the date of the current invoice or as otherwise set forth in the quotation. Late payments are subject to a late fee of 5% of the total invoice amount. Recurring late payments may lead to a deposit requirement on future services or sale of goods. Buyer shall be liable to Hi-Speed for any and all fees and expenses incurred by Hi-Speed to collect any invoices or to enforce these Standard Terms and Conditions, including but not limited to, attorney's fees.
- 5. <u>DELIVERY OF GOODS AND/OR SERVICES.</u> Unless otherwise identified in the quotation, all shipments are F.O.B. Hi-Speed's warehouse and the title to and all risk of loss with respect to any goods shipped shall pass to Buyer when such goods are delivered to the carrier at Hi-Speed's warehouse. Hi-Speed will use its best efforts to affect delivery by the date or dates specified in the quotation. However, Hi-Speed shall not be liable for delay in or failure to make shipment, or to perform services, by any identified date for any reason whatsoever, including but not limited to, causes beyond its reasonable control, such as strikes, fires, floods, epidemics, quarantines, restrictions, severe weather, embargos, acts of God, or public enemy, war, riot, delays in transportation or the inability to obtain necessary labor, materials or manufacturing facilities.
- **DELIVERY SITE AND TIME FOR PERFORMANCE.** Hi-Speed and Buver agree that time is of the essence for the purchase order and that Buyer shall fully cooperate with Hi-Speed in order to allow Hi-Speed full access to prosecute its work diligently and in an orderly manner. Buyer shall assist Hi-Speed in every way possible to avoid delaying, disrupting or interfering with the progress of Hi-Speed's work at the project site. In the event Hi-Speed's work is delayed, hindered, suspended, disrupted, re-sequenced or interfered with or rendered less efficient or more costly or adversely affected in any way as a result of acts or omissions of Buyer or other contractors or employees of Buyer or by any other reason beyond Hi-Speed's control and without the fault of Hi-Speed, then, in such event, Buyer shall be liable to Hi-Speed for any damages, additional costs, expenses, labor, materials, man hours, acceleration costs, overtime, additional jobsite overhead, extended home office overhead, and any and all other direct and indirect expenses of whatsoever nature or kind, caused in whole or in part, as a result of any of the above-referenced occurrences. Hi-Speed's project records will be the basis for computing the additional costs and damages of Hi-Speed's labor, materials, expenses and overhead related to such changes. BUYER WARRANTS THAT THE SITE FOR DELIVERY OR INSTALLATION OF ANY GOODS AND/OR FOR THE PERFORMANCE OF ANY SERVICES SHALL BE READY AND ADEQUATE FOR HI-SPEED'S DELIVERY OF GOODS AND/OR PERFORMANCE OF SERVICES AND THAT HI-SPEED SHALL HAVE FULL ACCESS THERETO, FREE OF ALL OBSTRUCTIONS. BUYER SHALL ASSUME ALL EXTRA COSTS ASSOCIATED WITH HI-SPEED'S INABILITY TO INSTALL ANY GOODS OR PERFORM ANY SERVICES AS A RESULT OF BUYER'S FAILURE TO COMPLY WITH THIS PROVISION. HI-SPEED MAY NOT INSPECT THE SITE PRIOR TO DELIVERY AND/OR INSTALLATION OF GOODS AND/OR PERFORMANCE OF SERVICES AND MAKES NO WARRANTY AS TO THE SUFFICIENCY OF THE SITE FOR THE DELIVERY AND/OR INSTALLATION OF GOODS AND/OR THE PERFORMANCE OF SERVICES AT SUCH SITE.
- 7. INSPECTION/ACCEPTANCE. All goods and services ordered pursuant to any quotation shall be subject to inspection by Buyer after delivery or performance to determine conformity with the quotation and/or purchase order and Hi-Speed's advertised or published specifications. Buyer shall have a period of thirty (30) days from shipment of goods at the delivery destination specified in the quotation within which to inspect the goods for conformity with the quotation, order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. Buyer shall have a period of thirty (30) days following completion of any services within which to inspect the services for conformity with the quotation, purchase order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. If the goods delivered or services performed do not so conform, upon delivery of notice to Hi-Speed of any discrepancy, nonconformance or rejection, Hi-Speed shall have sixty (60) days to cure the alleged discrepancy and/or nonconformance. If Hi-Speed fails to cure in this time period, Buyer shall have the right to reject such goods or services. After the cure period, goods that have been delivered and rejected, in whole or in part, shall be returned to Hi-Speed. Buyer shall notify Hi-Speed and arrange for the return of the goods as required. Should such non-conforming services be rejected Hi-Speed shall, at its sole cost, re-perform the non-conforming services. Inspection or failure to inspect on any occasion shall not affect Buyer's rights under the warranty provisions herein.
- 8. <u>WARRANTIES.</u> Hi-Speed warrants that all goods shall conform in all material aspects to the goods identified in the quotation to Buyer and/or purchase order, and Hi-Speed makes to Buyer the manufacturer's express warranty for any goods sold to Buyer, which is offered by the manufacturer at the time of acceptance of any quotation by Buyer. This warranty is conditioned upon the installation, operation, and maintenance of the goods in accordance with the manufacturer's recommendations and/or standard industry practice and the goods at all times being operated or used under normal operating conditions for which they were designed. Hi-Speed, at its sole option, will repair or

replace any defective or non-conforming goods in accordance with the applicable manufacturer's warranty. Warranty for any defective or incorrect parts is limited to the repair or replacement of those parts. Hi-Speed warrants that all services will conform in all material respects to the description of services identified in the quotation and will be performed in a good and workmanlike manner in accordance with industry practices and standards. Should the services be reasonably rejected or not conform with the foregoing warranties, Hi-Speed shall, at its sole cost, re-perform the defective or nonconforming services. Notwithstanding the foregoing, these warranties do not extend to goods or services to the extent that such goods have been subject to misuse, neglect or abuse not caused by Hi-Speed or have been used in violation of the approved written instructions furnished to Buyer. THE FOREGOING REPRESENTS THE SOLE AND EXCLUSIVE WARRANTY GIVEN BY HI-SPEED WITH RESPECT TO ALL GOODS SOLD AND IS IN LIEU OF ALL OTHER WARRANTIES EITHER EXPRESS OR IMPLIED. HI-SPEED EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICLAR USE OR PURPOSE. BUYER WAIVES ANY CLAIM THAT THESE EXCLUSIONS OR LIMITATIONS DEPRIVE IT OF AN ADEQUATE REMEDY AT EQUITY OR LAW OR CAUSE THIS AGREEMENT TO FAIL IN ITS ESSENTIAL PURPOSE. BUYER SHALL BE ENTITLED TO NO OTHER REMEDY OTHER THAN AS SET FORTH HEREIN, REGARDLESS OF THE CLAIM OR CAUSE OF ACTION, WHETHER BASED IN CONTRACT, TORT, NEGLIGENCE, GOODS LIABILITY, STRICT LIABILITY OR OTHERWISE.

- 9. <u>LIMITATION OF DAMAGES.</u> HI-SPEED SHALL HAVE NO LIABILITY TO BUYER WITH RESPECT TO THE SALE OR DELIVERY OF ANY GOODS OR THE REPAIR THEREOF OR WITH RESPECT TO THE SALE OR PERFORMANCE OF ANY SERVICES, FOR LOST PROFITS, SPECIAL, CONSEQUENTIAL, EXEMPLARY, PUNITIVE OR INCIDENTAL DAMAGES OF ANY KIND OR NATURE WHETHER ARISING IN CONTRACT, TORT, GOODS LIABILITY OR OTHERWISE, EVEN IF HI-SPEED WAS ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGES. HI-SPEED SHALL NOT BE LIABLE FOR ANY DAMAGES OR DELAYS CAUSED BY ANY FAILURE TO MAKE ANY DELIVERY OF GOODS BY ANY EXPECTED TIME OR DATE OR THE FAILURE TO PROVIDE OR COMPLETE ANY SERVICES BY ANY EXPECTED DATE OR TIME. IN NO EVENT SHALL HI-SPEED BE LIABLE TO BUYER FOR ANY DAMAGES WHATSOEVER IN EXCESS OF THE TOTAL PRICE PAID FOR ALL GOODS AND/OR SERVICES HEREUNDER OR REFERENCED IN ANY QUOTATION OR THE PURCHASE ORDER.
- 10. <u>SEVERABILITY.</u> The partial or complete invalidity of any provision of these Standard Terms and Conditions shall not affect the enforceability of the remainder of these Standard Terms and Conditions. If any provision is found to be invalid or unenforceable, that portion shall be modified to make it enforceable or shall be stricken and the remainder of these Standard Terms and Conditions shall enforced.
- 11. **GOVERNING LAW AND JURISDICTION.** Any controversy arising out of any quotation, the purchase order, the goods sold or delivered, repair or replacement thereof, or any services provided pursuant to any quotation or any purchase order, or these Standard Terms and Conditions shall be governed by the laws of the state of Tennessee without regard to any choice of law provisions and any cause of action related in any manner thereto shall be brought only in the state or federal courts of Shelby County, Tennessee.
- 12. ABANDONED EQUIPMENT. Hi-Speed requires that Buyer promptly pick up or provide shipment instructions for Buyer equipment or other Buyer property in Hi-Speed's possession. If equipment or other Buyer property is left with Hi-Speed and not picked up within six (6) months after Hi-Speed's final action related to the applicable property (e.g. evaluation, teardown, estimate, completion of services), Hi-Speed will consider such property abandoned and may dispose of it in accordance with applicable law. Buyer agrees to hold Hi-Speed harmless for any damage or claim for such abandoned property and acknowledges that Hi-Speed may discard or recycle it at Hi-Speed's sole and absolute discretion. Specifically, Hi-Speed may sell Buyer's abandoned property at a private or public sale and retain the proceeds to offset Hi-Speed's storage, inspection and servicing costs. For the avoidance of doubt, Hi-Speed reserves its statutory and other lawful liens for unpaid charges related to abandoned property.
- 13. FORCE MAJEURE. Neither party shall be responsible for any delay or failure in performance of any party of the quotation, purchase order or these Standard Terms and Conditions to the extent that such delays or failures are caused by fire, flood, earth quake, explosion, war, embargo, government requirement, civil or military authority, acts of God, or any other circumstances beyond its reasonable control and not involving any fault or negligence on the party affected ("Condition"). If any such Condition occurs, the party delayed or unable to perform shall promptly give written notice to the other party and, if such Condition remains at the end of thirty (30) days, the party affected by the other party's delay and inability to perform may elect to (i) terminate such order or part thereof, or (ii) suspend the order for the duration of the Condition, if the Buyer is the suspending party, buy elsewhere comparable material to be sold under the order and apply to any commitment the purchase price of such purchase, and resume performance of the order once the Condition ceases, with an option in the affected party to extend the period of this order up to the length of the time the Condition endures.
- 14. <u>NONWAIVER.</u> No course of dealing or failure of either party to strictly enforce any term, right, or condition of these Standard Terms and Conditions will be construed as a waiver of such term, right or condition. Any waiver by Hi-Speed will only be in writing and will waive no succeeding breach of a term, right or condition.
- 15. **ASSIGNMENT.** The rights and obligations of the parties shall neither be assigned nor delegated without the prior written consent of the other party. However, any party may assign or delegate its respective rights and obligations, in whole or in part, (i) to any subsidiary, (ii) pursuant to other financing, merger or reorganization or (iii) pursuant to any sale or transfer of substantially all of the assets of the assigning party. These Standard Terms and Conditions shall bind the heirs, successors and assigns of the parties hereto.
- 16. NO INDIVIDUAL LIABILITY. Notwithstanding any other agreement to the contrary, the Buyer agrees that in no event will the Buyer hold and HI-Speed owner, director, officer or employee personally liable for unintentional tortious conduct or conduct that constitutes the breach of any contract between HI-Speed and the Buyer, even if the HI-Speed owner, director, officer or employee is or could be construed to be a party to such contract.