

# EVERY DAY SINCE 1946

LR Motor Shop Repairs

## Job Number 103603

Prepared for Baldor Warranty Division

685 Mid America Blvd Hot Springs AR 71913

### Table of Contents

AC Inspection as Found - MOTOR SHOP LR



Hi-Speed Industrial Service 7030 Ryburn Dr Millington, Tn 38053 901-873-5300

> FolderID: 103603 FormID: 21834033

#### **AC Inspection as Found**

Baldor Warranty Division 685 Mid America Blvd Hot Springs, AR 71913

#### AC Inspection - Rev. 2

Location:	MOTOR SHOP LR	
Serial Number:	F2401221847	

Description:1HP BALDOR 1770RPM

Hi-Speed Job Number:	103603
Manufacturer:	Baldor
Product Number:	CATL EM3546T
Spec/ID #:	35AA001G004G1
Serial Number:	F2401221847
HP/kW:	1 (HP)
RPM:	1770 (RPM)
Frame:	143T
Voltage:	230 / 460
Phase:	Three
Hz:	60 (Hz)
Service Factor:	1.15
Enclosure:	TEFC
# of Leads:	9
J-box Included:	Complete
Coupling/Sheave:	None
Date Received:	10/02/2024
Bearing RTDs:	No
Stator RTDs:	No
Repair Stage:	Final
Rewind:	Yes
Shaft Machined Fit Repairs Required:	No
Bearing Housing Machined Fit Repairs Required:	No
Heaters:	No
Winding Type :	Random Wound
Bearing Type:	Rolling Element

Priorities Found: 🔵 5 - High

🔵 7 - Good

#### **Overall Condition**

1. Report Date

12/31/2024

#### 2. Nameplate Picture



3. Photos of all six sides of the machine.






























4.	Describe the Overall Condition	on of the Equipment as Received		
	Dirty			
Initia	I Mechanical/Electrical			
5.	Does Shaft Turn Freely?			(Y) Yes
6.	Does the shaft require T.I.R	n Lathe to identify additional repairs?		(No) No
7.	Does Shaft Have Visible Dar	nage?		
8.	Assembled Shaft Runout			0 Inches
9.	Assembled Shaft End Play			inches
10.	Air Gap Variation <10%			
11.	Lead Condition			(P) Pass
12.	Lead Length			14 Inches
13.	Does it have Lugs?, If so wh	at is the Stud Size?		(No) No
14.	Lead Numbers			1-9
<b>)</b> 15.	Frame Condition			
<b>1</b> 6.	Fan Condition			(P) Pass
17.	Broken or Missing Compone	nts		
Initia	I Electrical Inspection			
<b>)</b> 18.	Insulation Resistance/Megge	r		Megohms
9 19.	Winding Resistance			
	1-2	1-3	2-3	
20.	Perform Surge Test			(F) Fail

21.	Number of Stator Slots			
	Stator Condition			
	Stator Thermistors/Ohms			
24.	Stator Overloads/Ohms			
Mech	anical Inspection			
	Drive End Bearing Brand			
26.				
27.	Drive End Bearing Qty.			
28.	Drive End Bearing Type			
29.	Drive End Lubrication Type			
30.	Drive End Bearing Insulation or Grou	nding Device?		
31.	Drive End Wavy Washer/Snap-Ring	Other Retention Device?		
32.	Drive End Bearing Condition			
33.	Opposite Drive End Bearing Brand			
34.	-11			
35.	11 0 3			
	Opposite Drive End Bearing Type			
	Opposite Drive End Lubrication Type			
38.				
39.	11 7			
40.				
	Drive End Seal			
	. Opposite Drive End Seal			
	Inspection			
	Rotor Type/Material Growler Test			
	Number of Rotor Bars Rotor Condition			
	List the Parts needed for the Repair Below			
	Signature of Technician that Disassembled Motor			
	echanical Fits- Rotor			
49.			inches	
50.	Rotor Runout			
	Drive End Bearing Fit	Rotor Body	Opposite Drive End Bearing	
51.	1. Coupling Fit Closest to Bearing Housing			
	0 Degrees	90 Degrees	120 Degrees	
52.	2. Coupling Fit Closest to the end of the Shaft			
	0 Degrees	60 Degrees	120 Degrees	
53.	Drive End Bearing Shaft Fit			
	0 Degrees	60 Degrees	120 Degrees	
EA	Drive End Bearing Shaft Fit Conditior			
54. 55	Opposite Drive End Bearing Shaft Fit			
55.	0 Degrees	60 Degrees	120 Degrees	
	U Deglees	UU Degrees	120 Deglees	

56.	Opposite Drive End Bearing Shaft Fit	Condition		
	Shaft Air Seal Fits			
-	Drive End Air Seal	Opposite Drive End Air Seal		
Mecha	anical Fits- Bearing Housings			
58.	Drive End - Endbell Bearing Fit			
	0 Degrees	60 Degrees	120 Degrees	
	Drive End - Endbell Bearing Fit Condi			
60.	Opposite Drive End - Endbell Bearing		100 D	
	0 Degrees	60 Degrees	120 Degrees	
61.	Opposite Drive End - Endbell Bearing	Fit Condition		
62.	Bearing Cap Condition			
	Drive End Bearing Cap	Opposite Drive End Bearing Cap		
	5 1	11 5 1		
63.	End Bell Air Seal Fits			
	Drive End Air Seal	Opposite Drive End Air Seal		
E A	List Machine Work Needed Below			
	Technician		Cw	
Root	Cause of Failure			
<b>6</b> 6.	Failure locations			
	Leads/windings			
67.	Root cause of failure			
	Open lead on lead 3 short in windings			
-	nic Balance Report			
68.	Rotor Weight and Balance Grade			
	Rotor Weight	Balance Grade		
69.	Initial Balance Readings			
	Drive End	Opposite Drive End		
70.	Final Balance Readings			
	Drive End	Opposite Drive End		
74	Tashaisian			
71. Technician Rewind				
72. Core Test Results - Watts loss per Pound				
12.	Pre-Burnout	Post Burnout		
	The Bulllout	r ost Bullout		
73.	Core Hot Spot Test			
	Pre-Burnout	Post-Burnout		

75. Post Rewind Polarization Index         76. Post Rewind Winding Resistance         1-2       1-3         1-2       1-3         77. Post Rewind Surge Test         78. Post Rewind Hi-Pot         79. Technician         Assembly         80. QC Check All Parts for Cleanliness Prior to Assembly         81. Photograph All Major Components prior to Assembly         82. Final Insulation Resistance Test         83. Assembled Shaft Endplay         84. Assembled Shaft Runout         85. Test Run Anperage         Volts       Volts         Volts       Volts         86. Test Run Amperage         Amps       Amps         87. Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         88. Opposite Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         89. Ambient Temperature - Fahrenheit         90. Drive End Bearing Temps - Fahrenheit         91. Opposite Drive End Bearing Temps - Fahrenheit         92. Drive End Bearing Temps - Fahrenheit         93. Ambient Temperature - Fahrenheit         94. Opposite Drive End Bearing Temps - Fahrenheit         95. Minutes       10 Minutes       15 Minutes	74.	Post Rewind Electrical Test- Insulation	Resistance		
1-2     1-3     2-3       77.     Post Rewind Surge Test	75.				
77.       Post Rewind Surge Test         78.       Post Rewind Hi-Pot         79.       Technician         Assembly         80.       QC Check All Parts for Cleanliness Prior to Assembly         81.       Photograph All Major Components prior to assembly         82.       Final Insulation Resistance Test         83.       Assembled Shaft Endplay         84.       Assembled Shaft Runout         85.       Test Run Voltage         Volts       Volts         Volts       Volts         86.       Test Run Amperage         Amps       Amps         Amps       Amps         Assemole Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         88.       Opposite Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         89.       Ambient Temperature - Fahrenheit         90.       Drive End Bearing Temps - Fahrenheit         91.       Drive End Bearing Temps - Fahrenheit         92.       Minutes       10 Minutes       15 Minutes	76.				
78. Post Rewind Hi-Pot         79. Technician         Assembly         80. QC Check All Parts for Cleanliness Prior to Assembly         81. Photograph All Major Components prior to assembly         82. Final Insulation Resistance Test         83. Assembled Shaft Endplay         84. Assembled Shaft Runout         85. Test Run Voltage         Volts       Volts         Volts       Volts         86. Test Run Amperage         Amps       Amps         87. Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         88. Opposite Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         88. Opposite Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         89. Ambient Temperature - Fahrenheit         90. Drive End Bearing Temps - Fahrenheit         91. Drive End Bearing Temps - Fahrenheit         92. Drive End Bearing Temps - Fahrenheit         93. Ambient Temperature - Fahrenheit         94. Drive End Bearing Temps - Fahrenheit		1-2	1-3	2-3	
78. Post Rewind Hi-Pot         79. Technician         Assembly         80. QC Check All Parts for Cleanliness Prior to Assembly         81. Photograph All Major Components prior to assembly         82. Final Insulation Resistance Test         83. Assembled Shaft Endplay         84. Assembled Shaft Runout         85. Test Run Voltage         Volts       Volts         Volts       Volts         86. Test Run Amperage         Amps       Amps         87. Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         88. Opposite Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         88. Opposite Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         89. Ambient Temperature - Fahrenheit         90. Drive End Bearing Temps - Fahrenheit         91. Drive End Bearing Temps - Fahrenheit         92. Drive End Bearing Temps - Fahrenheit         93. Ambient Temperature - Fahrenheit         94. Drive End Bearing Temps - Fahrenheit					
79. Technician         Assembly         80. QC Check All Parts for Cleanliness Prior to Assembly         81. Photograph All Major Components prior to assembly         82. Final Insulation Resistance Test         83. Assembled Shaft Endplay         84. Assembled Shaft Runout         85. Test Run Voltage         Volts       Volts         86. Test Run Amperage         Amps       Amps         Amps       Amps         87. Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical       Axial         88. Opposite Drive End Vibration Readings - Inches Per Second       Axial         89. Ambient Temperature - Fahrenheit       Inches Per Second       Increation (Second)         89. Ambient Temperature - Fahrenheit       Information (Second)       Information (Second)         89. Ambient Temperature - Fahrenheit       Information (Second)       Information (Second)         89. Ambient Temperature - Fahrenheit       Information (Second)       Information (Second)         80. Drive End Bearing Temps - Fahrenheit       Information (Second)       Information (Second)         80. Drive End Bearing Temps - Fahrenheit       Information (Second)       Information (Second)         81. Optice End Bearing Temps - Fahrenheit       Information (Second)       Information	77.	Post Rewind Surge Test			
Assembly         80. QC Check All Parts for Cleanliness Prior to Assembly         81. Photograph All Major Components prior to assembly         82. Final Insulation Resistance Test         83. Assembled Shaft Endplay         84. Assembled Shaft Runout         85. Test Run Voltage         Volts       Volts         86. Test Run Amperage         Amps       Amps         87. Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical       Axial         88. Opposite Drive End Vibration Readings - Inches Per Second       Axial         89. Ambient Temperature - Fahrenheit       Vertical       Axial         89. Ambient Temperature - Fahrenheit       5 Minutes       10 Minutes       15 Minutes	78.	Post Rewind Hi-Pot			
80. QC Check All Parts for Cleanliness Prior to Assembly         81. Photograph All Major Components prior to assembly         82. Final Insulation Resistance Test         83. Assembled Shaft Endplay         84. Assembled Shaft Runout         85. Test Run Voltage         Volts       Volts         86. Test Run Amperage         Amps       Amps         87. Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         88. Opposite Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         89. Ambient Temperature - Fahrenheit         90. Drive End Bearing Temps - Fahrenheit         91. Orive End Bearing Temps - Fahrenheit         92. Orive End Bearing Temps - Fahrenheit	79.	Technician			
81. Photograph All Major Components prior to assembly         82. Final Insulation Resistance Test         83. Assembled Shaft Endplay         84. Assembled Shaft Runout         85. Test Run Voltage         Volts       Volts         86. Test Run Amperage         Amps       Amps         87. Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         88. Opposite Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         89. Ambient Temperature - Fahrenheit         90. Drive End Bearing Temps - Fahrenheit         91. Orive End Bearing Temps - Fahrenheit         92. Orive End Bearing Temps - Fahrenheit	Assen	nbly			
82. Final Insulation Resistance Test         83. Assembled Shaft Endplay         84. Assembled Shaft Runout         85. Test Run Voltage         Volts       Volts         86. Test Run Amperage         Amps       Amps         87. Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         88. Opposite Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         89. Ambient Temperature - Fahrenheit         90. Drive End Bearing Temps - Fahrenheit         5 Minutes       10 Minutes	80.	QC Check All Parts for Cleanliness Pr	ior to Assembly		
83. Assembled Shaft Endplay         84. Assembled Shaft Runout         85. Test Run Voltage         Volts       Volts         86. Test Run Amperage         Amps       Amps         87. Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         88. Opposite Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         88. Opposite Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         89. Ambient Temperature - Fahrenheit         90. Drive End Bearing Temps - Fahrenheit         5 Minutes       10 Minutes			or to assembly		
84. Assembled Shaft Runout         85. Test Run Voltage         Volts       Volts         86. Test Run Amperage         Amps       Amps         87. Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         88. Opposite Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         88. Opposite Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         Ambient Temperature - Fahrenheit         90. Drive End Bearing Temps - Fahrenheit         5 Minutes       10 Minutes					
85. Test Run Voltage       Volts       Volts         86. Test Run Amperage       Amps       Amps         87. Drive End Vibration Readings - Inches Per Second       Axial         88. Opposite Drive End Vibration Readings - Inches Per Second       Axial         88. Opposite Drive End Vibration Readings - Inches Per Second       Axial         89. Ambient Temperature - Fahrenheit       Vertical       Axial         89. Ambient Temperature - Fahrenheit       Inches Per Second       Inches Per Second         89. Ambient Temperature - Fahrenheit       Inches Per Second       Inches Per Second					
Volts       Volts         86. Test Run Amperage       Amps         Amps       Amps         87. Drive End Vibration Readings - Inches Per Second       Amps         Horizontal       Vertical       Axial         88. Opposite Drive End Vibration Readings - Inches Per Second       Axial         89. Ambient Temperature - Fahrenheit       4xial         90. Drive End Bearing Temps - Fahrenheit       5 Minutes         10 Minutes       15 Minutes					
86. Test Run Amperage       Amps       Amps         87. Drive End Vibration Readings - Inches Per Second       Axial         88. Opposite Drive End Vibration Readings - Inches Per Second       Axial         88. Opposite Drive End Vibration Readings - Inches Per Second       Axial         89. Ambient Temperature - Fahrenheit       Vertical       Axial         89. Ambient Temperature - Fahrenheit       10 Minutes       15 Minutes	85.	Test Run Voltage			
Amps Amps Amps   87. Drive End Vibration Readings - Inches Per Second   Horizontal Vertical   88. Opposite Drive End Vibration Readings - Inches Per Second   Horizontal Vertical   4 Horizontal   Vertical Axial		Volts	Volts	Volts	
Amps       Amps       Amps         87.       Drive End Vibration Readings - Inches Per Second       Axial         87.       Horizontal       Vertical       Axial         88.       Opposite Drive End Vibration Readings - Inches Per Second       Axial         88.       Opposite Drive End Vibration Readings - Inches Per Second       Axial         89.       Ambient Temperature - Fahrenheit       Axial         90.       Drive End Bearing Temps - Fahrenheit       5 Minutes         10 Minutes       15 Minutes	96				
87. Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         88. Opposite Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         Axial         89. Ambient Temperature - Fahrenheit         90. Drive End Bearing Temps - Fahrenheit         5 Minutes       10 Minutes	00.		Amno	4 mm n	
Horizontal       Vertical       Axial         88.       Opposite Drive End Vibration Readings - Inches Per Second       Axial         Horizontal       Vertical       Axial         89.       Ambient Temperature - Fahrenheit       Second         90.       Drive End Bearing Temps - Fahrenheit       Second         5 Minutes       10 Minutes       15 Minutes		Amps	Amps	Amps	
88. Opposite Drive End Vibration Readings - Inches Per Second         Horizontal       Vertical         89. Ambient Temperature - Fahrenheit         90. Drive End Bearing Temps - Fahrenheit         5 Minutes       10 Minutes	87.	. Drive End Vibration Readings - Inches Per Second			
Horizontal     Vertical     Axial       89.     Ambient Temperature - Fahrenheit     -       90.     Drive End Bearing Temps - Fahrenheit     -       5 Minutes     10 Minutes     15 Minutes		Horizontal	Vertical	Axial	
Horizontal     Vertical     Axial       89.     Ambient Temperature - Fahrenheit     -       90.     Drive End Bearing Temps - Fahrenheit     -       5 Minutes     10 Minutes     15 Minutes					
89. Ambient Temperature - Fahrenheit         90. Drive End Bearing Temps - Fahrenheit         5 Minutes       10 Minutes         15 Minutes	88.	Opposite Drive End Vibration Reading	s - Inches Per Second		
90. Drive End Bearing Temps - Fahrenheit         5 Minutes       10 Minutes         15 Minutes		Horizontal	Vertical	Axial	
90. Drive End Bearing Temps - Fahrenheit         5 Minutes       10 Minutes         15 Minutes					
5 Minutes 10 Minutes 15 Minutes					
	90.	- · ·			
91 Opposite Drive End Bearing Temps - Fahrenheit		5 Minutes	10 Minutes	15 Minutes	
ar. Opposite Drive Litu Deatility Fettipe - Fatteritteit	91.	Opposite Drive End Bearing Temps - I	Fahrenheit		
5 Minutes 10 Minutes 15 Minutes				15 Minutes	
Document Final Condition with Pictures after paint					
93. Final Pics and QC Review	93.	Final Pics and QC Review			



#### STANDARD TERMS AND CONDITIONS FOR PURCHASE OF GOOD AND/OR SERVICES

- 1. <u>APPLICABILITY.</u> The sale of any and all goods and/or services by Mock, Inc. d/b/a Hi-Speed Industrial Service ("Hi-Speed") shall be specifically conditioned upon and subject to the following terms and conditions which are incorporated by reference into any contracts and purchase orders with Hi-Speed, and which shall form and become a part of any agreement related thereto. Buyer's acceptance of any offer or quotation made by Hi-Speed for sale of any goods or services is expressly made subject to the terms and conditions set forth herein and to be so effective, Buyer need not sign or approve these Terms and Conditions to be bound hereunder provided a copy of same is provided to Buyer through any means. None of the terms and conditions contained herein may be added to, expanded, changed, modified, superseded or otherwise altered except as revised in writing and duly executed by Hi-Speed, and all orders received by Hi-Speed shall be governed only by the terms and conditions contained herein, notwithstanding any terms, conditions or provisions of any purchase order, release order, authorization or any other form issued by the Buyer. Hi-Speed hereby objects to any additional, modified, changed, deleted, altered or other terms and conditions not contained herein and notifies Buyer that any such terms or provisions are expressly rejected by Hi-Speed.
- 2. PRICE. All quoted prices shall remain firm and binding for a period of thirty (30) days from the date of quotation or for the period specifically stated in the quotation. The price for any and all goods and/or services ordered or approved by Buyer after thirty (30) days from the date of any quotation are subject to any increase in price that may occur after the expiration of thirty (30) days from the issuance of the quotation and the date the Buyer releases any shipment.
- 3. <u>SCOPE OF GOODS AND/OR SERVICES.</u> The goods and/or services provided by Hi-Speed pursuant to any quotation shall be limited exclusively to those goods and/or services expressly identified therein. Hi-Speed does not assume any responsibility and/or liability for the failure to provide any other goods and/or services not identified in any quotation. Modifications, additions or deletions to or from the scope referenced in any quotation shall only be effective if evidenced in writing and signed by Hi-Speed. The sale of any of all goods and/or services affected by such modification, addition or deletion shall be subject to these same Standard Terms and Conditions whether or not referenced therein.
- 4. <u>BILLING AND PAYMENT TERMS.</u> Hi-Speed shall invoice Buyer for all goods and/or services as same are rendered at the address listed on the quotation. Payments for all goods and/or services shall be due thirty (30) days from the date of the current invoice or as otherwise set forth in the quotation. Late payments are subject to a late fee of 5% of the total invoice amount. Recurring late payments may lead to a deposit requirement on future services or sale of goods. Buyer shall be liable to Hi-Speed for any and all fees and expenses incurred by Hi-Speed to collect any invoices or to enforce these Standard Terms and Conditions, including but not limited to, attorney's fees.
- 5. DELIVERY OF GOODS AND/OR SERVICES. Unless otherwise identified in the quotation, all shipments are F.O.B. Hi-Speed's warehouse and the title to and all risk of loss with respect to any goods shipped shall pass to Buyer when such goods are delivered to the carrier at Hi-Speed's warehouse. Hi-Speed will use its best efforts to affect delivery by the date or dates specified in the quotation. However, Hi-Speed shall not be liable for delay in or failure to make shipment, or to perform services, by any identified date for any reason whatsoever, including but not limited to, causes beyond its reasonable control, such as strikes, fires, floods, epidemics, quarantines, restrictions, severe weather, embargos, acts of God, or public enemy, war, riot, delays in transportation or the inability to obtain necessary labor, materials or manufacturing facilities.
- 6. DELIVERY SITE AND TIME FOR PERFORMANCE. Hi-Speed and Buver agree that time is of the essence for the purchase order and that Buyer shall fully cooperate with Hi-Speed in order to allow Hi-Speed full access to prosecute its work diligently and in an orderly manner. Buyer shall assist Hi-Speed in every way possible to avoid delaying, disrupting or interfering with the progress of Hi-Speed's work at the project site. In the event Hi-Speed's work is delayed, hindered, suspended, disrupted, re-sequenced or interfered with or rendered less efficient or more costly or adversely affected in any way as a result of acts or omissions of Buyer or other contractors or employees of Buyer or by any other reason beyond Hi-Speed's control and without the fault of Hi-Speed, then, in such event, Buyer shall be liable to Hi-Speed for any damages, additional costs, expenses, labor, materials, man hours, acceleration costs, overtime, additional jobsite overhead, extended home office overhead, and any and all other direct and indirect expenses of whatsoever nature or kind, caused in whole or in part, as a result of any of the above-referenced occurrences. Hi-Speed's project records will be the basis for computing the additional costs and damages of Hi-Speed's labor, materials, expenses and overhead related to such changes. BUYER WARRANTS THAT THE SITE FOR DELIVERY OR INSTALLATION OF ANY GOODS AND/OR FOR THE PERFORMANCE OF ANY SERVICES SHALL BE READY AND ADEQUATE FOR HI-SPEED'S DELIVERY OF GOODS AND/OR PERFORMANCE OF SERVICES AND THAT HI-SPEED SHALL HAVE FULL ACCESS THERETO, FREE OF ALL OBSTRUCTIONS. BUYER SHALL ASSUME ALL EXTRA COSTS ASSOCIATED WITH HI-SPEED'S INABILITY TO INSTALL ANY GOODS OR PERFORM ANY SERVICES AS A RESULT OF BUYER'S FAILURE TO COMPLY WITH THIS PROVISION. HI-SPEED MAY NOT INSPECT THE SITE PRIOR TO DELIVERY AND/OR INSTALLATION OF GOODS AND/OR PERFORMANCE OF SERVICES AND MAKES NO WARRANTY AS TO THE SUFFICIENCY OF THE SITE FOR THE DELIVERY AND/OR INSTALLATION OF GOODS AND/OR THE PERFORMANCE OF SERVICES AT SUCH SITE.
- 7. INSPECTION/ACCEPTANCE. All goods and services ordered pursuant to any quotation shall be subject to inspection by Buyer after delivery or performance to determine conformity with the quotation and/or purchase order and Hi-Speed's advertised or published specifications. Buyer shall have a period of thirty (30) days from shipment of goods at the delivery destination specified in the quotation within which to inspect the goods for conformity with the quotation, order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. Buyer shall have a period of thirty (30) days following completion of any services within which to inspect the services for conformity with the quotation, purchase order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. If the goods delivered or services performed do not so conform, upon delivery of notice to Hi-Speed of any discrepancy, nonconformance or rejection, Hi-Speed shall have the right to reject such goods or services. After the cure period, goods that have been delivered and rejected, in whole or in part, shall be returned to Hi-Speed shall, at its sole cost, re-perform the non-conforming services. Inspection or failure to inspect on any occasion shall not affect Buyer's rights under the warranty provisions herein.
- 8. WARRANTIES. Hi-Speed warrants that all goods shall conform in all material aspects to the goods identified in the quotation to Buyer and/or purchase order, and Hi-Speed makes to Buyer the manufacturer's express warranty for any goods sold to Buyer, which is offered by the manufacturer at the time of acceptance of any quotation by Buyer. This warranty is conditioned upon the installation, operation, and maintenance of the goods in accordance with the manufacturer's recommendations and/or standard industry practice and the goods at all times being operated or used under normal operating conditions for which they were designed. Hi-Speed, at its sole option, will repair or

**TermsAndConditions** 

replace any defective or non-conforming goods in accordance with the applicable manufacturer's warranty. Warranty for any defective or incorrect parts is limited to the repair or replacement of those parts. Hi-Speed warrants that all services will conform in all material respects to the description of services identified in the quotation and will be performed in a good and workmanlike manner in accordance with industry practices and standards. Should the services be reasonably rejected or not conform with the foregoing warranties, Hi-Speed shall, at its sole cost, re-perform the defective or nonconforming services. Notwithstanding the foregoing, these warranties do not extend to goods or services to the extent that such goods have been subject to misuse, neglect or abuse not caused by Hi-Speed or have been used in violation of the approved written instructions furnished to Buyer. THE FOREGOING REPRESENTS THE SOLE AND EXCLUSIVE WARRANTY GIVEN BY HI-SPEED WITH RESPECT TO ALL GOODS SOLD AND IS IN LIEU OF ALL OTHER WARRANTIES EITHER EXPRESS OR IMPLIED. HI-SPEED EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICLAR USE OR PURPOSE. BUYER WAIVES ANY CLAIM THAT THESE EXCLUSIONS OR LIMITATIONS DEPRIVE IT OF AN ADEQUATE REMEDY AT EQUITY OR LAW OR CAUSE THIS AGREEMENT TO FAIL IN ITS ESSENTIAL PURPOSE. BUYER SHALL BE ENTITLED TO NO OTHER REMEDY OTHER THAN AS SET FORTH HEREIN, REGARDLESS OF THE CLAIM OR CAUSE OF ACTION, WHETHER BASED IN CONTRACT, TORT, NEGLIGENCE, GOODS LIABILITY, STRICT LIABILITY OR OTHERWISE.

- 9. LIMITATION OF DAMAGES. HI-SPEED SHALL HAVE NO LIABILITY TO BUYER WITH RESPECT TO THE SALE OR DELIVERY OF ANY GOODS OR THE REPAIR THEREOF OR WITH RESPECT TO THE SALE OR PERFORMANCE OF ANY SERVICES, FOR LOST PROFITS, SPECIAL, CONSEQUENTIAL, EXEMPLARY, PUNITIVE OR INCIDENTAL DAMAGES OF ANY KIND OR NATURE WHETHER ARISING IN CONTRACT, TORT, GOODS LIABILITY OR OTHERWISE, EVEN IF HI-SPEED WAS ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGES. HI-SPEED SHALL NOT BE LIABLE FOR ANY DAMAGES OR DELAYS CAUSED BY ANY FAILURE TO MAKE ANY DELIVERY OF GOODS BY ANY EXPECTED TIME OR DATE OR THE FAILURE TO PROVIDE OR COMPLETE ANY SERVICES BY ANY EXPECTED DATE OR TIME. IN NO EVENT SHALL HI-SPEED BE LIABLE TO BUYER FOR ANY DAMAGES WHATSOEVER IN EXCESS OF THE TOTAL PRICE PAID FOR ALL GOODS AND/OR SERVICES HEREUNDER OR REFERENCED IN ANY QUOTATION OR THE PURCHASE ORDER.
- 10. <u>SEVERABILITY</u>. The partial or complete invalidity of any provision of these Standard Terms and Conditions shall not affect the enforceability of the remainder of these Standard Terms and Conditions. If any provision is found to be invalid or unenforceable, that portion shall be modified to make it enforceable or shall be stricken and the remainder of these Standard Terms and Conditions shall enforced.
- 11. <u>GOVERNING LAW AND JURISDICTION.</u> Any controversy arising out of any quotation, the purchase order, the goods sold or delivered, repair or replacement thereof, or any services provided pursuant to any quotation or any purchase order, or these Standard Terms and Conditions shall be governed by the laws of the state of Tennessee without regard to any choice of law provisions and any cause of action related in any manner thereto shall be brought only in the state or federal courts of Shelby County, Tennessee.
- 12. <u>ABANDONED EQUIPMENT.</u> Hi-Speed requires that Buyer promptly pick up or provide shipment instructions for Buyer equipment or other Buyer property in Hi-Speed's possession. If equipment or other Buyer property is left with Hi-Speed and not picked up within six (6) months after Hi-Speed's final action related to the applicable property (e.g. evaluation, teardown, estimate, completion of services), Hi-Speed will consider such property abandoned and may dispose of it in accordance with applicable law. Buyer agrees to hold Hi-Speed harmless for any damage or claim for such abandoned property and acknowledges that Hi-Speed may discard or recycle it at Hi-Speed's sole and absolute discretion. Specifically, Hi-Speed may sell Buyer's abandoned property at a private or public sale and retain the proceeds to offset Hi-Speed's storage, inspection and servicing costs. For the avoidance of doubt, Hi-Speed reserves its statutory and other lawful liens for unpaid charges related to abandoned property.
- 13. FORCE MAJEURE. Neither party shall be responsible for any delay or failure in performance of any party of the quotation, purchase order or these Standard Terms and Conditions to the extent that such delays or failures are caused by fire, flood, earth quake, explosion, war, embargo, government requirement, civil or military authority, acts of God, or any other circumstances beyond its reasonable control and not involving any fault or negligence on the party affected ("Condition"). If any such Condition occurs, the party delayed or unable to perform shall promptly give written notice to the other party and, if such Condition remains at the end of thirty (30) days, the party affected by the other party's delay and inability to perform may elect to (i) terminate such order or part thereof, or (ii) suspend the order for the duration of the Condition, if the Buyer is the suspending party, buy elsewhere comparable material to be sold under the order and apply to any commitment the purchase price of such purchase, and resume performance of the order once the Condition ceases, with an option in the affected party to extend the period of this order up to the length of the time the Condition endures.
- 14. <u>NONWAIVER</u>. No course of dealing or failure of either party to strictly enforce any term, right, or condition of these Standard Terms and Conditions will be construed as a waiver of such term, right or condition. Any waiver by Hi-Speed will only be in writing and will waive no succeeding breach of a term, right or condition.
- 15. <u>ASSIGNMENT.</u> The rights and obligations of the parties shall neither be assigned nor delegated without the prior written consent of the other party. However, any party may assign or delegate its respective rights and obligations, in whole or in part, (i) to any subsidiary, (ii) pursuant to other financing, merger or reorganization or (iii) pursuant to any sale or transfer of substantially all of the assets of the assigning party. These Standard Terms and Conditions shall bind the heirs, successors and assigns of the parties hereto.
- 16. <u>NO INDIVIDUAL LIABILITY</u>. Notwithstanding any other agreement to the contrary, the Buyer agrees that in no event will the Buyer hold and HI-Speed owner, director, officer or employee personally liable for unintentional tortious conduct or conduct that constitutes the breach of any contract between HI-Speed and the Buyer, even if the HI-Speed owner, director, officer or employee is or could be construed to be a party to such contract.