

— EVERY DAY SINCE 1946 —

LR Motor Shop Repairs

Job Number 102686

Prepared for Baldor Warranty Division

685 Mid America Blvd Hot Springs AR 71913

Table of Contents

AC Inspection as Found - MOTOR SHOP LR

AC Inspection - Rev. 2

1.0



MOTOR SHOP LR

Hi-Speed Industrial Service 7030 Ryburn Dr Millington, Tn 38053 901-873-5300

> FolderID: 102686 FormID: 19849787

AC Inspection as Found Baldor Warranty Division

685 Mid America Blvd Hot Springs, AR 71913

AC Inspection - Rev. 2

Serial Number:

Location:

Hi-Speed Job Number:	102686
Manufacturer:	Baldor
Spec/ID #:	37Q301R228G1
Serial Number:	F2304125610
HP/kW:	15 (HP)
RPM:	3500 (RPM)
Frame:	215TYZ
Voltage:	208-230/460
Current:	36.8-34/17
Phase:	Three
Hz:	60 (Hz)
Service Factor:	1.25
Enclosure:	TEFC
J-box Included:	Complete
Coupling/Sheave:	None
Date Received:	03/22/2024
Bearing RTDs:	No
Stator RTDs:	No

Final

Overall Condition

- 1. Report Date
- 2. Nameplate Picture



Photos of all six sides of the machine.

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

Repair Stage:



















Metal contaminate

 Describe the Overall Condition of the Equipment as Received 	4.	Describe the	Overall (Condition (of the	Equipment	as Received
---	----	--------------	-----------	-------------	--------	-----------	-------------

Initial Mechanical/Electrical

- 5. Does Shaft Turn Freely?
- 6. Does the shaft require T.I.R in Lathe to identify additional repairs?
- 7. Does Shaft Have Visible Damage?
- 8. Assembled Shaft Runout
- 9. Assembled Shaft End Play
- 10. Air Gap Variation <10%
- 11. Lead Condition
- 12. Lead Length
- 13. Does it have Lugs?, If so what is the Stud Size?
- 14. Lead Numbers
 - 15. Frame Condition
- 16. Fan Condition
- 17. Heater Quantity, Ratings

Quantity Volts/Watts Pass/Fail

18. Broken or Missing Components

Initial Electrical Inspection

19. Insulation Resistance/Megger

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

20.	Winding Resistance			
	1-2	1-3	2-3	
21.	Perform Surge Test			
22.	Number of Stator Slots			
23.	Stator Condition			
24.	Stator Thermistors/Ohms			
25.	Stator Overloads/Ohms			
Mecha	anical Inspection			
26.	3			
27.	Drive End Bearing Number-			
28.	3,			
29.	3 71 -			
30.	Drive End Lubrication Type			
31.	3	-		
32.	Drive End Wavy Washer/Snap-Ring O	ther Retention Device?		
33.	<u> </u>			
34.	-11			
35.	-11			
36.	Opposite Drive End Bearing Qty.			
37.	11 5 71			
38.	Opposite Drive End Lubrication Type	an Crown din a Davids 2		
39.	Opposite Drive End Bearing Insulation			
40.	31,111			
41. 42.	Opposite Drive End Bearing Condition Drive End Seal			
43.				
	DE Sleeve Bearing Inside Diameter			
77.	0 degrees	120 degrees	240 degrees	
	o degrees	120 degrees	240 degrees	
45.	DE Sleeve Bearing Outside Diameter			
	0 degrees	120 degrees	240 degrees	
46.	DE Sleeve Bearing Housing Inside Dia	ameter		
	0 degrees	120 degrees	240 degrees	
4-	DE 01 D			
47.	DE Sleeve Bearing to Housing Cleara		040	
	0 degrees	120 degrees	240 degrees	
48.	ODE Sleeve Bearing Inside Diameter			
το.	0 degrees	120 degrees	240 degrees	
	o dogrood	120 dogiood	2 10 dog1000	
49.	ODE Sleeve Bearing Outside Diamete	r		
	0 degrees	120 degrees	240 degrees	
	-	-	-	
50.	ODE Sleeve Bearing Housing Inside D	Diameter		
	0 degrees	120 degrees	240 degrees	

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

Rotor Inspection 52. Rotor Type/Material 53. Growler Test 54. Number of Rotor Bars 55. Rotor Condition 56. List the Parts needed for the Repair Below 57. Signature of Technician that Disassembled Motor Mechanical Fits- Rotor 58. Shaft Runout 59. Rotor Runout Drive End Bearing Fit Rotor Body 60. Coupling Fit Closest to Bearing Housing 0 Degrees 90 Degrees 120 Degrees 61. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 62. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 63. Drive End Bearing Shaft Fit Condition 64. Opposite Drive End Bearing Shaft Fit Condition 65. Opposite Drive End Bearing Shaft Fit Condition 66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 69. Opposite Drive End Bearing Shaft Fit Condition 60. Shaft Air Seal Fits Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 69. Drive End - Endbell Bearing Fit 10 Degrees 60 Degrees 120 Degrees 69. Opposite Drive End - Endbell Bearing Fit 10 Degrees 60 Degrees 120 Degrees 60. Degrees 120 Degrees 61. Coupling Fit Condition 62. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 63. Drive End - Endbell Bearing Fit 10 Degrees 60 Degrees 120 Degrees 64. Drive End - Endbell Bearing Fit 10 Degrees 60 Degrees 120 Degrees 65. Opposite Drive End - Endbell Bearing Fit 10 Degrees 60 Degrees 120 Degrees 66. Drive End - Endbell Bearing Fit 10 Degrees 60 Degrees 120 Degrees 67. Drive End - Endbell Bearing Fit Condition 68. Drive End - Endbell Bearing Fit Condition 79. Drive End Bearing Cap Opposite Drive End Bearing Cap 70. Drive End Air Seal Opposite Drive End Air Seal 71. List Machine Work Needed Below 72. List Machine Work Needed Below 73. List Machine Work Needed Below 74. Technician	51.	ODE Sleeve Bearing to Housing Clea	rance	
Rotor Inspection 52. Rotor Type:Material 53. Growler Test 54. Number of Rotor Bars 55. Rotor Condition 56. List the Parts needed for the Repair Below 57. Signature of Technician that Disassembled Motor Mechanical Fits- Rotor 58. Shaft Runout 59. Rotor Runout Drive End Bearing Fit Rotor Body Opposite Drive End Bearing 60. Coupling Fit Closest to Bearing Housing 0 Degrees 90 Degrees 120 Degrees 61. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 62. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 63. Drive End Bearing Shaft Fit Condition 64. Opposite Drive End Bearing Shaft Fit Condition 65. Opposite Drive End Bearing Shaft Fit Condition 66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 71. Elst Machine Work Needed Below 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Bearing Cap 73. List Machine Work Needed Below		<u> </u>		240 degrees
52. Rotor Type/Material 53. Growler Test 54. Number of Rotor Bars 55. Rotor Condition 56. List the Parts needed for the Repair Below 57. Signature of Technician that Disassembled Motor Mechanical Fits- Rotor 58. Shaft Runout 59. Rotor Runout 59. Rotor Runout 50. Coupling Fit Closest to Bearing Housing 50. Degrees 50		o dog.coo	.20 dog.000	2 10 deg.000
53. Growler Test 54. Number of Rotor Bars 55. Rotor Condition 56. List the Parts needed for the Repair Below 57. Signature of Technician that Disassembled Motor Mechanical Fits- Rotor 58. Shaft Runout 59. Rotor Runout Drive End Bearing Fit Rotor Body Opposite Drive End Bearing 0 Degrees 90 Degrees 120 Degrees 61. Coupling Fit Closest to Bearing Housing 0 Degrees 60 Degrees 120 Degrees 62. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 63. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 64. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 65. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Searing Cap Opposite Drive End Air Seal	Rotor	Inspection		
55. Rotor Condition 56. List the Parts needed for the Repair Below 57. Signature of Technician that Disassembled Motor Mechanical Fits- Rotor 58. Shaft Runout 59. Rotor Runout Drive End Bearing Fit Rotor Body Opposite Drive End Bearing 60. Coupling Fit Closest to Bearing Housing 0 Degrees 90 Degrees 120 Degrees 61. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 62. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 63. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 64. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 65. Opposite Drive End Bearing Shaft Fit Condition 66. Shaft Air Seal Fits Drive End Bearing Fit Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit 0 Degrees 70. Opposite Drive End - Endbell Bearing Fit 0 Degrees 71. Drive End - Endbell Bearing Fit Condition 10. Degrees 71. Drive End - Endbell Bearing Fit Condition 11. Bearing Cap Condition 12. End Bell Air Seal Fits Drive End Bearing Cap Opposite Drive End Air Seal 73. List Machine Work Needed Below	52.	Rotor Type/Material		
55. Rotor Condition 56. List the Parts needed for the Repair Below 77. Signature of Technician that Disassembled Motor Mechanical Fits- Rotor 58. Shaft Runout 59. Rotor Runout Drive End Bearing Fit Rotor Body Opposite Drive End Bearing 60. Coupling Fit Closest to Bearing Housing 0 Degrees 90 Degrees 120 Degrees 61. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 62. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 63. Drive End Bearing Shaft Fit Condition 64. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 65. Opposite Drive End Bearing Shaft Fit Condition 66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 69. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 10 Degrees 0 Degrees 120 Degrees 71. Degrees 0 Degrees 120 Degrees 72. End Bell Air Seal Fits Drive End Bearing Cap Opposite Drive End Bearing Cap 73. List Machine Work Needed Below	53.	Growler Test		
56. List the Parts needed for the Repair Below 57. Signature of Technician that Disassembled Motor Mechanical Fits- Rotor 58. Shaft Rumout 59. Rotor Rumout Drive End Bearing Fit Rotor Body Opposite Drive End Bearing 60. Coupling Fit Closest to Bearing Housing 0 Degrees 90 Degrees 120 Degrees 61. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 62. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 63. Drive End Bearing Shaft Fit Condition 64. Opposite Drive End Bearing Shaft Fit Condition 65. Opposite Drive End Bearing Shaft Fit Condition 66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 69. Opposite Drive End Searing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 69. Opposite Drive End - Endbell Bearing Fit Condition 69. Opposite Drive End - Endbell Bearing Fit Condition 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Opposite Drive End Bearing Cap 72. End Beal Air Seal Fits Drive End Air Seal Bearing Cap	54.	Number of Rotor Bars		
Signature of Technician that Disassembled Motor Mechanical Fits- Rotor	55.	Rotor Condition		
Mechanical Fits- Rotor	56.	List the Parts needed for the Repair B	elow	
59. Rotor Runout Drive End Bearing Fit Rotor Body Opposite Drive End Bearing 60. Coupling Fit Closest to Bearing Housing 0 Degrees 90 Degrees 120 Degrees 61. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 62. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 63. Drive End Bearing Shaft Fit Condition 64. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 65. Opposite Drive End Bearing Shaft Fit Condition 66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 71. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 72. End Bearing Cap Opposite Drive End Bearing Cap 73. List Machine Work Needed Below	57.	Signature of Technician that Disassen	nbled Motor	
For Rutor Runout Drive End Bearing Fit Rotor Body Opposite Drive End Bearing 60. Coupling Fit Closest to Bearing Housing 0 Degrees 90 Degrees 120 Degrees 61. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 62. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 63. Drive End Bearing Shaft Fit Condition 64. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 65. Opposite Drive End Bearing Shaft Fit Condition 66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Degrees 60 Degrees 120 Degrees 71. Opposite Drive End - Endbell Bearing Fit Degrees 60 Degrees 120 Degrees 72. End Bearing Cap Opposite Drive End Bearing Cap 73. List Machine Work Needed Below	Mecha	anical Fits- Rotor		
Drive End Bearing Fit Rotor Body Opposite Drive End Bearing 60. Coupling Fit Closest to Bearing Housing	58.	Shaft Runout		
60. Coupling Fit Closest to Bearing Housing 0 Degrees 90 Degrees 120 Degrees 61. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 62. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 63. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 64. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 65. Opposite Drive End Bearing Shaft Fit Condition 66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition 72. End Bell Air Seal Fits Drive End Bearing Cap Opposite Drive End Air Seal	59.	Rotor Runout		
0 Degrees 90 Degrees 120 Degrees 61. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 62. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 63. Drive End Bearing Shaft Fit Condition 64. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 65. Opposite Drive End Bearing Shaft Fit Condition 66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 67. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal		Drive End Bearing Fit	Rotor Body	Opposite Drive End Bearing
0 Degrees 90 Degrees 120 Degrees 61. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 62. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 63. Drive End Bearing Shaft Fit Condition 64. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 65. Opposite Drive End Bearing Shaft Fit Condition 66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 67. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal				
61. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 62. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 63. Drive End Bearing Shaft Fit Condition 64. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 65. Opposite Drive End Bearing Shaft Fit Condition 66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Opposite Drive End Air Seal	60.		-	400 5
62. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 63. Drive End Bearing Shaft Fit Condition 64. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 65. Opposite Drive End Bearing Shaft Fit Condition 66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Opposite Drive End Air Seal		0 Degrees	90 Degrees	120 Degrees
62. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 63. Drive End Bearing Shaft Fit Condition 64. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 65. Opposite Drive End Bearing Shaft Fit Condition 66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Opposite Drive End Air Seal	61.	Coupling Fit Closest to the end of the	Shaft	
62. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 63. Drive End Bearing Shaft Fit Condition 64. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 65. Opposite Drive End Bearing Shaft Fit Condition 66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit Condition 69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Opposite Drive End Air Seal	• • • • • • • • • • • • • • • • • • • •			120 Degrees
0 Degrees 60 Degrees 120 Degrees 63. Drive End Bearing Shaft Fit Condition 64. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 65. Opposite Drive End Bearing Shaft Fit Condition 66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 71. Opposite Drive End - Endbell Bearing Fit Condition 72. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 73. List Machine Work Needed Below		0 20g.000	00 2 0g. 000	.20 Dog. 000
63. Drive End Bearing Shaft Fit Condition 64. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 65. Opposite Drive End Bearing Shaft Fit Condition 66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 610 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Seal Fits Drive End Air Seal Opposite Drive End Seal Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal	62.	Drive End Bearing Shaft Fit		
64. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 65. Opposite Drive End Bearing Shaft Fit Condition 66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 68. Drive End - Endbell Bearing Fit Condition 69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal 73. List Machine Work Needed Below		0 Degrees	60 Degrees	120 Degrees
64. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 65. Opposite Drive End Bearing Shaft Fit Condition 66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 68. Drive End - Endbell Bearing Fit Condition 69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal 73. List Machine Work Needed Below				
0 Degrees 60 Degrees 120 Degrees 65. Opposite Drive End Bearing Shaft Fit Condition 66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit Condition 69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal				
65. Opposite Drive End Bearing Shaft Fit Condition 66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal	64.		00 B	100 D
66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit Condition 69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal 73. List Machine Work Needed Below		0 Degrees	60 Degrees	120 Degrees
66. Shaft Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit Condition 69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal 73. List Machine Work Needed Below	65.	Opposite Drive End Bearing Shaft Fit	Condition	
Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit Condition 69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal		* * * * * * * * * * * * * * * * * * * *		
Mechanical Fits- Bearing Housings 67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit Condition 69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal		Drive End Air Seal	Opposite Drive End Air Seal	
67. Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit Condition 69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal 73. List Machine Work Needed Below		2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		
0 Degrees 60 Degrees 120 Degrees 68. Drive End - Endbell Bearing Fit Condition 69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal	Mecha	anical Fits- Bearing Housings		
68. Drive End - Endbell Bearing Fit Condition 69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal 73. List Machine Work Needed Below	67.	Drive End - Endbell Bearing Fit		
69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal 73. List Machine Work Needed Below		0 Degrees	60 Degrees	120 Degrees
69. Opposite Drive End - Endbell Bearing Fit 0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal 73. List Machine Work Needed Below				
0 Degrees 60 Degrees 120 Degrees 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal 73. List Machine Work Needed Below		-		
 70. Opposite Drive End - Endbell Bearing Fit Condition 71. Bearing Cap Condition	69.			100 B
71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal 73. List Machine Work Needed Below		0 Degrees	60 Degrees	120 Degrees
71. Bearing Cap Condition Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal 73. List Machine Work Needed Below	70.	Opposite Drive End - Endbell Bearing	Fit Condition	
Drive End Bearing Cap Opposite Drive End Bearing Cap 72. End Bell Air Seal Fits Drive End Air Seal Opposite Drive End Air Seal 73. List Machine Work Needed Below				
Drive End Air Seal Opposite Drive End Air Seal 73. List Machine Work Needed Below			Opposite Drive End Bearing Cap	
Drive End Air Seal Opposite Drive End Air Seal 73. List Machine Work Needed Below	72	End Bell Air Seal Fits		
73. List Machine Work Needed Below	,		Opposite Drive End Air Seal	
		Z Z Elia / III Coal	opposite billo billo billo billo	
74. Technician	73.	List Machine Work Needed Below		
	74.	Technician		

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

Root	ot Cause of Failure				
75.	Failure locations				
	Windings are open				
76.	Root cause of failure				
Dynar	nic Balance Report				
77.	Rotor Weight and Balance Grade				
	Rotor Weight	Balance Grade			
78.	Initial Balance Readings	Occasio Brita Fall			
	Drive End	Opposite Drive End			
79.	Final Balance Readings				
	Drive End	Opposite Drive End			
		opposite z me zm			
80.	Technician				
Rewir	nd				
81.	Core Test Results - Watts loss per Po	ound			
	Pre-Burnout	Post Burnout			
00	Care Hat Coat Toot				
82.	Core Hot Spot Test Pre-Burnout	Post-Burnout			
	Pre-Burnout	Post-Burnout			
83.	. Post Rewind Electrical Test- Insulation Resistance				
84.	. Post Rewind Polarization Index				
85.	Post Rewind Winding Resistance				
	1-2	1-3	2-3		
86	Post Rewind Surge Test				
	Post Rewind Hi-Pot				
	Technician				
	echanical Fits- Rotor - Post Repair				
	Shaft Runout Post Repair				
	Rotor Runout Post Repair				
	Drive End Bearing Fit	Rotor Body	Opposite Drive End Bearing		
	3	,	1,111		
91.	Coupling Fit Closest to Bearing Housi	ng Post Repair			
	0 Degrees	90 Degrees	120 Degrees		
92.	Coupling Fit Closest to the end of the	Shaft Post Repair			
32.	0 Degrees	60 Degrees	120 Degrees		
	3	3	3		
93.	Drive End Bearing Shaft Fit Post Rep	air			
	0 Degrees	60 Degrees	120 Degrees		
_					
94.	11		100 5		
	0 Degrees	60 Degrees	120 Degrees		

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

95.	Shaft Air Seal Fits Post Repair				
	Drive End Air Seal	Opposite Drive End Air Seal			
96.	Shaft Repair Sign-off				
	nanical Fits- Bearing Housings - Post Repair				
97.	Drive End - Endbell Bearing Fit Post F	Repair			
	0 Degrees	60 Degrees	120 Degrees		
08	Opposite Drive End - Endbell Bearing	Fit Post Renair			
30.	0 Degrees	60 Degrees	120 Degrees		
	o Degrees	oo begrees	120 Dog1000		
99.	Bearing Cap Condition Post Repair				
	Drive End Bearing Cap	Opposite Drive End Bearing Cap			
400	Ford Doll Air Cool Fite Doot Donois				
100.	End Bell Air Seal Fits Post Repair Drive End Air Seal	Opposite Drive End Air Seal			
	Drive Erid Ali Seai	Opposite Drive End All Seal			
101.	DE Sleeve Bearing Inside ID Post Rep	pair			
	Measure 1	Measure 2	Measure 3		
100					
102.	DE Sleeve Bearing Outside ID Post R	•	Maraura O		
	Measure 1	Measure 2	Measure 3		
103.	DE Sleeve Bearing Inside OD Post Re	epair			
	Measure 1	Measure 2	Measure 3		
104.	DE Sleeve Bearing Outside OD Post	•			
	Measure 1	Measure 2	Measure 3		
105.	End Bell Repair Sign-off				
106.	ODE Sleeve Bearing Inside ID Post R	epair			
	Measure 1	Measure 2	Measure 3		
107.	ODE Sleeve Bearing Outside ID Post	•	Marriago		
	Measure 1	Measure 2	Measure 3		
108.	ODE Sleeve Bearing Inside OD Post	Repair			
	Measure 1	Measure 2	Measure 3		
109.	ODE Sleeve Bearing Outside OD Pos	•			
	Measure 1	Measure 2	Measure 3		
Assen	Assembly				
	QC Check All Parts for Cleanliness Pr	ior to Assembly			
	Photograph All Major Components pri	· · · · · · · · · · · · · · · · · · ·			
112.	Final Insulation Resistance Test				
	Assembled Shaft Endplay				
114.	Assembled Shaft Runout				

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

115.	Test Run Voltage				
	Volts	Volts	Volts		
116.	Test Run Amperage				
	Amps	Amps	Amps		
44-	5. 5.1				
117.	Drive End Vibration Readings - Inches				
	Horizontal	Vertical	Axial		
118.	Opposite Drive End Vibration Reading	as - Inches Per Second			
	Horizontal	Vertical	Axial		
119.	Ambient Temperature - Fahrenheit				
120.	Drive End Bearing Temps - Fahrenhei	it			
	5 Minutes	10 Minutes	15 Minutes		
101	Drive Fnd Deering Torons - Fakrantes	it 20 20 Minutes			
121.	Drive End Bearing Temps - Fahrenhei		20 Minutes		
	20 Minutes	25 Minutes	30 Minutes		
122.	Drive End Bearing Temps - Fahrenhei	it 35-45 Minutes			
	35 Minutes	40 Minutes	45 Minutes		
123.	Drive End Bearing Temps - Fahrenhe	it 50-60 Minutes			
	50 Minutes	55 Minutes	60 Minutes		
124	Opposite Drive End Bearing Temps -	Fahrenheit			
127.	5 Minutes	10 Minutes	15 Minutes		
	o Minutes	TO WIII Idios	10 Miliates		
125.	5. Opposite Drive End Bearing Temps - Fahrenheit 20-30 Minutes				
	20 Minutes	25 Minutes	30 Minutes		
126.	Opposite Drive End Bearing Temps -				
	35 Minutes	40 Minutes	45 Minutes		
127.	Opposite Drive End Bearing Temps -	Fahrenheit 50-60 Minutes			
	50 Minutes	55 Minutes	60 Minutes		
128.	Stator Temperatures- Fahrenheit				
	5 Minutes	10 Minutes	15 Minutes		
400	Otataa Taraa aratuu 5 1 1 200	O Minutes			
129.	Stator Temperatures- Fahrenheit 20-3		20 Minutes		
	20 Minutes	25 Minutes	30 Minutes		
130.	Stator Temperatures- Fahrenheit 35-4	15 Minutes			
	35 Minutes	40 Minutes	45 Minutes		
131.	Stator Temperatures- Fahrenheit 50-6	60 Minutes			
	50 Minutes	55 Minutes	60 Minutes		

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

132. Document Final Condition with Pictures after paint	
133. Final Pics and QC Review	

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.



STANDARD TERMS AND CONDITIONS FOR PURCHASE OF GOOD AND/OR SERVICES

- 1. APPLICABILITY. The sale of any and all goods and/or services by Mock, Inc. d/b/a Hi-Speed Industrial Service ("Hi-Speed") shall be specifically conditioned upon and subject to the following terms and conditions which are incorporated by reference into any contracts and purchase orders with Hi-Speed, and which shall form and become a part of any agreement related thereto. Buyer's acceptance of any offer or quotation made by Hi-Speed for sale of any goods or services is expressly made subject to the terms and conditions set forth herein and to be so effective, Buyer need not sign or approve these Terms and Conditions to be bound hereunder provided a copy of same is provided to Buyer through any means. None of the terms and conditions contained herein may be added to, expanded, changed, modified, superseded or otherwise altered except as revised in writing and duly executed by Hi-Speed, and all orders received by Hi-Speed shall be governed only by the terms and conditions contained herein, notwithstanding any terms, conditions or provisions of any purchase order, release order, authorization or any other form issued by the Buyer. Hi-Speed hereby objects to any additional, modified, changed, deleted, altered or other terms and conditions not contained herein and notifies Buyer that any such terms or provisions are expressly rejected by Hi-Speed.
- 2. PRICE. All quoted prices shall remain firm and binding for a period of thirty (30) days from the date of quotation or for the period specifically stated in the quotation. The price for any and all goods and/or services ordered or approved by Buyer after thirty (30) days from the date of any quotation are subject to any increase in price that may occur after the expiration of thirty (30) days from the issuance of the quotation and the date the Buyer releases any shipment.
- 3. SCOPE OF GOODS AND/OR SERVICES. The goods and/or services provided by Hi-Speed pursuant to any quotation shall be limited exclusively to those goods and/or services expressly identified therein. Hi-Speed does not assume any responsibility and/or liability for the failure to provide any other goods and/or services not identified in any quotation. Modifications, additions or deletions to or from the scope referenced in any quotation shall only bee effective if evidenced in writing and signed by Hi-Speed. The sale of any of all goods and/or services affected by such modification, addition or deletion shall be subject to these same Standard Terms and Conditions whether or not referenced therein.
- 4. <u>BILLING AND PAYMENT TERMS.</u> Hi-Speed shall invoice Buyer for all goods and/or services as same are rendered at the address listed on the quotation. Payments for all goods and/or services shall be due thirty (30) days from the date of the current invoice or as otherwise set forth in the quotation. Late payments are subject to a late fee of 5% of the total invoice amount. Recurring late payments may lead to a deposit requirement on future services or sale of goods. Buyer shall be liable to Hi-Speed for any and all fees and expenses incurred by Hi-Speed to collect any invoices or to enforce these Standard Terms and Conditions, including but not limited to, attorney's fees.
- 5. <u>DELIVERY OF GOODS AND/OR SERVICES.</u> Unless otherwise identified in the quotation, all shipments are F.O.B. Hi-Speed's warehouse and the title to and all risk of loss with respect to any goods shipped shall pass to Buyer when such goods are delivered to the carrier at Hi-Speed's warehouse. Hi-Speed will use its best efforts to affect delivery by the date or dates specified in the quotation. However, Hi-Speed shall not be liable for delay in or failure to make shipment, or to perform services, by any identified date for any reason whatsoever, including but not limited to, causes beyond its reasonable control, such as strikes, fires, floods, epidemics, quarantines, restrictions, severe weather, embargos, acts of God, or public enemy, war, riot, delays in transportation or the inability to obtain necessary labor, materials or manufacturing facilities.
- **DELIVERY SITE AND TIME FOR PERFORMANCE.** Hi-Speed and Buver agree that time is of the essence for the purchase order and that Buyer shall fully cooperate with Hi-Speed in order to allow Hi-Speed full access to prosecute its work diligently and in an orderly manner. Buyer shall assist Hi-Speed in every way possible to avoid delaying, disrupting or interfering with the progress of Hi-Speed's work at the project site. In the event Hi-Speed's work is delayed, hindered, suspended, disrupted, re-sequenced or interfered with or rendered less efficient or more costly or adversely affected in any way as a result of acts or omissions of Buyer or other contractors or employees of Buyer or by any other reason beyond Hi-Speed's control and without the fault of Hi-Speed, then, in such event, Buyer shall be liable to Hi-Speed for any damages, additional costs, expenses, labor, materials, man hours, acceleration costs, overtime, additional jobsite overhead, extended home office overhead, and any and all other direct and indirect expenses of whatsoever nature or kind, caused in whole or in part, as a result of any of the above-referenced occurrences. Hi-Speed's project records will be the basis for computing the additional costs and damages of Hi-Speed's labor, materials, expenses and overhead related to such changes. BUYER WARRANTS THAT THE SITE FOR DELIVERY OR INSTALLATION OF ANY GOODS AND/OR FOR THE PERFORMANCE OF ANY SERVICES SHALL BE READY AND ADEQUATE FOR HI-SPEED'S DELIVERY OF GOODS AND/OR PERFORMANCE OF SERVICES AND THAT HI-SPEED SHALL HAVE FULL ACCESS THERETO, FREE OF ALL OBSTRUCTIONS. BUYER SHALL ASSUME ALL EXTRA COSTS ASSOCIATED WITH HI-SPEED'S INABILITY TO INSTALL ANY GOODS OR PERFORM ANY SERVICES AS A RESULT OF BUYER'S FAILURE TO COMPLY WITH THIS PROVISION. HI-SPEED MAY NOT INSPECT THE SITE PRIOR TO DELIVERY AND/OR INSTALLATION OF GOODS AND/OR PERFORMANCE OF SERVICES AND MAKES NO WARRANTY AS TO THE SUFFICIENCY OF THE SITE FOR THE DELIVERY AND/OR INSTALLATION OF GOODS AND/OR THE PERFORMANCE OF SERVICES AT SUCH SITE.
- 7. INSPECTION/ACCEPTANCE. All goods and services ordered pursuant to any quotation shall be subject to inspection by Buyer after delivery or performance to determine conformity with the quotation and/or purchase order and Hi-Speed's advertised or published specifications. Buyer shall have a period of thirty (30) days from shipment of goods at the delivery destination specified in the quotation within which to inspect the goods for conformity with the quotation, order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. Buyer shall have a period of thirty (30) days following completion of any services within which to inspect the services for conformity with the quotation, purchase order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. If the goods delivered or services performed do not so conform, upon delivery of notice to Hi-Speed of any discrepancy, nonconformance or rejection, Hi-Speed shall have sixty (60) days to cure the alleged discrepancy and/or nonconformance. If Hi-Speed fails to cure in this time period, Buyer shall have the right to reject such goods or services. After the cure period, goods that have been delivered and rejected, in whole or in part, shall be returned to Hi-Speed. Buyer shall notify Hi-Speed and arrange for the return of the goods as required. Should such non-conforming services be rejected Hi-Speed shall, at its sole cost, re-perform the non-conforming services. Inspection or failure to inspect on any occasion shall not affect Buyer's rights under the warranty provisions herein.
- 8. WARRANTIES. Hi-Speed warrants that all goods shall conform in all material aspects to the goods identified in the quotation to Buyer and/or purchase order, and Hi-Speed makes to Buyer the manufacturer's express warranty for any goods sold to Buyer, which is offered by the manufacturer at the time of acceptance of any quotation by Buyer. This warranty is conditioned upon the installation, operation, and maintenance of the goods in accordance with the manufacturer's recommendations and/or standard industry practice and the goods at all times being operated or used under normal operating conditions for which they were designed. Hi-Speed, at its sole option, will repair or

replace any defective or non-conforming goods in accordance with the applicable manufacturer's warranty. Warranty for any defective or incorrect parts is limited to the repair or replacement of those parts. Hi-Speed warrants that all services will conform in all material respects to the description of services identified in the quotation and will be performed in a good and workmanlike manner in accordance with industry practices and standards. Should the services be reasonably rejected or not conform with the foregoing warranties, Hi-Speed shall, at its sole cost, re-perform the defective or nonconforming services. Notwithstanding the foregoing, these warranties do not extend to goods or services to the extent that such goods have been subject to misuse, neglect or abuse not caused by Hi-Speed or have been used in violation of the approved written instructions furnished to Buyer. THE FOREGOING REPRESENTS THE SOLE AND EXCLUSIVE WARRANTY GIVEN BY HI-SPEED WITH RESPECT TO ALL GOODS SOLD AND IS IN LIEU OF ALL OTHER WARRANTIES EITHER EXPRESS OR IMPLIED. HI-SPEED EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICLAR USE OR PURPOSE. BUYER WAIVES ANY CLAIM THAT THESE EXCLUSIONS OR LIMITATIONS DEPRIVE IT OF AN ADEQUATE REMEDY AT EQUITY OR LAW OR CAUSE THIS AGREEMENT TO FAIL IN ITS ESSENTIAL PURPOSE. BUYER SHALL BE ENTITLED TO NO OTHER REMEDY OTHER THAN AS SET FORTH HEREIN, REGARDLESS OF THE CLAIM OR CAUSE OF ACTION, WHETHER BASED IN CONTRACT, TORT, NEGLIGENCE, GOODS LIABILITY, STRICT LIABILITY OR OTHERWISE.

- 9. <u>LIMITATION OF DAMAGES.</u> HI-SPEED SHALL HAVE NO LIABILITY TO BUYER WITH RESPECT TO THE SALE OR DELIVERY OF ANY GOODS OR THE REPAIR THEREOF OR WITH RESPECT TO THE SALE OR PERFORMANCE OF ANY SERVICES, FOR LOST PROFITS, SPECIAL, CONSEQUENTIAL, EXEMPLARY, PUNITIVE OR INCIDENTAL DAMAGES OF ANY KIND OR NATURE WHETHER ARISING IN CONTRACT, TORT, GOODS LIABILITY OR OTHERWISE, EVEN IF HI-SPEED WAS ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGES. HI-SPEED SHALL NOT BE LIABLE FOR ANY DAMAGES OR DELAYS CAUSED BY ANY FAILURE TO MAKE ANY DELIVERY OF GOODS BY ANY EXPECTED TIME OR DATE OR THE FAILURE TO PROVIDE OR COMPLETE ANY SERVICES BY ANY EXPECTED DATE OR TIME. IN NO EVENT SHALL HI-SPEED BE LIABLE TO BUYER FOR ANY DAMAGES WHATSOEVER IN EXCESS OF THE TOTAL PRICE PAID FOR ALL GOODS AND/OR SERVICES HEREUNDER OR REFERENCED IN ANY QUOTATION OR THE PURCHASE ORDER.
- 10. <u>SEVERABILITY.</u> The partial or complete invalidity of any provision of these Standard Terms and Conditions shall not affect the enforceability of the remainder of these Standard Terms and Conditions. If any provision is found to be invalid or unenforceable, that portion shall be modified to make it enforceable or shall be stricken and the remainder of these Standard Terms and Conditions shall enforced.
- 11. **GOVERNING LAW AND JURISDICTION.** Any controversy arising out of any quotation, the purchase order, the goods sold or delivered, repair or replacement thereof, or any services provided pursuant to any quotation or any purchase order, or these Standard Terms and Conditions shall be governed by the laws of the state of Tennessee without regard to any choice of law provisions and any cause of action related in any manner thereto shall be brought only in the state or federal courts of Shelby County, Tennessee.
- 12. ABANDONED EQUIPMENT. Hi-Speed requires that Buyer promptly pick up or provide shipment instructions for Buyer equipment or other Buyer property in Hi-Speed's possession. If equipment or other Buyer property is left with Hi-Speed and not picked up within six (6) months after Hi-Speed's final action related to the applicable property (e.g. evaluation, teardown, estimate, completion of services), Hi-Speed will consider such property abandoned and may dispose of it in accordance with applicable law. Buyer agrees to hold Hi-Speed harmless for any damage or claim for such abandoned property and acknowledges that Hi-Speed may discard or recycle it at Hi-Speed's sole and absolute discretion. Specifically, Hi-Speed may sell Buyer's abandoned property at a private or public sale and retain the proceeds to offset Hi-Speed's storage, inspection and servicing costs. For the avoidance of doubt, Hi-Speed reserves its statutory and other lawful liens for unpaid charges related to abandoned property.
- 13. FORCE MAJEURE. Neither party shall be responsible for any delay or failure in performance of any party of the quotation, purchase order or these Standard Terms and Conditions to the extent that such delays or failures are caused by fire, flood, earth quake, explosion, war, embargo, government requirement, civil or military authority, acts of God, or any other circumstances beyond its reasonable control and not involving any fault or negligence on the party affected ("Condition"). If any such Condition occurs, the party delayed or unable to perform shall promptly give written notice to the other party and, if such Condition remains at the end of thirty (30) days, the party affected by the other party's delay and inability to perform may elect to (i) terminate such order or part thereof, or (ii) suspend the order for the duration of the Condition, if the Buyer is the suspending party, buy elsewhere comparable material to be sold under the order and apply to any commitment the purchase price of such purchase, and resume performance of the order once the Condition ceases, with an option in the affected party to extend the period of this order up to the length of the time the Condition endures.
- 14. <u>NONWAIVER.</u> No course of dealing or failure of either party to strictly enforce any term, right, or condition of these Standard Terms and Conditions will be construed as a waiver of such term, right or condition. Any waiver by Hi-Speed will only be in writing and will waive no succeeding breach of a term, right or condition.
- 15. <u>ASSIGNMENT.</u> The rights and obligations of the parties shall neither be assigned nor delegated without the prior written consent of the other party. However, any party may assign or delegate its respective rights and obligations, in whole or in part, (i) to any subsidiary, (ii) pursuant to other financing, merger or reorganization or (iii) pursuant to any sale or transfer of substantially all of the assets of the assigning party. These Standard Terms and Conditions shall bind the heirs, successors and assigns of the parties hereto.
- 16. NO INDIVIDUAL LIABILITY. Notwithstanding any other agreement to the contrary, the Buyer agrees that in no event will the Buyer hold and HI-Speed owner, director, officer or employee personally liable for unintentional tortious conduct or conduct that constitutes the breach of any contract between HI-Speed and the Buyer, even if the HI-Speed owner, director, officer or employee is or could be construed to be a party to such contract.