

EVERY DAY SINCE 1946

LR Motor Shop Repairs

Job Number 103572

Prepared for Bryce Corporation (10053-BRC)

450 S. Benton Searcy AR 72143

Table of Contents

AC Inspection as Found - MOTOR SHOP LR



MOTOR SHOP LR

X2011M04138

Description: 300HP BALDOR 1785RPM

Hi-Speed Industrial Service 7030 Ryburn Dr Millington, Tn 38053 901-873-5300

> FolderID: 103572 FormID: 21768595

AC Inspection as Found

Bryce Corporation (10053-BRC) 450 S. Benton

AC Inspection - Rev. 2

Searcy, AR 72143

Serial Number:

Location:

	Hi-Speed Job Number:	103572
२	Manufacturer:	Baldor
	Product Number:	CAT: 12085880471-20
PM	Spec/ID #:	P40T1331
	Serial Number:	X2011M04138
	HP/kW:	300 (HP)
	RPM:	1785 (RPM)
	Frame:	PFL4034
	Voltage:	460
	Phase:	Three
	Hz:	60 (Hz)
	# of Leads:	3
	J-box Included:	None
	Coupling/Sheave:	Coupling
	Date Received:	09/30/2024
	Bearing RTDs:	No
	Stator RTDs:	No
	Repair Stage:	Final
	Rewind:	Yes
	Shaft Machined Fit Repairs Required:	Yes
	Bearing Housing Machined Fit Repairs Required:	Yes
	Heaters:	No
	Winding Type :	Random Wound
	Bearing Type:	Rolling Element
4 - Good		

Priorities Found: **6 - High**

Overall Condition

1. Report Date

09/30/2024

2. Nameplate Picture



3. Photos of all six sides of the machine.





































4.	Describe the Overall Condition of	the Equipment as Received		
	Plastic melted to top			
5.	Distance from the end of the shaft	to the Coupling/Sheave		0.9755 inches
6.	Report Date [COPY]			09/30/2024
Initia	I Mechanical/Electrical			
• 7.	Does Shaft Turn Freely?			(Y) Yes
8.	Does the shaft require T.I.R in Lat	he to identify additional repairs?		(No) No
9.	Does Shaft Have Visible Damage?	?		(No) No
10.	Assembled Shaft Runout			0 Inches
11.	Assembled Shaft End Play			0 inches
12.	Air Gap Variation <10%			none
13.	Lead Condition			(P) Pass
14.	Lead Length			18 Inches
15.	Does it have Lugs?, If so what is the	he Stud Size?		(Yes) Yes
	3/8			
16.	Lead Numbers			1-3
17.	Frame Condition			good
18.	Fan Condition			(N) NA
19.	Broken or Missing Components			none
Initia	Electrical Inspection			
20.	Insulation Resistance/Megger			2000 Megohms
21.	Winding Resistance			
	1-2	1-3	2-3	
	0	0	0	
22.	Perform Surge Test			(F) Fail
23.	Number of Stator Slots			72
24.	Stator Condition			rewind
25.	Stator Thermistors/Ohms			0
26.	Stator Overloads/Ohms			1
	3 overloads			
Mech	anical Inspection			

27. Drive End Bearing Brand



28.	Drive End Bearing Number-	6219
29.	Drive End Bearing Qty.	1
30.	Drive End Bearing Type	(Ball) Ball Bearing
31.	Drive End Lubrication Type	(Grease) Grease Lubricated
32.	Drive End Bearing Insulation or Grounding Device?	none
33.	Drive End Wavy Washer/Snap-Ring Other Retention Device?	none
34.	Drive End Bearing Condition	fatigued
35.	Opposite Drive End Bearing Brand	nachi
36.	Opposite Drive End Bearing Number-	6316
37.	Opposite Drive End Bearing Qty.	1
38.	Opposite Drive End Bearing Type	(Ball) Ball Bearing
39.	Opposite Drive End Lubrication Type	(Grease) Grease Lubricated
40.	Opposite Drive End Bearing Insulation or Grounding Device?	none
41.	Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device?	wavy. snap ring groove but no snap ring
42.	Opposite Drive End Bearing Condition	frosting
43.	Drive End Seal	none
44.	Opposite Drive End Seal	none
Rotor	Inspection	
45.	Rotor Type/Material	(Squirrel Aluminum) Squirrel Cage Aluminum Die Cast
46.	Growler Test	(Pass) Pass
47.	Number of Rotor Bars	
48.	Rotor Condition	good
49.	List the Parts needed for the Repair Below	
	3.590 aegis rewind 6219 6316	
50.	Signature of Technician that Disassembled Motor	David Maclin
	M	
L		
/ Mecha	anical Fits- Rotor	

52.	Rotor Runout		
	Drive End Bearing Fit	Rotor Body	Opposite Drive End Bearing
	0	0	0
53.	Coupling Fit Closest to Bearing Housi	ng	
	0 Degrees	90 Degrees	120 Degrees
	0	0	0
54.	Coupling Fit Closest to the end of the	Shaft	
	0 Degrees	60 Degrees	120 Degrees
	0	0	0
55.	Drive End Bearing Shaft Fit		
	0 Degrees	60 Degrees	120 Degrees
	0	0	0
	Badly damaged		
56.	Drive End Bearing Shaft Fit Condition		(F) Fail
57.	Opposite Drive End Bearing Shaft Fit		
	0 Degrees	60 Degrees	120 Degrees
	3.9375	3.9374	3.9374
58.	Opposite Drive End Bearing Shaft Fit	Condition	(P) Pass
59.	Shaft Air Seal Fits		
	Drive End Air Seal	Opposite Drive End Air Seal	
	ok	ok	
Mecha	anical Fits- Bearing Housings		
60.	Drive End - Endbell Bearing Fit		
	0 Degrees	60 Degrees	120 Degrees
	0	0	0
	Badly damaged		
61.	Drive End - Endbell Bearing Fit Condi	tion	(F) Fail
62.	Opposite Drive End - Endbell Bearing	Fit	
	0 Degrees	60 Degrees	120 Degrees
	8.465	8.465	8.465
63.	Opposite Drive End - Endbell Bearing	Fit Condition	(F) Fail
64.	Bearing Cap Condition		
	Drive End Bearing Cap	Opposite Drive End Bearing Cap	
	sleeve	ok	
65.	End Bell Air Seal Fits		
	Drive End Air Seal	Opposite Drive End Air Seal	
	sleeve	ok	
66.			
		air seal, DE bearing cap air seal, fit aegis DE	
67.	Technician		David Maclin
	$\langle \rangle$		
/		$ \rangle$	
Root	Cause of Failure		
Root			

68.	Failure locations		
	De bearing		
69.	Root cause of failure		
	Fatigue, may have been due to frosting		
	mic Balance Report		
70.	Rotor Weight and Balance Grade		
	Rotor Weight	Balance Grade	
74			
71.	Initial Balance Readings		
	Drive End	Opposite Drive End	
72.	Final Balance Readings		
	Drive End	Opposite Drive End	
73.	Technician		
Rewin	nd		
74.	Core Test Results - Watts loss per Po	und	
	Pre-Burnout	Post Burnout	
75.	Core Hot Spot Test		
	Pre-Burnout	Post-Burnout	
76.	Post Rewind Electrical Test- Insulatio	n Resistance	
77.	Post Rewind Polarization Index		
78.	Post Rewind Winding Resistance		
	1-2	1-3	2-3
79.	Post Rewind Surge Test		
80.	Post Rewind Hi-Pot		
81.	Technician		
Mecha	anical Fits- Rotor - Post Repair		
82.	Shaft Runout Post Repair		0.0005 inches
83.	Rotor Runout Post Repair		
	Drive End Bearing Fit	Rotor Body	Opposite Drive End Bearing
	0.002	0.002	0.001
84.	Coupling Fit Closest to Bearing Housi	ng Post Repair	
	0 Degrees	90 Degrees	120 Degrees
85.	1 0		
	0 Degrees	60 Degrees	120 Degrees

86.				
	Drive End Bearing Shaft Fit Post Rep		100 Degrees	
	0 Degrees 3.7409	60 Degrees 3.7409	120 Degrees 3.7409	
87.	••••••			
	0 Degrees	60 Degrees	120 Degrees	
88	Shaft Air Seal Fits Post Repair			
00.	Drive End Air Seal	Opposite Drive End Air Seal		
	.018	Opposite Drive End All Geal		
200	3,7319			
89.	Shaft Repair Sign-off		Ga	rу
	Shaft Repair Sign-off Anical Fits- Bearing Housings - P	ost Repair	Ga	ry
Mech	2		Ga	ry
Mech	anical Fits- Bearing Housings - P		Ga 120 Degrees	ry
Mech 90.	anical Fits- Bearing Housings - P Drive End - Endbell Bearing Fit Post F 0 Degrees	Repair 60 Degrees		ry
Mech 90.	anical Fits- Bearing Housings - P Drive End - Endbell Bearing Fit Post F 0 Degrees Opposite Drive End - Endbell Bearing	Repair 60 Degrees Fit Post Repair	120 Degrees	ry
Mech 90.	anical Fits- Bearing Housings - P Drive End - Endbell Bearing Fit Post F 0 Degrees	Repair 60 Degrees		ry

Drive End Bearing Cap Opposite Drive End Bearing Cap 93. End Bell Air Seal Fits Post Repair Drive End Air Seal Opposite Drive End Air Seal 94. End Bell Repair Sign-off Assembly 95. QC Check All Parts for Cleanliness Prior to Assembly 96. Photograph All Major Components prior to Assembly 97. Final Insulation Resistance Test 98. Assembled Shaft Runout 100. Test Run Voltage Volts Volts Volts Volts 101. Test Run Amperage Amps Amps 102. Drive End Vibration Readings - Inches Per Second Horizontal Vertical 103. Opposite Drive End Vibration Readings - Inches Per Second Horizontal Vertical Axial 103. Opposite Drive End Vibration Readings - Inches Per Second Horizontal Vertical Axial 104. Ambient Temperature - Fahrenheit 105. Drive End Bearing Temps - Fahrenheit 106. Opposite Drive End Bearing Temps - Fahrenheit 107. Document Final Condition with Pictures after paint 108. Final Pics and QC Review	92.	Bearing Cap Condition Post Repair		
Drive End Air Seal Opposite Drive End Air Seal 94. End Bell Repair Sign-off Assembly 95. QC Check All Parts for Cleanliness Prior to Assembly 96. Photograph All Major Components prior to assembly 97. Final Insulation Resistance Test 98. Assembled Shaft Endplay 99. Assembled Shaft Endplay 100. Test Run Amperage Amps Amps Amps Amps Amps Amps Assembled Vibration Readings - Inches Per Second Horizontal Vertical Axial 104. Ambient Temperature - Fahrenheit 105. Drive End Bearing Temps - Fahrenheit 106. Opposite Drive End Bearing Tem		Drive End Bearing Cap	Opposite Drive End Bearing Cap	
Drive End Air Seal Opposite Drive End Air Seal 94. End Bell Repair Sign-off Assembly 95. QC Check All Parts for Cleanliness Prior to Assembly 96. Photograph All Major Components prior to assembly 97. Final Insulation Resistance Test 98. Assembled Shaft Endplay 99. Assembled Shaft Endplay 100. Test Run Amperage Amps Amps Amps Amps Amps Amps Assembled Vibration Readings - Inches Per Second Horizontal Vertical Axial 104. Ambient Temperature - Fahrenheit 105. Drive End Bearing Temps - Fahrenheit 106. Opposite Drive End Bearing Tem				
94. End Bell Repair Sign-off Assembly 95. QC Check All Parts for Cleanliness Prior to Assembly 96. Photograph All Major Components prior to assembly 97. Final Insulation Resistance Test 98. Assembled Shaft Endplay 99. Assembled Shaft Runout 100. Test Run Voltage Volts Volts Volts Volts Volts Volts 101. Test Run Amperage Amps Amps Amps 102. Drive End Vibration Readings - Inches Per Second Horizontal Vertical Axial 103. Opposite Drive End Vibration Readings - Inches Per Second Horizontal Vertical 104. Ambient Temperature - Fahrenheit 105. Drive End Bearing Temps - Fahrenheit 5 Minutes 106. Opposite Drive End Bearing Temps - Fahrenheit 5 Minutes 107. Document Final Condition with Pictures after paint	93.	End Bell Air Seal Fits Post Repair		
Assembly 95. QC Check All Parts for Cleanliness Prior to Assembly 96. Photograph All Major Components prior to assembly 97. Final Insulation Resistance Test 98. Assembled Shaft Endplay 99. Assembled Shaft Runout 100. Test Run Voltage Volts Volts Volts Volts 101. Test Run Amperage Amps Amps Amps Amps 102. Drive End Vibration Readings - Inches Per Second Horizontal Vertical Axial 103. Opposite Drive End Vibration Readings - Inches Per Second Horizontal Vertical Axial 104. Ambient Temperature - Fahrenheit 105. Drive End Bearing Temps - Fahrenheit 106. Opposite Drive End Bearing Temps - Fahrenheit 107. Drive End Bearing Temps - Fahrenheit 108. Opposite Drive End Bearing Temps - Fahrenheit 109. Opposite Drive End Bearing Temps - Fahrenheit 1010. Opposite Drive End Bearing Temps - Fahrenheit 1011. Test Condition with Pictures after paint		Drive End Air Seal	Opposite Drive End Air Seal	
Assembly 95. QC Check All Parts for Cleanliness Prior to Assembly 96. Photograph All Major Components prior to assembly 97. Final Insulation Resistance Test 98. Assembled Shaft Endplay 99. Assembled Shaft Runout 100. Test Run Voltage Volts Volts Volts Volts 101. Test Run Amperage Amps Amps Amps Amps 102. Drive End Vibration Readings - Inches Per Second Horizontal Vertical Axial 103. Opposite Drive End Vibration Readings - Inches Per Second Horizontal Vertical Axial 104. Ambient Temperature - Fahrenheit 105. Drive End Bearing Temps - Fahrenheit 106. Opposite Drive End Bearing Temps - Fahrenheit 107. Drive End Bearing Temps - Fahrenheit 108. Opposite Drive End Bearing Temps - Fahrenheit 109. Opposite Drive End Bearing Temps - Fahrenheit 1010. Opposite Drive End Bearing Temps - Fahrenheit 1011. Test Condition with Pictures after paint	94.	End Bell Repair Sign-off		
95. QC Check All Parts for Cleanliness Prior to Assembly 96. Photograph All Major Components prior to assembly 97. Final Insulation Resistance Test 98. Assembled Shaft Endplay 99. Assembled Shaft Runout 100. Test Run Voltage Volts Volts 101. Test Run Amperage Amps Amps 102. Drive End Vibration Readings - Inches Per Second Horizontal Vertical 103. Opposite Drive End Vibration Readings - Inches Per Second Horizontal Vertical 103. Opposite Drive End Vibration Readings - Inches Per Second Horizontal Vertical 104. Ambient Temperature - Fahrenheit 105. Drive End Bearing Temps - Fahrenheit 106. Opposite Drive End Bearing Temps - Fahrenheit 107. Document Final Condition with Pictures after paint		· •		
96. Photograph All Major Components prior to assembly 97. Final Insulation Resistance Test 98. Assembled Shaft Endplay 99. Assembled Shaft Runout 100. Test Run Voltage Volts Volts Volts Volts 101. Test Run Amperage Amps Amps Amps Amps 102. Drive End Vibration Readings - Inches Per Second Horizontal Vertical Axial 103. Opposite Drive End Vibration Readings - Inches Per Second Horizontal Vertical Axial 104. Ambient Temperature - Fahrenheit 105. Drive End Bearing Temps - Fahrenheit 106. Opposite Drive End Bearing Temps - Fahrenheit 107. Document Final Condition with Pictures after paint		•	ior to Assembly	
97. Final Insulation Resistance Test 98. Assembled Shaft Endplay 99. Assembled Shaft Runout 100. Test Run Voltage Volts Volts 101. Test Run Amperage Amps Amps Amps Amps 102. Drive End Vibration Readings - Inches Per Second Horizontal Vertical Axial 103. Opposite Drive End Vibration Readings - Inches Per Second Horizontal Vertical Axial 104. Ambient Temperature - Fahrenheit 105. Drive End Bearing Temps - Fahrenheit 106. Opposite Drive End Bearing Temps - Fahrenheit 106. Opposite Drive End Bearing Temps - Fahrenheit 107. Document Final Condition with Pictures after paint			-	
98. Assembled Shaft Endplay 99. Assembled Shaft Runout 100. Test Run Voltage Volts Volts 101. Test Run Amperage Amps Amps 102. Drive End Vibration Readings - Inches Per Second Horizontal Vertical 103. Opposite Drive End Vibration Readings - Inches Per Second Horizontal Vertical Axial 104. Ambient Temperature - Fahrenheit 105. Drive End Bearing Temps - Fahrenheit 5 Minutes 10 Minutes 106. Opposite Drive End Bearing Temps - Fahrenheit 5 Minutes 10 Minutes 107. Document Final Condition with Pictures after paint				
99. Assembled Shaft Runout 100. Test Run Voltage Volts Volts 101. Test Run Amperage Amps Amps 102. Drive End Vibration Readings - Inches Per Second Horizontal Vertical 103. Opposite Drive End Vibration Readings - Inches Per Second Horizontal Vertical Ambient Temperature - Fahrenheit 105. Drive End Bearing Temps - Fahrenheit 5 Minutes 10 Minutes 106. Opposite Drive End Bearing Temps - Fahrenheit 5 Minutes 10 Minutes 107. Document Final Condition with Pictures after paint				
VoltsVoltsVolts101. Test Run AmperageAmpsAmpsAmpsAmps102. Drive End Vibration Readings - Inches Per SecondHorizontalVerticalAxial103. Opposite Drive End Vibration Readings - Inches Per SecondHorizontalVerticalAxial104. Ambient Temperature - Fahrenheit105. Drive End Bearing Temps - Fahrenheit5 Minutes10 Minutes106. Opposite Drive End Bearing Temps - Fahrenheit107. Document Final Condition with Pictures after paint		· · ·		
VoltsVoltsVolts101. Test Run AmperageAmpsAmpsAmpsAmps102. Drive End Vibration Readings - Inches Per SecondHorizontalVerticalAxial103. Opposite Drive End Vibration Readings - Inches Per SecondHorizontalVerticalAxial104. Ambient Temperature - Fahrenheit105. Drive End Bearing Temps - Fahrenheit5 Minutes10 Minutes106. Opposite Drive End Bearing Temps - Fahrenheit107. Document Final Condition with Pictures after paint	100.	Test Run Voltage		
Amps Amps Amps 102. Drive End Vibration Readings - Inches Per Second Axial 103. Opposite Drive End Vibration Readings - Inches Per Second Axial 103. Opposite Drive End Vibration Readings - Inches Per Second Axial 104. Ambient Temperature - Fahrenheit Axial 105. Drive End Bearing Temps - Fahrenheit 15 Minutes 106. Opposite Drive End Bearing Temps - Fahrenheit 15 Minutes 107. Document Final Condition with Pictures after paint 15 Minutes		-	Volts	Volts
Amps Amps Amps 102. Drive End Vibration Readings - Inches Per Second Axial 103. Opposite Drive End Vibration Readings - Inches Per Second Axial 103. Opposite Drive End Vibration Readings - Inches Per Second Axial 104. Ambient Temperature - Fahrenheit Axial 105. Drive End Bearing Temps - Fahrenheit 15 Minutes 106. Opposite Drive End Bearing Temps - Fahrenheit 15 Minutes 107. Document Final Condition with Pictures after paint 15 Minutes				
102. Drive End Vibration Readings - Inches Per Second Horizontal Vertical 103. Opposite Drive End Vibration Readings - Inches Per Second Horizontal Vertical Axial 104. Ambient Temperature - Fahrenheit 105. Drive End Bearing Temps - Fahrenheit 5 Minutes 10 Minutes 106. Opposite Drive End Bearing Temps - Fahrenheit 5 Minutes 10 Minutes 107. Document Final Condition with Pictures after paint	101.	Test Run Amperage		
Horizontal Vertical Axial 103. Opposite Drive End Vibration Readings - Inches Per Second		Amps	Amps	Amps
Horizontal Vertical Axial 103. Opposite Drive End Vibration Readings - Inches Per Second	100	Drive End Vibratian Deadings Inches	Der Second	
103. Opposite Drive End Vibration Readings - Inches Per Second Horizontal Vertical Axial 104. Ambient Temperature - Fahrenheit 105. Drive End Bearing Temps - Fahrenheit 5 Minutes 10 Minutes 106. Opposite Drive End Bearing Temps - Fahrenheit 5 Minutes 10 Minutes 107. Document Final Condition with Pictures after paint	102.	-		Avial
Horizontal Vertical Axial 104. Ambient Temperature - Fahrenheit - 105. Drive End Bearing Temps - Fahrenheit - 5 Minutes 10 Minutes 106. Opposite Drive End Bearing Temps - Fahrenheit - 5 Minutes 10 Minutes 107. Document Final Condition with Pictures after paint -		Honzontai	venical	Axiai
104. Ambient Temperature - Fahrenheit 105. Drive End Bearing Temps - Fahrenheit 5 Minutes 10 Minutes 106. Opposite Drive End Bearing Temps - Fahrenheit 5 Minutes 10 Minutes 106. Opposite Drive End Bearing Temps - Fahrenheit 107. Document Final Condition with Pictures after paint	103.	3. Opposite Drive End Vibration Readings - Inches Per Second		
105. Drive End Bearing Temps - Fahrenheit 5 Minutes 10 Minutes 106. Opposite Drive End Bearing Temps - Fahrenheit 5 Minutes 10 Minutes 107. Document Final Condition with Pictures after paint		Horizontal	Vertical	Axial
105. Drive End Bearing Temps - Fahrenheit 5 Minutes 10 Minutes 106. Opposite Drive End Bearing Temps - Fahrenheit 5 Minutes 10 Minutes 107. Document Final Condition with Pictures after paint				
5 Minutes 10 Minutes 15 Minutes 106. Opposite Drive End Bearing Temps - Fahrenheit 5 Minutes 10 Minutes 5 Minutes 10 Minutes 15 Minutes 107. Document Final Condition with Pictures after paint 15 Minutes		04. Ambient Temperature - Fahrenheit		
106. Opposite Drive End Bearing Temps - Fahrenheit 5 Minutes 10 Minutes 107. Document Final Condition with Pictures after paint	105.			
5 Minutes 10 Minutes 15 Minutes 107. Document Final Condition with Pictures after paint 15 Minutes		5 Minutes	10 Minutes	15 Minutes
5 Minutes 10 Minutes 15 Minutes 107. Document Final Condition with Pictures after paint 15 Minutes	106.	Opposite Drive End Bearing Temps -	Fahrenheit	
107. Document Final Condition with Pictures after paint				15 Minutes
· · · · · · · · · · · · · · · · · · ·				
108. Final Pics and QC Review	107.	Document Final Condition with Picture	es after paint	
	108.	Final Pics and QC Review		



STANDARD TERMS AND CONDITIONS FOR PURCHASE OF GOOD AND/OR SERVICES

- 1. <u>APPLICABILITY.</u> The sale of any and all goods and/or services by Mock, Inc. d/b/a Hi-Speed Industrial Service ("Hi-Speed") shall be specifically conditioned upon and subject to the following terms and conditions which are incorporated by reference into any contracts and purchase orders with Hi-Speed, and which shall form and become a part of any agreement related thereto. Buyer's acceptance of any offer or quotation made by Hi-Speed for sale of any goods or services is expressly made subject to the terms and conditions set forth herein and to be so effective, Buyer need not sign or approve these Terms and Conditions to be bound hereunder provided a copy of same is provided to Buyer through any means. None of the terms and conditions contained herein may be added to, expanded, changed, modified, superseded or otherwise altered except as revised in writing and duly executed by Hi-Speed, and all orders received by Hi-Speed shall be governed only by the terms and conditions contained herein, notwithstanding any terms, conditions or provisions of any purchase order, release order, authorization or any other form issued by the Buyer. Hi-Speed hereby objects to any additional, modified, changed, deleted, altered or other terms and conditions not contained herein and notifies Buyer that any such terms or provisions are expressly rejected by Hi-Speed.
- 2. PRICE. All quoted prices shall remain firm and binding for a period of thirty (30) days from the date of quotation or for the period specifically stated in the quotation. The price for any and all goods and/or services ordered or approved by Buyer after thirty (30) days from the date of any quotation are subject to any increase in price that may occur after the expiration of thirty (30) days from the issuance of the quotation and the date the Buyer releases any shipment.
- 3. <u>SCOPE OF GOODS AND/OR SERVICES.</u> The goods and/or services provided by Hi-Speed pursuant to any quotation shall be limited exclusively to those goods and/or services expressly identified therein. Hi-Speed does not assume any responsibility and/or liability for the failure to provide any other goods and/or services not identified in any quotation. Modifications, additions or deletions to or from the scope referenced in any quotation shall only be effective if evidenced in writing and signed by Hi-Speed. The sale of any of all goods and/or services affected by such modification, addition or deletion shall be subject to these same Standard Terms and Conditions whether or not referenced therein.
- 4. <u>BILLING AND PAYMENT TERMS.</u> Hi-Speed shall invoice Buyer for all goods and/or services as same are rendered at the address listed on the quotation. Payments for all goods and/or services shall be due thirty (30) days from the date of the current invoice or as otherwise set forth in the quotation. Late payments are subject to a late fee of 5% of the total invoice amount. Recurring late payments may lead to a deposit requirement on future services or sale of goods. Buyer shall be liable to Hi-Speed for any and all fees and expenses incurred by Hi-Speed to collect any invoices or to enforce these Standard Terms and Conditions, including but not limited to, attorney's fees.
- 5. DELIVERY OF GOODS AND/OR SERVICES. Unless otherwise identified in the quotation, all shipments are F.O.B. Hi-Speed's warehouse and the title to and all risk of loss with respect to any goods shipped shall pass to Buyer when such goods are delivered to the carrier at Hi-Speed's warehouse. Hi-Speed will use its best efforts to affect delivery by the date or dates specified in the quotation. However, Hi-Speed shall not be liable for delay in or failure to make shipment, or to perform services, by any identified date for any reason whatsoever, including but not limited to, causes beyond its reasonable control, such as strikes, fires, floods, epidemics, quarantines, restrictions, severe weather, embargos, acts of God, or public enemy, war, riot, delays in transportation or the inability to obtain necessary labor, materials or manufacturing facilities.
- 6. DELIVERY SITE AND TIME FOR PERFORMANCE. Hi-Speed and Buver agree that time is of the essence for the purchase order and that Buyer shall fully cooperate with Hi-Speed in order to allow Hi-Speed full access to prosecute its work diligently and in an orderly manner. Buyer shall assist Hi-Speed in every way possible to avoid delaying, disrupting or interfering with the progress of Hi-Speed's work at the project site. In the event Hi-Speed's work is delayed, hindered, suspended, disrupted, re-sequenced or interfered with or rendered less efficient or more costly or adversely affected in any way as a result of acts or omissions of Buyer or other contractors or employees of Buyer or by any other reason beyond Hi-Speed's control and without the fault of Hi-Speed, then, in such event, Buyer shall be liable to Hi-Speed for any damages, additional costs, expenses, labor, materials, man hours, acceleration costs, overtime, additional jobsite overhead, extended home office overhead, and any and all other direct and indirect expenses of whatsoever nature or kind, caused in whole or in part, as a result of any of the above-referenced occurrences. Hi-Speed's project records will be the basis for computing the additional costs and damages of Hi-Speed's labor, materials, expenses and overhead related to such changes. BUYER WARRANTS THAT THE SITE FOR DELIVERY OR INSTALLATION OF ANY GOODS AND/OR FOR THE PERFORMANCE OF ANY SERVICES SHALL BE READY AND ADEQUATE FOR HI-SPEED'S DELIVERY OF GOODS AND/OR PERFORMANCE OF SERVICES AND THAT HI-SPEED SHALL HAVE FULL ACCESS THERETO, FREE OF ALL OBSTRUCTIONS. BUYER SHALL ASSUME ALL EXTRA COSTS ASSOCIATED WITH HI-SPEED'S INABILITY TO INSTALL ANY GOODS OR PERFORM ANY SERVICES AS A RESULT OF BUYER'S FAILURE TO COMPLY WITH THIS PROVISION. HI-SPEED MAY NOT INSPECT THE SITE PRIOR TO DELIVERY AND/OR INSTALLATION OF GOODS AND/OR PERFORMANCE OF SERVICES AND MAKES NO WARRANTY AS TO THE SUFFICIENCY OF THE SITE FOR THE DELIVERY AND/OR INSTALLATION OF GOODS AND/OR THE PERFORMANCE OF SERVICES AT SUCH SITE.
- 7. INSPECTION/ACCEPTANCE. All goods and services ordered pursuant to any quotation shall be subject to inspection by Buyer after delivery or performance to determine conformity with the quotation and/or purchase order and Hi-Speed's advertised or published specifications. Buyer shall have a period of thirty (30) days from shipment of goods at the delivery destination specified in the quotation within which to inspect the goods for conformity with the quotation, order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. Buyer shall have a period of thirty (30) days following completion of any services within which to inspect the services for conformity with the quotation, purchase order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. If the goods delivered or services performed do not so conform, upon delivery of notice to Hi-Speed of any discrepancy, nonconformance or rejection, Hi-Speed shall have the right to reject such goods or services. After the cure period, goods that have been delivered and rejected, in whole or in part, shall be returned to Hi-Speed. Buyer shall notify Hi-Speed and arrange for the return of the goods as required. Should such non-conforming services be rejected Hi-Speed shall, at its sole cost, re-perform the non-conforming services. Inspection or failure to inspect on any occasion shall not affect Buyer's rights under the warranty provisions herein.
- 8. WARRANTIES. Hi-Speed warrants that all goods shall conform in all material aspects to the goods identified in the quotation to Buyer and/or purchase order, and Hi-Speed makes to Buyer the manufacturer's express warranty for any goods sold to Buyer, which is offered by the manufacturer at the time of acceptance of any quotation by Buyer. This warranty is conditioned upon the installation, operation, and maintenance of the goods in accordance with the manufacturer's recommendations and/or standard industry practice and the goods at all times being operated or used under normal operating conditions for which they were designed. Hi-Speed, at its sole option, will repair or

TermsAndConditions

replace any defective or non-conforming goods in accordance with the applicable manufacturer's warranty. Warranty for any defective or incorrect parts is limited to the repair or replacement of those parts. Hi-Speed warrants that all services will conform in all material respects to the description of services identified in the quotation and will be performed in a good and workmanlike manner in accordance with industry practices and standards. Should the services be reasonably rejected or not conform with the foregoing warranties, Hi-Speed shall, at its sole cost, re-perform the defective or nonconforming services. Notwithstanding the foregoing, these warranties do not extend to goods or services to the extent that such goods have been subject to misuse, neglect or abuse not caused by Hi-Speed or have been used in violation of the approved written instructions furnished to Buyer. THE FOREGOING REPRESENTS THE SOLE AND EXCLUSIVE WARRANTY GIVEN BY HI-SPEED WITH RESPECT TO ALL GOODS SOLD AND IS IN LIEU OF ALL OTHER WARRANTIES EITHER EXPRESS OR IMPLIED. HI-SPEED EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICLAR USE OR PURPOSE. BUYER WAIVES ANY CLAIM THAT THESE EXCLUSIONS OR LIMITATIONS DEPRIVE IT OF AN ADEQUATE REMEDY AT EQUITY OR LAW OR CAUSE THIS AGREEMENT TO FAIL IN ITS ESSENTIAL PURPOSE. BUYER SHALL BE ENTITLED TO NO OTHER REMEDY OTHER THAN AS SET FORTH HEREIN, REGARDLESS OF THE CLAIM OR CAUSE OF ACTION, WHETHER BASED IN CONTRACT, TORT, NEGLIGENCE, GOODS LIABILITY, STRICT LIABILITY OR OTHERWISE.

- 9. LIMITATION OF DAMAGES. HI-SPEED SHALL HAVE NO LIABILITY TO BUYER WITH RESPECT TO THE SALE OR DELIVERY OF ANY GOODS OR THE REPAIR THEREOF OR WITH RESPECT TO THE SALE OR PERFORMANCE OF ANY SERVICES, FOR LOST PROFITS, SPECIAL, CONSEQUENTIAL, EXEMPLARY, PUNITIVE OR INCIDENTAL DAMAGES OF ANY KIND OR NATURE WHETHER ARISING IN CONTRACT, TORT, GOODS LIABILITY OR OTHERWISE, EVEN IF HI-SPEED WAS ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGES. HI-SPEED SHALL NOT BE LIABLE FOR ANY DAMAGES OR DELAYS CAUSED BY ANY FAILURE TO MAKE ANY DELIVERY OF GOODS BY ANY EXPECTED TIME OR DATE OR THE FAILURE TO PROVIDE OR COMPLETE ANY SERVICES BY ANY EXPECTED DATE OR TIME. IN NO EVENT SHALL HI-SPEED BE LIABLE TO BUYER FOR ANY DAMAGES WHATSOEVER IN EXCESS OF THE TOTAL PRICE PAID FOR ALL GOODS AND/OR SERVICES HEREUNDER OR REFERENCED IN ANY QUOTATION OR THE PURCHASE ORDER.
- 10. <u>SEVERABILITY</u>. The partial or complete invalidity of any provision of these Standard Terms and Conditions shall not affect the enforceability of the remainder of these Standard Terms and Conditions. If any provision is found to be invalid or unenforceable, that portion shall be modified to make it enforceable or shall be stricken and the remainder of these Standard Terms and Conditions shall enforced.
- 11. <u>GOVERNING LAW AND JURISDICTION.</u> Any controversy arising out of any quotation, the purchase order, the goods sold or delivered, repair or replacement thereof, or any services provided pursuant to any quotation or any purchase order, or these Standard Terms and Conditions shall be governed by the laws of the state of Tennessee without regard to any choice of law provisions and any cause of action related in any manner thereto shall be brought only in the state or federal courts of Shelby County, Tennessee.
- 12. <u>ABANDONED EQUIPMENT.</u> Hi-Speed requires that Buyer promptly pick up or provide shipment instructions for Buyer equipment or other Buyer property in Hi-Speed's possession. If equipment or other Buyer property is left with Hi-Speed and not picked up within six (6) months after Hi-Speed's final action related to the applicable property (e.g. evaluation, teardown, estimate, completion of services), Hi-Speed will consider such property abandoned and may dispose of it in accordance with applicable law. Buyer agrees to hold Hi-Speed harmless for any damage or claim for such abandoned property and acknowledges that Hi-Speed may discard or recycle it at Hi-Speed's sole and absolute discretion. Specifically, Hi-Speed may sell Buyer's abandoned property at a private or public sale and retain the proceeds to offset Hi-Speed's storage, inspection and servicing costs. For the avoidance of doubt, Hi-Speed reserves its statutory and other lawful liens for unpaid charges related to abandoned property.
- 13. FORCE MAJEURE. Neither party shall be responsible for any delay or failure in performance of any party of the quotation, purchase order or these Standard Terms and Conditions to the extent that such delays or failures are caused by fire, flood, earth quake, explosion, war, embargo, government requirement, civil or military authority, acts of God, or any other circumstances beyond its reasonable control and not involving any fault or negligence on the party affected ("Condition"). If any such Condition occurs, the party delayed or unable to perform shall promptly give written notice to the other party and, if such Condition remains at the end of thirty (30) days, the party affected by the other party's delay and inability to perform may elect to (i) terminate such order or part thereof, or (ii) suspend the order for the duration of the Condition, if the Buyer is the suspending party, buy elsewhere comparable material to be sold under the order and apply to any commitment the purchase price of such purchase, and resume performance of the order once the Condition ceases, with an option in the affected party to extend the period of this order up to the length of the time the Condition endures.
- 14. <u>NONWAIVER</u>. No course of dealing or failure of either party to strictly enforce any term, right, or condition of these Standard Terms and Conditions will be construed as a waiver of such term, right or condition. Any waiver by Hi-Speed will only be in writing and will waive no succeeding breach of a term, right or condition.
- 15. <u>ASSIGNMENT.</u> The rights and obligations of the parties shall neither be assigned nor delegated without the prior written consent of the other party. However, any party may assign or delegate its respective rights and obligations, in whole or in part, (i) to any subsidiary, (ii) pursuant to other financing, merger or reorganization or (iii) pursuant to any sale or transfer of substantially all of the assets of the assigning party. These Standard Terms and Conditions shall bind the heirs, successors and assigns of the parties hereto.
- 16. <u>NO INDIVIDUAL LIABILITY</u>. Notwithstanding any other agreement to the contrary, the Buyer agrees that in no event will the Buyer hold and HI-Speed owner, director, officer or employee personally liable for unintentional tortious conduct or conduct that constitutes the breach of any contract between HI-Speed and the Buyer, even if the HI-Speed owner, director, officer or employee is or could be construed to be a party to such contract.