

EVERY DAY SINCE 1946

LR Motor Shop Repairs

Job Number 103668

Prepared for PRODUCERS RICE STUTTGART

603 N. PARK AVE STUTTGART AR 72160

Table of Contents

AC Inspection as Found - MOTOR SHOP LR



Hi-Speed Industrial Service 7030 Ryburn Dr Millington, Tn 38053 901-873-5300

FolderID: 103668

FormID: 22044515

AC Inspection as Found

PRODUCERS RICE STUTTGART 603 N. PARK AVE

STUTTGART, AR 72160

AC Inspection	- Rev. 2	Hi-Speed Job Number:	103668
Location:	MOTOR SHOP LR	Manufacturer:	KICE
Serial Number:	MD1234642301	Product Number:	M: PD-6000
Description:KIC	E BLOWER	Serial Number:	MD1234642301
		Repair Stage:	Final

Priorities Found: 🔵 2 - High

Overall Condition

- 1. Report Date
- 2. Nameplate Picture



3. Photos of all six sides of the machine.

























































4.	Describe the Overall Condition of the E	Equipment as Received	
5.	Distance from the end of the shaft to the Coupling/Sheave		
6.	Report Date [COPY]		
Initial	Mechanical/Electrical		
7.	Does Shaft Turn Freely?		
8.	Does the shaft require T.I.R in Lathe to	o identify additional repairs?	
9.	Does Shaft Have Visible Damage?		
10.	Assembled Shaft Runout		
11.	Assembled Shaft End Play		
12.	Air Gap Variation <10%		
13.	Lead Condition		
14.	Lead Length		
15.	Does it have Lugs?, If so what is the S	tud Size?	
16.	Lead Numbers		
17.	Stator Temperature Detector Rating an	nd Function	
	Quantity	Rating	Quantity Passed
18.	Bearing Temperature Detector Rating		
	Quantity	Rating	Quantity Passed
19	Frame Condition		
	Fan Condition		
	Heater Quantity, Ratings		
2	Quantity	Volts/Watts	Pass/Fail
	Quantity	volto, vvdito	
22.	Broken or Missing Components		
Initial	Electrical Inspection		
23.	Insulation Resistance/Megger		
24.	Winding Resistance		
	1-2	1-3	2-3
25.	Perform Surge Test		
26.	Number of Stator Slots		
27.	Stator Condition		
28.	Stator Thermistors/Ohms		

Mechanical inspection 30. Drive End Bearing Number. 31. Drive End Bearing Qry. 33. Drive End Bearing Qry. 34. Drive End Bearing Qry. 35. Drive End Bearing Qry. 36. Drive End Bearing Type 37. Drive End Bearing Type. 38. Drive End Bearing Insulation or Grounding Device? 39. Drive End Bearing Condition 30. Opposite Drive End Bearing Rumber- 40. Opposite Drive End Bearing Qry. 41. Opposite Drive End Bearing Number- 42. Opposite Drive End Bearing Qry. 43. Opposite Drive End Bearing Number- 44. Opposite Drive End Bearing Condition 45. Opposite Drive End Bearing Condition 46. Drive End Bearing Condition 47. Opposite Drive End Bearing Condition 48. DE Steeve Bearing Inside Diameter 0 degrees 120 degrees 120 degrees 240 degrees 50. DE Steeve Bearing Inside Diameter 0 degrees 120 degrees 51. DE Steeve Bearing Inside Diameter 0 degrees 120 degrees 52. ODE Steeve Bearing Inside Diameter 0 degrees 120 degrees 120 degrees 240 degrees 120 d	29.	Stator Overloads/Ohms		
30. Drive End Bearing Brand 31. Drive End Bearing Number- 32. Drive End Bearing Type 33. Drive End Bearing Type 34. Drive End Bearing Type 35. Drive End Bearing Type 36. Drive End Bearing Insuitation or Grounding Device? 37. Drive End Bearing Insuitation or Grounding Device? 38. Opposite Drive End Bearing Number- 40. Opposite Drive End Bearing Insuitation or Grounding Device? 41. Opposite Drive End Bearing Insuitation or Grounding Device? 42. Opposite Drive End Bearing Insuitation or Grounding Device? 43. Opposite Drive End Bearing Insuitation or Grounding Device? 44. Opposite Drive End Bearing Condition 45. Opposite Drive End Bearing Insuitation or Grounding Device? 46. Drive End Seal 47. Opposite Drive End Bearing Insuitation or Grounding Device? 48. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees 50. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees 51. DE Sleeve Bearing Inside Diameter <th>Mecha</th> <th>anical Inspection</th> <th></th> <th></th>	Mecha	anical Inspection		
31. Drive End Bearing Number- 32. Drive End Bearing City. 33. Drive End Bearing Type 34. Drive End Bearing Insulation or Grounding Device? 35. Drive End Bearing Insulation or Grounding Device? 36. Drive End Bearing Condition 37. Drive End Bearing Condition 38. Opposite Drive End Bearing Number- 40. Opposite Drive End Bearing Number- 41. Opposite Drive End Bearing Number- 42. Opposite Drive End Bearing Number- 43. Opposite Drive End Bearing Number- 44. Opposite Drive End Bearing Insulation or Grounding Device? 45. Opposite Drive End Bearing Condition 46. Drive End Bearing Condition 47. Opposite Drive End Seal 48. DE Sleeve Bearing Insulation or Grounding Device? 49. DE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees 50. DE Sleeve Bearing Inside Diameter 0 0 degrees 120 degrees 51. DE Sleeve Bearing Inside Diameter 0 0 degrees 120 degrees 240 degrees		•		
33. Drive End Bearing Type 34. Drive End Bearing Insulation or Grounding Device? 35. Drive End Bearing Insulation or Grounding Device? 36. Drive End Bearing Grand 37. Drive End Bearing Grand 38. Opposite Drive End Bearing Grand 39. Opposite Drive End Bearing Grand 39. Opposite Drive End Bearing Type 40. Opposite Drive End Bearing Type 41. Opposite Drive End Bearing Type 42. Opposite Drive End Bearing Type 43. Opposite Drive End Bearing Type 44. Opposite Drive End Bearing Condition 45. Opposite Drive End Bearing Condition 46. Derive End Bearing Condition 47. Opposite Drive End Bearing Condition 48. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 120 Degrees 240 degrees 50. DE Sleeve Bearing Inside Diameter 0 0 degrees 120 degrees 240 degrees 51. DE Sleeve Bearing Inside Diameter 0 240 degrees 52. O	31.	Drive End Bearing Number-		
34. Drive End Lubrication Type 35. Drive End Bearing Insulation or Grounding Device? 36. Drive End Wary Washer/Nap-Ring Other Retention Device? 37. Drive End Bearing Condition 38. Opposite Drive End Bearing Number- 39. Opposite Drive End Bearing Number- 30. Opposite Drive End Bearing Oty. 41. Opposite Drive End Bearing Oty. 42. Opposite Drive End Bearing Type 43. Opposite Drive End Bearing Insulation or Grounding Device? 44. Opposite Drive End Bearing Condition 45. Opposite Drive End Bearing Condition or Grounding Device? 46. Opposite Drive End Bearing Condition or Grounding Device? 47. Opposite Drive End Bearing Condition 48. Drive End Seal 49. DE Sleeve Bearing Inside Diameter 0 degrees 10 degrees 120 degrees 50. DE Sleeve Bearing Inside Diameter 0 degrees 11 DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees 51. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees 52. ODE Sleeve Bearing Inside Diameter 0 0 degrees <t< th=""><th>32.</th><th colspan="3">-</th></t<>	32.	-		
35. Drive End Bearing Insulation or Grounding Device? 36. Drive End Wary Washer/Snap-Ring Other Retention Device? 37. Drive End Bearing Outhion 38. Opposite Drive End Bearing Number- 40. Opposite Drive End Bearing Number- 41. Opposite Drive End Bearing Number- 42. Opposite Drive End Bearing Insulation or Grounding Device? 43. Opposite Drive End Bearing Insulation or Grounding Device? 44. Opposite Drive End Bearing Condition 45. Opposite Drive End Bearing Condition 46. Drive End Seal 47. Opposite Drive End Seal 48. Drive End Seal 49. Drive End Seal 41. Opposite Drive End Seal 42. Opposite Drive End Seal 43. Drive End Seal 44. Drive End Seal 45. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 0 Degrees 120 degrees 51. DE Sleeve Bearing Inside Diameter 240 degrees 0 degrees 120 degrees 240 degrees <t< th=""><th>33.</th><th>Drive End Bearing Type</th><th></th><th></th></t<>	33.	Drive End Bearing Type		
36. Drive End Wavy Washer/Snap-Ring Other Retention Device? 37. Drive End Bearing Condition 38. Opposite Drive End Bearing Number- 40. Opposite Drive End Bearing Number- 41. Opposite Drive End Bearing Number- 42. Opposite Drive End Bearing Insulation or Grounding Device? 43. Opposite Drive End Bearing Condition 44. Opposite Drive End Bearing Condition or Grounding Device? 45. Opposite Drive End Bearing Condition 46. Drive End Seal 47. Opposite Drive End Seal 48. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees 49. DE Sleeve Bearing Housing Inside Diameter 0 0 degrees 120 degrees 240 degrees 50. DE Sleeve Bearing Housing Inside Diameter 0 0 degrees 120 degrees 240 degrees 51. DE Sleeve Bearing Inside Diameter 0 0 degrees 120 degrees 240 degrees 52. ODE Sleeve Bearing Inside Diameter 0 0 degrees 120 degrees 240 degrees 53	34.	Drive End Lubrication Type		
37. Drive End Bearing Condition 38. Opposite Drive End Bearing Brand 39. Opposite Drive End Bearing Rive 41. Opposite Drive End Bearing Type 42. Opposite Drive End Bearing Insulation or Grounding Device? 43. Opposite Drive End Bearing Condition 44. Opposite Drive End Bearing Condition or Grounding Device? 45. Opposite Drive End Bearing Condition 46. Drive End Seal 47. Opposite Drive End Seal 48. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 49. DE Sleeve Bearing Nuside Diameter 0 degrees 120 degrees 50. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 51. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 52. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 52. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 53. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 54. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 55. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees <t< th=""><th>35.</th><th>Drive End Bearing Insulation or Grour</th><th>nding Device?</th><th></th></t<>	35.	Drive End Bearing Insulation or Grour	nding Device?	
38. Opposite Drive End Bearing Number- 39. Opposite Drive End Bearing Number- 40. Opposite Drive End Bearing Number- 41. Opposite Drive End Bearing Type 42. Opposite Drive End Bearing Insulation or Grounding Device? 43. Opposite Drive End Bearing Insulation or Grounding Device? 44. Opposite Drive End Bearing Insulation or Grounding Device? 45. Opposite Drive End Bearing Condition 46. Drive End Bearing Insulation or Grounding Device? 47. Opposite Drive End Bearing Insulation or Grounding Device? 48. DE Steeve Bearing Inside Diameter 0 degrees 120 degrees 9. DE Steeve Bearing Outside Diameter 0 degrees 120 degrees 9. DE Steeve Bearing Housing Inside Diameter 0 degrees 120 degrees 9. DE Steeve Bearing Housing Inside Diameter 0 degrees 120 degrees 9. DE Steeve Bearing Inside Diameter 0 degrees 120 degrees 9. DE Steeve Bearing Inside Diameter 0 degrees 120 degrees 9. DE Steeve Bearing Inside Diameter 0 degrees 120 degrees 9. DE Steeve Bearing Housing Inside Diameter 0 degrees 120 degrees 9. DE Steeve	36.	Drive End Wavy Washer/Snap-Ring C	Other Retention Device?	
39. Opposite Drive End Bearing Qu. 40. Opposite Drive End Bearing Type 41. Opposite Drive End Bearing Type 42. Opposite Drive End Lubrication Type 43. Opposite Drive End Bearing Insulation or Grounding Device? 44. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? 45. Opposite Drive End Seal 47. Opposite Drive End Seal 48. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 49. DE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 50. DE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 51. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 52. ODE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 51. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 22. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 52. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 53. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 53. ODE Sleeve Bearing Housing Inside Diameter 0 degrees	37.	-		
40. Opposite Drive End Bearing Qu. 41. Opposite Drive End Bearing Type 42. Opposite Drive End Lubrication Type 43. Opposite Drive End Bearing Insulation or Grounding Device? 44. Opposite Drive End Bearing Condition 45. Opposite Drive End Bearing Condition 46. Drive End Seal 47. Opposite Drive End Bearing Condition 48. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees 49. DE Sleeve Bearing Outside Diameter 40 0 degrees 120 degrees 240 degrees 60. DE Sleeve Bearing Housing Inside Diameter 40 0 degrees 120 degrees 240 degrees 50. DE Sleeve Bearing Housing Inside Diameter 40 0 degrees 120 degrees 240 degrees 51. DE Sleeve Bearing Inside Diameter 40 0 degrees 120 degrees 240 degrees 52. ODE Sleeve Bearing Inside Diameter 40 0 degrees 120 degrees 240 degrees 53. ODE Sleeve Bearing Housing Inside Diameter 40				
41. Opposite Drive End Lubrication Type 42. Opposite Drive End Lubrication Type 43. Opposite Drive End Bearing Insulation or Grounding Device? 44. Opposite Drive End Bearing Condition 45. Opposite Drive End Bearing Condition 46. Drive End Seal 47. Opposite Drive End Seal 47. Opposite Drive End Seal 48. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 249. DE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 250. DE Sleeve Bearing Housing Inside Diameter 0 0 degrees 120 degrees 240 degrees 51. DE Sleeve Bearing to Housing Clearance 240 degrees 240 degrees 0 degrees 120 degrees 240 degrees 52. ODE Sleeve Bearing Inside Diameter 0 240 degrees 0 degrees 120 degrees 240 degrees 53. ODE Sleeve Bearing Inside Diameter 0 240 degrees 0 degrees 120 degrees 240 degrees <td< th=""><th></th><th></th><th></th><th></th></td<>				
42. Opposite Drive End Lubrication Type 43. Opposite Drive End Bearing Insulation or Grounding Device? 44. Opposite Drive End Bearing Condition 45. Opposite Drive End Bearing Condition 46. Drive End Seal 47. Opposite Drive End Seal 48. DE Steeve Bearing Inside Diameter 0 degrees 120 degrees 49. DE Steeve Bearing Outside Diameter 0 degrees 120 degrees 49. DE Steeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees 250. DE Steeve Bearing Inside Diameter 0 degrees 120 degrees 260 degrees 120 degrees 270 degrees 240 degrees 280 degrees 120 degrees 240 degrees 240 degrees 251. DE Steeve Bearing Inside Diameter U 0 degrees 120 degrees 240 degrees 252. ODE Steeve Bearing Inside Diameter U 0 degrees 120 degrees 240 degrees 280 degrees 120 degrees 240 degrees 290 degrees 120 degrees 240 degrees 290 degrees 120 degrees 240 degrees				
43. Opposite Drive End Bearing Insulation or Grounding Device? 44. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? 45. Orive End Bearing Condition 47. Opposite Drive End Bearing Condition 47. Opposite Drive End Seal 47. Opposite Drive End Seal 48. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 49. DE Sleeve Bearing Outside Diameter 40 0 degrees 120 degrees 240 degrees 52. ODE Sleeve Bearing Inside Diameter 0 240 degrees 0 degrees 120 degrees 240 degrees 53. ODE Sleeve Bearing Housing Inside Diameter 0 240 degrees 0 <th></th> <th></th> <th></th> <th></th>				
44. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? 45. Opposite Drive End Bearing Condition 46. Drive End Seal 47. Opposite Drive End Seal 48. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 0 degrees 120 degrees 240 degrees 240 degrees 0 degrees 120 degrees 0 degrees 120 degrees 240 degrees 240 degrees 0 degrees 120 degrees 240 degrees 240 degrees 0 degrees 120 degrees 240 degrees 240 degrees 51. DE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 240 degrees 52. ODE Sleeve Bearing Inside Diameter U 0 degrees 120 degrees 240 degrees 53. ODE Sleeve Bearing Outside Diameter U 0 degrees 120 degrees 240 degrees 54. ODE Sleeve Bearing Housing Inside Diameter U 0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bearing Housing				
 45. Opposite Drive End Bearing Condition 46. Drive End Seal 47. Opposite Drive End Seal 48. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degr			-	
46. Drive End Seal 47. Opposite Drive End Seal 48. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 49. DE Sleeve Bearing Outside Diameter 0 0 degrees 120 degrees 240 degrees 49. DE Sleeve Bearing Outside Diameter 0 0 0 degrees 120 degrees 240 degrees 50. DE Sleeve Bearing Housing Inside Diameter 0 0 degrees 0 degrees 120 degrees 240 degrees 240 degrees 51. DE Sleeve Bearing to Housing Clearance 0 0 degrees 240 degrees 62. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees 53. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees 54. ODE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bear				
47. Opposite Drive End Seal 48. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees 49. DE Sleeve Bearing Outside Diameter 0 0 degrees 120 degrees 240 degrees 50. DE Sleeve Bearing Housing Inside Diameter 0 0 degrees 120 degrees 240 degrees 51. DE Sleeve Bearing to Housing Clearance 0 0 degrees 120 degrees 240 degrees 240 degrees 52. ODE Sleeve Bearing Inside Diameter 0 0 degrees 240 degrees 0 degrees 120 degrees 240 degrees 120 degrees 120 degrees 240 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees 120 degrees <th></th> <th></th> <th></th> <th></th>				
48. DE Sleeve Bearing Inside Diameter 240 degrees 49. DE Sleeve Bearing Outside Diameter 240 degrees 0 degrees 120 degrees 240 degrees 50. DE Sleeve Bearing Housing Inside Diameter 240 degrees 0 degrees 120 degrees 240 degrees 51. DE Sleeve Bearing to Housing Clearance 0 240 degrees 0 degrees 120 degrees 240 degrees 52. ODE Sleeve Bearing Inside Diameter 0 240 degrees 0 degrees 120 degrees 240 degrees 53. ODE Sleeve Bearing Inside Diameter 240 degrees 0 degrees 120 degrees 240 degrees 54. ODE Sleeve Bearing Housing Inside Diameter 240 degrees 0 degrees 120 degrees 240 degrees 54. ODE Sleeve Bearing Housing Inside Diameter 0 240 degrees 0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 240 degrees 0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 240 degrees 240 degrees 66. Rotor Type/Material 57. Growler Test 57. Growler Test 57. Growler Te				
0 degrees 120 degrees 240 degrees 49. DE Sleeve Bearing Outside Diameter 240 degrees 0 degrees 120 degrees 240 degrees 50. DE Sleeve Bearing Housing Inside Diameter 0 degrees 240 degrees 0 degrees 120 degrees 240 degrees 51. DE Sleeve Bearing to Housing Clearance 0 degrees 240 degrees 0 degrees 120 degrees 240 degrees 52. ODE Sleeve Bearing Inside Diameter 240 degrees 240 degrees 0 degrees 120 degrees 240 degrees 240 degrees 53. ODE Sleeve Bearing Outside Diameter 240 degrees 240 degrees 240 degrees 54. ODE Sleeve Bearing Housing Inside Diameter 240 degrees 240 degrees 240 degrees 54. ODE Sleeve Bearing to Housing Clearance 240 degrees 240 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 240 degrees 240 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 240 degrees 240 degrees 240 degrees 56. Rotor Type/Material 120 degrees 240 degrees 240 degrees 240 degrees 57. Growler Test 57. Growler Test </th <th></th> <th></th> <th></th> <th></th>				
49. DE Sleeve Bearing Outside Diameter 240 degrees 0 degrees 120 degrees 240 degrees 50. DE Sleeve Bearing Housing Inside Diameter 0 degrees 240 degrees 0 degrees 120 degrees 240 degrees 51. DE Sleeve Bearing to Housing Clearance 0 degrees 240 degrees 0 degrees 120 degrees 240 degrees 52. ODE Sleeve Bearing Inside Diameter 0 degrees 240 degrees 0 degrees 120 degrees 240 degrees 53. ODE Sleeve Bearing Outside Diameter 0 degrees 240 degrees 0 degrees 120 degrees 240 degrees 54. ODE Sleeve Bearing Housing Inside Diameter 240 degrees 240 degrees 0 degrees 120 degrees 240 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 240 degrees 240 degrees 64. ODE Sleeve Bearing to Housing Clearance 240 degrees 240 degrees 75. ODE Sleeve Bearing to Housing Clearance 240 degrees 240 degrees 76. Rotor Type/Material 57. Growler Test 57. Growler Test 57. Growler Test		-	120 degrees	240 degrees
0 degrees 120 degrees 240 degrees 50. DE Sleeve Bearing Housing Inside Diameter 0 degrees 0 degrees 120 degrees 240 degrees 51. DE Sleeve Bearing to Housing Clearance 240 degrees 0 degrees 120 degrees 240 degrees 52. ODE Sleeve Bearing Inside Diameter 240 degrees 0 degrees 120 degrees 240 degrees 53. ODE Sleeve Bearing Outside Diameter 240 degrees 0 degrees 120 degrees 240 degrees 54. ODE Sleeve Bearing Housing Inside Diameter 240 degrees 0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bearing Housing Inside Diameter 240 degrees 65. ODE Sleeve Bearing to Housing Clearance 240 degrees 0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 240 degrees 0 degrees 120 degrees 240 degrees 56. Rotor Type/Material 57. Growler Test				
50. DE Sleeve Bearing Housing Inside Diameter 0 0 degrees 120 degrees 240 degrees 51. DE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees 250 ODE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees 240 degrees 240 degrees 250 ODE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees	49.	DE Sleeve Bearing Outside Diameter		
0 degrees 120 degrees 240 degrees 51. DE Sleeve Bearing to Housing Clearance 0 degrees 240 degrees 0 degrees 120 degrees 240 degrees 52. ODE Sleeve Bearing Inside Diameter 0 degrees 240 degrees 0 degrees 120 degrees 240 degrees 53. ODE Sleeve Bearing Outside Diameter 0 degrees 240 degrees 54. ODE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 55. ODE Sleeve Bearing to Housing Clearance 240 degrees 65. ODE Sleeve Bearing to Housing Clearance 240 degrees 75. ODE Sleeve Bearing to Housing Clearance 240 degrees 75. ODE Sleeve Bearing to Housing Clearance 240 degrees 75. ODE Sleeve Bearing to Housing Clearance 240 degrees 75. ODE Sleeve Bearing to Housing Clearance 240 degrees 76. Rotor Type/Material 240 degrees 77. Growler Test 57. Growler Test		0 degrees	120 degrees	240 degrees
0 degrees 120 degrees 240 degrees 51. DE Sleeve Bearing to Housing Clearance 0 degrees 240 degrees 0 degrees 120 degrees 240 degrees 52. ODE Sleeve Bearing Inside Diameter 0 degrees 240 degrees 0 degrees 120 degrees 240 degrees 53. ODE Sleeve Bearing Outside Diameter 0 degrees 240 degrees 54. ODE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 55. ODE Sleeve Bearing to Housing Clearance 240 degrees 65. ODE Sleeve Bearing to Housing Clearance 240 degrees 75. ODE Sleeve Bearing to Housing Clearance 240 degrees 75. ODE Sleeve Bearing to Housing Clearance 240 degrees 75. ODE Sleeve Bearing to Housing Clearance 240 degrees 75. ODE Sleeve Bearing to Housing Clearance 240 degrees 76. Rotor Type/Material 240 degrees 77. Growler Test 57. Growler Test	=0			
51. DE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees 52. ODE Sleeve Bearing Inside Diameter 0 degrees 240 degrees 53. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 64. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 53. ODE Sleeve Bearing Outside Diameter 0 degrees 240 degrees 54. ODE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 55. ODE Sleeve Bearing to Housing Clearance 240 degrees 66. Rotor Type/Material 120 degrees 240 degrees 56. Rotor Type/Material 57. Growler Test 57. Growler Test	50.			040 1
0 degrees 120 degrees 240 degrees 52. ODE Sleeve Bearing Inside Diameter 0 degrees 240 degrees 53. ODE Sleeve Bearing Outside Diameter 240 degrees 0 degrees 120 degrees 240 degrees 54. ODE Sleeve Bearing Housing Inside Diameter 240 degrees 0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 240 degrees 0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 240 degrees 0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 240 degrees 56. Rotor Type/Material 57. Growler Test		0 degrees	120 degrees	240 degrees
0 degrees 120 degrees 240 degrees 52. ODE Sleeve Bearing Inside Diameter 0 degrees 240 degrees 53. ODE Sleeve Bearing Outside Diameter 240 degrees 0 degrees 120 degrees 240 degrees 54. ODE Sleeve Bearing Housing Inside Diameter 240 degrees 0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 240 degrees 0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 240 degrees 0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 240 degrees 56. Rotor Type/Material 57. Growler Test	51.	DE Sleeve Bearing to Housing Cleara	nce	
52. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees 53. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 54. ODE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 54. ODE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees 240 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees 56. Rotor Type/Material 57. Growler Test				240 degrees
0 degrees 120 degrees 240 degrees 53. ODE Sleeve Bearing Outside Diameter 240 degrees 0 degrees 120 degrees 240 degrees 54. ODE Sleeve Bearing Housing Inside Diameter 240 degrees 0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 240 degrees 240 degrees 65. ODE Sleeve Bearing to Housing Clearance 240 degrees 240 degrees 75. ODE Sleeve Bearing to Housing Clearance 240 degrees 240 degrees 75. ODE Sleeve Bearing to Housing Clearance 240 degrees 240 degrees 75. ODE Sleeve Bearing to Housing Clearance 240 degrees 240 degrees 76. Rotor Type/Material 57. Growler Test 57. Growler Test				
53. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 54. ODE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees 75. ODE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees 75. ODE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees 75. ODE Sleeve Bearing to Housing Clearance 76. Rotor Type/Material 77. Growler Test	52.	ODE Sleeve Bearing Inside Diameter		
0 degrees 120 degrees 240 degrees 54. ODE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 240 degrees 0 degrees 120 degrees 240 degrees 75. ODE Sleeve Bearing to Housing Clearance 240 degrees 8 120 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 240 degrees 56. Rotor Type/Material 57. Growler Test		0 degrees	120 degrees	240 degrees
0 degrees 120 degrees 240 degrees 54. ODE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 240 degrees 0 degrees 120 degrees 240 degrees 75. ODE Sleeve Bearing to Housing Clearance 240 degrees 8 120 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 240 degrees 56. Rotor Type/Material 57. Growler Test	50	ODE Sloove Destine Outside Die		
54. ODE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 0 degrees 240 degrees 0 degrees 120 degrees 240 degrees Roter Inspection 56. Rotor Type/Material 57. Growler Test	53.	-		240 degrees
0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees Rotor Inspection 56. Rotor Type/Material 57. Growler Test		o degrees	120 degrees	240 degrees
0 degrees 120 degrees 240 degrees 55. ODE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees Rotor Inspection 56. Rotor Type/Material 57. Growler Test	54.	ODE Sleeve Bearing Housing Inside I	Diameter	
0 degrees 120 degrees 240 degrees Rotor Inspection				240 degrees
Rotor Inspection 56. Rotor Type/Material 57. Growler Test	55.	ODE Sleeve Bearing to Housing Clea	rance	
56. Rotor Type/Material57. Growler Test		0 degrees	120 degrees	240 degrees
56. Rotor Type/Material57. Growler Test	Rotor	Inspection		
57. Growler Test				
58 Number of Rotor Bars		••		
	58.	Number of Rotor Bars		

59.	Rotor Condition		
60.	List the Parts needed for the Repair Below		
61.	Signature of Technician that Disassembled Motor		
Mech	nanical Fits- Rotor		
62.	Shaft Runout		
63.	Rotor Runout		
	Drive End Bearing Fit	Rotor Body	Opposite Drive End Bearing
64.	Coupling Fit Closest to Bearing Housi	-	100 5
	0 Degrees	90 Degrees	120 Degrees
65.	Coupling Fit Closest to the end of the	Shaft	
	0 Degrees	60 Degrees	120 Degrees
	0 2 0 9 1 0 0 0	00 2091000	120 209,000
66.	Drive End Bearing Shaft Fit		
	0 Degrees	60 Degrees	120 Degrees
	Drive End Bearing Shaft Fit Condition		
68.	Opposite Drive End Bearing Shaft Fit		
	0 Degrees	60 Degrees	120 Degrees
69.	Opposite Drive End Bearing Shaft Fit	Condition	
	Shaft Air Seal Fits		
	Drive End Air Seal	Opposite Drive End Air Seal	
	anical Fits- Bearing Housings		
71.	Drive End - Endbell Bearing Fit		
	0 Degrees	60 Degrees	120 Degrees
72	Drive End - Endbell Bearing Fit Condi	tion	
	Opposite Drive End - Endbell Bearing		
70.	0 Degrees	60 Degrees	120 Degrees
	0 Degrees	of Degrees	
74.	Opposite Drive End - Endbell Bearing	Fit Condition	
75.	Bearing Cap Condition		
	Drive End Bearing Cap	Opposite Drive End Bearing Cap	
70			
76.	End Bell Air Seal Fits	Opposite Drive Fred Air Cool	
	Drive End Air Seal	Opposite Drive End Air Seal	
77.	List Machine Work Needed Below		
78.			
Root	Cause of Failure		





8 0.	Root cause of failure		
	Bearing failed causing rotor to drag end plate		
Dyna	mic Balance Report		
81.	Rotor Weight and Balance Grade		
	Rotor Weight	Balance Grade	
82.	Initial Balance Readings		
	Drive End	Opposite Drive End	
83	Final Balance Readings		
05.	Drive End	Opposite Drive End	
	Drive Lifu	Opposite Drive Lind	
84.	Technician		
Rewin	nd		
85.	Core Test Results - Watts loss per Po	und	
	Pre-Burnout	Post Burnout	
86.	Core Hot Spot Test		
	Pre-Burnout	Post-Burnout	
07	Post Rewind Electrical Test- Insulation	- Desistance	
	Post Rewind Polarization Index	I RESISTATICE	
	Post Rewind Winding Resistance		
09.	1-2	1-3	2-3
	1-2	1-5	2-3
90.	Post Rewind Surge Test		
91.	Post Rewind Hi-Pot		
92.	Technician		
Mech	anical Fits- Rotor - Post Repair		
93.	Shaft Runout Post Repair		
94.	Rotor Runout Post Repair		
	Drive End Bearing Fit	Rotor Body	Opposite Drive End Bearing

95.	Coupling Fit Closest to Bearing Housi	ng Post Repair	
	0 Degrees	90 Degrees	120 Degrees
96.	Coupling Fit Closest to the end of the Shaft Post Repair		
	0 Degrees	60 Degrees	120 Degrees
		<u> </u>	J.
97.	Drive End Bearing Shaft Fit Post Rep	air	
	0 Degrees	60 Degrees	120 Degrees
98.	Opposite Drive End Bearing Shaft Fit	Post Repair	
	0 Degrees	60 Degrees	120 Degrees
99.	Shaft Air Seal Fits Post Repair		
	Drive End Air Seal	Opposite Drive End Air Seal	
100			
	Shaft Repair Sign-off		
	anical Fits- Bearing Housings - P	-	
101.	Drive End - Endbell Bearing Fit Post F	•	
	0 Degrees	60 Degrees	120 Degrees
100	Opposite Drive End - Endbell Bearing	Fit Doot Dopoir	
102.			
	0 Degrees	60 Degrees	120 Degrees
103.	Bearing Cap Condition Post Repair		
	Drive End Bearing Cap	Opposite Drive End Bearing Cap	
104.	End Bell Air Seal Fits Post Repair		
	Drive End Air Seal	Opposite Drive End Air Seal	
105.	DE Sleeve Bearing Inside ID Post Re	pair	
	Measure 1	Measure 2	Measure 3
106.	DE Sleeve Bearing Outside ID Post R		
	Measure 1	Measure 2	Measure 3
107	DE Sleeve Bearing Inside OD Post R	anair	
107.	Measure 1		Magaura 2
	IVIEASULE I	Measure 2	Measure 3
108	DE Sleeve Bearing Outside OD Post	Repair	
	Measure 1	Measure 2	Measure 3
109.	End Bell Repair Sign-off		
	ODE Sleeve Bearing Inside ID Post R	epair	
	Measure 1	Measure 2	Measure 3
111.	ODE Sleeve Bearing Outside ID Post	Repair	
	Measure 1	Measure 2	Measure 3

112.	ODE Sleeve Bearing Inside OD Post	Repair	
	Measure 1	Measure 2	Measure 3
113.	 ODE Sleeve Bearing Outside OD Post Repair 		
	Measure 1	Measure 2	Measure 3
Assen	nbly		
114.	QC Check All Parts for Cleanliness P	rior to Assembly	
115.	Photograph All Major Components pr	ior to assembly	
116.	Final Insulation Resistance Test		
117.	Assembled Shaft Endplay		
118.	Assembled Shaft Runout		
119.	Test Run Voltage		
	Volts	Volts	Volts
120.	Test Run Amperage		
	Amps	Amps	Amps
121.	Drive End Vibration Readings - Inches		
	Horizontal	Vertical	Axial
122.	Opposite Drive End Vibration Reading	-	
	Horizontal	Vertical	Axial
400			
	Ambient Temperature - Fahrenheit	14	
124.	Drive End Bearing Temps - Fahrenhe		
	5 Minutes	10 Minutes	15 Minutes
125	Drive End Bearing Temps - Fahrenhe	it 20-30 Minutes	
125.	20 Minutes	25 Minutes	30 Minutes
	20 Minutes	23 Minutes	50 Minutes
126.	Drive End Bearing Temps - Fahrenhe	it 35-45 Minutes	
	35 Minutes	40 Minutes	45 Minutes
127.	Drive End Bearing Temps - Fahrenhe	it 50-60 Minutes	
	50 Minutes	55 Minutes	60 Minutes
128.	Opposite Drive End Bearing Temps -	Fahrenheit	
	5 Minutes	10 Minutes	15 Minutes
129.	Opposite Drive End Bearing Temps -	Fahrenheit 20-30 Minutes	
	20 Minutes	25 Minutes	30 Minutes
130.	Opposite Drive End Bearing Temps -		
	35 Minutes	40 Minutes	45 Minutes
131.	Opposite Drive End Bearing Temps -		
	50 Minutes	55 Minutes	60 Minutes

132. Stator Temperature	es- Fahrenheit	
5 Minutes	10 Minutes	15 Minutes
133. Stator Temperature	es- Fahrenheit 20-30 Minutes	
20 Minutes	25 Minutes	30 Minutes
134. Stator Temperature	es- Fahrenheit 35-45 Minutes	
35 Minutes	40 Minutes	45 Minutes
135. Stator Temperature	es- Fahrenheit 50-60 Minutes	
50 Minutes	55 Minutes	60 Minutes
136. Document Final Co	ondition with Pictures after paint	
137. Final Pics and QC	Review	



STANDARD TERMS AND CONDITIONS FOR PURCHASE OF GOOD AND/OR SERVICES

- 1. <u>APPLICABILITY.</u> The sale of any and all goods and/or services by Mock, Inc. d/b/a Hi-Speed Industrial Service ("Hi-Speed") shall be specifically conditioned upon and subject to the following terms and conditions which are incorporated by reference into any contracts and purchase orders with Hi-Speed, and which shall form and become a part of any agreement related thereto. Buyer's acceptance of any offer or quotation made by Hi-Speed for sale of any goods or services is expressly made subject to the terms and conditions set forth herein and to be so effective, Buyer need not sign or approve these Terms and Conditions to be bound hereunder provided a copy of same is provided to Buyer through any means. None of the terms and conditions contained herein may be added to, expanded, changed, modified, superseded or otherwise altered except as revised in writing and duly executed by Hi-Speed, and all orders received by Hi-Speed shall be governed only by the terms and conditions contained herein, notwithstanding any terms, conditions or provisions of any purchase order, release order, authorization or any other form issued by the Buyer. Hi-Speed hereby objects to any additional, modified, changed, deleted, altered or other terms and conditions not contained herein and notifies Buyer that any such terms or provisions are expressly rejected by Hi-Speed.
- 2. PRICE. All quoted prices shall remain firm and binding for a period of thirty (30) days from the date of quotation or for the period specifically stated in the quotation. The price for any and all goods and/or services ordered or approved by Buyer after thirty (30) days from the date of any quotation are subject to any increase in price that may occur after the expiration of thirty (30) days from the issuance of the quotation and the date the Buyer releases any shipment.
- 3. <u>SCOPE OF GOODS AND/OR SERVICES.</u> The goods and/or services provided by Hi-Speed pursuant to any quotation shall be limited exclusively to those goods and/or services expressly identified therein. Hi-Speed does not assume any responsibility and/or liability for the failure to provide any other goods and/or services not identified in any quotation. Modifications, additions or deletions to or from the scope referenced in any quotation shall only be effective if evidenced in writing and signed by Hi-Speed. The sale of any of all goods and/or services affected by such modification, addition or deletion shall be subject to these same Standard Terms and Conditions whether or not referenced therein.
- 4. <u>BILLING AND PAYMENT TERMS.</u> Hi-Speed shall invoice Buyer for all goods and/or services as same are rendered at the address listed on the quotation. Payments for all goods and/or services shall be due thirty (30) days from the date of the current invoice or as otherwise set forth in the quotation. Late payments are subject to a late fee of 5% of the total invoice amount. Recurring late payments may lead to a deposit requirement on future services or sale of goods. Buyer shall be liable to Hi-Speed for any and all fees and expenses incurred by Hi-Speed to collect any invoices or to enforce these Standard Terms and Conditions, including but not limited to, attorney's fees.
- 5. DELIVERY OF GOODS AND/OR SERVICES. Unless otherwise identified in the quotation, all shipments are F.O.B. Hi-Speed's warehouse and the title to and all risk of loss with respect to any goods shipped shall pass to Buyer when such goods are delivered to the carrier at Hi-Speed's warehouse. Hi-Speed will use its best efforts to affect delivery by the date or dates specified in the quotation. However, Hi-Speed shall not be liable for delay in or failure to make shipment, or to perform services, by any identified date for any reason whatsoever, including but not limited to, causes beyond its reasonable control, such as strikes, fires, floods, epidemics, quarantines, restrictions, severe weather, embargos, acts of God, or public enemy, war, riot, delays in transportation or the inability to obtain necessary labor, materials or manufacturing facilities.
- 6. DELIVERY SITE AND TIME FOR PERFORMANCE. Hi-Speed and Buver agree that time is of the essence for the purchase order and that Buyer shall fully cooperate with Hi-Speed in order to allow Hi-Speed full access to prosecute its work diligently and in an orderly manner. Buyer shall assist Hi-Speed in every way possible to avoid delaying, disrupting or interfering with the progress of Hi-Speed's work at the project site. In the event Hi-Speed's work is delayed, hindered, suspended, disrupted, re-sequenced or interfered with or rendered less efficient or more costly or adversely affected in any way as a result of acts or omissions of Buyer or other contractors or employees of Buyer or by any other reason beyond Hi-Speed's control and without the fault of Hi-Speed, then, in such event, Buyer shall be liable to Hi-Speed for any damages, additional costs, expenses, labor, materials, man hours, acceleration costs, overtime, additional jobsite overhead, extended home office overhead, and any and all other direct and indirect expenses of whatsoever nature or kind, caused in whole or in part, as a result of any of the above-referenced occurrences. Hi-Speed's project records will be the basis for computing the additional costs and damages of Hi-Speed's labor, materials, expenses and overhead related to such changes. BUYER WARRANTS THAT THE SITE FOR DELIVERY OR INSTALLATION OF ANY GOODS AND/OR FOR THE PERFORMANCE OF ANY SERVICES SHALL BE READY AND ADEQUATE FOR HI-SPEED'S DELIVERY OF GOODS AND/OR PERFORMANCE OF SERVICES AND THAT HI-SPEED SHALL HAVE FULL ACCESS THERETO, FREE OF ALL OBSTRUCTIONS. BUYER SHALL ASSUME ALL EXTRA COSTS ASSOCIATED WITH HI-SPEED'S INABILITY TO INSTALL ANY GOODS OR PERFORM ANY SERVICES AS A RESULT OF BUYER'S FAILURE TO COMPLY WITH THIS PROVISION. HI-SPEED MAY NOT INSPECT THE SITE PRIOR TO DELIVERY AND/OR INSTALLATION OF GOODS AND/OR PERFORMANCE OF SERVICES AND MAKES NO WARRANTY AS TO THE SUFFICIENCY OF THE SITE FOR THE DELIVERY AND/OR INSTALLATION OF GOODS AND/OR THE PERFORMANCE OF SERVICES AT SUCH SITE.
- 7. INSPECTION/ACCEPTANCE. All goods and services ordered pursuant to any quotation shall be subject to inspection by Buyer after delivery or performance to determine conformity with the quotation and/or purchase order and Hi-Speed's advertised or published specifications. Buyer shall have a period of thirty (30) days from shipment of goods at the delivery destination specified in the quotation within which to inspect the goods for conformity with the quotation, order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. Buyer shall have a period of thirty (30) days following completion of any services within which to inspect the services for conformity with the quotation, purchase order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. If the goods delivered or services performed do not so conform, upon delivery of notice to Hi-Speed of any discrepancy, nonconformance or rejection, Hi-Speed shall have the right to reject such goods or services. After the cure period, goods that have been delivered and rejected, in whole or in part, shall be returned to Hi-Speed shall, at its sole cost, re-perform the non-conforming services. Inspection or failure to inspect on any occasion shall not affect Buyer's rights under the warranty provisions herein.
- 8. WARRANTIES. Hi-Speed warrants that all goods shall conform in all material aspects to the goods identified in the quotation to Buyer and/or purchase order, and Hi-Speed makes to Buyer the manufacturer's express warranty for any goods sold to Buyer, which is offered by the manufacturer at the time of acceptance of any quotation by Buyer. This warranty is conditioned upon the installation, operation, and maintenance of the goods in accordance with the manufacturer's recommendations and/or standard industry practice and the goods at all times being operated or used under normal operating conditions for which they were designed. Hi-Speed, at its sole option, will repair or

TermsAndConditions

replace any defective or non-conforming goods in accordance with the applicable manufacturer's warranty. Warranty for any defective or incorrect parts is limited to the repair or replacement of those parts. Hi-Speed warrants that all services will conform in all material respects to the description of services identified in the quotation and will be performed in a good and workmanlike manner in accordance with industry practices and standards. Should the services be reasonably rejected or not conform with the foregoing warranties, Hi-Speed shall, at its sole cost, re-perform the defective or nonconforming services. Notwithstanding the foregoing, these warranties do not extend to goods or services to the extent that such goods have been subject to misuse, neglect or abuse not caused by Hi-Speed or have been used in violation of the approved written instructions furnished to Buyer. THE FOREGOING REPRESENTS THE SOLE AND EXCLUSIVE WARRANTY GIVEN BY HI-SPEED WITH RESPECT TO ALL GOODS SOLD AND IS IN LIEU OF ALL OTHER WARRANTIES EITHER EXPRESS OR IMPLIED. HI-SPEED EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICLAR USE OR PURPOSE. BUYER WAIVES ANY CLAIM THAT THESE EXCLUSIONS OR LIMITATIONS DEPRIVE IT OF AN ADEQUATE REMEDY AT EQUITY OR LAW OR CAUSE THIS AGREEMENT TO FAIL IN ITS ESSENTIAL PURPOSE. BUYER SHALL BE ENTITLED TO NO OTHER REMEDY OTHER THAN AS SET FORTH HEREIN, REGARDLESS OF THE CLAIM OR CAUSE OF ACTION, WHETHER BASED IN CONTRACT, TORT, NEGLIGENCE, GOODS LIABILITY, STRICT LIABILITY OR OTHERWISE.

- 9. LIMITATION OF DAMAGES. HI-SPEED SHALL HAVE NO LIABILITY TO BUYER WITH RESPECT TO THE SALE OR DELIVERY OF ANY GOODS OR THE REPAIR THEREOF OR WITH RESPECT TO THE SALE OR PERFORMANCE OF ANY SERVICES, FOR LOST PROFITS, SPECIAL, CONSEQUENTIAL, EXEMPLARY, PUNITIVE OR INCIDENTAL DAMAGES OF ANY KIND OR NATURE WHETHER ARISING IN CONTRACT, TORT, GOODS LIABILITY OR OTHERWISE, EVEN IF HI-SPEED WAS ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGES. HI-SPEED SHALL NOT BE LIABLE FOR ANY DAMAGES OR DELAYS CAUSED BY ANY FAILURE TO MAKE ANY DELIVERY OF GOODS BY ANY EXPECTED TIME OR DATE OR THE FAILURE TO PROVIDE OR COMPLETE ANY SERVICES BY ANY EXPECTED DATE OR TIME. IN NO EVENT SHALL HI-SPEED BE LIABLE TO BUYER FOR ANY DAMAGES WHATSOEVER IN EXCESS OF THE TOTAL PRICE PAID FOR ALL GOODS AND/OR SERVICES HEREUNDER OR REFERENCED IN ANY QUOTATION OR THE PURCHASE ORDER.
- 10. <u>SEVERABILITY</u>. The partial or complete invalidity of any provision of these Standard Terms and Conditions shall not affect the enforceability of the remainder of these Standard Terms and Conditions. If any provision is found to be invalid or unenforceable, that portion shall be modified to make it enforceable or shall be stricken and the remainder of these Standard Terms and Conditions shall enforced.
- 11. <u>GOVERNING LAW AND JURISDICTION.</u> Any controversy arising out of any quotation, the purchase order, the goods sold or delivered, repair or replacement thereof, or any services provided pursuant to any quotation or any purchase order, or these Standard Terms and Conditions shall be governed by the laws of the state of Tennessee without regard to any choice of law provisions and any cause of action related in any manner thereto shall be brought only in the state or federal courts of Shelby County, Tennessee.
- 12. <u>ABANDONED EQUIPMENT.</u> Hi-Speed requires that Buyer promptly pick up or provide shipment instructions for Buyer equipment or other Buyer property in Hi-Speed's possession. If equipment or other Buyer property is left with Hi-Speed and not picked up within six (6) months after Hi-Speed's final action related to the applicable property (e.g. evaluation, teardown, estimate, completion of services), Hi-Speed will consider such property abandoned and may dispose of it in accordance with applicable law. Buyer agrees to hold Hi-Speed harmless for any damage or claim for such abandoned property and acknowledges that Hi-Speed may discard or recycle it at Hi-Speed's sole and absolute discretion. Specifically, Hi-Speed may sell Buyer's abandoned property at a private or public sale and retain the proceeds to offset Hi-Speed's storage, inspection and servicing costs. For the avoidance of doubt, Hi-Speed reserves its statutory and other lawful liens for unpaid charges related to abandoned property.
- 13. FORCE MAJEURE. Neither party shall be responsible for any delay or failure in performance of any party of the quotation, purchase order or these Standard Terms and Conditions to the extent that such delays or failures are caused by fire, flood, earth quake, explosion, war, embargo, government requirement, civil or military authority, acts of God, or any other circumstances beyond its reasonable control and not involving any fault or negligence on the party affected ("Condition"). If any such Condition occurs, the party delayed or unable to perform shall promptly give written notice to the other party and, if such Condition remains at the end of thirty (30) days, the party affected by the other party's delay and inability to perform may elect to (i) terminate such order or part thereof, or (ii) suspend the order for the duration of the Condition, if the Buyer is the suspending party, buy elsewhere comparable material to be sold under the order and apply to any commitment the purchase price of such purchase, and resume performance of the order once the Condition ceases, with an option in the affected party to extend the period of this order up to the length of the time the Condition endures.
- 14. <u>NONWAIVER</u>. No course of dealing or failure of either party to strictly enforce any term, right, or condition of these Standard Terms and Conditions will be construed as a waiver of such term, right or condition. Any waiver by Hi-Speed will only be in writing and will waive no succeeding breach of a term, right or condition.
- 15. <u>ASSIGNMENT.</u> The rights and obligations of the parties shall neither be assigned nor delegated without the prior written consent of the other party. However, any party may assign or delegate its respective rights and obligations, in whole or in part, (i) to any subsidiary, (ii) pursuant to other financing, merger or reorganization or (iii) pursuant to any sale or transfer of substantially all of the assets of the assigning party. These Standard Terms and Conditions shall bind the heirs, successors and assigns of the parties hereto.
- 16. <u>NO INDIVIDUAL LIABILITY</u>. Notwithstanding any other agreement to the contrary, the Buyer agrees that in no event will the Buyer hold and HI-Speed owner, director, officer or employee personally liable for unintentional tortious conduct or conduct that constitutes the breach of any contract between HI-Speed and the Buyer, even if the HI-Speed owner, director, officer or employee is or could be construed to be a party to such contract.