

EVERY DAY SINCE 1946

LR Motor Shop Repairs

Job Number 103782

Prepared for Tenenbaum Recycling Group (10611)

4500 W. Bethany Road North Little Rock AR 72117

Table of Contents

AC Inspection as Found - LITTLE ROCK MOTOR SHOP



Hi-Speed Industrial Service 7030 Ryburn Dr Millington, Tn 38053 901-873-5300

> FolderID: 103782 FormID: 22318837

AC Inspection as Found

Tenenbaum Recycling Group (10611) 4500 W. Bethany Road

North Little Rock, AR 72117

AC Inspection -	Rev. 2	Hi-Speed Job Number:	103782
Location:	LITTLE ROCK MOTOR SHOP	Manufacturer:	Other
Serial Number:	TV / 700000	Spec/ID #:	M: U3960609138
	TV4733CCD3	Serial Number:	TV4733CCD3
Description:125H	P LINCOLN 1770RPM	HP/kW:	125 (HP)
		RPM:	1770 (RPM)
		Frame:	405T
		Voltage:	230 / 460
		Current:	288/144 (Amps)
		Phase:	Three
		Hz:	60 (Hz)
		Service Factor:	1.15
		Enclosure:	ODP
		# of Leads:	12
		J-box Included:	Complete
		Coupling/Sheave:	None
		Date Received:	11/19/2024
		Bearing RTDs:	No
		Stator RTDs:	No
		Repair Stage:	Final
		Rewind:	Yes
		Shaft Machined Fit Repairs Required:	No
		Bearing Housing Machined Fit Repairs Required:	No
		Heaters:	No
		Winding Type :	Random Wound
		Bearing Type:	Rolling Element
iorities Found: 🔵	1 - High 🛛 🔵 2 - Medium	🦲 2 - Low 🛛 🔵 8 - Go	bod

Overall Condition

1. Report Date

11/20/2024

2. Nameplate Picture



3. Photos of all six sides of the machine.

































	4.	Describe the Overall Condition of the Equipment as Received	
		Dirty	
In	itial	Mechanical/Electrical	
	5.	Does Shaft Turn Freely?	(Y) Yes
	6.	Does the shaft require T.I.R in Lathe to identify additional repairs?	(No) No
	7.	Does Shaft Have Visible Damage?	(No) No
	8.	Assembled Shaft Runout	Inches
	9.	Assembled Shaft End Play	inches
	10.	Air Gap Variation <10%	

• 11.	Lead Condition		(NA) Not Applicable
	Rewind		
12.	Lead Length		10 Inches
13.	Does it have Lugs?, If so what is th	e Stud Size?	(No) No
14.	Lead Numbers		1-12
15.	Frame Condition		
16.	Fan Condition		(N) NA
17.	Broken or Missing Components		
Initial	Electrical Inspection		
18.	Insulation Resistance/Megger		Megohms
19.	Winding Resistance		
	1-2	1-3	2-3
20.	Perform Surge Test		(NA) Not Applicable
-	Windings over heated		
21.	Number of Stator Slots		72
22.	Stator Condition		
	Needs extensive cleaning		
23.	Stator Thermistors/Ohms		
24.	Stator Overloads/Ohms		
Mecha	anical Inspection		
25.			0//=
20.	Drive End Bearing Brand		SKF



27. Drive End Bearing Qty.	1
28. Drive End Bearing Type	(Ball) Ball Bearing
29. Drive End Lubrication Type	(Grease) Grease Lubricated
30. Drive End Bearing Insulation or Grounding Device?	
31. Drive End Wavy Washer/Snap-Ring Other Retention Device?	wavy washer

Wear



33.	Opposite Drive End Bearing Brand	SKF
34.	Opposite Drive End Bearing Number-	6315



35.	Opposite Drive End Bearing Qty.	1
36.	Opposite Drive End Bearing Type	(Ball) Ball Bearing
37.	Opposite Drive End Lubrication Type	(Grease) Grease Lubricated
38.	Opposite Drive End Bearing Insulation or Grounding Device?	
39.	Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device?	
4 0.	Opposite Drive End Bearing Condition	

Contamination



41. Drive End Seal 42. Opposite Drive End Seal Rotor Inspection 43. Rotor Type/Material (Squirrel Aluminum) Squirrel Cage Aluminum Die Cast 44. Growler Test (Pass) Pass 45. Number of Rotor Bars 62 46. Rotor Condition needs cleaned 47. List the Parts needed for the Repair Below 6375x2 48. Signature of Technician that Disassembled Motor Cw Motor Stars Stars Stars Stars Stars Opegrees <th></th> <th></th> <th></th> <th></th>						
Rotor Type/Material (Squirrel Aluminum) Squirrel Cage Aluminum Die Cast (Pass) Pass 44. Growler Test (Pass) Pass 45. Number of Rotor Bars 62 46. Rotor Condition needs cleaned 47. List the Parts needed for the Repair Below 6375x2 62 48. Signature of Technician that Disassembled Motor Cw Mechanical Fits- Rotor Mechanical Fits- Rotor 49. Shaft Runout inches 50. Rotor Runout inches Drive End Bearing Fit Rotor Body 0 Degrees 90 Degrees 120 Degrees 51. Coupling Fit Closest to the end of the Shatt 0 Degrees 60 Degrees 52. Coupling Fit Closest to the end of the Shatt 0 Degrees 60 Degrees 53. Drive End Bearing Shaft Fit 0 Degrees 120 Degrees 53. Drive End Bearing Shaft Fit (P) Pass 54. Drive End Bearing Shaft Fit (P) Pass 55. Opposite Drive End Bearing Shaft Fit (P) Pass 55. Opposite Drive End Bearing Shaft Fit (P)	41.	Drive End Seal				
43. Rotor Type/Material (Squirrel Aluminum) Squirrel Cage Aluminum Die Cast 44. Growier Test (Pass) Pass 45. Number of Rotor Bars 62 46. Rotor Condition needs cleaned 47. List the Parts needed for the Repair Below 6375x2 7 48. Signature of Technician that Disassembled Motor Cw Method State Parts Needed for the Repair Below 6375x2 48. Signature of Technician that Disassembled Motor Cw Method State Parts Needed for the Repair Below 6375x2 Method State Parts Needed for the Repair Below 6375x2 48. Signature of Technician that Disassembled Motor Cw Method State Parts Needed for the Repair Below 6375x2 Method State Parts Needed for the Repair Below 6375x2 Method State Parts Needed for the Repair Below 6375x2 Method State Parts Needed for the Repair Below 6375x2 Method State Parts Needed for the Repair Below 6375x2 Method State Parts Needed for the Repair Below 600 Page 80 Opposite Drive End Bearing Parts Needed For Page 80 Opgrees 120 Degrees 0 Degrees 60 Degrees 120 Degrees Method State Fit	42.	Opposite Drive End Seal				
Cage Aluminum Die Cast 44. Growler Test (Pass) Pass 45. Number of Rotor Bars 62 46. Rotor Condition needs cleaned 47. List the Parts needed for the Repair Below 6315x2 needs cleaned 48. Signature of Technician that Disassembled Motor Cw Mechanican that Disassembled Motor Image that Disassembled	Rotor	r Inspection				
45. Number of Rotor Bars 62 46. Rotor Condition needs cleaned 47. List the Parts needed for the Repair Below 6315x2 seeds cleaned 48. Signature of Technician that Disassembled Motor Cw Mechanical Fits- Rotor Mechanical Fits- Rotor 49. Shaft Runout inches 50. Rotor Runout inches 51. Coupling Fit Closest to Bearing Fit Rotor Body Opposite Drive End Bearing 51. Coupling Fit Closest to Bearing Housing 0 Degrees 90 Degrees 120 Degrees 52. Coupling Fit Closest to the end of the Shaft 0 Degrees 120 Degrees 120 Degrees 53. Drive End Bearing Shaft Fit 0 Degrees 120 Degrees 120 Degrees 53. Drive End Bearing Shaft Fit 0 Degrees 120 Degrees 120 Degrees 54. Drive End Bearing Shaft Fit 0 Degrees 120 Degrees 120 Degrees 55. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 120 Degrees 55. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 120 Degrees 54. Drive End Bearing Shaft Fit Condition (P) Pass 120 Degrees 120 Degrees 54. Drive End Bearing Shaft	43.	Rotor Type/Material				
46. Rotor Condition needs cleaned 47. List the Parts needed for the Repair Below 8315x2 48. Signature of Technician that Disassembled Motor Cw 48. Signature of Technician that Disassembled Motor Cw Mediation 1000000000000000000000000000000000000	44.	Growler Test		(Pass) Pass		
47. List the Parts needed for the Repair Below 3315x2 48. Signature of Technician that Disassembled Motor Cw 48. Signature of Technician that Disassembled Motor Cw 49. Shaft Runout Cw 49. Shaft Runout inches 50. Rotor Runout Drive End Bearing Fit 61. Coupling Fit Closest to Bearing Housing 0 Degrees 90 Degrees 90 Degrees 90 Degrees 120 Degrees 91. Coupling Fit Closest to the end of the Shaft 120 Degrees 90 Degrees 60 Degrees 120 Degrees 90 Degrees 120 Degrees 120 Degrees 91. Drive End Bearing Shaft Fit 0 Degrees 120 Degrees 92. Sora3 2.9533 2.9533 2.9533 2.9533 2.9533 52. Orypestic Drive End Bearing Shaft Fit Condition (P) Pass 53. Orypestic Drive End Bearing Shaft Fit Condition (P) Pass 54. Drive End Bearing Shaft Fit Condition (P) Pass 55. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 56. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 57. Opposite Drive End Bearing Shaft Fit Condition (P) Pass <	45.	Number of Rotor Bars		62		
6315x2 48. Signature of Technician that Disassembled Motor Cw Method Signature of Technician that Disassembled Motor 49. Shaft Runout inches 50. Rotor Runout Inches 51. Coupling Fit Closest to Bearing Hous Method Signature of Technician that Disassembled Motor 52. Coupling Fit Closest to the end of the Shaft 0 Degrees 120 Degrees 53. Drive End Bearing Shaft Fit 29533 29533 54. Drive End Bearing Shaft Fit Condition (P) Pass 55. Opposite Drive End Bearing Shaft Fit (P) Pass 56. Opposite Drive End Bearing Shaft Fit (P) Pass	46.	Rotor Condition		needs cleaned		
Mechanical Fits- Rotor inches 49. Shaft Runout inches 50. Rotor Runout Drive End Bearing Fit Rotor Body Opposite Drive End Bearing 51. Coupling Fit Closest to Bearing Housing 0 Degrees 90 Degrees 120 Degrees 51. Coupling Fit Closest to the end of the Shaft 120 Degrees 120 Degrees 52. Coupling Fit Closest to the end of the Shaft 120 Degrees 120 Degrees 53. Drive End Bearing Shaft Fit 0 Degrees 120 Degrees 120 Degrees 53. Drive End Bearing Shaft Fit 0 Degrees 120 Degrees 120 Degrees 54. Drive End Bearing Shaft Fit (P) Pass 120 Degrees 120 Degrees 55. Opposite Drive End Bearing Shaft Fit (P) Pass 120 Degrees 120 Degrees 55. Opposite Drive End Bearing Shaft Fit (P) Pass 120 Degrees 120 Degrees 56. Opposite Drive End Bearing Shaft Fit (P) Pass 120 Degrees 120 Degrees 55. Opposite Drive End Bearing Shaft Fit (P) Pass 120 Degrees 120 Degrees 57. Opposite Drive End Bearing Shaft Fit (P) Pass 120 Degrees 120 Degrees 56. Opposite Drive End Bearing Shaft Fit (P) Pass <t< td=""><td>47.</td><td></td><td>elow</td><td></td></t<>	47.		elow			
49. Shaft Runout inches 50. Rotor Runout Drive End Bearing Fit Rotor Body Opposite Drive End Bearing 51. Coupling Fit Closest to Bearing Housing 0 Degrees 120 Degrees 51. Coupling Fit Closest to the end of the Shaft 0 Degrees 120 Degrees 52. Coupling Fit Closest to the end of the Shaft 120 Degrees 120 Degrees 53. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 53. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 54. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 55. Opposite Drive End Bearing Shaft Fit Condition (P) Pass (P) Pass 55. Opposite Drive End Bearing Shaft Fit Condition (P) Pass (P) Pass 55. Opposite Drive End Bearing Shaft Fit Condition 120 Degrees 120 Degrees 60 Degrees 60 Degrees 120 Degrees (P) Pass 55. Opposite Drive End Bearing Shaft Fit 120 Degrees (P) Pass 56. Opposite Drive End Bearing Shaft Fit 2.9532 2.9532	48.	•		Cw		
50. Rotor RunoutRotor BodyOpposite Drive End BearingDrive End Bearing FitRotor BodyOpposite Drive End Bearing51. Coupling Fit Closest to Bearing Housing120 Degrees0 Degrees90 Degrees120 Degrees52. Coupling Fit Closest to the end of the Shaft120 Degrees0 Degrees60 Degrees120 Degrees53. Drive End Bearing Shaft Fit120 Degrees0 Degrees60 Degrees120 Degrees2.95332.95332.953354. Drive End Bearing Shaft Fit Condition(P) Pass55. Opposite Drive End Bearing Shaft Fit(P) Pass55. Opposite Drive End Bearing Shaft Fit120 Degrees0 Degrees60 Degrees120 Degrees53. Drive End Bearing Shaft Fit120 Degrees54. Drive End Bearing Shaft Fit Condition(P) Pass55. Opposite Drive End Bearing Shaft Fit120 Degrees0 Degrees60 Degrees120 Degrees55. Opposite Drive End Bearing Shaft Fit120 Degrees56. Opposite Drive End Bearing Shaft Fit120 Degrees57. Drive End Bearing Shaft Fit120 Degrees57. Opposite Drive End Bearing Shaft Fit120 Degrees57. Op	Mecha	anical Fits- Rotor				
Drive End Bearing FitRotor BodyOpposite Drive End Bearing51.Coupling Fit Closest to Bearing Housing120 Degrees0 Degrees90 Degrees120 Degrees52.Coupling Fit Closest to the end of the Shaft120 Degrees0 Degrees60 Degrees120 Degrees53.Drive End Bearing Shaft Fit20 Degrees0 Degrees60 Degrees120 Degrees53.Drive End Bearing Shaft Fit120 Degrees0 Degrees60 Degrees120 Degrees54.Drive End Bearing Shaft Fit Condition(P) Pass55.Opposite Drive End Bearing Shaft Fit(P) Pass55.Opposite Drive End Bearing Shaft Fit120 Degrees0 Degrees60 Degrees120 Degrees55.Opposite Drive End Bearing Shaft Fit120 Degrees0 Degrees60 Degrees120 Degrees55.Opposite Drive End Bearing Shaft Fit120 Degrees0 Degrees60 Degrees120 Degrees	49.	Shaft Runout		inches		
51. Coupling Fit Closest to Bearing Housing 0 Degrees 90 Degrees 120 Degrees 52. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 120 Degrees 53. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 53. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 53. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 54. Drive End Bearing Shaft Fit Condition (P) Pass (P) Pass 55. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 54. Drive End Bearing Shaft Fit Condition (P) Pass (P) Pass 55. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 54. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees	50.	Rotor Runout				
0 Degrees90 Degrees120 Degrees52. Coupling Fit Closest to the end of the Shaft0 Degrees60 Degrees120 Degrees60 Degrees53. Drive End Bearing Shaft Fit0 Degrees60 Degrees2.95332.95332.95332.953354. Drive End Bearing Shaft Fit Condition(P) Pass55. Opposite Drive End Bearing Shaft Fit0 Degrees60 Degrees2.95312.95322.95312.9532		Drive End Bearing Fit	Rotor Body	Opposite Drive End Bearing		
52. Coupling Fit Closest to the end of the Shaft 0 Degrees 60 Degrees 53. Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 2.9533 2.9533 2.9533 2.9533 54. Drive End Bearing Shaft Fit Condition (P) Pass 55. Opposite Drive End Bearing Shaft Fit Condition (P) Pass 55. Opposite Drive End Bearing Shaft Fit 120 Degrees 2.9531 2.9532	51.	Coupling Fit Closest to Bearing Housi	ng			
0 Degrees60 Degrees120 Degrees53. Drive End Bearing Shaft Fit60 Degrees120 Degrees0 Degrees60 Degrees120 Degrees2.95332.95332.953354. Drive End Bearing Shaft Fit Condition(P) Pass55. Opposite Drive End Bearing Shaft Fit(P) Pass55. Opposite Drive End Bearing Shaft Fit120 Degrees0 Degrees60 Degrees120 Degrees2.95312.9532		0 Degrees	90 Degrees	120 Degrees		
53. Drive End Bearing Shaft Fit0 Degrees60 Degrees120 Degrees2.95332.95332.953354. Drive End Bearing Shaft Fit Condition(P) Pass55. Opposite Drive End Bearing Shaft Fit(P) Pass0 Degrees60 Degrees120 Degrees2.95312.9532	52.	Coupling Fit Closest to the end of the	Shaft			
0 Degrees 60 Degrees 120 Degrees 2.9533 2.9533 2.9533 54. Drive End Bearing Shaft Fit Condition (P) Pass 55. Opposite Drive End Bearing Shaft Fit (P) Pass 0 Degrees 60 Degrees 120 Degrees 2.9531 2.9532 2.9532		0 Degrees	60 Degrees	120 Degrees		
2.9533 2.9533 2.9533 54. Drive End Bearing Shaft Fit Condition (P) Pass 55. Opposite Drive End Bearing Shaft Fit (P) Pass 0 Degrees 60 Degrees 120 Degrees 2.9531 2.9532 2.9532	53.	Drive End Bearing Shaft Fit				
54.Drive End Bearing Shaft Fit Condition(P) Pass55.Opposite Drive End Bearing Shaft Fit0 Degrees120 Degrees2.95312.95322.9532		0 Degrees	60 Degrees	120 Degrees		
55. Opposite Drive End Bearing Shaft Fit 0 Degrees 60 Degrees 120 Degrees 2.9531 2.9532 2.9532		2.9533	2.9533	2.9533		
0 Degrees 60 Degrees 120 Degrees 2.9531 2.9532 2.9532	54.	Drive End Bearing Shaft Fit Condition		(P) Pass		
2.9531 2.9532 2.9532	55.	Opposite Drive End Bearing Shaft Fit				
		0 Degrees	60 Degrees	120 Degrees		
56. Opposite Drive End Bearing Shaft Fit Condition(P) Pass		2.9531	2.9532	2.9532		
	56.	Opposite Drive End Bearing Shaft Fit	Condition	(P) Pass		

57.	Shaft Air Seal Fits			
	Drive End Air Seal	Opposite Drive End Air Seal		
Mecha	anical Fits- Bearing Housings			
58.	Drive End - Endbell Bearing Fit			
	0 Degrees	60 Degrees	120 Degrees	
	6.3009	6.3008	6.3008	
59.	Drive End - Endbell Bearing Fit Cond	tion		(P) Pass
60.	Opposite Drive End - Endbell Bearing	Fit		
	0 Degrees	60 Degrees	120 Degrees	
	6.2996	6.2997	6.2996	
61.		Fit Condition		(P) Pass
_	Bearing Cap Condition			(1)1111
	Drive End Bearing Cap	Opposite Drive End Bearing Cap		
	Brive End Bearing Cap	opposite Drive End Dealing Oup		
63.	End Bell Air Seal Fits			
	Drive End Air Seal	Opposite Drive End Air Seal		
64.	List Machine Work Needed Below			
65.	Technician			Cw
	(1			
	Ann			
	Co sign: RRW			
	Cause of Failure			
	Failure locations			
00.	Windings and bearings			
07	Root cause of failure			
67.				
_	Windings burned up from loss of airflo	w due to constants		
-	mic Balance Report			
68.	Rotor Weight and Balance Grade			
	Rotor Weight	Balance Grade		
69.	Initial Balance Readings	0 / D / T /		
	Drive End	Opposite Drive End		
70	Final Dalamar, Danding			
70.	Final Balance Readings			
	Drive End	Opposite Drive End		
71	Technician			
Rewin		· · · · · · · · · · · · · · · · · · ·		
72.	Core Test Results - Watts loss per Po			
	Pre-Burnout	Post Burnout		
70				
73.	Core Hot Spot Test			
	Pre-Burnout	Post-Burnout		

74.	Post Rewind Electrical Test- Insulation	Resistance	
	Post Rewind Polarization Index		
76.	Post Rewind Winding Resistance		
	1-2	1-3	2-3
77.	Post Rewind Surge Test		
78.	Post Rewind Hi-Pot		
79.	Technician		
Assen	nbly		
80.	QC Check All Parts for Cleanliness Pr	ior to Assembly	
81.	Photograph All Major Components price	or to assembly	
82.	Final Insulation Resistance Test		
	Assembled Shaft Endplay		
	Assembled Shaft Runout		
85.	Test Run Voltage		
	Volts	Volts	Volts
	T (D)		
86.	Test Run Amperage	•	•
	Amps	Amps	Amps
87.	Drive End Vibration Readings - Inches	Per Second	
	Horizontal	Vertical	Axial
88.	Opposite Drive End Vibration Reading		
	Horizontal	Vertical	Axial
00	Ambient Temperature - Tehnert V		
	Ambient Temperature - Fahrenheit	4	
90.	Drive End Bearing Temps - Fahrenhei		15 Minuton
	5 Minutes	10 Minutes	15 Minutes
91.	Opposite Drive End Bearing Temps - F	Fahrenheit	
	5 Minutes	10 Minutes	15 Minutes
	Document Final Condition with Picture	s after paint	
93.	Final Pics and QC Review		



STANDARD TERMS AND CONDITIONS FOR PURCHASE OF GOOD AND/OR SERVICES

- 1. <u>APPLICABILITY.</u> The sale of any and all goods and/or services by Mock, Inc. d/b/a Hi-Speed Industrial Service ("Hi-Speed") shall be specifically conditioned upon and subject to the following terms and conditions which are incorporated by reference into any contracts and purchase orders with Hi-Speed, and which shall form and become a part of any agreement related thereto. Buyer's acceptance of any offer or quotation made by Hi-Speed for sale of any goods or services is expressly made subject to the terms and conditions set forth herein and to be so effective, Buyer need not sign or approve these Terms and Conditions to be bound hereunder provided a copy of same is provided to Buyer through any means. None of the terms and conditions contained herein may be added to, expanded, changed, modified, superseded or otherwise altered except as revised in writing and duly executed by Hi-Speed, and all orders received by Hi-Speed shall be governed only by the terms and conditions contained herein, notwithstanding any terms, conditions or provisions of any purchase order, release order, authorization or any other form issued by the Buyer. Hi-Speed hereby objects to any additional, modified, changed, deleted, altered or other terms and conditions not contained herein and notifies Buyer that any such terms or provisions are expressly rejected by Hi-Speed.
- 2. PRICE. All quoted prices shall remain firm and binding for a period of thirty (30) days from the date of quotation or for the period specifically stated in the quotation. The price for any and all goods and/or services ordered or approved by Buyer after thirty (30) days from the date of any quotation are subject to any increase in price that may occur after the expiration of thirty (30) days from the issuance of the quotation and the date the Buyer releases any shipment.
- 3. <u>SCOPE OF GOODS AND/OR SERVICES.</u> The goods and/or services provided by Hi-Speed pursuant to any quotation shall be limited exclusively to those goods and/or services expressly identified therein. Hi-Speed does not assume any responsibility and/or liability for the failure to provide any other goods and/or services not identified in any quotation. Modifications, additions or deletions to or from the scope referenced in any quotation shall only be effective if evidenced in writing and signed by Hi-Speed. The sale of any of all goods and/or services affected by such modification, addition or deletion shall be subject to these same Standard Terms and Conditions whether or not referenced therein.
- 4. <u>BILLING AND PAYMENT TERMS.</u> Hi-Speed shall invoice Buyer for all goods and/or services as same are rendered at the address listed on the quotation. Payments for all goods and/or services shall be due thirty (30) days from the date of the current invoice or as otherwise set forth in the quotation. Late payments are subject to a late fee of 5% of the total invoice amount. Recurring late payments may lead to a deposit requirement on future services or sale of goods. Buyer shall be liable to Hi-Speed for any and all fees and expenses incurred by Hi-Speed to collect any invoices or to enforce these Standard Terms and Conditions, including but not limited to, attorney's fees.
- 5. DELIVERY OF GOODS AND/OR SERVICES. Unless otherwise identified in the quotation, all shipments are F.O.B. Hi-Speed's warehouse and the title to and all risk of loss with respect to any goods shipped shall pass to Buyer when such goods are delivered to the carrier at Hi-Speed's warehouse. Hi-Speed will use its best efforts to affect delivery by the date or dates specified in the quotation. However, Hi-Speed shall not be liable for delay in or failure to make shipment, or to perform services, by any identified date for any reason whatsoever, including but not limited to, causes beyond its reasonable control, such as strikes, fires, floods, epidemics, quarantines, restrictions, severe weather, embargos, acts of God, or public enemy, war, riot, delays in transportation or the inability to obtain necessary labor, materials or manufacturing facilities.
- 6. DELIVERY SITE AND TIME FOR PERFORMANCE. Hi-Speed and Buver agree that time is of the essence for the purchase order and that Buyer shall fully cooperate with Hi-Speed in order to allow Hi-Speed full access to prosecute its work diligently and in an orderly manner. Buyer shall assist Hi-Speed in every way possible to avoid delaying, disrupting or interfering with the progress of Hi-Speed's work at the project site. In the event Hi-Speed's work is delayed, hindered, suspended, disrupted, re-sequenced or interfered with or rendered less efficient or more costly or adversely affected in any way as a result of acts or omissions of Buyer or other contractors or employees of Buyer or by any other reason beyond Hi-Speed's control and without the fault of Hi-Speed, then, in such event, Buyer shall be liable to Hi-Speed for any damages, additional costs, expenses, labor, materials, man hours, acceleration costs, overtime, additional jobsite overhead, extended home office overhead, and any and all other direct and indirect expenses of whatsoever nature or kind, caused in whole or in part, as a result of any of the above-referenced occurrences. Hi-Speed's project records will be the basis for computing the additional costs and damages of Hi-Speed's labor, materials, expenses and overhead related to such changes. BUYER WARRANTS THAT THE SITE FOR DELIVERY OR INSTALLATION OF ANY GOODS AND/OR FOR THE PERFORMANCE OF ANY SERVICES SHALL BE READY AND ADEQUATE FOR HI-SPEED'S DELIVERY OF GOODS AND/OR PERFORMANCE OF SERVICES AND THAT HI-SPEED SHALL HAVE FULL ACCESS THERETO, FREE OF ALL OBSTRUCTIONS. BUYER SHALL ASSUME ALL EXTRA COSTS ASSOCIATED WITH HI-SPEED'S INABILITY TO INSTALL ANY GOODS OR PERFORM ANY SERVICES AS A RESULT OF BUYER'S FAILURE TO COMPLY WITH THIS PROVISION. HI-SPEED MAY NOT INSPECT THE SITE PRIOR TO DELIVERY AND/OR INSTALLATION OF GOODS AND/OR PERFORMANCE OF SERVICES AND MAKES NO WARRANTY AS TO THE SUFFICIENCY OF THE SITE FOR THE DELIVERY AND/OR INSTALLATION OF GOODS AND/OR THE PERFORMANCE OF SERVICES AT SUCH SITE.
- 7. INSPECTION/ACCEPTANCE. All goods and services ordered pursuant to any quotation shall be subject to inspection by Buyer after delivery or performance to determine conformity with the quotation and/or purchase order and Hi-Speed's advertised or published specifications. Buyer shall have a period of thirty (30) days from shipment of goods at the delivery destination specified in the quotation within which to inspect the goods for conformity with the quotation, order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. Buyer shall have a period of thirty (30) days following completion of any services within which to inspect the services for conformity with the quotation, purchase order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. If the goods delivered or services performed do not so conform, upon delivery of notice to Hi-Speed of any discrepancy, nonconformance or rejection, Hi-Speed shall have the right to reject such goods or services. After the cure period, goods that have been delivered and rejected, in whole or in part, shall be returned to Hi-Speed shall, at its sole cost, re-perform the non-conforming services. Inspection or failure to inspect on any occasion shall not affect Buyer's rights under the warranty provisions herein.
- 8. WARRANTIES. Hi-Speed warrants that all goods shall conform in all material aspects to the goods identified in the quotation to Buyer and/or purchase order, and Hi-Speed makes to Buyer the manufacturer's express warranty for any goods sold to Buyer, which is offered by the manufacturer at the time of acceptance of any quotation by Buyer. This warranty is conditioned upon the installation, operation, and maintenance of the goods in accordance with the manufacturer's recommendations and/or standard industry practice and the goods at all times being operated or used under normal operating conditions for which they were designed. Hi-Speed, at its sole option, will repair or

TermsAndConditions

replace any defective or non-conforming goods in accordance with the applicable manufacturer's warranty. Warranty for any defective or incorrect parts is limited to the repair or replacement of those parts. Hi-Speed warrants that all services will conform in all material respects to the description of services identified in the quotation and will be performed in a good and workmanlike manner in accordance with industry practices and standards. Should the services be reasonably rejected or not conform with the foregoing warranties, Hi-Speed shall, at its sole cost, re-perform the defective or nonconforming services. Notwithstanding the foregoing, these warranties do not extend to goods or services to the extent that such goods have been subject to misuse, neglect or abuse not caused by Hi-Speed or have been used in violation of the approved written instructions furnished to Buyer. THE FOREGOING REPRESENTS THE SOLE AND EXCLUSIVE WARRANTY GIVEN BY HI-SPEED WITH RESPECT TO ALL GOODS SOLD AND IS IN LIEU OF ALL OTHER WARRANTIES EITHER EXPRESS OR IMPLIED. HI-SPEED EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICLAR USE OR PURPOSE. BUYER WAIVES ANY CLAIM THAT THESE EXCLUSIONS OR LIMITATIONS DEPRIVE IT OF AN ADEQUATE REMEDY AT EQUITY OR LAW OR CAUSE THIS AGREEMENT TO FAIL IN ITS ESSENTIAL PURPOSE. BUYER SHALL BE ENTITLED TO NO OTHER REMEDY OTHER THAN AS SET FORTH HEREIN, REGARDLESS OF THE CLAIM OR CAUSE OF ACTION, WHETHER BASED IN CONTRACT, TORT, NEGLIGENCE, GOODS LIABILITY, STRICT LIABILITY OR OTHERWISE.

- 9. LIMITATION OF DAMAGES. HI-SPEED SHALL HAVE NO LIABILITY TO BUYER WITH RESPECT TO THE SALE OR DELIVERY OF ANY GOODS OR THE REPAIR THEREOF OR WITH RESPECT TO THE SALE OR PERFORMANCE OF ANY SERVICES, FOR LOST PROFITS, SPECIAL, CONSEQUENTIAL, EXEMPLARY, PUNITIVE OR INCIDENTAL DAMAGES OF ANY KIND OR NATURE WHETHER ARISING IN CONTRACT, TORT, GOODS LIABILITY OR OTHERWISE, EVEN IF HI-SPEED WAS ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGES. HI-SPEED SHALL NOT BE LIABLE FOR ANY DAMAGES OR DELAYS CAUSED BY ANY FAILURE TO MAKE ANY DELIVERY OF GOODS BY ANY EXPECTED TIME OR DATE OR THE FAILURE TO PROVIDE OR COMPLETE ANY SERVICES BY ANY EXPECTED DATE OR TIME. IN NO EVENT SHALL HI-SPEED BE LIABLE TO BUYER FOR ANY DAMAGES WHATSOEVER IN EXCESS OF THE TOTAL PRICE PAID FOR ALL GOODS AND/OR SERVICES HEREUNDER OR REFERENCED IN ANY QUOTATION OR THE PURCHASE ORDER.
- 10. <u>SEVERABILITY</u>. The partial or complete invalidity of any provision of these Standard Terms and Conditions shall not affect the enforceability of the remainder of these Standard Terms and Conditions. If any provision is found to be invalid or unenforceable, that portion shall be modified to make it enforceable or shall be stricken and the remainder of these Standard Terms and Conditions shall enforced.
- 11. <u>GOVERNING LAW AND JURISDICTION.</u> Any controversy arising out of any quotation, the purchase order, the goods sold or delivered, repair or replacement thereof, or any services provided pursuant to any quotation or any purchase order, or these Standard Terms and Conditions shall be governed by the laws of the state of Tennessee without regard to any choice of law provisions and any cause of action related in any manner thereto shall be brought only in the state or federal courts of Shelby County, Tennessee.
- 12. <u>ABANDONED EQUIPMENT.</u> Hi-Speed requires that Buyer promptly pick up or provide shipment instructions for Buyer equipment or other Buyer property in Hi-Speed's possession. If equipment or other Buyer property is left with Hi-Speed and not picked up within six (6) months after Hi-Speed's final action related to the applicable property (e.g. evaluation, teardown, estimate, completion of services), Hi-Speed will consider such property abandoned and may dispose of it in accordance with applicable law. Buyer agrees to hold Hi-Speed harmless for any damage or claim for such abandoned property and acknowledges that Hi-Speed may discard or recycle it at Hi-Speed's sole and absolute discretion. Specifically, Hi-Speed may sell Buyer's abandoned property at a private or public sale and retain the proceeds to offset Hi-Speed's storage, inspection and servicing costs. For the avoidance of doubt, Hi-Speed reserves its statutory and other lawful liens for unpaid charges related to abandoned property.
- 13. FORCE MAJEURE. Neither party shall be responsible for any delay or failure in performance of any party of the quotation, purchase order or these Standard Terms and Conditions to the extent that such delays or failures are caused by fire, flood, earth quake, explosion, war, embargo, government requirement, civil or military authority, acts of God, or any other circumstances beyond its reasonable control and not involving any fault or negligence on the party affected ("Condition"). If any such Condition occurs, the party delayed or unable to perform shall promptly give written notice to the other party and, if such Condition remains at the end of thirty (30) days, the party affected by the other party's delay and inability to perform may elect to (i) terminate such order or part thereof, or (ii) suspend the order for the duration of the Condition, if the Buyer is the suspending party, buy elsewhere comparable material to be sold under the order and apply to any commitment the purchase price of such purchase, and resume performance of the order once the Condition ceases, with an option in the affected party to extend the period of this order up to the length of the time the Condition endures.
- 14. <u>NONWAIVER</u>. No course of dealing or failure of either party to strictly enforce any term, right, or condition of these Standard Terms and Conditions will be construed as a waiver of such term, right or condition. Any waiver by Hi-Speed will only be in writing and will waive no succeeding breach of a term, right or condition.
- 15. <u>ASSIGNMENT.</u> The rights and obligations of the parties shall neither be assigned nor delegated without the prior written consent of the other party. However, any party may assign or delegate its respective rights and obligations, in whole or in part, (i) to any subsidiary, (ii) pursuant to other financing, merger or reorganization or (iii) pursuant to any sale or transfer of substantially all of the assets of the assigning party. These Standard Terms and Conditions shall bind the heirs, successors and assigns of the parties hereto.
- 16. <u>NO INDIVIDUAL LIABILITY</u>. Notwithstanding any other agreement to the contrary, the Buyer agrees that in no event will the Buyer hold and HI-Speed owner, director, officer or employee personally liable for unintentional tortious conduct or conduct that constitutes the breach of any contract between HI-Speed and the Buyer, even if the HI-Speed owner, director, officer or employee is or could be construed to be a party to such contract.