

## LR Motor Shop Repairs

## **Job Number 102863**

Prepared for Union Pacific-Vine St 10945

1020 N. Vine Street North Liittle Rock AR

## **Table of Contents**

AC Inspection as Found - Shop

AC Inspection - Rev. 2: 4808-7725 2816 1

1.0





### **AC Inspection as Found** Union Pacific-Vine St 10945

1020 N. Vine Street North Liittle Rock, AR

FolderID: 102863 FormID: 20233201

#### AC Inspection - Rev. 2

Location:

Shop

Serial Number:

4808-7725 2816 1

Description:STROMAG EDDY CURRENT

CLUTCH

Hi-Speed Job Number:	100600
Manufacturer:	Other
Product Number:	IBV-360
Serial Number:	4808-7725 2816 1
Voltage:	Other
Current:	2.17
Hz:	60 (Hz)
Enclosure:	ODP
# of Leads:	2
J-box Included:	Half
Coupling/Sheave:	Coupling
Date Received:	04/30/2024
Bearing RTDs:	No
Stator RTDs:	No
Repair Stage:	Final
Rewind:	No
Bearing Housing Machined Fit Repairs Required:	No
Heaters:	No
Winding Type :	Random Wound
Bearing Type:	Rolling Element

Priorities Found: **a** 2 - High



8 - Good

#### **Overall Condition**

04/30/2024 Report Date

Nameplate Picture



3. Photos of all six sides of the machine.







Go by these marks



























	4.	Describe the Overall Condition of the Equipment as Received  Dirty	
	5.	Distance from the end of the shaft to the Coupling/Sheave	inches
	-	Flush	
In	itial	Mechanical/Electrical	
	6.	Does Shaft Turn Freely?	(Y) Yes
	7.	Does the shaft require T.I.R in Lathe to identify additional repairs?	(Yes) Yes
	8.	Does Shaft Have Visible Damage?	(No) No
	9.	Assembled Shaft Runout	Inches
	-	Na	
	10.	Assembled Shaft End Play	inches
	-	Na	
	11.	Air Gap Variation <10%	
	-	Na	
	12.	Lead Condition	(P) Pass
	13.	Lead Length	8 Inches
	14.	Does it have Lugs?, If so what is the Stud Size?	(No) No
	15.	Lead Numbers	na
	16.	Frame Condition	pass
	17.	Fan Condition	(N) NA
	18.	Broken or Missing Components	J-Box cover
In	itial	Electrical Inspection	

	19.	Insulation Resistance/Megger		Megohms
	7	Pass		
	20.	Winding Resistance		
		1-2	1-3	2-3
	•	43.8 ohms		
	21.	Perform Surge Test		(NA) Not Applicable
	22.	Number of Stator Slots		
	•	Na		
	23.	Stator Condition		
	-	Pass		
	24.	Stator Thermistors/Ohms		
	-	Na		
	25.	Stator Overloads/Ohms		
	•	Na		
N	lecha	anical Inspection		
	26.	Drive End Bearing Brand		AMI
	27.	Drive End Bearing Number-		UC211-34
	28.	Drive End Bearing Qty.		1
	29.	Drive End Bearing Type		(Ball) Ball Bearing
	30.	Drive End Lubrication Type		(Grease) Grease Lubricated
	31.	Drive End Bearing Insulation or Groun	nding Device?	na
	32.	Drive End Wavy Washer/Snap-Ring O	Other Retention Device?	hub bearing
	33.	Drive End Bearing Condition		
	34.	Opposite Drive End Bearing Brand		FAG
	35.	Opposite Drive End Bearing Number-		6020 RSR



36. Opposite Drive End Bearing Qty.	2
37. Opposite Drive End Bearing Type	(Ball) Ball Bearing
38. Opposite Drive End Lubrication Type	(Grease) Grease Lubricated
39. Opposite Drive End Bearing Insulation or Grounding Device?	na
40. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device?	snap ring

#### Normal wear





42. Drive End Seal na 43. Opposite Drive End Seal Na **Rotor Inspection** 

- 44. Rotor Type/Material
- Na
- 45. Growler Test
- Na
- 46. Number of Rotor Bars
- Na
- 47. Rotor Condition
- Na
- 48. List the Parts needed for the Repair Below UC211-34 6020x2

49. Signature of Technician that Disassembled Motor

Cw

# vis

#### **Mechanical Fits- Rotor**

 	announ i ito i itotoi		
50.	Shaft Runout		15 millimeters
51.	Rotor Runout		
	Drive End Bearing Fit	Rotor Body	Opposite Drive End Bearing
	Na		
52.	Coupling Fit Closest to Bearing Housi	ng	
	0 Degrees	90 Degrees	120 Degrees
	Na		

	53	Coupling Fit Closest to the end of the	Shaft		
	55.	O Degrees	60 Degrees	120 Degrees	
		0 Degrees	oo Degrees	120 Degrees	
	-	Na			
	54.	Drive End Bearing Shaft Fit			
		0 Degrees	60 Degrees	120 Degrees	
	-	Na			
	55.	Drive End Bearing Shaft Fit Condition			(P) Pass
	56.	Opposite Drive End Bearing Shaft Fit			,
		0 Degrees	60 Degrees	120 Degrees	
		S .	ŭ	3	
	-	Na			
	57.	Opposite Drive End Bearing Shaft Fit	Condition		(P) Pass
	58.	Shaft Air Seal Fits			
		Drive End Air Seal	Opposite Drive End Air Seal		
	7	Na			
M		anical Fits- Bearing Housings			
	59.	Drive End - Endbell Bearing Fit			
		0 Degrees	60 Degrees	120 Degrees	
	_	Out of tolerance			
	•	Sign off: David W.			
_					
	60.	Drive End - Endbell Bearing Fit Condi	tion		(P) Pass
		Drive End - Endbell Bearing Fit Condi Opposite Drive End - Endbell Bearing			(P) Pass
		-		120 Degrees	(P) Pass
		Opposite Drive End - Endbell Bearing	Fit	120 Degrees 5.905	(P) Pass
		Opposite Drive End - Endbell Bearing  O Degrees	Fit 60 Degrees 5.9051	_	(P) Pass
	61. 62.	Opposite Drive End - Endbell Bearing 0 Degrees 5.905	Fit 60 Degrees 5.9051	_	·
	61. 62.	Opposite Drive End - Endbell Bearing 0 Degrees 5.905 Opposite Drive End - Endbell Bearing	Fit 60 Degrees 5.9051	_	•
	61. 62. 63.	Opposite Drive End - Endbell Bearing 0 Degrees 5.905 Opposite Drive End - Endbell Bearing Bearing Cap Condition Drive End Bearing Cap	Fit 60 Degrees 5.9051 Fit Condition	_	•
	<ul><li>61.</li><li>62.</li><li>63.</li></ul>	Opposite Drive End - Endbell Bearing 0 Degrees 5.905 Opposite Drive End - Endbell Bearing Bearing Cap Condition Drive End Bearing Cap	Fit 60 Degrees 5.9051 Fit Condition	_	•
•	<ul><li>61.</li><li>62.</li><li>63.</li></ul>	Opposite Drive End - Endbell Bearing 0 Degrees 5.905 Opposite Drive End - Endbell Bearing Bearing Cap Condition Drive End Bearing Cap  Na End Bell Air Seal Fits	Fit 60 Degrees 5.9051 Fit Condition Opposite Drive End Bearing Cap	_	•
•	<ul><li>61.</li><li>62.</li><li>63.</li></ul>	Opposite Drive End - Endbell Bearing 0 Degrees 5.905 Opposite Drive End - Endbell Bearing Bearing Cap Condition Drive End Bearing Cap	Fit 60 Degrees 5.9051 Fit Condition	_	
	<ul><li>61.</li><li>62.</li><li>63.</li><li>64.</li></ul>	Opposite Drive End - Endbell Bearing  0 Degrees  5.905  Opposite Drive End - Endbell Bearing Bearing Cap Condition  Drive End Bearing Cap  Na  End Bell Air Seal Fits  Drive End Air Seal	Fit 60 Degrees 5.9051 Fit Condition Opposite Drive End Bearing Cap	_	
•	61. 62. 63. 64.	Opposite Drive End - Endbell Bearing  0 Degrees  5.905  Opposite Drive End - Endbell Bearing Bearing Cap Condition  Drive End Bearing Cap  Na  End Bell Air Seal Fits  Drive End Air Seal	Fit 60 Degrees 5.9051 Fit Condition Opposite Drive End Bearing Cap	_	
	61. 62. 63. 64.	Opposite Drive End - Endbell Bearing  0 Degrees  5.905  Opposite Drive End - Endbell Bearing Bearing Cap Condition  Drive End Bearing Cap  Na  End Bell Air Seal Fits  Drive End Air Seal	Fit 60 Degrees 5.9051 Fit Condition Opposite Drive End Bearing Cap	_	` '
	61. 62. 63. 64.	Opposite Drive End - Endbell Bearing O Degrees 5.905 Opposite Drive End - Endbell Bearing Bearing Cap Condition Drive End Bearing Cap  Na End Bell Air Seal Fits Drive End Air Seal  Na List Machine Work Needed Below	Fit 60 Degrees 5.9051 Fit Condition Opposite Drive End Bearing Cap	_	
	61. 62. 63. 64.	Opposite Drive End - Endbell Bearing  0 Degrees  5.905  Opposite Drive End - Endbell Bearing  Bearing Cap Condition  Drive End Bearing Cap  Na  End Bell Air Seal Fits  Drive End Air Seal  Na  List Machine Work Needed Below  Shaft	Fit 60 Degrees 5.9051 Fit Condition Opposite Drive End Bearing Cap Opposite Drive End Air Seal	_	(P) Pass
R	61. 62. 63. 64. 65.	Opposite Drive End - Endbell Bearing O Degrees 5.905 Opposite Drive End - Endbell Bearing Bearing Cap Condition Drive End Bearing Cap  Na End Bell Air Seal Fits Drive End Air Seal  Na List Machine Work Needed Below Shaft Technician	Fit 60 Degrees 5.9051 Fit Condition Opposite Drive End Bearing Cap Opposite Drive End Air Seal	_	(P) Pass
R	61. 62. 63. 64. 65.	Opposite Drive End - Endbell Bearing O Degrees 5.905 Opposite Drive End - Endbell Bearing Bearing Cap Condition Drive End Bearing Cap  Na End Bell Air Seal Fits Drive End Air Seal  Na List Machine Work Needed Below Shaft Technician	Fit 60 Degrees 5.9051 Fit Condition Opposite Drive End Bearing Cap Opposite Drive End Air Seal	_	(P) Pass

Shaft and bearings

Second cause of failure   Wear	00	D		
Dynamic Balance Report  68. Rotor Weight and Balance Grade Rotor Weight Balance Grade  Rotor Weight Balance Grade  70. Initial Balance Readings Drive End Opposite Drive End  71. Ifinal Balance Readings Drive End Opposite Drive End  72. Tendinician  73. Shaft Runout Post Repair  74. Rotor Runout Post Repair  75. Coupling Fit Closest to Bearing Housing Post Repair  76. Coupling Fit Closest to the end of the Shaft Post Repair  77. Drive End Bearing Shaft Fit Post Repair  78. Opposite Drive End Bearing Shaft Fit Post Repair  79. Drive End Bearing Shaft Fit Post Repair  70. Degrees  80. Degrees  80. Shaft Repair Sign-off  Na  79. Shaft Repair Sign-off	68.			
69. Rotor Weight and Balance Grade Rotor Weight Balance Grade  ***Na**  70. Initial Balance Readings Drive End Opposite Drive End  ***Na**  71. Final Balance Readings Drive End Opposite Drive End  ***Na**  71. Final Balance Readings Drive End Opposite Drive End  ***Na**  72. Tachnician **Na**  ***Mechanical Fits- Rotor - Post Repair **Na**  73. Shaft Runout Post Repair **Drive End Bearing Fit Rotor Body Opposite Drive End Bearing  **Na**  74. Rotor Runout Post Repair **Drive End Bearing Fit Rotor Body Opposite Drive End Bearing  **Na**  75. Coupling Fit Closest to Bearing Housing Post Repair 0 Degrees 90 Degrees 120 Degrees  **Na**  76. Coupling Fit Closest to the end of the Shaft Post Repair 0 Degrees 60 Degrees 120 Degrees  **Na**  77. Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  **Na**  78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  **Na**  78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  **Na**  79. Shaft Air Seal Fits Post Repair Drive End Air Seal Opposite Drive End Air Seal  **Na**  79. Shaft Air Seal Fits Post Repair Drive End Air Seal Opposite Drive End Air Seal	D			
Rotor Weight Balance Grade  Na 70. Initial Balance Readings Drive End Opposite Drive End  Na 71. Final Balance Readings Drive End Opposite Drive End  Na 72. Technician Na Mechanical Fits- Rotor - Post Repair 73. Shaft Runout Post Repair Drive End Bearing Fit Rotor Body Opposite Drive End Bearing  Na 74. Rotor Runout Post Repair Drive End Bearing Fit Rotor Body Opposite Drive End Bearing  Na 75. Coupling Fit Closest to Bearing Housing Post Repair 0 Degrees 90 Degrees 120 Degrees  Na 76. Coupling Fit Closest to the end of the Shaft Post Repair 0 Degrees 60 Degrees 120 Degrees  Na 77. Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na 78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na 78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na 78. Opposite Drive End Bearing Shaft Fit Post Repair O Degrees 60 Degrees 120 Degrees  Na 79. Shaft Air Seal Fits Post Repair Drive End Air Seal Opposite Drive End Air Seal	-			
Na 70. Initial Balance Readings Drive End Opposite Drive End  Na 71. Final Balance Readings Drive End Opposite Drive End  Na 72. Ferbidian Na	69.	-		
70. Initial Balance Readings Drive End Opposite Drive End  ***Na**  71. Final Balance Readings Drive End Opposite Drive End  ***Na**  72. Technician ***Na**  ***Mechanical Fits- Rotor - Post Repair Na**  73. Shaft Runout Post Repair Drive End Bearing Fit Rotor Body Opposite Drive End Bearing  ***Na**  74. Rotor Runout Post Repair Drive End Bearing Fit Rotor Body Opposite Drive End Bearing  ***Na**  75. Coupling Fit Closest to Bearing Housing Post Repair 0 Degrees 90 Degrees 120 Degrees  ***Na**  76. Coupling Fit Closest to the end of the Shaft Post Repair 0 Degrees 60 Degrees 120 Degrees  ***Na**  77. Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  ***Na**  78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  ***Na**  78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  ***Na**  78. Na**  79. Shaft Air Seal Fits Post Repair Drive End Air Seal Opposite Drive End Air Seal  ***Na**  Na**  79. Shaft Air Seal Fits Post Repair Drive End Air Seal Opposite Drive End Air Seal		Rotor Weight	Balance Grade	
70. Initial Balance Readings Drive End Opposite Drive End  ***Na**  71. Final Balance Readings Drive End Opposite Drive End  ***Na**  72. Technician ***Na**  ***Mechanical Fits- Rotor - Post Repair Na**  73. Shaft Runout Post Repair Drive End Bearing Fit Rotor Body Opposite Drive End Bearing  ***Na**  74. Rotor Runout Post Repair Drive End Bearing Fit Rotor Body Opposite Drive End Bearing  ***Na**  75. Coupling Fit Closest to Bearing Housing Post Repair 0 Degrees 90 Degrees 120 Degrees  ***Na**  76. Coupling Fit Closest to the end of the Shaft Post Repair 0 Degrees 60 Degrees 120 Degrees  ***Na**  77. Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  ***Na**  78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  ***Na**  78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  ***Na**  78. Na**  79. Shaft Air Seal Fits Post Repair Drive End Air Seal Opposite Drive End Air Seal  ***Na**  Na**  79. Shaft Air Seal Fits Post Repair Drive End Air Seal Opposite Drive End Air Seal		Na		
Drive End Opposite Drive End  Na 71. Final Balance Readings Drive End Opposite Drive End  Na 72. Technician Na  Mechanical Fits-Rotor - Post Repair 73. Shaft Runout Post Repair 74. Rotor Runout Post Repair Drive End Bearing Fit Rotor Body Opposite Drive End Bearing  Na 75. Coupling Fit Closest to Bearing Housing Post Repair 0 Degrees 90 Degrees 120 Degrees  Na 76. Coupling Fit Closest to the end of the Shaft Post Repair 0 Degrees 60 Degrees 120 Degrees  Na 77. Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na 78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na 78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na 78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees				
Tinal Balance Readings Drive End Opposite Drive End  Na  72. Technician Na  Mechanical Fits-Rotor - Post Repair 73. Shaft Runout Post Repair Na  74. Rotor Runout Post Repair Drive End Bearing Fit Rotor Body Opposite Drive End Bearing  Na  75. Coupling Fit Closest to Bearing Housing Post Repair 0 Degrees 90 Degrees 120 Degrees  Na  76. Coupling Fit Closest to the end of the Shaft Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  77. Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  79. Shaft Air Seal Fits Post Repair Drive End Air Seal Opposite Drive End Air Seal	7 0.		Opposite Drive End	
71. Final Balance Readings Drive End Opposite Drive End    Na		DIVO LIIG	Opposito Bitto Elia	
Drive End Opposite Drive End    Na	-	Na		
Technician  Na  72. Technician  Na  Mechanical Fits- Rotor - Post Repair  73. Shaft Runout Post Repair  Prive End Bearing Fit Rotor Body Opposite Drive End Bearing  Na  74. Rotor Runout Post Repair  Drive End Bearing Fit Rotor Body Opposite Drive End Bearing  Na  75. Coupling Fit Closest to Bearing Housing Post Repair  0 Degrees 90 Degrees 120 Degrees  Na  76. Coupling Fit Closest to the end of the Shaft Post Repair  0 Degrees 60 Degrees 120 Degrees  Na  77. Drive End Bearing Shaft Fit Post Repair  0 Degrees 60 Degrees 120 Degrees  Na  78. Opposite Drive End Bearing Shaft Fit Post Repair  0 Degrees 60 Degrees 120 Degrees  Na  79. Shaft Air Seal Fits Post Repair  Drive End Air Seal Opposite Drive End Air Seal  Na  80. Shaft Repair Sign-off  Na  80. Shaft Repair Sign-off	71.	Final Balance Readings		
Mechanical Fits- Rotor - Post Repair  73. Shaft Runout Post Repair  74. Rotor Runout Post Repair  75. Coupling Fit Closest to Bearing Housing Post Repair  76. Coupling Fit Closest to Bearing Housing Post Repair  77. Daysees  78. Opegrees  79. Degrees  79. Opegrees  79. Shaft Air Seal Fits Post Repair  79. Opegrees  79. Shaft Air Seal Fits Post Repair  79. Opposite Drive End Air Seal  79. Opposite Drive End Air Seal  79. Opposite Sprooff  70. Na		Drive End	Opposite Drive End	
Mechanical Fits- Rotor - Post Repair  73. Shaft Runout Post Repair  74. Rotor Runout Post Repair  75. Coupling Fit Closest to Bearing Housing Post Repair  76. Coupling Fit Closest to Bearing Housing Post Repair  77. Daysees  78. Opegrees  79. Degrees  79. Opegrees  79. Shaft Air Seal Fits Post Repair  79. Opegrees  79. Shaft Air Seal Fits Post Repair  79. Opposite Drive End Air Seal  79. Opposite Drive End Air Seal  79. Shaft Air Seal Fits Post Repair  79. Shaft Air Seal Fits Post Repair  79. Shaft Air Seal Opposite Drive End Air Seal				
Mechanical Fits- Rotor - Post Repair 73. Shaft Runout Post Repair Na Na 74. Rotor Runout Post Repair Drive End Bearing Fit Rotor Body Opposite Drive End Bearing Na 75. Coupling Fit Closest to Bearing Housing Post Repair 0 Degrees 90 Degrees 120 Degrees  Na 76. Coupling Fit Closest to the end of the Shaft Post Repair 0 Degrees 60 Degrees 120 Degrees  Na 77. Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na 78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na 78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 0 Degrees 120 Degrees  Na 79. Shaft Air Seal Fits Post Repair Drive End Air Seal Opposite Drive End Air Seal  Na 80. Shaft Repair Sign-off Na				
### Action of the post Repair   Inches    73. Shaft Runout Post Repair   Inches    74. Rotor Runout Post Repair   Opposite Drive End Bearing Fit    75. Coupling Fit Closest to Bearing Housing Post Repair    76. Coupling Fit Closest to Bearing Housing Post Repair    77. Dougrees   60 Degrees   120 Degrees    78. Pory End Bearing Shaft Fit Post Repair    79. Drive End Bearing Shaft Fit Post Repair    70. Dougrees   60 Degrees   120 Degrees    71. Drive End Bearing Shaft Fit Post Repair    72. Drive End Bearing Shaft Fit Post Repair    73. Dougrees   60 Degrees   120 Degrees    74. Na  75. Opposite Drive End Bearing Shaft Fit Post Repair    76. Opposite Drive End Bearing Shaft Fit Post Repair    77. Dougrees   60 Degrees   120 Degrees    78. Opposite Drive End Bearing Shaft Fit Post Repair    79. Opgrees   60 Degrees   120 Degrees    79. Shaft Air Seal Fits Post Repair    79. Shaft Air Seal Fits Post Repair    79. Drive End Air Seal   Opposite Drive End Air Seal    79. Na  80. Shaft Repair Sign-off    70. Na				
73. Shaft Runout Post Repair  Na  74. Rotor Runout Post Repair  Drive End Bearing Fit Rotor Body Opposite Drive End Bearing  Na  75. Coupling Fit Closest to Bearing Housing Post Repair  0 Degrees 90 Degrees 120 Degrees  Na  76. Coupling Fit Closest to the end of the Shaft Post Repair  0 Degrees 60 Degrees 120 Degrees  Na  77. Drive End Bearing Shaft Fit Post Repair  0 Degrees 60 Degrees 120 Degrees  Na  78. Opposite Drive End Bearing Shaft Fit Post Repair  0 Degrees 60 Degrees 120 Degrees  Na  78. Opposite Drive End Bearing Shaft Fit Post Repair  0 Degrees 60 Degrees 120 Degrees  Na  79. Shaft Air Seal Fits Post Repair  Drive End Air Seal Opposite Drive End Air Seal  Na  80. Shaft Repair Sign-off  Na	,			
Na  74. Rotor Runout Post Repair Drive End Bearing Fit Rotor Body Opposite Drive End Bearing  Na  75. Coupling Fit Closest to Bearing Housing Post Repair 0 Degrees 90 Degrees 120 Degrees  Na  76. Coupling Fit Closest to the end of the Shaft Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  77. Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  79. Shaft Air Seal Fits Post Repair Drive End Air Seal Opposite Drive End Air Seal  Na  80. Shaft Repair Sign-off Na		· ·		in the co
74. Rotor Runout Post Repair Drive End Bearing Fit Rotor Body Opposite Drive End Bearing  Na  75. Coupling Fit Closest to Bearing Housing Post Repair 0 Degrees 90 Degrees 120 Degrees  Na  76. Coupling Fit Closest to the end of the Shaft Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  77. Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  79. Shaft Air Seal Fits Post Repair Drive End Air Seal Opposite Drive End Air Seal  Na  80. Shaft Repair Sign-off Na				inches
Drive End Bearing Fit Rotor Body Opposite Drive End Bearing  Na  75. Coupling Fit Closest to Bearing Housing Post Repair 0 Degrees 90 Degrees 120 Degrees  Na  76. Coupling Fit Closest to the end of the Shaft Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  77. Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  79. Shaft Air Seal Fits Post Repair Drive End Air Seal Opposite Drive End Air Seal  Na  80. Shaft Repair Sign-off Na	-			
<ul> <li>Na</li> <li>75. Coupling Fit Closest to Bearing Housing Post Repair  0 Degrees 90 Degrees 120 Degrees</li> <li>Na</li> <li>76. Coupling Fit Closest to the end of the Shaft Post Repair  0 Degrees 60 Degrees 120 Degrees</li> <li>Na</li> <li>77. Drive End Bearing Shaft Fit Post Repair  0 Degrees 60 Degrees 120 Degrees</li> <li>Na</li> <li>78. Opposite Drive End Bearing Shaft Fit Post Repair  0 Degrees 60 Degrees 120 Degrees</li> <li>Na</li> <li>79. Shaft Air Seal Fits Post Repair  Drive End Air Seal Opposite Drive End Air Seal</li> <li>Na</li> <li>80. Shaft Repair Sign-off</li> <li>Na</li> </ul>	74.		Potor Pody	Opposite Drive End Rearing
75. Coupling Fit Closest to Bearing Housing Post Repair 0 Degrees 90 Degrees 120 Degrees  Na  76. Coupling Fit Closest to the end of the Shaft Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  77. Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  79. Shaft Air Seal Fits Post Repair Drive End Air Seal Opposite Drive End Air Seal  Na  80. Shaft Repair Sign-off Na		Drive Life Bearing Fit	Notor Body	Opposite Drive Life Bearing
<ul> <li>Na</li> <li>76. Coupling Fit Closest to the end of the Shaft Post Repair 0 Degrees 60 Degrees 120 Degrees</li> <li>Na</li> <li>77. Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees</li> <li>Na</li> <li>78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees</li> <li>Na</li> <li>78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees</li> <li>Na</li> <li>79. Shaft Air Seal Fits Post Repair Drive End Air Seal Opposite Drive End Air Seal</li> <li>Na</li> <li>80. Shaft Repair Sign-off</li> <li>Na</li> </ul>	-	Na		
Na  76. Coupling Fit Closest to the end of the Shaft Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  77. Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  79. Shaft Air Seal Fits Post Repair Drive End Air Seal Opposite Drive End Air Seal  Na  80. Shaft Repair Sign-off Na	75.	Coupling Fit Closest to Bearing Housi	ng Post Repair	
76. Coupling Fit Closest to the end of the Shaft Post Repair  0 Degrees 60 Degrees 120 Degrees  Na  77. Drive End Bearing Shaft Fit Post Repair  0 Degrees 60 Degrees 120 Degrees  Na  78. Opposite Drive End Bearing Shaft Fit Post Repair  0 Degrees 60 Degrees 120 Degrees  Na  79. Shaft Air Seal Fits Post Repair  Drive End Air Seal Opposite Drive End Air Seal  Na  80. Shaft Repair Sign-off  Na		0 Degrees	90 Degrees	120 Degrees
76. Coupling Fit Closest to the end of the Shaft Post Repair  0 Degrees 60 Degrees 120 Degrees  Na  77. Drive End Bearing Shaft Fit Post Repair  0 Degrees 60 Degrees 120 Degrees  Na  78. Opposite Drive End Bearing Shaft Fit Post Repair  0 Degrees 60 Degrees 120 Degrees  Na  79. Shaft Air Seal Fits Post Repair  Drive End Air Seal Opposite Drive End Air Seal  Na  80. Shaft Repair Sign-off  Na				
0 Degrees 60 Degrees 120 Degrees  Na  77. Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  79. Shaft Air Seal Fits Post Repair Drive End Air Seal Opposite Drive End Air Seal  Na  80. Shaft Repair Sign-off Na				
<ul> <li>Na</li> <li>77. Drive End Bearing Shaft Fit Post Repair  0 Degrees 60 Degrees 120 Degrees</li> <li>Na</li> <li>78. Opposite Drive End Bearing Shaft Fit Post Repair  0 Degrees 60 Degrees 120 Degrees</li> <li>Na</li> <li>79. Shaft Air Seal Fits Post Repair  Drive End Air Seal Opposite Drive End Air Seal</li> <li>Na</li> <li>80. Shaft Repair Sign-off  Na</li> </ul>	76.			400 B
77. Drive End Bearing Shaft Fit Post Repair  0 Degrees 60 Degrees 120 Degrees  Na  78. Opposite Drive End Bearing Shaft Fit Post Repair  0 Degrees 60 Degrees 120 Degrees  Na  79. Shaft Air Seal Fits Post Repair  Drive End Air Seal Opposite Drive End Air Seal  Na  80. Shaft Repair Sign-off  Na		0 Degrees	60 Degrees	120 Degrees
0 Degrees 60 Degrees 120 Degrees  Na  78. Opposite Drive End Bearing Shaft Fit Post Repair 0 Degrees 60 Degrees 120 Degrees  Na  79. Shaft Air Seal Fits Post Repair Drive End Air Seal Opposite Drive End Air Seal  Na  80. Shaft Repair Sign-off Na	-	Na		
O Degrees  Na  Na  78. Opposite Drive End Bearing Shaft Fit Post Repair O Degrees  60 Degrees  120 Degrees  120 Degrees  120 Degrees  Na  79. Shaft Air Seal Fits Post Repair Drive End Air Seal  Opposite Drive End Air Seal  Na  80. Shaft Repair Sign-off Na	77.	Drive End Bearing Shaft Fit Post Repa	air	
<ul> <li>Na</li> <li>78. Opposite Drive End Bearing Shaft Fit Post Repair  0 Degrees 60 Degrees 120 Degrees</li> <li>Na</li> <li>79. Shaft Air Seal Fits Post Repair  Drive End Air Seal Opposite Drive End Air Seal</li> <li>Na</li> <li>80. Shaft Repair Sign-off  Na</li> </ul>				120 Degrees
78. Opposite Drive End Bearing Shaft Fit Post Repair  0 Degrees 60 Degrees 120 Degrees  Na  79. Shaft Air Seal Fits Post Repair  Drive End Air Seal Opposite Drive End Air Seal  Na  80. Shaft Repair Sign-off  Na			· ·	<u> </u>
O Degrees 60 Degrees 120 Degrees  Na  79. Shaft Air Seal Fits Post Repair Drive End Air Seal Opposite Drive End Air Seal  Na  80. Shaft Repair Sign-off Na	-			
<ul> <li>Na</li> <li>79. Shaft Air Seal Fits Post Repair</li> <li>Drive End Air Seal Opposite Drive End Air Seal</li> <li>Na</li> <li>80. Shaft Repair Sign-off</li> <li>Na</li> </ul>	78.			
79. Shaft Air Seal Fits Post Repair Drive End Air Seal Opposite Drive End Air Seal  Na  80. Shaft Repair Sign-off Na		0 Degrees	60 Degrees	120 Degrees
79. Shaft Air Seal Fits Post Repair  Drive End Air Seal Opposite Drive End Air Seal  Na  80. Shaft Repair Sign-off  Na		Na		
Drive End Air Seal  Opposite Drive End Air Seal  Na  80. Shaft Repair Sign-off  Na				
Na  80. Shaft Repair Sign-off  Na	10.	·	Opposite Drive End Air Seal	
80. Shaft Repair Sign-off  Na		DIVO ENG AII OCAI	Opposite Diffe Life All Ocal	
■ Na	-	Na		
	80.	Shaft Repair Sign-off		
Assembly	-	Na		
	Asser	nbly		

Mnr

82. Photograph All Major Components prior to assembly











83. Final Insulation Resistance Test

Pass

84. Assembled Shaft Endplay

Megohms

inches

-	Na			
85.	Assembled Shaft Runout		inches	
-	Na			
86.	Test Run Voltage			
	Volts	Volts	Volts	
	Na			
	Test Run Amperage			
07.	Amps	Amps	Amps	
	Απρο	Απρο	Allips	
-	Na			
88.	Drive End Vibration Readings - Inches Per Second			
	Horizontal	Vertical	Axial	
_	Ma			
90	Na Opposite Drive End Vibration Booding	un Inghan Day Conond		
89.	Opposite Drive End Vibration Reading Horizontal	Vertical	Axial	
	Horizoniai	vertical	Axiai	
-	Na			
90.	Ambient Temperature - Fahrenheit			
-	Na			
91.	Drive End Bearing Temps - Fahrenhei	it		
	5 Minutes	10 Minutes	15 Minutes	
	Na			
	Opposite Drive End Bearing Temps - Fahrenheit			
J	5 Minutes	10 Minutes	15 Minutes	
-	Na			
93.	Document Final Condition with Pictures after paint			





 $\mathsf{Cw}$ 

94. Final Pics and QC Review

Co sign:DLW



#### STANDARD TERMS AND CONDITIONS FOR PURCHASE OF GOOD AND/OR SERVICES

- 1. APPLICABILITY. The sale of any and all goods and/or services by Mock, Inc. d/b/a Hi-Speed Industrial Service ("Hi-Speed") shall be specifically conditioned upon and subject to the following terms and conditions which are incorporated by reference into any contracts and purchase orders with Hi-Speed, and which shall form and become a part of any agreement related thereto. Buyer's acceptance of any offer or quotation made by Hi-Speed for sale of any goods or services is expressly made subject to the terms and conditions set forth herein and to be so effective, Buyer need not sign or approve these Terms and Conditions to be bound hereunder provided a copy of same is provided to Buyer through any means. None of the terms and conditions contained herein may be added to, expanded, changed, modified, superseded or otherwise altered except as revised in writing and duly executed by Hi-Speed, and all orders received by Hi-Speed shall be governed only by the terms and conditions contained herein, notwithstanding any terms, conditions or provisions of any purchase order, release order, authorization or any other form issued by the Buyer. Hi-Speed hereby objects to any additional, modified, changed, deleted, altered or other terms and conditions not contained herein and notifies Buyer that any such terms or provisions are expressly rejected by Hi-Speed.
- 2. PRICE. All quoted prices shall remain firm and binding for a period of thirty (30) days from the date of quotation or for the period specifically stated in the quotation. The price for any and all goods and/or services ordered or approved by Buyer after thirty (30) days from the date of any quotation are subject to any increase in price that may occur after the expiration of thirty (30) days from the issuance of the quotation and the date the Buyer releases any shipment.
- 3. SCOPE OF GOODS AND/OR SERVICES. The goods and/or services provided by Hi-Speed pursuant to any quotation shall be limited exclusively to those goods and/or services expressly identified therein. Hi-Speed does not assume any responsibility and/or liability for the failure to provide any other goods and/or services not identified in any quotation. Modifications, additions or deletions to or from the scope referenced in any quotation shall only bee effective if evidenced in writing and signed by Hi-Speed. The sale of any of all goods and/or services affected by such modification, addition or deletion shall be subject to these same Standard Terms and Conditions whether or not referenced therein.
- 4. <u>BILLING AND PAYMENT TERMS.</u> Hi-Speed shall invoice Buyer for all goods and/or services as same are rendered at the address listed on the quotation. Payments for all goods and/or services shall be due thirty (30) days from the date of the current invoice or as otherwise set forth in the quotation. Late payments are subject to a late fee of 5% of the total invoice amount. Recurring late payments may lead to a deposit requirement on future services or sale of goods. Buyer shall be liable to Hi-Speed for any and all fees and expenses incurred by Hi-Speed to collect any invoices or to enforce these Standard Terms and Conditions, including but not limited to, attorney's fees.
- 5. <u>DELIVERY OF GOODS AND/OR SERVICES.</u> Unless otherwise identified in the quotation, all shipments are F.O.B. Hi-Speed's warehouse and the title to and all risk of loss with respect to any goods shipped shall pass to Buyer when such goods are delivered to the carrier at Hi-Speed's warehouse. Hi-Speed will use its best efforts to affect delivery by the date or dates specified in the quotation. However, Hi-Speed shall not be liable for delay in or failure to make shipment, or to perform services, by any identified date for any reason whatsoever, including but not limited to, causes beyond its reasonable control, such as strikes, fires, floods, epidemics, quarantines, restrictions, severe weather, embargos, acts of God, or public enemy, war, riot, delays in transportation or the inability to obtain necessary labor, materials or manufacturing facilities.
- **DELIVERY SITE AND TIME FOR PERFORMANCE.** Hi-Speed and Buver agree that time is of the essence for the purchase order and that Buyer shall fully cooperate with Hi-Speed in order to allow Hi-Speed full access to prosecute its work diligently and in an orderly manner. Buyer shall assist Hi-Speed in every way possible to avoid delaying, disrupting or interfering with the progress of Hi-Speed's work at the project site. In the event Hi-Speed's work is delayed, hindered, suspended, disrupted, re-sequenced or interfered with or rendered less efficient or more costly or adversely affected in any way as a result of acts or omissions of Buyer or other contractors or employees of Buyer or by any other reason beyond Hi-Speed's control and without the fault of Hi-Speed, then, in such event, Buyer shall be liable to Hi-Speed for any damages, additional costs, expenses, labor, materials, man hours, acceleration costs, overtime, additional jobsite overhead, extended home office overhead, and any and all other direct and indirect expenses of whatsoever nature or kind, caused in whole or in part, as a result of any of the above-referenced occurrences. Hi-Speed's project records will be the basis for computing the additional costs and damages of Hi-Speed's labor, materials, expenses and overhead related to such changes. BUYER WARRANTS THAT THE SITE FOR DELIVERY OR INSTALLATION OF ANY GOODS AND/OR FOR THE PERFORMANCE OF ANY SERVICES SHALL BE READY AND ADEQUATE FOR HI-SPEED'S DELIVERY OF GOODS AND/OR PERFORMANCE OF SERVICES AND THAT HI-SPEED SHALL HAVE FULL ACCESS THERETO, FREE OF ALL OBSTRUCTIONS. BUYER SHALL ASSUME ALL EXTRA COSTS ASSOCIATED WITH HI-SPEED'S INABILITY TO INSTALL ANY GOODS OR PERFORM ANY SERVICES AS A RESULT OF BUYER'S FAILURE TO COMPLY WITH THIS PROVISION. HI-SPEED MAY NOT INSPECT THE SITE PRIOR TO DELIVERY AND/OR INSTALLATION OF GOODS AND/OR PERFORMANCE OF SERVICES AND MAKES NO WARRANTY AS TO THE SUFFICIENCY OF THE SITE FOR THE DELIVERY AND/OR INSTALLATION OF GOODS AND/OR THE PERFORMANCE OF SERVICES AT SUCH SITE.
- 7. INSPECTION/ACCEPTANCE. All goods and services ordered pursuant to any quotation shall be subject to inspection by Buyer after delivery or performance to determine conformity with the quotation and/or purchase order and Hi-Speed's advertised or published specifications. Buyer shall have a period of thirty (30) days from shipment of goods at the delivery destination specified in the quotation within which to inspect the goods for conformity with the quotation, order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. Buyer shall have a period of thirty (30) days following completion of any services within which to inspect the services for conformity with the quotation, purchase order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. If the goods delivered or services performed do not so conform, upon delivery of notice to Hi-Speed of any discrepancy, nonconformance or rejection, Hi-Speed shall have sixty (60) days to cure the alleged discrepancy and/or nonconformance. If Hi-Speed fails to cure in this time period, Buyer shall have the right to reject such goods or services. After the cure period, goods that have been delivered and rejected, in whole or in part, shall be returned to Hi-Speed. Buyer shall notify Hi-Speed and arrange for the return of the goods as required. Should such non-conforming services be rejected Hi-Speed shall, at its sole cost, re-perform the non-conforming services. Inspection or failure to inspect on any occasion shall not affect Buyer's rights under the warranty provisions herein.
- 8. <u>WARRANTIES.</u> Hi-Speed warrants that all goods shall conform in all material aspects to the goods identified in the quotation to Buyer and/or purchase order, and Hi-Speed makes to Buyer the manufacturer's express warranty for any goods sold to Buyer, which is offered by the manufacturer at the time of acceptance of any quotation by Buyer. This warranty is conditioned upon the installation, operation, and maintenance of the goods in accordance with the manufacturer's recommendations and/or standard industry practice and the goods at all times being operated or used under normal operating conditions for which they were designed. Hi-Speed, at its sole option, will repair or

replace any defective or non-conforming goods in accordance with the applicable manufacturer's warranty. Warranty for any defective or incorrect parts is limited to the repair or replacement of those parts. Hi-Speed warrants that all services will conform in all material respects to the description of services identified in the quotation and will be performed in a good and workmanlike manner in accordance with industry practices and standards. Should the services be reasonably rejected or not conform with the foregoing warranties, Hi-Speed shall, at its sole cost, re-perform the defective or nonconforming services. Notwithstanding the foregoing, these warranties do not extend to goods or services to the extent that such goods have been subject to misuse, neglect or abuse not caused by Hi-Speed or have been used in violation of the approved written instructions furnished to Buyer. THE FOREGOING REPRESENTS THE SOLE AND EXCLUSIVE WARRANTY GIVEN BY HI-SPEED WITH RESPECT TO ALL GOODS SOLD AND IS IN LIEU OF ALL OTHER WARRANTIES EITHER EXPRESS OR IMPLIED. HI-SPEED EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICLAR USE OR PURPOSE. BUYER WAIVES ANY CLAIM THAT THESE EXCLUSIONS OR LIMITATIONS DEPRIVE IT OF AN ADEQUATE REMEDY AT EQUITY OR LAW OR CAUSE THIS AGREEMENT TO FAIL IN ITS ESSENTIAL PURPOSE. BUYER SHALL BE ENTITLED TO NO OTHER REMEDY OTHER THAN AS SET FORTH HEREIN, REGARDLESS OF THE CLAIM OR CAUSE OF ACTION, WHETHER BASED IN CONTRACT, TORT, NEGLIGENCE, GOODS LIABILITY, STRICT LIABILITY OR OTHERWISE.

- 9. LIMITATION OF DAMAGES. HI-SPEED SHALL HAVE NO LIABILITY TO BUYER WITH RESPECT TO THE SALE OR DELIVERY OF ANY GOODS OR THE REPAIR THEREOF OR WITH RESPECT TO THE SALE OR PERFORMANCE OF ANY SERVICES, FOR LOST PROFITS, SPECIAL, CONSEQUENTIAL, EXEMPLARY, PUNITIVE OR INCIDENTAL DAMAGES OF ANY KIND OR NATURE WHETHER ARISING IN CONTRACT, TORT, GOODS LIABILITY OR OTHERWISE, EVEN IF HI-SPEED WAS ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGES. HI-SPEED SHALL NOT BE LIABLE FOR ANY DAMAGES OR DELAYS CAUSED BY ANY FAILURE TO MAKE ANY DELIVERY OF GOODS BY ANY EXPECTED TIME OR DATE OR THE FAILURE TO PROVIDE OR COMPLETE ANY SERVICES BY ANY EXPECTED DATE OR TIME. IN NO EVENT SHALL HI-SPEED BE LIABLE TO BUYER FOR ANY DAMAGES WHATSOEVER IN EXCESS OF THE TOTAL PRICE PAID FOR ALL GOODS AND/OR SERVICES HEREUNDER OR REFERENCED IN ANY QUOTATION OR THE PURCHASE ORDER.
- 10. <u>SEVERABILITY.</u> The partial or complete invalidity of any provision of these Standard Terms and Conditions shall not affect the enforceability of the remainder of these Standard Terms and Conditions. If any provision is found to be invalid or unenforceable, that portion shall be modified to make it enforceable or shall be stricken and the remainder of these Standard Terms and Conditions shall enforced.
- 11. **GOVERNING LAW AND JURISDICTION.** Any controversy arising out of any quotation, the purchase order, the goods sold or delivered, repair or replacement thereof, or any services provided pursuant to any quotation or any purchase order, or these Standard Terms and Conditions shall be governed by the laws of the state of Tennessee without regard to any choice of law provisions and any cause of action related in any manner thereto shall be brought only in the state or federal courts of Shelby County, Tennessee.
- 12. <u>ABANDONED EQUIPMENT.</u> Hi-Speed requires that Buyer promptly pick up or provide shipment instructions for Buyer equipment or other Buyer property in Hi-Speed's possession. If equipment or other Buyer property is left with Hi-Speed and not picked up within six (6) months after Hi-Speed's final action related to the applicable property (e.g. evaluation, teardown, estimate, completion of services), Hi-Speed will consider such property abandoned and may dispose of it in accordance with applicable law. Buyer agrees to hold Hi-Speed harmless for any damage or claim for such abandoned property and acknowledges that Hi-Speed may discard or recycle it at Hi-Speed's sole and absolute discretion. Specifically, Hi-Speed may sell Buyer's abandoned property at a private or public sale and retain the proceeds to offset Hi-Speed's storage, inspection and servicing costs. For the avoidance of doubt, Hi-Speed reserves its statutory and other lawful liens for unpaid charges related to abandoned property.
- 13. FORCE MAJEURE. Neither party shall be responsible for any delay or failure in performance of any party of the quotation, purchase order or these Standard Terms and Conditions to the extent that such delays or failures are caused by fire, flood, earth quake, explosion, war, embargo, government requirement, civil or military authority, acts of God, or any other circumstances beyond its reasonable control and not involving any fault or negligence on the party affected ("Condition"). If any such Condition occurs, the party delayed or unable to perform shall promptly give written notice to the other party and, if such Condition remains at the end of thirty (30) days, the party affected by the other party's delay and inability to perform may elect to (i) terminate such order or part thereof, or (ii) suspend the order for the duration of the Condition, if the Buyer is the suspending party, buy elsewhere comparable material to be sold under the order and apply to any commitment the purchase price of such purchase, and resume performance of the order once the Condition ceases, with an option in the affected party to extend the period of this order up to the length of the time the Condition endures.
- 14. <u>NONWAIVER.</u> No course of dealing or failure of either party to strictly enforce any term, right, or condition of these Standard Terms and Conditions will be construed as a waiver of such term, right or condition. Any waiver by Hi-Speed will only be in writing and will waive no succeeding breach of a term, right or condition.
- 15. **ASSIGNMENT.** The rights and obligations of the parties shall neither be assigned nor delegated without the prior written consent of the other party. However, any party may assign or delegate its respective rights and obligations, in whole or in part, (i) to any subsidiary, (ii) pursuant to other financing, merger or reorganization or (iii) pursuant to any sale or transfer of substantially all of the assets of the assigning party. These Standard Terms and Conditions shall bind the heirs, successors and assigns of the parties hereto.
- 16. NO INDIVIDUAL LIABILITY. Notwithstanding any other agreement to the contrary, the Buyer agrees that in no event will the Buyer hold and HI-Speed owner, director, officer or employee personally liable for unintentional tortious conduct or conduct that constitutes the breach of any contract between HI-Speed and the Buyer, even if the HI-Speed owner, director, officer or employee is or could be construed to be a party to such contract.