

## 

# **Motor Shop Repairs**

## Job Number 97571

Prepared for Greenbrier Central (01238105)

7755 Highway 34 W Marmaduke AR 72443

## **Table of Contents**



Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

Printed on 11/16/2020 Powered by INSPECTALL Table of Contents





### **AC Recondition Repair Report**

**Greenbrier Central (01238105)** 7755 Highway 34 W

Marmaduke, AR 72443

FolderID: 97571 FormID: 9375451

Gene	ral		
1.	Job Number	97571	
2.	Report Date		
3.	Customer		
Name	Plate Information		0
4.	Manufacturer		P!
5.	Model		
6.	Serial Number		
7.	Horsepower		
8.	KW		
9.	Volts		
10.	Amps		
11.	RPM		
12.	Frame		
13.	Enclosure		
14.	Cycles		
15.	Phase		
16.	Service Factor		
	Motor Mount Position		
	Inspection		0
18.	Number of Leads	3	
19.	Lead Length	8 Inches	P20
20.	Lead Size	4	
21.	Lead Condition	(P) Pass	
22.	Lead Markings	none	
23.	Lug Size, Condition, and Type  None		
24.	Winding RTD's		
25.	Winding Rtd's Condition		
26.	Shaft Run Out	0.001	
27.	Does Shaft Turn Freely	yes	
28.	Does Shaft Have Visible Damage	no	
29.	Bearing Rtd's		
30.	Bearing Rtd's Condition		
	Contamination		

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

• 00	France Occasións	(D) D	D400
	Frame Condition	(P) Pass	P106
	Fan Condition		
34.	Broken or missing components		
	No		
	l Electric Test		
	Resistance to Ground		
36.	Winding Resistance 1-2		
37.	<u> </u>		
38.	3		
39.			
40.	Hi-Pot		
<b>4</b> 1.	Surge Test	(F) Fail	
42.	Stator Condition	rewind	
43.	Failure Location	in slot	
Initial	Rotor Inspection		
44.	Rotor Type	cast aluminum	
45.	Air Gap <10% Variation		
46.	Number of Rotor Bars	30	
47.	Number of Broken Rotor Bars	0	
<b>4</b> 8.	Growler Test	(P) Pass	
<b>4</b> 9.	Rotor Condition	(P) Pass	
Mech	anical Inspection		О
50.	Bearing Manufacture	ntn	
51.	Bearing DE Size	6211c3	P15
52.	Bearing DE Type	ball	
53.	DE Bearing Qty.	1	
54.	Bearing ODE Size	6309lb	P43
55.	Bearing ODE Type	ball	
56.	ODE Bearing Qty.	1	
57.	Insulated Bearing	no	
58.	Lubrication Type	grease	
<b>5</b> 9.	Grease Condition	(P) Pass	
60.	Bearing Retainers		
61.	Shaft Grounding Device		
<b>6</b> 2.		(Y) Yes	
-	Missing	.,	
63.	DE Seal Type/Size	50x72x8	
64.	ODE Seal		
65.	ODE Seal Type/Size		
	Cause of Failure		
	Component Failure	windings	
67.		90	
٠	shorted coil		
	Comments		

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

	69.	Service Technician	Trevor Hall	
M	lachi	ne Fit Inspection Report		o
		Shaft Run Out	(P) Pass	
	71.	Initial Shaft Run Out	0.001 "	
	72.	Final Shaft Run Out		
	73.	DE Bearing Shaft Fit	(P) Pass	
	74.	DE Initial Shaft Bearing Fit Size 1	2.1656 "	
	75.	DE Initial Shaft Bearing Fit Size 2	2.1656 "	
	76.	DE Initial Shaft Bearing Fit Size 3	2.1656 "	
	77.	DE Finial Shaft Bearing Fit Size 1		
	78.	DE Finial Shaft Bearing Fit Size 2		
	79.	DE Finial Shaft Bearing Fit Size 3		
	80.	ODE Bearing Shaft Fit	(P) Pass	
	81.	ODE Initial Shaft Bearing Fit Size 1	1.772 "	
	82.	ODE Initial Shaft Bearing Fit Size 2	1.772 "	
	83.	ODE Initial Shaft Bearing Fit Size 3	1.772 "	
	84.	ODE Finial Shaft Bearing Fit Size 1		
	85.	ODE Finial Shaft Bearing Fit Size 2		
	86.	ODE Finial Shaft Bearing Fit Size 3		
	87.	DE Air Seal Shaft Fit		
	88.	DE Initial Air Seal Shaft Size		
	89.	DE Final Air Seal Shaft Size		
	90.	ODE Air Seal Shaft Fit		
	91.	ODE Initial Air Seal Shaft Size		
	92.	ODE Final Air Seal Shaft Size		
	93.	DE Endbell Fit	(P) Pass	P129
	94.	DE Initial Endbell Fit Size 1	3.9377 "	
	95.	DE Initial Endbell Fit Size 2	3.9371 "	
	96.	DE Initial Endbell Fit Size 3	3.9374 "	
	07	DEE: LE H HERO: A		

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

97. DE Final Endbell Fit Size 1
98. DE Finial Endbell Fit Size 2
99. DE Final Endbell Fit Size 3
100. DE Endbell Fit Insulated
101. DE Endbell Air Seal Fit

102. Initial Endbell Air Seal Fit Size103. Finial Endbell Air Seal Fit Size

105. ODE Initial Endbell Fit Size 1

106. ODE Initial Endbell Fit Size 2107. ODE Initial Endbell Fit Size 3

108. ODE Final Endbell Fit Size 1109. ODE Final Endbell Fit Size 2110. ODE Final Endbell Fit Size 3

104. ODE Endbell Fit

(P) Pass

3.9378 "

3.9374 "

3.9377 "

P145

111. ODE Endbell Air Issulated 112. ODE Findbell Air Issulated 113. ODE Initial Endbell Seal Fit Size 114. ODE Finial Endbell Seal Fit Size 115. Foot Endbell Seal Fit Size 116. Foot Condition ■ 117. Flange Condition ■ 117. Flange Condition ■ 118. Service Technician ■ 119. Balance Type 120. Balance Type 120. Balance Operating Speed 121. Start Left End 122. Start Right End 122. Start Right End 123. Balancing Specification 124. Fliniah Left End 125. Finiah Right End 126. Service Technician ■ 127. Meggar Testing Reading 128. Surge Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 1-3 132. Winding Resistance 1-3 133. Test Run Voltage Phase A 135. Test Run Voltage Phase A 136. Test Run Amps B 137. Test Run Amps A 138. Test Run Amps C 139. De Horizontal Vibration Reading 140. De Vertical Vibration Reading 141. ODE Avial Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Avial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 149. Temp at 20 minutes 149. Temp at 20 minutes 151. Temp at 30 minutes 151. Temp at 30 minutes				
113. ODE Initial Endbell Seal Fit Size 114. ODE Finial Endbell Seal Fit Size 115. Foot Elanness 116. Foot Condition 117. Flange Condition 118. Service Technician 118. Service Technician 119. Balance Type 120. Balance Operating Speed 121. Start Left End 122. Start Right End 123. Balancing Specification 124. Finish Left End 125. Finish Right End 126. Service Technician 127. Megagar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 2-3 131. Winding Resistance 2-3 132. Winding Resistance 1-2 131. Winding Resistance 2-3 133. Test Run Voltage Phase A 134. Test Run Amps A 135. Test Run Voltage Phase C 139. De Horizontal Vibration Reading 140. De Vertical Vibration Reading 141. De E Avist Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Vertical Vibration Reading 145. Ambient Temp at 15 minutes 147. Temp at 15 minutes 148. Temp at 15 minutes 149. Temp at 25 minutes				
114. ODE Finial Endbell Seal Fit Size  115. Foot Condition  117. Flange Condition  117. Flange Condition  118. Service Technician  119. Balance Type  119. Balance Operating Speed  121. Start Left End  122. Start Right End  123. Balancing Specification  124. Finish Left End  125. Finish Right End  126. Service Technician  Assembly and Final Test  127. Megaar Testing Reading  128. Surgar Testing Reading  129. Surgar Testing Reading  129. Surgar Testing Reading  120. Winding Resistance 1-2  131. Winding Resistance 1-2  131. Winding Resistance 1-3  132. Winding Resistance 1-3  133. Test Run Voltage Phase A  134. Test Run Amps A  135. Test Run Voltage Phase B  136. Test Run Amps B  137. Test Run Voltage Phase C  139. De Horizontal Vibration Reading  140. DE Vertical Vibration Reading  141. DE Askal Vibration Reading  142. ODE Horizontal Vibration Reading  143. ODE Vertical Vibration Reading  144. ODE Validal Vibration Reading  145. Temp at 15 minutes  146. Temp at 5 minutes				
116. Foot Condition 117. Flagg Condition 118. Service Technician 119. Balance Type 120. Balance Operating Speed 121. Start Left End 122. Start Right End 123. Balancing Specification 124. Finish Left End 125. Finish Right End 126. Service Technician 127. Hingh Left End 128. Surge Technician 129. Winding Resistance 1:3 120. Winding Resistance 1:3 121. Start Left End 122. Start Right End 123. Service Technician 124. Finish Left End 125. Finish Right End 126. Service Technician 127. Meggar Testing Reading 128. Surge Technician 129. Hi-Pot 130. Winding Resistance 1:3 131. Test Run Voltage Phase A 134. Test Run Amps A 135. Test Run Voltage Phase A 136. Test Run Amps B 137. Test Run Voltage Phase B 138. Test Run Voltage Phase C 139. De Horizontal Vibration Reading 140. De Vertical Vibration Reading 141. De Varical Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Vertical Vibration Reading 145. Temp at 5 minutes 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 15 minutes 149. Temp at 20 minutes				
116. Foot Condition  117. Flange Condition  118. Service Technician  Trevor Hall  Service Technician  Service Technician  Service Technician  Service Technician  Service Technician  Service Technician  Assembly and Final Test  Service Technician  Service Technician  Assembly and Final Test  Service Technician  Service Technician  Service Technician  Assembly and Final Test  Service Technician  Sesure Testing Reading  Service Technician  Sesure Testing Service				
117. Flange Condition (P) Pass P188 118. Service Technician Trevor Hall 119. Balance Type 120. Balance Operating Speed 121. Start Left End 122. Start Right End 123. Balancing Specification 124. Finish Left End 125. Finish Right End 126. Service Technician 127. Finish Right End 128. Surpe Test 129. Meggar Testing Reading 129. Surge Test 121. Winding Resistance 1-2 130. Winding Resistance 1-2 131. Winding Resistance 1-2 131. Winding Resistance 1-3 133. Test Run Voltage Phase A 135. Test Run Voltage Phase B 136. Test Run Amps B 137. Test Run Amps B 138. Test Run Amps B 139. Test Run Amps B 130. De Horizontal Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 15 minutes 149. Temp at 20 minutes 140. Temp at 5 minutes 141. Temp at 15 minutes 142. Temp at 25 minutes				
Balancing Report  119. Balance Type 120. Balance Operating Speed 121. Start Left End 122. Start Right End 122. Start Right End 123. Balancing Specification 124. Finish Left End 125. Finish Right End 126. Service Technician  Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 1-2 131. Winding Resistance 1-3 132. Winding Resistance 1-3 133. Test Run Voltage Phase A 135. Test Run Amps A 136. Test Run Amps A 137. Test Run Voltage Phase B 138. Test Run Voltage Phase C 139. DE Horizonial Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizonial Vibration Reading 143. ODE Verical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 10 minutes 149. Temp at 20 minutes				
Balancing Report  119. Balance Type  120. Balance Operating Speed  121. Start Left End  122. Start Right End  123. Balancing Specification  124. Finish Left End  125. Finish Right End  126. Service Technician  Assembly and Final Test  127. Meggar Testing Reading  128. Surge Test  129. Hi-Pot  130. Winding Resistance 1-2  131. Winding Resistance 2-3  132. Winding Resistance 2-3  133. Test Run Voltage Phase A  134. Test Run Amps A  135. Test Run Voltage Phase B  137. Test Run Voltage Phase C  138. Test Run Amps B  137. Test Run Voltage Phase C  138. Test Run Amps C  139. De Horizontal Vibration Reading  140. DE Vertical Vibration Reading  141. De Axial Vibration Reading  142. ODE Horizontal Vibration Reading  143. ODE Vertical Vibration Reading  144. ODE Axial Vibration Reading  145. Ambient Temp at start of Test Run  146. Temp at 5 minutes  147. Temp at 10 minutes  148. Temp at 15 minutes				
119. Balance Type 120. Balance Operating Speed 121. Start Left End 122. Start Right End 123. Balancing Specification 124. Finish Left End 125. Finish Right End 126. Service Technician  Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3 132. Winding Resistance 2-3 132. Winding Resistance 2-3 133. Test Run Voltage Phase A 134. Test Run Amps A 135. Test Run Voltage Phase B 136. Test Run Voltage Phase C 137. Test Run Voltage Phase C 138. Test Run Voltage Phase C 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 15 minutes 148. Temp at 15 minutes 149. Temp at 20 minutes 150. Temp at 25 minutes	118.	Service Technician Trevor Hall		
120. Balance Operating Speed 121. Start Left End 122. Start Right End 123. Balancing Specification 124. Finish Left End 125. Finish Right End 126. Service Technician  Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3 132. Winding Resistance 2-3 133. Test Run Voltage Phase A 134. Test Run Amps A 135. Test Run Amps B 136. Test Run Amps B 137. Test Run Voltage Phase C 138. Test Run Voltage Phase C 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at 15 minutes 147. Temp at 20 minutes 148. Temp at 15 minutes 149. Temp at 20 minutes 150. Temp at 25 minutes	Balan	cing Report		
121. Start Left End 122. Start Right End 123. Balancing Specification 124. Finish Left End 125. Finish Right End 126. Service Technician  Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 1-2 131. Winding Resistance 2-3 132. Winding Resistance 1-3 133. Test Run Voltage Phase A 134. Test Run Amps A 135. Test Run Voltage Phase B 136. Test Run Amps B 137. Test Run Voltage Phase C 138. Test Run Amps C 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 15 minutes 148. Temp at 10 minutes 149. Temp at 10 minutes 150. Temp at 20 minutes	119.	Balance Type		
122. Start Right End 123. Balancing Specification 124. Finish Left End 125. Finish Left End 126. Service Technician  Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3 132. Winding Resistance 2-3 132. Winding Resistance 1-3 133. Test Run Voltage Phase A 134. Test Run Voltage Phase B 136. Test Run Voltage Phase B 137. Test Run Voltage Phase C 138. Test Run Amps C 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 15 minutes 149. Temp at 20 minutes 150. Temp at 25 minutes	120.	Balance Operating Speed		
123. Balancing Specification 124. Finish Left End 125. Finish Right End 126. Service Technician  Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3 132. Winding Resistance 2-3 133. Test Run Voltage Phase A 134. Test Run Amps A 135. Test Run Voltage Phase B 136. Test Run Amps B 137. Test Run Amps B 137. Test Run Amps C 138. Test Run Amps C 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 15 minutes 149. Temp at 25 minutes	121.	Start Left End		
124. Finish Left End 125. Finish Right End 126. Service Technician  Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3 132. Winding Resistance 2-3 133. Test Run Voltage Phase A 134. Test Run Amps A 135. Test Run Amps A 136. Test Run Amps B 137. Test Run Voltage Phase C 138. Test Run Voltage Phase C 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 5 minutes 149. Temp at 20 minutes 149. Temp at 20 minutes	122.	Start Right End		
125. Finish Right End 126. Service Technician  Assembly and Final Test  127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3 132. Winding Resistance 1-3 133. Test Run Voltage Phase A 134. Test Run Amps A 135. Test Run Voltage Phase B 136. Test Run Amps B 137. Test Run Voltage Phase C 138. Test Run Amps C 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 15 minutes 148. Temp at 20 minutes 149. Temp at 20 minutes	123.	Balancing Specification		
126. Service Technician  Assembly and Final Test  127. Meggar Testing Reading  128. Surge Test  129. Hi-Pot  130. Winding Resistance 1-2  131. Winding Resistance 2-3  132. Winding Resistance 1-3  133. Test Run Voltage Phase A  134. Test Run Amps A  135. Test Run Voltage Phase B  136. Test Run Voltage Phase B  137. Test Run Voltage Phase C  138. Test Run Voltage Phase C  139. DE Horizontal Vibration Reading  140. DE Vertical Vibration Reading  141. DE Axial Vibration Reading  142. ODE Horizontal Vibration Reading  143. ODE Vertical Vibration Reading  144. ODE Axial Vibration Reading  145. Ambient Temp at start of Test Run  146. Temp at 15 minutes  147. Temp at 10 minutes  148. Temp at 20 minutes  149. Temp at 20 minutes	124.	Finish Left End		
Assembly and Final Test  127. Meggar Testing Reading  128. Surge Test  129. Hi-Pot  130. Winding Resistance 1-2  131. Winding Resistance 2-3  132. Winding Resistance 1-3  133. Test Run Voltage Phase A  134. Test Run Amps A  135. Test Run Voltage Phase B  136. Test Run Amps B  137. Test Run Voltage Phase C  138. Test Run Amps C  139. DE Horizontal Vibration Reading  140. DE Vertical Vibration Reading  141. DE Axial Vibration Reading  142. ODE Horizontal Vibration Reading  143. ODE Vertical Vibration Reading  144. ODE Axial Vibration Reading  145. Ambient Temp at start of Test Run  146. Temp at 5 minutes  147. Temp at 10 minutes  148. Temp at 20 minutes  150. Temp at 25 minutes	125.	Finish Right End		
127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3 132. Winding Resistance 1-3 133. Test Run Voltage Phase A 134. Test Run Amps A 135. Test Run Voltage Phase B 136. Test Run Voltage Phase C 138. Test Run Amps C 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 25 minutes 149. Temp at 25 minutes	126.	Service Technician		
128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3 132. Winding Resistance 1-3 133. Test Run Voltage Phase A 134. Test Run Amps A 135. Test Run Voltage Phase B 136. Test Run Voltage Phase C 137. Test Run Voltage Phase C 138. Test Run Amps C 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 15 minutes 148. Temp at 25 minutes 149. Temp at 25 minutes	Assen	nbly and Final Test		
129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3 132. Winding Resistance 1-3 133. Test Run Voltage Phase A 134. Test Run Amps A 135. Test Run Voltage Phase B 136. Test Run Voltage Phase C 138. Test Run Voltage Phase C 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 20 minutes 149. Temp at 25 minutes	127.	Meggar Testing Reading		
130. Winding Resistance 1-2  131. Winding Resistance 2-3  132. Winding Resistance 1-3  133. Test Run Voltage Phase A  134. Test Run Amps A  135. Test Run Voltage Phase B  136. Test Run Amps B  137. Test Run Voltage Phase C  138. Test Run Amps C  139. DE Horizontal Vibration Reading  140. DE Vertical Vibration Reading  141. DE Axial Vibration Reading  142. ODE Horizontal Vibration Reading  143. ODE Vertical Vibration Reading  144. ODE Axial Vibration Reading  145. Ambient Temp at start of Test Run  146. Temp at 5 minutes  147. Temp at 15 minutes  148. Temp at 20 minutes  149. Temp at 25 minutes	128.	Surge Test		
131. Winding Resistance 2-3 132. Winding Resistance 1-3 133. Test Run Voltage Phase A 134. Test Run Amps A 135. Test Run Voltage Phase B 136. Test Run Amps B 137. Test Run Voltage Phase C 138. Test Run Amps C 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 20 minutes 149. Temp at 25 minutes	129.	Hi-Pot		
<ul> <li>132. Winding Resistance 1-3</li> <li>133. Test Run Voltage Phase A</li> <li>134. Test Run Amps A</li> <li>135. Test Run Voltage Phase B</li> <li>136. Test Run Amps B</li> <li>137. Test Run Voltage Phase C</li> <li>138. Test Run Amps C</li> <li>139. DE Horizontal Vibration Reading</li> <li>140. DE Vertical Vibration Reading</li> <li>141. DE Axial Vibration Reading</li> <li>142. ODE Horizontal Vibration Reading</li> <li>143. ODE Vertical Vibration Reading</li> <li>144. ODE Axial Vibration Reading</li> <li>145. Ambient Temp at start of Test Run</li> <li>146. Temp at 5 minutes</li> <li>147. Temp at 10 minutes</li> <li>148. Temp at 15 minutes</li> <li>149. Temp at 20 minutes</li> <li>150. Temp at 25 minutes</li> </ul>	130.	Winding Resistance 1-2		
133. Test Run Voltage Phase A  134. Test Run Amps A  135. Test Run Voltage Phase B  136. Test Run Amps B  137. Test Run Voltage Phase C  138. Test Run Amps C  139. DE Horizontal Vibration Reading  140. DE Vertical Vibration Reading  141. DE Axial Vibration Reading  142. ODE Horizontal Vibration Reading  143. ODE Vertical Vibration Reading  144. ODE Axial Vibration Reading  145. Ambient Temp at start of Test Run  146. Temp at 5 minutes  147. Temp at 10 minutes  148. Temp at 15 minutes  149. Temp at 20 minutes  150. Temp at 25 minutes	131.	Winding Resistance 2-3		
134. Test Run Amps A 135. Test Run Voltage Phase B 136. Test Run Amps B 137. Test Run Voltage Phase C 138. Test Run Amps C 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 15 minutes 149. Temp at 20 minutes 150. Temp at 25 minutes	132.	Winding Resistance 1-3		
135. Test Run Voltage Phase B  136. Test Run Amps B  137. Test Run Voltage Phase C  138. Test Run Amps C  139. DE Horizontal Vibration Reading  140. DE Vertical Vibration Reading  141. DE Axial Vibration Reading  142. ODE Horizontal Vibration Reading  143. ODE Vertical Vibration Reading  144. ODE Axial Vibration Reading  145. Ambient Temp at start of Test Run  146. Temp at 5 minutes  147. Temp at 10 minutes  148. Temp at 15 minutes  149. Temp at 20 minutes  150. Temp at 25 minutes	133.	Test Run Voltage Phase A		
136. Test Run Amps B  137. Test Run Voltage Phase C  138. Test Run Amps C  139. DE Horizontal Vibration Reading  140. DE Vertical Vibration Reading  141. DE Axial Vibration Reading  142. ODE Horizontal Vibration Reading  143. ODE Vertical Vibration Reading  144. ODE Axial Vibration Reading  145. Ambient Temp at start of Test Run  146. Temp at 5 minutes  147. Temp at 10 minutes  148. Temp at 20 minutes  149. Temp at 20 minutes	134.	Test Run Amps A		
137. Test Run Voltage Phase C  138. Test Run Amps C  139. DE Horizontal Vibration Reading  140. DE Vertical Vibration Reading  141. DE Axial Vibration Reading  142. ODE Horizontal Vibration Reading  143. ODE Vertical Vibration Reading  144. ODE Axial Vibration Reading  145. Ambient Temp at start of Test Run  146. Temp at 5 minutes  147. Temp at 10 minutes  148. Temp at 15 minutes  149. Temp at 20 minutes  150. Temp at 25 minutes	135.	Test Run Voltage Phase B		
138. Test Run Amps C  139. DE Horizontal Vibration Reading  140. DE Vertical Vibration Reading  141. DE Axial Vibration Reading  142. ODE Horizontal Vibration Reading  143. ODE Vertical Vibration Reading  144. ODE Axial Vibration Reading  145. Ambient Temp at start of Test Run  146. Temp at 5 minutes  147. Temp at 10 minutes  148. Temp at 15 minutes  149. Temp at 20 minutes  150. Temp at 25 minutes	136.	Test Run Amps B		
139. DE Horizontal Vibration Reading  140. DE Vertical Vibration Reading  141. DE Axial Vibration Reading  142. ODE Horizontal Vibration Reading  143. ODE Vertical Vibration Reading  144. ODE Axial Vibration Reading  145. Ambient Temp at start of Test Run  146. Temp at 5 minutes  147. Temp at 10 minutes  148. Temp at 15 minutes  149. Temp at 20 minutes  150. Temp at 25 minutes	137.	Test Run Voltage Phase C		
140. DE Vertical Vibration Reading  141. DE Axial Vibration Reading  142. ODE Horizontal Vibration Reading  143. ODE Vertical Vibration Reading  144. ODE Axial Vibration Reading  145. Ambient Temp at start of Test Run  146. Temp at 5 minutes  147. Temp at 10 minutes  148. Temp at 15 minutes  149. Temp at 20 minutes	138.	Test Run Amps C		
141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 15 minutes 149. Temp at 20 minutes 150. Temp at 25 minutes	139.	DE Horizontal Vibration Reading		
142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 15 minutes 149. Temp at 20 minutes 150. Temp at 25 minutes	140.	DE Vertical Vibration Reading		
143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 15 minutes 149. Temp at 20 minutes 150. Temp at 25 minutes	141.	DE Axial Vibration Reading		
144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 15 minutes 149. Temp at 20 minutes 150. Temp at 25 minutes	142.	ODE Horizontal Vibration Reading		
145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 15 minutes 149. Temp at 20 minutes 150. Temp at 25 minutes	143.	ODE Vertical Vibration Reading		
146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 15 minutes 149. Temp at 20 minutes 150. Temp at 25 minutes	144.	ODE Axial Vibration Reading		
147. Temp at 10 minutes 148. Temp at 15 minutes 149. Temp at 20 minutes 150. Temp at 25 minutes	145.	Ambient Temp at start of Test Run		
148. Temp at 15 minutes 149. Temp at 20 minutes 150. Temp at 25 minutes	146.	Temp at 5 minutes		
149. Temp at 20 minutes 150. Temp at 25 minutes	147.	Temp at 10 minutes		
150. Temp at 25 minutes	148.	Temp at 15 minutes		
	149.	Temp at 20 minutes		
151. Temp at 30 minutes	150.	Temp at 25 minutes		
	151.	Temp at 30 minutes		

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

152. Temp at 35 minutes	
153. Temp at 40 minutes	
154. Temp at 45 minutes	
155. Temp at 50 minutes	
156. Temp at 55 minutes	
157. Temp at 60 minutes	
158. Motor Paint	
159. Service Technician	



Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.





P145.13 P158.14



#### STANDARD TERMS AND CONDITIONS FOR PURCHASE OF GOOD AND/OR SERVICES

- 1. APPLICABILITY. The sale of any and all goods and/or services by Mock, Inc. d/b/a Hi-Speed Industrial Service ("Hi-Speed") shall be specifically conditioned upon and subject to the following terms and conditions which are incorporated by reference into any contracts and purchase orders with Hi-Speed, and which shall form and become a part of any agreement related thereto. Buyer's acceptance of any offer or quotation made by Hi-Speed for sale of any goods or services is expressly made subject to the terms and conditions set forth herein and to be so effective, Buyer need not sign or approve these Terms and Conditions to be bound hereunder provided a copy of same is provided to Buyer through any means. None of the terms and conditions contained herein may be added to, expanded, changed, modified, superseded or otherwise altered except as revised in writing and duly executed by Hi-Speed, and all orders received by Hi-Speed shall be governed only by the terms and conditions contained herein, notwithstanding any terms, conditions or provisions of any purchase order, release order, authorization or any other form issued by the Buyer. Hi-Speed hereby objects to any additional, modified, changed, deleted, altered or other terms and conditions not contained herein and notifies Buyer that any such terms or provisions are expressly rejected by Hi-Speed.
- 2. PRICE. All quoted prices shall remain firm and binding for a period of thirty (30) days from the date of quotation or for the period specifically stated in the quotation. The price for any and all goods and/or services ordered or approved by Buyer after thirty (30) days from the date of any quotation are subject to any increase in price that may occur after the expiration of thirty (30) days from the issuance of the quotation and the date the Buyer releases any shipment.
- 3. SCOPE OF GOODS AND/OR SERVICES. The goods and/or services provided by Hi-Speed pursuant to any quotation shall be limited exclusively to those goods and/or services expressly identified therein. Hi-Speed does not assume any responsibility and/or liability for the failure to provide any other goods and/or services not identified in any quotation. Modifications, additions or deletions to or from the scope referenced in any quotation shall only bee effective if evidenced in writing and signed by Hi-Speed. The sale of any of all goods and/or services affected by such modification, addition or deletion shall be subject to these same Standard Terms and Conditions whether or not referenced therein.
- 4. <u>BILLING AND PAYMENT TERMS.</u> Hi-Speed shall invoice Buyer for all goods and/or services as same are rendered at the address listed on the quotation. Payments for all goods and/or services shall be due thirty (30) days from the date of the current invoice or as otherwise set forth in the quotation. Late payments are subject to a late fee of 5% of the total invoice amount. Recurring late payments may lead to a deposit requirement on future services or sale of goods. Buyer shall be liable to Hi-Speed for any and all fees and expenses incurred by Hi-Speed to collect any invoices or to enforce these Standard Terms and Conditions, including but not limited to, attorney's fees.
- 5. <u>DELIVERY OF GOODS AND/OR SERVICES.</u> Unless otherwise identified in the quotation, all shipments are F.O.B. Hi-Speed's warehouse and the title to and all risk of loss with respect to any goods shipped shall pass to Buyer when such goods are delivered to the carrier at Hi-Speed's warehouse. Hi-Speed will use its best efforts to affect delivery by the date or dates specified in the quotation. However, Hi-Speed shall not be liable for delay in or failure to make shipment, or to perform services, by any identified date for any reason whatsoever, including but not limited to, causes beyond its reasonable control, such as strikes, fires, floods, epidemics, quarantines, restrictions, severe weather, embargos, acts of God, or public enemy, war, riot, delays in transportation or the inability to obtain necessary labor, materials or manufacturing facilities.
- **DELIVERY SITE AND TIME FOR PERFORMANCE.** Hi-Speed and Buver agree that time is of the essence for the purchase order and that Buyer shall fully cooperate with Hi-Speed in order to allow Hi-Speed full access to prosecute its work diligently and in an orderly manner. Buyer shall assist Hi-Speed in every way possible to avoid delaying, disrupting or interfering with the progress of Hi-Speed's work at the project site. In the event Hi-Speed's work is delayed, hindered, suspended, disrupted, re-sequenced or interfered with or rendered less efficient or more costly or adversely affected in any way as a result of acts or omissions of Buyer or other contractors or employees of Buyer or by any other reason beyond Hi-Speed's control and without the fault of Hi-Speed, then, in such event, Buyer shall be liable to Hi-Speed for any damages, additional costs, expenses, labor, materials, man hours, acceleration costs, overtime, additional jobsite overhead, extended home office overhead, and any and all other direct and indirect expenses of whatsoever nature or kind, caused in whole or in part, as a result of any of the above-referenced occurrences. Hi-Speed's project records will be the basis for computing the additional costs and damages of Hi-Speed's labor, materials, expenses and overhead related to such changes. BUYER WARRANTS THAT THE SITE FOR DELIVERY OR INSTALLATION OF ANY GOODS AND/OR FOR THE PERFORMANCE OF ANY SERVICES SHALL BE READY AND ADEQUATE FOR HI-SPEED'S DELIVERY OF GOODS AND/OR PERFORMANCE OF SERVICES AND THAT HI-SPEED SHALL HAVE FULL ACCESS THERETO, FREE OF ALL OBSTRUCTIONS. BUYER SHALL ASSUME ALL EXTRA COSTS ASSOCIATED WITH HI-SPEED'S INABILITY TO INSTALL ANY GOODS OR PERFORM ANY SERVICES AS A RESULT OF BUYER'S FAILURE TO COMPLY WITH THIS PROVISION. HI-SPEED MAY NOT INSPECT THE SITE PRIOR TO DELIVERY AND/OR INSTALLATION OF GOODS AND/OR PERFORMANCE OF SERVICES AND MAKES NO WARRANTY AS TO THE SUFFICIENCY OF THE SITE FOR THE DELIVERY AND/OR INSTALLATION OF GOODS AND/OR THE PERFORMANCE OF SERVICES AT SUCH SITE.
- 7. INSPECTION/ACCEPTANCE. All goods and services ordered pursuant to any quotation shall be subject to inspection by Buyer after delivery or performance to determine conformity with the quotation and/or purchase order and Hi-Speed's advertised or published specifications. Buyer shall have a period of thirty (30) days from shipment of goods at the delivery destination specified in the quotation within which to inspect the goods for conformity with the quotation, order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. Buyer shall have a period of thirty (30) days following completion of any services within which to inspect the services for conformity with the quotation, purchase order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. If the goods delivered or services performed do not so conform, upon delivery of notice to Hi-Speed of any discrepancy, nonconformance or rejection, Hi-Speed shall have sixty (60) days to cure the alleged discrepancy and/or nonconformance. If Hi-Speed fails to cure in this time period, Buyer shall have the right to reject such goods or services. After the cure period, goods that have been delivered and rejected, in whole or in part, shall be returned to Hi-Speed. Buyer shall notify Hi-Speed and arrange for the return of the goods as required. Should such non-conforming services be rejected Hi-Speed shall, at its sole cost, re-perform the non-conforming services. Inspection or failure to inspect on any occasion shall not affect Buyer's rights under the warranty provisions herein.
- 8. WARRANTIES. Hi-Speed warrants that all goods shall conform in all material aspects to the goods identified in the quotation to Buyer and/or purchase order, and Hi-Speed makes to Buyer the manufacturer's express warranty for any goods sold to Buyer, which is offered by the manufacturer at the time of acceptance of any quotation by Buyer. This warranty is conditioned upon the installation, operation, and maintenance of the goods in accordance with the manufacturer's recommendations and/or standard industry practice and the goods at all times being operated or used under normal operating conditions for which they were designed. Hi-Speed, at its sole option, will repair or

replace any defective or non-conforming goods in accordance with the applicable manufacturer's warranty. Warranty for any defective or incorrect parts is limited to the repair or replacement of those parts. Hi-Speed warrants that all services will conform in all material respects to the description of services identified in the quotation and will be performed in a good and workmanlike manner in accordance with industry practices and standards. Should the services be reasonably rejected or not conform with the foregoing warranties, Hi-Speed shall, at its sole cost, re-perform the defective or nonconforming services. Notwithstanding the foregoing, these warranties do not extend to goods or services to the extent that such goods have been subject to misuse, neglect or abuse not caused by Hi-Speed or have been used in violation of the approved written instructions furnished to Buyer. THE FOREGOING REPRESENTS THE SOLE AND EXCLUSIVE WARRANTY GIVEN BY HI-SPEED WITH RESPECT TO ALL GOODS SOLD AND IS IN LIEU OF ALL OTHER WARRANTIES EITHER EXPRESS OR IMPLIED. HI-SPEED EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICLAR USE OR PURPOSE. BUYER WAIVES ANY CLAIM THAT THESE EXCLUSIONS OR LIMITATIONS DEPRIVE IT OF AN ADEQUATE REMEDY AT EQUITY OR LAW OR CAUSE THIS AGREEMENT TO FAIL IN ITS ESSENTIAL PURPOSE. BUYER SHALL BE ENTITLED TO NO OTHER REMEDY OTHER THAN AS SET FORTH HEREIN, REGARDLESS OF THE CLAIM OR CAUSE OF ACTION, WHETHER BASED IN CONTRACT, TORT, NEGLIGENCE, GOODS LIABILITY, STRICT LIABILITY OR OTHERWISE.

- 9. <u>LIMITATION OF DAMAGES.</u> HI-SPEED SHALL HAVE NO LIABILITY TO BUYER WITH RESPECT TO THE SALE OR DELIVERY OF ANY GOODS OR THE REPAIR THEREOF OR WITH RESPECT TO THE SALE OR PERFORMANCE OF ANY SERVICES, FOR LOST PROFITS, SPECIAL, CONSEQUENTIAL, EXEMPLARY, PUNITIVE OR INCIDENTAL DAMAGES OF ANY KIND OR NATURE WHETHER ARISING IN CONTRACT, TORT, GOODS LIABILITY OR OTHERWISE, EVEN IF HI-SPEED WAS ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGES. HI-SPEED SHALL NOT BE LIABLE FOR ANY DAMAGES OR DELAYS CAUSED BY ANY FAILURE TO MAKE ANY DELIVERY OF GOODS BY ANY EXPECTED TIME OR DATE OR THE FAILURE TO PROVIDE OR COMPLETE ANY SERVICES BY ANY EXPECTED DATE OR TIME. IN NO EVENT SHALL HI-SPEED BE LIABLE TO BUYER FOR ANY DAMAGES WHATSOEVER IN EXCESS OF THE TOTAL PRICE PAID FOR ALL GOODS AND/OR SERVICES HEREUNDER OR REFERENCED IN ANY QUOTATION OR THE PURCHASE ORDER.
- 10. <u>SEVERABILITY.</u> The partial or complete invalidity of any provision of these Standard Terms and Conditions shall not affect the enforceability of the remainder of these Standard Terms and Conditions. If any provision is found to be invalid or unenforceable, that portion shall be modified to make it enforceable or shall be stricken and the remainder of these Standard Terms and Conditions shall enforced.
- 11. **GOVERNING LAW AND JURISDICTION.** Any controversy arising out of any quotation, the purchase order, the goods sold or delivered, repair or replacement thereof, or any services provided pursuant to any quotation or any purchase order, or these Standard Terms and Conditions shall be governed by the laws of the state of Tennessee without regard to any choice of law provisions and any cause of action related in any manner thereto shall be brought only in the state or federal courts of Shelby County, Tennessee.
- 12. ABANDONED EQUIPMENT. Hi-Speed requires that Buyer promptly pick up or provide shipment instructions for Buyer equipment or other Buyer property in Hi-Speed's possession. If equipment or other Buyer property is left with Hi-Speed and not picked up within six (6) months after Hi-Speed's final action related to the applicable property (e.g. evaluation, teardown, estimate, completion of services), Hi-Speed will consider such property abandoned and may dispose of it in accordance with applicable law. Buyer agrees to hold Hi-Speed harmless for any damage or claim for such abandoned property and acknowledges that Hi-Speed may discard or recycle it at Hi-Speed's sole and absolute discretion. Specifically, Hi-Speed may sell Buyer's abandoned property at a private or public sale and retain the proceeds to offset Hi-Speed's storage, inspection and servicing costs. For the avoidance of doubt, Hi-Speed reserves its statutory and other lawful liens for unpaid charges related to abandoned property.
- 13. FORCE MAJEURE. Neither party shall be responsible for any delay or failure in performance of any party of the quotation, purchase order or these Standard Terms and Conditions to the extent that such delays or failures are caused by fire, flood, earth quake, explosion, war, embargo, government requirement, civil or military authority, acts of God, or any other circumstances beyond its reasonable control and not involving any fault or negligence on the party affected ("Condition"). If any such Condition occurs, the party delayed or unable to perform shall promptly give written notice to the other party and, if such Condition remains at the end of thirty (30) days, the party affected by the other party's delay and inability to perform may elect to (i) terminate such order or part thereof, or (ii) suspend the order for the duration of the Condition, if the Buyer is the suspending party, buy elsewhere comparable material to be sold under the order and apply to any commitment the purchase price of such purchase, and resume performance of the order once the Condition ceases, with an option in the affected party to extend the period of this order up to the length of the time the Condition endures.
- 14. <u>NONWAIVER.</u> No course of dealing or failure of either party to strictly enforce any term, right, or condition of these Standard Terms and Conditions will be construed as a waiver of such term, right or condition. Any waiver by Hi-Speed will only be in writing and will waive no succeeding breach of a term, right or condition.
- 15. **ASSIGNMENT.** The rights and obligations of the parties shall neither be assigned nor delegated without the prior written consent of the other party. However, any party may assign or delegate its respective rights and obligations, in whole or in part, (i) to any subsidiary, (ii) pursuant to other financing, merger or reorganization or (iii) pursuant to any sale or transfer of substantially all of the assets of the assigning party. These Standard Terms and Conditions shall bind the heirs, successors and assigns of the parties hereto.
- 16. NO INDIVIDUAL LIABILITY. Notwithstanding any other agreement to the contrary, the Buyer agrees that in no event will the Buyer hold and HI-Speed owner, director, officer or employee personally liable for unintentional tortious conduct or conduct that constitutes the breach of any contract between HI-Speed and the Buyer, even if the HI-Speed owner, director, officer or employee is or could be construed to be a party to such contract.