

AC Recondition Repair Report

DELTA PLASTICS OF THE SOUTH

3104 SOUTH MAIN STREET STUTTGART, AR 72160 FolderID: 97985 FormID: 10242375

Priorities Found: 🔴 4 - High 💿 9 - Good		
General		
1. Job Number	97985	
2. Report Date	03/16/2021	
3. Customer	DELTA PLASTICS SOUTH	
Name Plate Information		
4. Manufacturer	WEG	P5






























5.	Model	13218ET3Y315S/M-W22	
6.	Serial Number	04MA112 1015868298	
7.	Horsepower	175 HP	
8.	KW		
9.	Volts	460	
10.	Amps	203	
11.	RPM	1790	
12.	Frame	315S/M	
13.	Enclosure	TEFC	
14.	Cycles	60 HZ	
15.	Phase	3	
16.	Service Factor	1.25	
17.	Motor Mount Position		
nitial I	nspection	0	
18.	Number of Leads	6	
19.	Lead Length		
20.	Lead Size		
21.	Lead Condition		
22.	Lead Markings	Т1-Т6	
23.	Lug Size, Condition, and Type		
24.	Winding RTD's		
25.	Winding Rtd's Condition		
26.	Shaft Run Out		
27.	Does Shaft Turn Freely	yes	
28.	Does Shaft Have Visible Damage	no	
29.	Bearing Rtd's		
30.	Bearing Rtd's Condition		
31.	Contamination		


31. Contamination





Initial Electric Test

Ο Resistance to Ground 35. 36. Winding Resistance 1-2 37. Winding Resistance 2-3 38. Winding Resistance 1-3 39. **Resistive Imbalance** Hi-Pot 40. P58 41. Surge Test (P) Pass



Stator Condition 42.



43. Failure Location


Initial Rotor Inspection

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

Ο

P65

good



51.	Bearing DE Size	
-----	-----------------	--

6319 C3



P43

52.	Bearing DE Type	deep groove ball bearing
53. 54.	DE Bearing Qty. Bearing ODE Size	1 6316 C3
55.	Bearing ODE Type	deep grove ball bearing
56.	ODE Bearing Qty.	1
57.	Insulated Bearing	no
58.	Lubrication Type	grease
• 59.	Grease Condition	(F) Fail



(Y) Yes

P80

P74

	61.	Shaft Grounding Device	(NA) Not Applicable
	62. 2	DE Seal	
	63. Sa	DE Seal Type/Size ODE Seal	
	64. 65.	ODE Seal ODE Seal Type/Size	
		Cause of Failure	
	б. 6	Component Failure	bearings
	67.	Cause of Failure	bearings
0	<i>.</i>	Bearing grease contaminated. Both housing fits require machine work.	
6	8.		
	69.		Terrer of Heller d
6		Service Technician	Terrence Holland
0		Service Technician	Terrence Holland
/	/-	Service Technician Me Fit Inspection Report	
Mac	/-	ta All of	
Mac 7	- /-	The Fit Inspection Report	0
Mac 7 7	chir 70.	The Fit Inspection Report Shaft Run Out	0
Mac 7 7 7	chir 70.	Pe Fit Inspection Report Shaft Run Out Initial Shaft Run Out Final Shaft Run Out DE Bearing Shaft Fit	(P) Pass (P) Pass
Mac 7 7 7 7 7 7 7	chir 70. 71. 72. 73. 74.	De Fit Inspection Report Shaft Run Out Initial Shaft Run Out Final Shaft Run Out DE Bearing Shaft Fit DE Initial Shaft Bearing Fit Size 1	(P) Pass (P) Pass 3.7412 "
Mac 7 7 7 7 7 7 7 7 7	chir 70. 71. 72. 73. 74. 75.	Pe Fit Inspection Report Shaft Run Out Initial Shaft Run Out Final Shaft Run Out DE Bearing Shaft Fit DE Initial Shaft Bearing Fit Size 1 DE Initial Shaft Bearing Fit Size 2	(P) Pass (P) Pass 3.7412 " 3.741 "
Mac 7 7 7 7 7 7 7 7 7 7 7 7 7	chir 70. 71. 72. 73. 74. 75. 76.	PE Fit Inspection Report Shaft Run Out Initial Shaft Run Out Final Shaft Run Out DE Bearing Shaft Fit DE Initial Shaft Bearing Fit Size 1 DE Initial Shaft Bearing Fit Size 2 DE Initial Shaft Bearing Fit Size 3	(P) Pass (P) Pass 3.7412 "
Mac 7 7 7 7 7 7 7 7 7 7 7	chir 70. 71. 72. 73. 74. 75. 76. 77.	A Addaded Stress of the second state of the se	(P) Pass (P) Pass 3.7412 " 3.741 "
Mac 7 7 7 7 7 7 7 7 7 7 7 7 7	chir 70. 71. 72. 73. 74. 75. 76. 77. 78.	Pe Fit Inspection Report Shaft Run Out Initial Shaft Run Out Final Shaft Run Out DE Bearing Shaft Fit DE Initial Shaft Bearing Fit Size 1 DE Initial Shaft Bearing Fit Size 2 DE Initial Shaft Bearing Fit Size 3 DE Finial Shaft Bearing Fit Size 1 DE Finial Shaft Bearing Fit Size 3 DE Finial Shaft Bearing Fit Size 1 DE Finial Shaft Bearing Fit Size 2	(P) Pass (P) Pass 3.7412 " 3.741 "
Mac 7 7 7 7 7 7 7 7 7 7 7 7 7	chir 70. 71. 72. 73. 74. 75. 76. 77. 78. 79.	A Addaded Strengton Report Shaft Run Out Initial Shaft Run Out Final Shaft Run Out DE Bearing Shaft Fit DE Initial Shaft Bearing Fit Size 1 DE Initial Shaft Bearing Fit Size 2 DE Initial Shaft Bearing Fit Size 3 DE Finial Shaft Bearing Fit Size 1 DE Finial Shaft Bearing Fit Size 2 DE Finial Shaft Bearing Fit Size 3	(P) Pass (P) Pass 3.7412 " 3.741 " 3.741 "
Mac 7 7 7 7 7 7 7 7 7 7 7 7 7	chir 70. 71. 72. 73. 74. 75. 76. 77. 78. 79. 30.	A Addaded Stress Adda	(P) Pass (P) Pass 3.741 " 3.741 " 3.741 " (P) Pass
Mac 7 7 7 7 7 7 7 7 7 7 7 7 7	chir 70. 71. 72. 73. 74. 75. 76. 77. 78. 79. 30. 31.	DefinitionAdded and ConstraintsAdded and Constraints	(P) Pass (P) Pass 3.741 " 3.741 " 3.741 " (P) Pass 3.15 "
Mac 7 7 7 7 7 7 7 7 7 7 7 7 8 8 8 8 8	chin 70. 71. 72. 73. 74. 75. 76. 77. 78. 79. 30. 31. 32.	Additional and the set of th	(P) Pass (P) Pass 3.7412 " 3.741 " 3.741 " (P) Pass 3.741 "
Mac • 7 7 7 7 7 7 7 7 7 7 8 8 8 8 8 8 8	chir 70. 71. 72. 73. 74. 75. 76. 77. 78. 79. 30. 31. 32. 33.	AAbFit Inspection Report Shaft Run OutInitial Shaft Run OutFinal Shaft Run OutDE Bearing Shaft FitDE Initial Shaft Bearing Fit Size 1DE Initial Shaft Bearing Fit Size 2DE Initial Shaft Bearing Fit Size 3DE Finial Shaft Bearing Fit Size 1DE Finial Shaft Bearing Fit Size 2DE Finial Shaft Bearing Fit Size 3DE Finial Shaft Bearing Fit Size 3ODE Bearing Shaft FitODE Initial Shaft Bearing Fit Size 1ODE Initial Shaft Bearing Fit Size 3ODE Initial Shaft Bearing Fit Size 1ODE Initial Shaft Bearing Fit Size 2ODE Initial Shaft Bearing Fit Size 3	(P) Pass (P) Pass 3.741 " 3.741 " 3.741 " (P) Pass 3.15 "
Mac 7 7 7 7 7 7 7 7 7 7 7 7 7	chin 70. 71. 72. 73. 74. 75. 76. 77. 78. 79. 30. 31. 32.	Additional and the set of th	(P) Pass (P) Pass 3.7412 " 3.741 " 3.741 " (P) Pass 3.741 "
Mac 7 7 7 7 7 7 7 7 7 7 7 7 7	chi r 70. 71. 72. 73. 74. 75. 76. 77. 78. 79. 30. 31. 32. 33. 33.	Additional and the second state of the second stat	(P) Pass (P) Pass 3.7412 " 3.741 " 3.741 " (P) Pass 3.741 "

88.	DE Initial Air Seal Shaft Size
89.	DE Final Air Seal Shaft Size

- 90. ODE Air Seal Shaft Fit
- 91. ODE Initial Air Seal Shaft Size
- 92. ODE Final Air Seal Shaft Size
- 93. DE Endbell Fit







(F) Fail

P129

-	



105.	ODE Initial Endbell Fit Size 1	5.5133 "
106.	ODE Initial Endbell Fit Size 2	5.5131 "
107.	ODE Initial Endbell Fit Size 3	5.5131 "
108.	ODE Final Endbell Fit Size 1	
109.	ODE Final Endbell Fit Size 2	
110.	ODE Final Endbell Fit Size 3	
111.	ODE Endbell Fit Insulated	(NA) Not Applicable
112.	ODE Endbell Air Seal Fit	
113.	ODE Initial Endbell Seal Fit Size	
114.	ODE Finial Endbell Seal Fit Size	
115.	Foot Flatness	(P) Pass
116.	Foot Condition	(P) Pass
117.	Flange Condition	
118.	Service Technician	Terrence Holland

La Lola

Balanciry Report119.Balance Type120.Balance Operating Speed121.Start Left End122.Start Right End123.Balancing Specification124.Finish Left End125.Finish Right End126.Service TechnicianAssembly and Final Test127.Meggar Testing Reading128.Surge Test129.Hi-Pot130.Winding Resistance 1-2131.Winding Resistance 2-3132.Winding Resistance 1-3		
 120. Balance Operating Speed 121. Start Left End 122. Start Right End 123. Balancing Specification 124. Finish Left End 125. Finish Right End 126. Service Technician Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3	Balanc	ing Report
 121. Start Left End 122. Start Right End 123. Balancing Specification 124. Finish Left End 125. Finish Right End 126. Service Technician Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3 	119.	Balance Type
 122. Start Right End 123. Balancing Specification 124. Finish Left End 125. Finish Right End 126. Service Technician Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3 	120.	Balance Operating Speed
 123. Balancing Specification 124. Finish Left End 125. Finish Right End 126. Service Technician Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3	121.	Start Left End
 124. Finish Left End 125. Finish Right End 126. Service Technician Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3	122.	Start Right End
 125. Finish Right End 126. Service Technician Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3 	123.	Balancing Specification
126.Service TechnicianAssembly and Final Test127.Meggar Testing Reading128.Surge Test129.Hi-Pot130.Winding Resistance 1-2131.Winding Resistance 2-3	124.	Finish Left End
Assembly and Final Test127. Meggar Testing Reading128. Surge Test129. Hi-Pot130. Winding Resistance 1-2131. Winding Resistance 2-3	125.	Finish Right End
 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3 	126.	Service Technician
128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3	Assem	bly and Final Test
129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3	127.	Meggar Testing Reading
130. Winding Resistance 1-2131. Winding Resistance 2-3	128.	Surge Test
131. Winding Resistance 2-3	129.	Hi-Pot
-	130.	Winding Resistance 1-2
132. Winding Resistance 1-3	131.	Winding Resistance 2-3
	132.	Winding Resistance 1-3

133.	Test Run Voltage Phase A
134.	Test Run Amps A
135.	Test Run Voltage Phase B
136.	Test Run Amps B
137.	Test Run Voltage Phase C
138.	Test Run Amps C
139.	DE Horizontal Vibration Reading
140.	DE Vertical Vibration Reading
141.	DE Axial Vibration Reading
142.	ODE Horizontal Vibration Reading
143.	ODE Vertical Vibration Reading
144.	ODE Axial Vibration Reading
145.	Ambient Temp at start of Test Run
146.	Temp at 5 minutes
147.	Temp at 10 minutes
148.	Temp at 15 minutes
149.	Temp at 20 minutes
150.	Temp at 25 minutes
151.	Temp at 30 minutes
152.	Temp at 35 minutes
153.	Temp at 40 minutes
154.	Temp at 45 minutes
155.	Temp at 50 minutes
156.	Temp at 55 minutes
157.	Temp at 60 minutes
158.	Motor Paint
159.	Service Technician