

AC Recondition Repair Report

FolderID: 98158 FormID: 10539691

7030 Ryburn Dr Millington, Tn 38053 901-873-5300

Hi-Speed Industrial Service

0

98158

Peco Foods

Hwy 67 Pocahontas, AR 72455

Priorities Found: 14 - Good

General

Job Number















2. Report Date 04/29/2021 Customer **PECO FOODS** 3.

Name Plate Information

Manufacturer

0

U.S. MOTORS P5





5.	Model	FG25	
6.	Serial Number	CAT # HO25V2BLG	
7.	Horsepower	25	
8.	KW		
9.	Volts	460	
10.	Amps	29	
11.	RPM	1775	

12. Frame	284TPH
13. Enclosure	WPI
14. Cycles	60
15. Phase	3
16. Service Factor	1.15
17. Motor Mount Position	


Initial Inspection 18. Number of Leads 9 P13



19.	Lead Length	15 Inches	
20.	Lead Size	12	
21.	Lead Condition	(P) Pass	P42



22.	Lead Markings	1-9
23.	Lug Size, Condition, and Type	
24.	Winding RTD's	(NA) Not Applicable
25.	Winding Rtd's Condition	(NA) Not Applicable
26.	Shaft Run Out	
27.	Does Shaft Turn Freely	yes
28.	Does Shaft Have Visible Damage	no
29.	Bearing Rtd's	(NA) Not Applicable
30.	Bearing Rtd's Condition	(NA) Not Applicable
31.	Contamination	
32.	Frame Condition	(P) Pass
33.	Fan Condition	(NA) Not Applicable





Stator Condition P65 rewind



43.	Failure Location		
Initial	Initial Rotor Inspection		
44.	Rotor Type	cast aluminum	
45.	Air Gap <10% Variation		
46.	Number of Rotor Bars		
47.	Number of Broken Rotor Bars		
48.	Growler Test		
4 9.	Rotor Condition	(P) Pass	
Mecha	Mechanical Inspection		
50.	Bearing Manufacture	FAG PEER	

P15

Ageis ring shaft size 2.364





52. Bearing DE Type P23 Thrust ball bearing



53. DE Bearing Qty. P43 54. Bearing ODE Size 6210ZZ





55.	Bearing ODE Type	ball bearing	
56.	ODE Bearing Qty.	1	
57.	Insulated Bearing	no	
58.	Lubrication Type	grease	
59.	Grease Condition	(P) Pass	P74



Bearing Retainers

● 61. Shaft Grounding Device (Y) Yes P81



6	62.	DE Seal	(NA) Not Applicable
6	3.	DE Seal Type/Size	
6	64.	ODE Seal	(NA) Not Applicable
6	65.	ODE Seal Type/Size	
Roc	ot C	ause of Failure	
6	66.	Component Failure	
6	67.	Cause of Failure	
6	88.	Comments	
6	69.	Service Technician	
Mad	hir	e Fit Inspection Report	
7	70.	Shaft Run Out	
7	71.	Initial Shaft Run Out	
7	72.	Final Shaft Run Out	
• 7	73.	DE Bearing Shaft Fit	(P) Pass
7	74.	DE Initial Shaft Bearing Fit Size 1	1.9689 "
7	75.	DE Initial Shaft Bearing Fit Size 2	1.9689 "
7	76.	DE Initial Shaft Bearing Fit Size 3	1.9689 "
7	77.	DE Finial Shaft Bearing Fit Size 1	
7	78.	DE Finial Shaft Bearing Fit Size 2	
7	79.	DE Finial Shaft Bearing Fit Size 3	
8	30.	ODE Bearing Shaft Fit	(P) Pass

81.	ODE Initial Shaft Bearing Fit Size 1	1.9688 "
82.	ODE Initial Shaft Bearing Fit Size 2	1.9688 "
83.	ODE Initial Shaft Bearing Fit Size 3	1.9688 "
84.	ODE Finial Shaft Bearing Fit Size 1	
85.	ODE Finial Shaft Bearing Fit Size 2	
86.	ODE Finial Shaft Bearing Fit Size 3	
87.	DE Air Seal Shaft Fit	
88.	DE Initial Air Seal Shaft Size	
89.	DE Final Air Seal Shaft Size	
90.	ODE Air Seal Shaft Fit	
91.	ODE Initial Air Seal Shaft Size	
92.	ODE Final Air Seal Shaft Size	
93.	DE Endbell Fit	(P) Pass
94.	DE Initial Endbell Fit Size 1	4.3315 "
95.	DE Initial Endbell Fit Size 2	4.3315 "
96.	DE Initial Endbell Fit Size 3	4.3315 "
97.	DE Final Endbell Fit Size 1	
98.	DE Finial Endbell Fit Size 2	
99.	DE Final Endbell Fit Size 3	
100.	DE Endbell Fit Insulated	(NA) Not Applicable
101.	DE Endbell Air Seal Fit	, ,
102.	Initial Endbell Air Seal Fit Size	
103.	Finial Endbell Air Seal Fit Size	
104.	ODE Endbell Fit	(P) Pass
105.	ODE Initial Endbell Fit Size 1	3.544 "
106.	ODE Initial Endbell Fit Size 2	3.544 "
107.	ODE Initial Endbell Fit Size 3	3.544 "
108.	ODE Final Endbell Fit Size 1	
109.	ODE Final Endbell Fit Size 2	
110.	ODE Final Endbell Fit Size 3	
	ODE Endbell Fit Insulated	
112.	ODE Endbell Air Seal Fit	
	ODE Initial Endbell Seal Fit Size	
	ODE Finial Endbell Seal Fit Size	
115.	Foot Flatness	
116.	Foot Condition	
117.	Flange Condition	(P) Pass
	Service Technician	RW
ſ.	2 1	
	cing Report	
	Balance Type	
	Balance Operating Speed	
121.	Start Left End	

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

122. Start Right End

	Balancing Specification
	Finish Left End
	Finish Right End
	Service Technician
	bly and Final Test
	Meggar Testing Reading
128.	Surge Test
129.	Hi-Pot
130.	Winding Resistance 1-2
131.	Winding Resistance 2-3
132.	Winding Resistance 1-3
133.	Test Run Voltage Phase A
134.	Test Run Amps A
135.	Test Run Voltage Phase B
136.	Test Run Amps B
137.	Test Run Voltage Phase C
138.	Test Run Amps C
139.	DE Horizontal Vibration Reading
140.	DE Vertical Vibration Reading
141.	DE Axial Vibration Reading
142.	ODE Horizontal Vibration Reading
143.	ODE Vertical Vibration Reading
144.	ODE Axial Vibration Reading
145.	Ambient Temp at start of Test Run
146.	Temp at 5 minutes
147.	Temp at 10 minutes
148.	Temp at 15 minutes
149.	Temp at 20 minutes
150.	Temp at 25 minutes
151.	Temp at 30 minutes
152.	Temp at 35 minutes
153.	Temp at 40 minutes
154.	Temp at 45 minutes
155.	Temp at 50 minutes
156.	Temp at 55 minutes
157.	Temp at 60 minutes
158.	Motor Paint
159.	Service Technician

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.