



Hi-Speed Industrial Service
7030 Ryburn Dr
Millington, Tn 38053
901-873-5300

AC Recondition Repair Report

FolderID: 98358
FormID: 10916929

FUTURE FUEL CHEMICAL
2800 GAP RD HWY 394 SO
BATESVILLE, AR 72501

Priorities Found: ● 4 - High ● 7 - Good

General

1. Job Number	98358
2. Report Date	06/22/2021
3. Customer	FUTURE FUEL

Name Plate Information



4. Manufacturer	U.S. MOTORS
-----------------	-------------

P5



Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.









5. Model	R923
6. Serial Number	CAT# H100E1S
7. Horsepower	100 HP
8. KW	KW
9. Volts	460 Volts
10. Amps	111
11. RPM	3560 RPM
12. Frame	405TS
13. Enclosure	TEFC
14. Cycles	60
15. Phase	3 PH
16. Service Factor	1.15
17. Motor Mount Position	
Initial Inspection	
18. Number of Leads	12
19. Lead Length	
20. Lead Size	
21. Lead Condition	(P) Pass
22. Lead Markings	1-12
23. Lug Size, Condition, and Type	
24. Winding RTD's	
25. Winding Rtd's Condition	
26. Shaft Run Out	



Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

27.	Does Shaft Turn Freely	no	
28.	Does Shaft Have Visible Damage	no	
29.	Bearing Rtd's		
30.	Bearing Rtd's Condition		
31.	Contamination		
32.	Frame Condition	(P) Pass	
33.	Fan Condition		
34.	Broken or missing components		
Initial Electric Test			
35.	Resistance to Ground		
36.	Winding Resistance 1-2		
37.	Winding Resistance 2-3		
38.	Winding Resistance 1-3		
39.	Resistive Imbalance		
40.	Hi-Pot		
41.	Surge Test	(P) Pass	P58
			 
42.	Stator Condition	pass	
43.	Failure Location		
Initial Rotor Inspection			
44.	Rotor Type	squirrel cage laminate	
45.	Air Gap <10% Variation		
46.	Number of Rotor Bars		
47.	Number of Broken Rotor Bars		
48.	Growler Test		
49.	Rotor Condition		
Mechanical Inspection			
50.	Bearing Manufacture	SKF	



52. Bearing DE Type

regular ball bearing

53. DE Bearing Qty.

1


54. Bearing ODE Size

6214

55. Bearing ODE Type

regular ball bearing

P53



56. ODE Bearing Qty.

1

57. Insulated Bearing

no

58. Lubrication Type

grease

59. Grease Condition

(F) Fail

☐ Dirty

60. Bearing Retainers

(Y) Yes

61. Shaft Grounding Device

(NA) Not Applicable

62. DE Seal

(NA) Not Applicable

63. DE Seal Type/Size

64. ODE Seal

(NA) Not Applicable

65. ODE Seal Type/Size

Root Cause of Failure

66. Component Failure

D.E. bearing came apart

67. Cause of Failure

D.E. bearing suffered catastrophic failure and came apart. As a result the drive end shaft was bent 10 thousands out of tolerance. Primary cause of bearing failure appears to be lack of lubrication. Also the drive end housing fit requires machine work as well.

68. Comments



Machine Fit Inspection Report

70.	Shaft Run Out	(F) Fail
71.	Initial Shaft Run Out	0.2 "
72.	Final Shaft Run Out	
73.	DE Bearing Shaft Fit	(F) Fail
74.	DE Initial Shaft Bearing Fit Size 1	
75.	DE Initial Shaft Bearing Fit Size 2	
76.	DE Initial Shaft Bearing Fit Size 3	
77.	DE Finial Shaft Bearing Fit Size 1	
78.	DE Finial Shaft Bearing Fit Size 2	
79.	DE Finial Shaft Bearing Fit Size 3	
80.	ODE Bearing Shaft Fit	
81.	ODE Initial Shaft Bearing Fit Size 1	
82.	ODE Initial Shaft Bearing Fit Size 2	
83.	ODE Initial Shaft Bearing Fit Size 3	
84.	ODE Finial Shaft Bearing Fit Size 1	
85.	ODE Finial Shaft Bearing Fit Size 2	
86.	ODE Finial Shaft Bearing Fit Size 3	
87.	DE Air Seal Shaft Fit	
88.	DE Initial Air Seal Shaft Size	
89.	DE Final Air Seal Shaft Size	
90.	ODE Air Seal Shaft Fit	
91.	ODE Initial Air Seal Shaft Size	
92.	ODE Final Air Seal Shaft Size	
93.	DE Endbell Fit	(F) Fail
	<i>Machine work needed.</i>	
94.	DE Initial Endbell Fit Size 1	
95.	DE Initial Endbell Fit Size 2	
96.	DE Initial Endbell Fit Size 3	
97.	DE Final Endbell Fit Size 1	
98.	DE Finial Endbell Fit Size 2	
99.	DE Final Endbell Fit Size 3	
100.	DE Endbell Fit Insulated	(NA) Not Applicable
101.	DE Endbell Air Seal Fit	
102.	Initial Endbell Air Seal Fit Size	
103.	Finial Endbell Air Seal Fit Size	
104.	ODE Endbell Fit	
105.	ODE Initial Endbell Fit Size 1	
106.	ODE Initial Endbell Fit Size 2	
107.	ODE Initial Endbell Fit Size 3	
108.	ODE Final Endbell Fit Size 1	
109.	ODE Final Endbell Fit Size 2	

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

110.	ODE Final Endbell Fit Size 3	
111.	ODE Endbell Fit Insulated	
112.	ODE Endbell Air Seal Fit	
113.	ODE Initial Endbell Seal Fit Size	
114.	ODE Finial Endbell Seal Fit Size	
●	115. Foot Flatness	(P) Pass
●	116. Foot Condition	(P) Pass
●	117. Flange Condition	(NA) Not Applicable
	118. Service Technician	
Balancing Report		
	119. Balance Type	
	120. Balance Operating Speed	
	121. Start Left End	
	122. Start Right End	
	123. Balancing Specification	
	124. Finish Left End	
	125. Finish Right End	
	126. Service Technician	
Assembly and Final Test		
	127. Meggar Testing Reading	
	128. Surge Test	
	129. Hi-Pot	
	130. Winding Resistance 1-2	
	131. Winding Resistance 2-3	
	132. Winding Resistance 1-3	
	133. Test Run Voltage Phase A	
	134. Test Run Amps A	
	135. Test Run Voltage Phase B	
	136. Test Run Amps B	
	137. Test Run Voltage Phase C	
	138. Test Run Amps C	
	139. DE Horizontal Vibration Reading	
	140. DE Vertical Vibration Reading	
	141. DE Axial Vibration Reading	
	142. ODE Horizontal Vibration Reading	
	143. ODE Vertical Vibration Reading	
	144. ODE Axial Vibration Reading	
	145. Ambient Temp at start of Test Run	
	146. Temp at 5 minutes	
	147. Temp at 10 minutes	
	148. Temp at 15 minutes	
	149. Temp at 20 minutes	
	150. Temp at 25 minutes	
	151. Temp at 30 minutes	
	152. Temp at 35 minutes	
	153. Temp at 40 minutes	
	154. Temp at 45 minutes	
	155. Temp at 50 minutes	

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

156. Temp at 55 minutes
157. Temp at 60 minutes
158. Motor Paint
159. Service Technician