



Hi-Speed Industrial Service
7030 Ryburn Dr
Millington, Tn 38053
901-873-5300

AC Recondition Repair Report

FolderID: 98679
FormID: 11518161

SAGE
5901 SLOAN DRIVE
LITTLE ROCK, AR 72206

Priorities Found: ● 2 - High ● 14 - Good

General

1. Job Number	98679
2. Report Date	09/07/2021
3. Customer	Sage V Foods
Little Rock	

Name Plate Information




4. Manufacturer	Baldor Reliance	P5
-----------------	-----------------	----



Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.



5. Model	12F654H88961
6. Serial Number	C0906200018
7. Horsepower	50
8. KW	
9. Volts	460
10. Amps	57
11. RPM	1775
12. Frame	326TDZ
13. Enclosure	TEFC
14. Cycles	60
15. Phase	3
16. Service Factor	1.00
17. Motor Mount Position	flange
Initial Inspection 	
18. Number of Leads	9
19. Lead Length	10 Inches
20. Lead Size	









22. Lead Markings		
23. Lug Size, Condition, and Type		
24. Winding RTD's		
25. Winding Rtd's Condition		
26. Shaft Run Out	0.015	
27. Does Shaft Turn Freely	yes	
28. Does Shaft Have Visible Damage		
29. Bearing Rtd's		
30. Bearing Rtd's Condition		
31. Contamination		
● 32. Frame Condition	(P) Pass	
● 33. Fan Condition	(P) Pass	P109



34. Broken or missing components		
Initial Electric Test		
35. Resistance to Ground		
36. Winding Resistance 1-2		
37. Winding Resistance 2-3		
38. Winding Resistance 1-3		
39. Resistive Imbalance		
40. Hi-Pot		
● 41. Surge Test	(P) Pass	
42. Stator Condition	recondition	

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

43.	Failure Location		
Initial Rotor Inspection			
44.	Rotor Type	cast aluminum	
45.	Air Gap <10% Variation		
46.	Number of Rotor Bars	40	
47.	Number of Broken Rotor Bars	0	
	48.	Growler Test	(P) Pass
	49.	Rotor Condition	(P) Pass
			P50
			
Mechanical Inspection			
50.	Bearing Manufacture	fag	
51.	Bearing DE Size	6312 2rsrc3	
52.	Bearing DE Type	ball	P23
			
53.	DE Bearing Qty.	1	
54.	Bearing ODE Size	6311 2rsrc3	



56. ODE Bearing Qty.

1

57. Insulated Bearing

58. Lubrication Type

grease

● 59. Grease Condition

(F) Fail

● 60. Bearing Retainers

(Y) Yes

P80



61. Shaft Grounding Device

62. DE Seal

63. DE Seal Type/Size

64. ODE Seal

65. ODE Seal Type/Size

Root Cause of Failure

66. Component Failure

bearings

67. Cause of Failure

68. Comments

69. Service Technician

Trevor Hall

Machine Fit Inspection Report

● 70. Shaft Run Out

(F) Fail

71. Initial Shaft Run Out

0.015 "

72. Final Shaft Run Out

● 73. DE Bearing Shaft Fit

(P) Pass


74. DE Initial Shaft Bearing Fit Size 1

2.3625 "

75. DE Initial Shaft Bearing Fit Size 2

2.3626 "

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

76.	DE Initial Shaft Bearing Fit Size 3	2.3626 "	
77.	DE Finial Shaft Bearing Fit Size 1		
78.	DE Finial Shaft Bearing Fit Size 2		
79.	DE Finial Shaft Bearing Fit Size 3		
80.	ODE Bearing Shaft Fit	(P) Pass	
81.	ODE Initial Shaft Bearing Fit Size 1	2.166 "	
82.	ODE Initial Shaft Bearing Fit Size 2	2.166 "	
83.	ODE Initial Shaft Bearing Fit Size 3	2.166 "	
84.	ODE Finial Shaft Bearing Fit Size 1		
85.	ODE Finial Shaft Bearing Fit Size 2		
86.	ODE Finial Shaft Bearing Fit Size 3		
87.	DE Air Seal Shaft Fit		
88.	DE Initial Air Seal Shaft Size		
89.	DE Final Air Seal Shaft Size		
90.	ODE Air Seal Shaft Fit		
91.	ODE Initial Air Seal Shaft Size		
92.	ODE Final Air Seal Shaft Size		
93.	DE Endbell Fit	(P) Pass	
94.	DE Initial Endbell Fit Size 1	5.1187 "	
95.	DE Initial Endbell Fit Size 2	5.1186 "	
96.	DE Initial Endbell Fit Size 3	5.1186 "	
97.	DE Final Endbell Fit Size 1		
98.	DE Finial Endbell Fit Size 2		
99.	DE Final Endbell Fit Size 3		
100.	DE Endbell Fit Insulated		
101.	DE Endbell Air Seal Fit		
102.	Initial Endbell Air Seal Fit Size		
103.	Finial Endbell Air Seal Fit Size		
104.	ODE Endbell Fit	(P) Pass	
105.	ODE Initial Endbell Fit Size 1	4.725 "	
106.	ODE Initial Endbell Fit Size 2	4.7249 "	
107.	ODE Initial Endbell Fit Size 3	4.7249 "	
108.	ODE Final Endbell Fit Size 1		
109.	ODE Final Endbell Fit Size 2		
110.	ODE Final Endbell Fit Size 3		
111.	ODE Endbell Fit Insulated		
112.	ODE Endbell Air Seal Fit		
113.	ODE Initial Endbell Seal Fit Size		
114.	ODE Finial Endbell Seal Fit Size		
115.	Foot Flatness	(P) Pass	
116.	Foot Condition	(P) Pass	
117.	Flange Condition	(P) Pass	P158
	 Worn from improper fit.		

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.



118. Service Technician

Balancing Report

119. Balance Type

120. Balance Operating Speed

121. Start Left End

122. Start Right End

123. Balancing Specification

124. Finish Left End

125. Finish Right End

126. Service Technician

Assembly and Final Test

127. Meggar Testing Reading

128. Surge Test

129. Hi-Pot

130. Winding Resistance 1-2

131. Winding Resistance 2-3

132. Winding Resistance 1-3

133. Test Run Voltage Phase A

134. Test Run Amps A

135. Test Run Voltage Phase B

136. Test Run Amps B

137. Test Run Voltage Phase C

138. Test Run Amps C

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

139.	DE Horizontal Vibration Reading
140.	DE Vertical Vibration Reading
141.	DE Axial Vibration Reading
142.	ODE Horizontal Vibration Reading
143.	ODE Vertical Vibration Reading
144.	ODE Axial Vibration Reading
145.	Ambient Temp at start of Test Run
146.	Temp at 5 minutes
147.	Temp at 10 minutes
148.	Temp at 15 minutes
149.	Temp at 20 minutes
150.	Temp at 25 minutes
151.	Temp at 30 minutes
152.	Temp at 35 minutes
153.	Temp at 40 minutes
154.	Temp at 45 minutes
155.	Temp at 50 minutes
156.	Temp at 55 minutes
157.	Temp at 60 minutes
158.	Motor Paint
159.	Service Technician