



AC Recondition Repair Report

FolderID: 99295
FormID: 12662794

Jacksonville Waste Water
248 Cloverdale Road
Jacksonville, AR 72076

Priorities Found: ● 1 - High ● 4 - Good

General

1. Job Number	99295
2. Report Date	01/25/2022
3. Customer	Jacksonville Wastewater

Name Plate Information



4. Manufacturer	Baldor	P5
-----------------	--------	----



Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.











5.	Model	ECP4316T
	 SPEC# A36C-0000000045	
6.	Serial Number	A2104012056
7.	Horsepower	75
8.	KW	
9.	Volts	460
10.	Amps	86
11.	RPM	1780
12.	Frame	365T
13.	Enclosure	TEFC

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

14.	Cycles	60	
15.	Phase	3	
16.	Service Factor	1.15	
17.	Motor Mount Position		
Initial Inspection			
18.	Number of Leads	9	
19.	Lead Length	11 Inches	P20
			
20.	Lead Size		
21.	Lead Condition		
22.	Lead Markings	1-9	
23.	Lug Size, Condition, and Type		
24.	Winding RTD's		
25.	Winding Rtd's Condition		
26.	Shaft Run Out		
27.	Does Shaft Turn Freely	yes	
28.	Does Shaft Have Visible Damage		
29.	Bearing Rtd's		
30.	Bearing Rtd's Condition		
31.	Contamination		
32.	Frame Condition		
	33. Fan Condition	(P) Pass	
34.	Broken or missing components		
Initial Electric Test			
35.	Resistance to Ground		
36.	Winding Resistance 1-2		
37.	Winding Resistance 2-3		
38.	Winding Resistance 1-3		
39.	Resistive Imbalance		
40.	Hi-Pot		



42. Stator Condition

P65



43. Failure Location

Initial Rotor Inspection





45. Air Gap <10% Variation

46. Number of Rotor Bars

47. Number of Broken Rotor Bars

0

● 48. Growler Test

(P) Pass

● 49. Rotor Condition

(P) Pass



Mechanical Inspection

50. Bearing Manufacture

SKF

51. Bearing DE Size

P15



52. Bearing DE Type

regular ball bearing

53. DE Bearing Qty.

1

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

54. Bearing ODE Size

P43



55. Bearing ODE Type

P53



56. ODE Bearing Qty.

1

57. Insulated Bearing

no



58. Lubrication Type

grease

59. Grease Condition

(F) Fail

P74



60. Bearing Retainers

P80



- 61. Shaft Grounding Device
- 62. DE Seal

(NA) Not Applicable

P86



- 63. DE Seal Type/Size
- 64. ODE Seal
- 65. ODE Seal Type/Size

Root Cause of Failure



- 66. Component Failure

D.E. shaft bearing journal worn beyond limits

P2



- 67. Cause of Failure
D.E. Shaft bearing journal worn out of limits.
- 68. Comments



Machine Fit Inspection Report

70.	Shaft Run Out	
71.	Initial Shaft Run Out	"
72.	Final Shaft Run Out	"
73.	DE Bearing Shaft Fit	
74.	DE Initial Shaft Bearing Fit Size 1	
75.	DE Initial Shaft Bearing Fit Size 2	
76.	DE Initial Shaft Bearing Fit Size 3	
77.	DE Finial Shaft Bearing Fit Size 1	
78.	DE Finial Shaft Bearing Fit Size 2	
79.	DE Finial Shaft Bearing Fit Size 3	
80.	ODE Bearing Shaft Fit	
81.	ODE Initial Shaft Bearing Fit Size 1	
82.	ODE Initial Shaft Bearing Fit Size 2	
83.	ODE Initial Shaft Bearing Fit Size 3	
84.	ODE Finial Shaft Bearing Fit Size 1	
85.	ODE Finial Shaft Bearing Fit Size 2	
86.	ODE Finial Shaft Bearing Fit Size 3	
87.	DE Air Seal Shaft Fit	
88.	DE Initial Air Seal Shaft Size	
89.	DE Final Air Seal Shaft Size	
90.	ODE Air Seal Shaft Fit	
91.	ODE Initial Air Seal Shaft Size	
92.	ODE Final Air Seal Shaft Size	
93.	DE Endbell Fit	
94.	DE Initial Endbell Fit Size 1	
95.	DE Initial Endbell Fit Size 2	
96.	DE Initial Endbell Fit Size 3	
97.	DE Final Endbell Fit Size 1	
98.	DE Finial Endbell Fit Size 2	
99.	DE Final Endbell Fit Size 3	
100.	DE Endbell Fit Insulated	
101.	DE Endbell Air Seal Fit	
102.	Initial Endbell Air Seal Fit Size	
103.	Finial Endbell Air Seal Fit Size	
104.	ODE Endbell Fit	
105.	ODE Initial Endbell Fit Size 1	
106.	ODE Initial Endbell Fit Size 2	
107.	ODE Initial Endbell Fit Size 3	
108.	ODE Final Endbell Fit Size 1	
109.	ODE Final Endbell Fit Size 2	
110.	ODE Final Endbell Fit Size 3	

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

111.	ODE Endbell Fit Insulated
112.	ODE Endbell Air Seal Fit
113.	ODE Initial Endbell Seal Fit Size
114.	ODE Finial Endbell Seal Fit Size
115.	Foot Flatness
116.	Foot Condition
117.	Flange Condition
118.	Service Technician
Balancing Report	
119.	Balance Type
120.	Balance Operating Speed
121.	Start Left End
122.	Start Right End
123.	Balancing Specification
124.	Finish Left End
125.	Finish Right End
126.	Service Technician
Assembly and Final Test	
127.	Meggar Testing Reading
128.	Surge Test
129.	Hi-Pot
130.	Winding Resistance 1-2
131.	Winding Resistance 2-3
132.	Winding Resistance 1-3
133.	Test Run Voltage Phase A
134.	Test Run Amps A
135.	Test Run Voltage Phase B
136.	Test Run Amps B
137.	Test Run Voltage Phase C
138.	Test Run Amps C
139.	DE Horizontal Vibration Reading
140.	DE Vertical Vibration Reading
141.	DE Axial Vibration Reading
142.	ODE Horizontal Vibration Reading
143.	ODE Vertical Vibration Reading
144.	ODE Axial Vibration Reading
145.	Ambient Temp at start of Test Run
146.	Temp at 5 minutes
147.	Temp at 10 minutes
148.	Temp at 15 minutes
149.	Temp at 20 minutes
150.	Temp at 25 minutes
151.	Temp at 30 minutes
152.	Temp at 35 minutes
153.	Temp at 40 minutes
154.	Temp at 45 minutes
155.	Temp at 50 minutes
156.	Temp at 55 minutes

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

157. Temp at 60 minutes
158. Motor Paint
159. Service Technician