

[Close this window](#)

SDS

**Common Name:** PVTLBL SSPR 6PK DMKT 70103F SFTY RED, 257619**Manufacturer:** RUST-OLEUM**SDS Revision Date:** 8/9/2018**SDS Format:** GHS-US**Item Number(s):** 335CX2, 6FGJ1**Manufacturer Model Number(s):**

## SDS Table of Contents

Click the desired link below to jump directly to that section in the SDS.

- [1. IDENTIFICATION](#)
- [2. HAZARD IDENTIFICATION](#)
- [3. COMPOSITION / INFORMATION ON INGREDIENTS](#)
- [4. FIRST-AID MEASURES](#)
- [5. FIRE-FIGHTING MEASURES](#)
- [6. ACCIDENTAL RELEASE MEASURES](#)
- [7. HANDLING AND STORAGE](#)
- [8. EXPOSURE CONTROLS / PERSONAL PROTECTION](#)
- [9. PHYSICAL AND CHEMICAL PROPERTIES](#)
- [10. STABILITY AND REACTIVITY](#)
- [11. TOXICOLOGICAL INFORMATION](#)
- [12. ECOLOGICAL INFORMATION](#)
- [13. DISPOSAL INFORMATION](#)
- [14. TRANSPORT INFORMATION](#)
- [15. REGULATORY INFORMATION](#)
- [16. OTHER INFORMATION](#)

DATE PRINTED: 8/9/2018

SAFETY DATA SHEET

RUST-OLEUM CORPORATION

TRUSTED QUALITY SINCE 1921

WWW.RUSTOLEUM.COM

## 1. IDENTIFICATION



PRODUCT NAME: PVTLBL SSPR 6PK DMKT 70103F SFTY RED

PRODUCT IDENTIFIER: 257619

RECOMMENDED USE: TOPCOAT/AEROSOL

REVISION DATE: 8/9/2018

SUPERCEDES DATE: 7/23/2018

SUPPLIER:

RUST-OLEUM CORPORATION  
11 HAWTHORN PARKWAY  
VERNON HILLS, IL 60061  
USA

RUST-OLEUM CANADA (ROCA):  
200 CONFEDERATION PARKWAY  
CONCORD, ON L4K 4T8  
CANADA

EMERGENCY PHONE: 800-387-3625

MANUFACTURER:  
RUST-OLEUM CORPORATION  
11 HAWTHORN PARKWAY  
VERNON HILLS, IL 60061  
USA

PREPARER: REGULATORY DEPARTMENT

EMERGENCY TELEPHONE:  
24 HOUR HOTLINE: 847-367-7700

## 2. HAZARD IDENTIFICATION



CLASSIFICATION:

SYMBOL(S) OF PRODUCT:  
FLAME  
EXCLAMATION MARK  
HEALTH HAZARD  
GAS CYLINDER

SIGNAL WORD: DANGER

POSSIBLE HAZARDS:  
36% OF THE MIXTURE CONSISTS OF INGREDIENT(S) OF UNKNOWN ACUTE TOXICITY.

GHS HAZARD STATEMENTS:

FLAMMABLE AEROSOL, CATEGORY 1:  
H222: EXTREMELY FLAMMABLE AEROSOL.

COMPRESSED GAS:  
H280: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

CARCINOGENICITY, CATEGORY 2:  
H351: SUSPECTED OF CAUSING CANCER.

STOT, SINGLE EXPOSURE, CATEGORY 3, NE:  
H336: MAY CAUSE DROWSINESS OR DIZZINESS.

EYE IRRITATION, CATEGORY 2:  
H319: CAUSES SERIOUS EYE IRRITATION.

GHS LABEL PRECAUTIONARY STATEMENTS:  
P210:  
KEEP AWAY FROM HEAT, HOT SURFACES, SPARKS, OPEN FLAMES AND OTHER IGNITION SOURCES. NO SMOKING.

P211: DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE.

P251: DO NOT PIERCE OR BURN, EVEN AFTER USE.

P410+P412:

PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING  
50 DEG. C / 122 DEG. F.

P410+P403: PROTECT FROM SUNLIGHT. STORE IN A WELL-VENTILATED PLACE.

P201: OBTAIN SPECIAL INSTRUCTIONS BEFORE USE.

P280:

WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION.

P308+P313:

IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ATTENTION.

P405: STORE LOCKED UP.

P501:

DISPOSE OF CONTENTS/CONTAINER IN ACCORDANCE WITH LOCAL, REGIONAL AND  
NATIONAL REGULATIONS.

P261: AVOID BREATHING DUST/FUME/GAS/MIST/VAPORS/SPRAY.

P271: USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.

P304+P340:

IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING.

P312: CALL A POISON CENTER OR DOCTOR/PHYSICIAN IF YOU FEEL UNWELL.

P403+P233: STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED.

P264: WASH HANDS THOROUGHLY AFTER HANDLING.

P305+P351+P338:

IF IN EYES:

RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF  
PRESENT AND EASY TO DO. CONTINUE RINSING.

P337+P313:

IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS



#### HAZARDOUS SUBSTANCES:

CHEMICAL NAME	CAS-NO.	WT. %	GHS SYMBOLS	GHS STATEMENTS
ACETONE	67-64-1	33	GHS02-GHS07	H225-319-332-336
PROPANE	74-98-6	23	GHS04	H280
N-BUTANE	106-97-8	11	GHS04	H280
HYDROTREATED LIGHT DISTILLATE	64742-47-8	5.1	GHS08	H304
NAPHTHA, PETROLEUM, HYDROTREATED LIGHT	64742-49-0	4.6	GHS08	H304
N-BUTYL ACETATE	123-86-4	4.4	GHS02-GHS07	H226-336
SOLVENT NAPHTHA, LIGHT AROMATIC	64742-95-6	3.2	GHS07-GHS08	H304-332
1,2,4-TRIMETHYLBENZENE	95-63-6	1.6	GHS02-GHS07-	H226-304-315-

			GHS08	319-332-335
NAPHTHA (PETROLEUM), HEAVY AROMATIC	64742-94-5	0.6	GHS07-GHS08	H304-312
TITANIUM DIOXIDE	13463-67-7	0.4	NOT AVAILABLE	NOT AVAILABLE
ETHYLBENZENE	100-41-4	0.2	GHS02-GHS07- GHS08	H225-304-332- 351-373

#### 4. FIRST-AID MEASURES



##### FIRST AID - EYE CONTACT:

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. DO NOT ALLOW RUBBING OF EYES OR KEEPING EYES CLOSED.

##### FIRST AID - SKIN CONTACT:

WASH SKIN WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.

##### FIRST AID - INHALATION:

IF YOU EXPERIENCE DIFFICULTY IN BREATHING, LEAVE THE AREA TO OBTAIN FRESH AIR. IF CONTINUED DIFFICULTY IS EXPERIENCED, GET MEDICAL ASSISTANCE IMMEDIATELY. REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET IMMEDIATE MEDICAL ATTENTION. DO NOT USE MOUTH-TO-MOUTH RESUSCITATION.

##### FIRST AID - INGESTION:

##### ASPIRATION HAZARD:

DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH BECAUSE THIS MATERIAL CAN ENTER THE LUNGS AND CAUSE SEVERE LUNG DAMAGE. GET IMMEDIATE MEDICAL ATTENTION. IF SWALLOWED, GET MEDICAL ATTENTION.

#### 5. FIRE-FIGHTING MEASURES



##### EXTINGUISHING MEDIA:

ALCOHOL FILM FORMING FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER FOG

##### UNUSUAL FIRE AND EXPLOSION HAZARDS:

FLASH POINT IS LESS THAN 20 DEG. F. EXTREMELY FLAMMABLE LIQUID AND VAPOR! WATER SPRAY MAY BE INEFFECTIVE. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. VAPORS CAN TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. PERFORATION OF THE PRESSURIZED CONTAINER MAY CAUSE BURSTING OF THE CAN. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT DUE TO BUILDUP OF STEAM. NO UNUSUAL FIRE OR EXPLOSION HAZARDS NOTED.

##### SPECIAL FIREFIGHTING PROCEDURES:

EVACUATE AREA AND FIGHT FIRE FROM A SAFE DISTANCE. FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILDUP AND POSSIBLE AUTOIGNITION OR EXPLOSION. USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL. CONTAINERS MAY EXPLODE WHEN HEATED.

SPECIAL FIRE AND EXPLOSION HAZARD (COMBUSTIBLE DUST): NO INFORMATION

#### 6. ACCIDENTAL RELEASE MEASURES



## STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS. DISPOSE OF ACCORDING TO LOCAL, STATE (PROVINCIAL) AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. ISOLATE THE HAZARD AREA AND DENY ENTRY TO UNNECESSARY AND UNPROTECTED PERSONNEL. VENTILATE AREA, ISOLATE SPILLED MATERIAL, AND REMOVE WITH INERT ABSORBENT. DISPOSE OF CONTAMINATED ABSORBENT, CONTAINER, AND UNUSED CONTENTS IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

**7. HANDLING AND STORAGE**

## HANDLING:

WASH THOROUGHLY AFTER HANDLING. WASH HANDS BEFORE EATING. USE ONLY IN A WELL-VENTILATED AREA. FOLLOW ALL SDS AND LABEL PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED BECAUSE IT MAY RETAIN PRODUCT RESIDUES. AVOID BREATHING FUMES, VAPORS, OR MIST. REMOVE CONTAMINATED CLOTHING AND LAUNDRER BEFORE REUSE. USE ONLY WITH ADEQUATE VENTILATION. AVOID CONTACT WITH EYES, SKIN AND CLOTHING.

## STORAGE:

KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. CONTENTS UNDER PRESSURE. DO NOT STORE ABOVE 120 DEG. F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF FLAMMABLE AEROSOLS. CONTENTS UNDER PRESSURE. DO NOT EXPOSE TO HEAT OR STORE ABOVE 120 DEG. F. PRODUCT SHOULD BE STORED IN TIGHTLY SEALED CONTAINERS AND PROTECTED FROM HEAT, MOISTURE, AND FOREIGN MATERIALS. STORE IN A DRY, WELL VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. KEEP AWAY FROM HEAT, SPARKS, FLAME AND SOURCES OF IGNITION. AVOID EXCESS HEAT.

ADVICE ON SAFE HANDLING OF COMBUSTIBLE DUST: NO INFORMATION

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

CHEMICAL NAME	CAS-NO.	WEIGHT % LESS THAN
ACETONE	67-64-1	35.0
PROPANE	74-98-6	25.0
N-BUTANE	106-97-8	15.0
HYDROTREATED LIGHT DISTILLATE	64742-47-8	10.0
NAPHTHA, PETROLEUM, HYDROTREATED LIGHT	64742-49-0	5.0
N-BUTYL ACETATE	123-86-4	5.0
SOLVENT NAPHTHA, LIGHT AROMATIC	64742-95-6	5.0
1,2,4-TRIMETHYLBENZENE	95-63-6	5.0
NAPHTHA (PETROLEUM), HEAVY AROMATIC	64742-94-5	1.0
TITANIUM DIOXIDE	13463-67-7	1.0
ETHYLBENZENE	100-41-4	1.0

CHEMICAL NAME	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING
---------------	------------------	-------------------	-----------------	---------------------

ACETONE	250 PPM	500 PPM	1000 PPM	N.E.
PROPANE	N.E.	N.E.	1000 PPM	N.E.
N-BUTANE	N.E.	1000 PPM	N.E.	N.E.
HYDROTREATED LIGHT DISTILLATE	N.E.	N.E.	N.E.	N.E.
NAPHTHA, PETROLEUM HYDROTREATED LIGHT	N.E.	N.E.	N.E.	N.E.
N-BUTYL ACETATE	50 PPM	150 PPM	150 PPM	N.E.
SOLVENT NAPHTHA, LIGHT AROMATIC	N.E.	N.E.	N.E.	N.E.
1,2,4-TRIMETHYLBENZENE	N.E.	N.E.	N.E.	N.E.
NAPHTHA (PETROLEUM), HEAVY AROMATIC	N.E.	N.E.	N.E.	N.E.
TITANIUM DIOXIDE	10 MG/M3	N.E.	15 MG/M3	N.E.
ETHYLBENZENE	20 PPM	N.E.	100 PPM	N.E.

#### PERSONAL PROTECTION:

#### ENGINEERING CONTROLS:

USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO CONTROL AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. USE EXPLOSION-PROOF VENTILATION EQUIPMENT. PREVENT BUILD-UP OF VAPORS BY OPENING ALL DOORS AND WINDOWS TO ACHIEVE CROSS-VENTILATION. PROVIDE GENERAL DILUTION OF LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP TLV OF HAZARDOUS INGREDIENTS BELOW ACCEPTABLE LIMITS.

#### RESPIRATORY PROTECTION:

A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE. A NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE LIMITS.

#### SKIN PROTECTION:

USE IMPERVIOUS GLOVES TO PREVENT SKIN CONTACT AND ABSORPTION OF THIS MATERIAL THROUGH THE SKIN. NITRILE OR NEOPRENE GLOVES MAY AFFORD ADEQUATE SKIN PROTECTION. USE GLOVES TO PREVENT PROLONGED SKIN CONTACT.

#### EYE PROTECTION:

USE SAFETY EYEWEAR DESIGNED TO PROTECT AGAINST SPLASH OF LIQUIDS.

#### OTHER PROTECTIVE EQUIPMENT:

REFER TO SAFETY SUPERVISOR OR INDUSTRIAL HYGIENIST FOR FURTHER INFORMATION REGARDING PERSONAL PROTECTIVE EQUIPMENT AND ITS APPLICATION. REFER TO SAFETY SUPERVISOR OR INDUSTRIAL HYGIENIST FOR FURTHER GUIDANCE REGARDING TYPES OF PERSONAL PROTECTIVE EQUIPMENT AND THEIR APPLICATIONS.

#### HYGIENIC PRACTICES:

WASH THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING OR SMOKING. REMOVE CONTAMINATED CLOTHING IMMEDIATELY AND LAUNDRY BEFORE REUSE.

ENGINEERING MEASURES FOR COMBUSTIBLE DUST: NO INFORMATION

## 9. PHYSICAL AND CHEMICAL PROPERTIES



APPEARANCE: AEROSOLIZED MIST

PHYSICAL STATE: LIQUID

ODOR: SOLVENT LIKE

ODOR THRESHOLD: N.E.

RELATIVE DENSITY: 0.701

PH: N.A.

FREEZE POINT, DEG. C: N.D.

VISCOSITY: N.D.

SOLUBILITY IN WATER: SLIGHT

PARTITION COEFFICIENT, N-OCTANOL/WATER: N.D.

DECOMPOSITION TEMP., DEG. C: N.D.

BOILING RANGE, DEG. C: -37 - 204

EXPLOSIVE LIMITS, VOL%: 0.9 - 13.0

FLAMMABILITY: SUPPORTS COMBUSTION

FLASH POINT, DEG. C: -96

EVAPORATION RATE: FASTER THAN ETHER

AUTO-IGNITION TEMP., DEG. C: N.D.

VAPOR DENSITY: HEAVIER THAN AIR

VAPOR PRESSURE: N.D.

(SEE "OTHER INFORMATION" SECTION FOR ABBREVIATION LEGEND)

## 10. STABILITY AND REACTIVITY



CONDITIONS TO AVOID:

AVOID TEMPERATURES ABOVE 120 DEG. F (49 DEG. C). AVOID ALL POSSIBLE SOURCES OF IGNITION.

INCOMPATIBILITY:

INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS AND STRONG ALKALIES.

HAZARDOUS DECOMPOSITION:

BY OPEN FLAME, CARBON MONOXIDE AND CARBON DIOXIDE. WHEN HEATED TO DECOMPOSITION, IT EMITS ACRID SMOKE AND IRRITATING FUMES. CONTAINS SOLVENTS WHICH MAY FORM CARBON MONOXIDE, CARBON DIOXIDE, AND FORMALDEHYDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR UNDER NORMAL CONDITIONS.

STABILITY: THIS PRODUCT IS STABLE UNDER NORMAL STORAGE CONDITIONS.

## 11. TOXICOLOGICAL INFORMATION



EFFECTS OF OVEREXPOSURE - EYE CONTACT: CAUSES SERIOUS EYE IRRITATION

EFFECTS OF OVEREXPOSURE - SKIN CONTACT:

SUBSTANCE MAY CAUSE SLIGHT SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN IRRITATION. MAY CAUSE SKIN IRRITATION. ALLERGIC REACTIONS ARE POSSIBLE.

EFFECTS OF OVEREXPOSURE - INHALATION:

HARMFUL IF INHALED. HIGH GAS, VAPOR, MIST OR DUST CONCENTRATIONS MAY BE HARMFUL IF INHALED. AVOID BREATHING FUMES, SPRAY, VAPORS, OR MIST. HIGH VAPOR CONCENTRATIONS ARE IRRITATING TO THE EYES, NOSE, THROAT AND LUNGS. PROLONGED OR EXCESSIVE INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION.

EFFECTS OF OVEREXPOSURE - INGESTION:

ASPIRATION HAZARD IF SWALLOWED; CAN ENTER LUNGS AND CAUSE DAMAGE. HARMFUL IF SWALLOWED.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:

IARC LISTS ETHYLBENZENE AS A POSSIBLE HUMAN CARCINOGEN (GROUP 2B). CONTAINS TITANIUM DIOXIDE. TITANIUM DIOXIDE IS LISTED AS A GROUP 2B-"POSSIBLY CARCINOGENIC TO HUMANS" BY IARC. NO SIGNIFICANT EXPOSURE TO TITANIUM DIOXIDE IS THOUGHT TO OCCUR DURING THE USE OF PRODUCTS IN WHICH TITANIUM DIOXIDE IS BOUND TO OTHER MATERIALS, SUCH AS IN PAINTS DURING BRUSH APPLICATION OR DRYING. RISK OF OVEREXPOSURE DEPENDS ON DURATION AND LEVEL OF EXPOSURE TO DUST FROM REPEATED SANDING OF SURFACES OR SPRAY MIST AND THE ACTUAL CONCENTRATION OF TITANIUM DIOXIDE IN THE FORMULA. (REF: IARC MONOGRAPH, VOL. 93, 2010) MAY CAUSE CENTRAL NERVOUS SYSTEM DISORDER (E.G., NARCOSIS INVOLVING A LOSS OF COORDINATION, WEAKNESS, FATIGUE, MENTAL CONFUSION, AND BLURRED VISION) AND/OR DAMAGE. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. HIGH CONCENTRATIONS MAY LEAD TO CENTRAL NERVOUS SYSTEM EFFECTS (DROWSINESS, DIZZINESS, NAUSEA, HEADACHES, PARALYSIS, AND BLURRED VISION) AND/OR DAMAGE.

PRIMARY ROUTE(S) OF ENTRY:

EYE CONTACT, INGESTION, INHALATION, SKIN ABSORPTION, SKIN CONTACT

ACUTE TOXICITY VALUES:

THE ACUTE EFFECTS OF THIS PRODUCT HAVE NOT BEEN TESTED. DATA ON INDIVIDUAL COMPONENTS ARE TABULATED BELOW:

CAS-NO.	CHEMICAL NAME	ORAL LD50	DERMAL LD50	VAPOR LC50
67-64-1	ACETONE	5800 MG/KG RAT	>15700 MG/KG RABBIT	50.1 MG/L RAT
106-97-8	N-BUTANE	N.E.	N.E.	658 MG/L RAT
64742-47-8	HYDROTREATED LIGHT DISTILLATE	>5000 MG/KG RAT	>2000 MG/KG RABBIT	>5000 MG/L RAT
64742-49-0	NAPHTHA, PETROLEUM, HYDROTREATED LIGHT	>5000 MG/KG RAT	>3160 MG/KG RABBIT	>4951 MG/L RAT
123-86-4	N-BUTYL ACETATE	10768 MG/KG RAT	>17600 MG/KG RABBIT	>21 MG/L RAT
64742-95-6	SOLVENT NAPHTHA, LIGHT AROMATIC	8400 MG/KG RAT	>2000 MG/KG RABBIT	N.E.
95-63-6	1,2,4-TRIMETHYL- BENZENE	3280 MG/KG RAT	>3160 MG/KG RABBIT	18 MG/L RAT
64742-94-5	NAPHTHA (PETROLEUM), HEAVY AROMATIC	>5000 MG/KG RAT	>1795 MG/KG RABBIT	36 MG/L RAT



13463-67-7	TITANIUM DIOXIDE	>10000 MG/KG RAT	2500 MG/KG	N.E.
100-41-4	ETHYLBENZENE	3500 MG/KG RAT	15400 MG/KG RABBIT	17.4 MG/L RAT

N.E. - NOT ESTABLISHED

## 12. ECOLOGICAL INFORMATION



### ECOLOGICAL INFORMATION:

PRODUCT IS A MIXTURE OF LISTED COMPONENTS. PRODUCT IS A MIXTURE OF LISTED COMPONENTS.

## 13. DISPOSAL INFORMATION



### DISPOSAL INFORMATION:

DISPOSE OF MATERIAL IN ACCORDANCE TO LOCAL, STATE, AND FEDERAL REGULATIONS AND ORDINANCES. DO NOT ALLOW TO ENTER WATERWAYS, WASTEWATER, SOIL, STORM DRAINS OR SEWER SYSTEMS. DO NOT INCINERATE CLOSED CONTAINERS. THIS PRODUCT AS SUPPLIED IS A USEPA DEFINED IGNITABLE HAZARDOUS WASTE. DISPOSE OF UNUSABLE PRODUCT AS A HAZARDOUS WASTE (D001) IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATION.

## 14. TRANSPORT INFORMATION



	DOMESTIC (USDOT)	INTERNATIONAL (IMDG)	AIR (IATA)	TDG (CANADA)
UN NUMBER	N.A.	1950	1950	N.A.
PROPER SHIPPING NAME	PAINT PRODUCTS IN LIMITED QUANTITIES	AEROSOLS	AEROSOLS	PAINT PRODUCTS IN LIMITED QUANTITIES
HAZARD CLASS	N.A.	2.1	2.1	N.A.
PACKING GROUP	N.A.	N.A.	N.A.	N.A.
LIMITED QUANTITY	YES	YES	YES	YES

## 15. REGULATORY INFORMATION



### U.S. FEDERAL REGULATIONS:

#### CERCLA - SARA HAZARD CATEGORY:

THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA 'HAZARD CATEGORIES' PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES:  
GAS UNDER PRESSURE, CARCINOGENICITY, SERIOUS EYE DAMAGE OR EYE IRRITATION, SPECIFIC TARGET ORGAN TOXICITY (SINGLE OR REPEATED EXPOSURE)

#### SARA SECTION 313:

THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENT AND

REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:

CHEMICAL NAME	CAS-NO.
1,2,4-TRIMETHYLBENZENE	95-63-6
ETHYLBENZENE	100-41-4

TOXIC SUBSTANCES CONTROL ACT:

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE UNITED STATES: NO TSCA 12(B) COMPONENTS EXIST IN THIS PRODUCT.

## 16. OTHER INFORMATION



### HMIS RATINGS:

HEALTH	2*
FLAMMABILITY	4
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X

### NFPA RATINGS:

HEALTH	2
FLAMMABILITY	4
INSTABILITY	0

MAXIMUM INCREMENTAL REACTIVITY: 0.94

SDS REVISION DATE: 8/9/2018

REASON FOR REVISION: SUBSTANCE CHEMICAL NAME CHANGED

### LEGEND:

N.A. - NOT APPLICABLE  
N.E. - NOT ESTABLISHED  
N.D. - NOT DETERMINED

THE MANUFACTURER BELIEVES, TO THE BEST OF ITS KNOWLEDGE, INFORMATION AND BELIEF, THE INFORMATION CONTAINED HEREIN TO BE ACCURATE AND RELIABLE AS OF THE DATE OF THIS SAFETY DATA SHEET. HOWEVER, BECAUSE THE CONDITIONS OF HANDLING, USE, AND STORAGE OF THESE MATERIALS ARE BEYOND OUR CONTROL, WE ASSUME NO RESPONSIBILITY OR LIABILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE INCURRED BY THE USE OF THESE MATERIALS. THE MANUFACTURER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, REGARDING THE ACCURACY OR RELIABILITY OF THE DATA OR RESULTS OBTAINED FROM THEIR USE. ALL MATERIALS MAY PRESENT UNKNOWN HAZARDS AND SHOULD BE USED WITH CAUTION. THE INFORMATION AND RECOMMENDATIONS IN THIS MATERIAL SAFETY DATA SHEET ARE OFFERED FOR THE USERS' CONSIDERATION AND EXAMINATION. IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE FINAL SUITABILITY OF THIS INFORMATION AND TO COMPLY WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.