

Job Information

Job #: 139446 Date: March 29, 2019

Priority: Authorized OT: No Authorized by:

Customer Information

Name: Ace Pump Corporation Reason:

Contact: Elizabeth Taliaferro Motor#: PO#:

Application: Special notes:

Name Plate Information

Manufacturer: GE Enclosure: Open Drop Proof **Enclosure Type image**

(ODP)

5K224E7 Serial#: NG19761 Model#:

Service Factor: 224 Frame:

Horsepower/kW: 2 Rated RPM: 1735

Rated Amps: 5.84/2.92 Rated Voltage: 220/440

Phase: 3 Cycles: 60

Special design:

No

Nameplate DE ODE F1 F2 Top













WEST TENNESSEE



Mechanical Inspection

Type of grounding device:

Shaft runout(TIR-Inbound):

Inspect bolt holes and fasteners. Validate correct fasteners.

Does the shaft turn freely?: Contaminant(s): Yes None

> Shaft rotation: Bi-directional Contaminant(s) Amt: None

Shaft grounding device No Contaminant Image:

present?:

.0000

Bearings DE: Worn Bearings DE make: Other

Insulated: Bearing DE Size: 6306 No

Bearings ODE: Worn Bearings ODE make: Other

Bearing Type: Bearing ODE Size: Ball 6306

Thermal Protection: Bearings Retainer: Yes No

Retainer condition: Thermal Protection Type:

Bearing Type Image



Bearing Make Image



Bearing Retainer Image



Thermal Protection





Mechanical Inspection (Continued)

Lubrication Type: Grease Thermal Protection device DE: N/A

Lubrication brand inbound: Unknown Thermal Protection device ODE: N/A

Lubrication brand outbound: Unknown

Grease Amt DE: 1/2 Grease Cond. DE: Hard

Grease Amt ODE: 1/2 Grease Cond. ODE: Hard

Seals DE type: N/A Seals Image:

Seals DE size:

N/A

N/A

Seals Image 2:

Seals ODE size:

Seals ODE type:

Seals ODE (inbound) condition

Seals DE (inbound) condition:

Shaft damage cause: None Shaft Image:

Fax 901-873-5301



Mechanical Inspection (Continued)





Bushings/sleeves image:



Water jacket:

N/A

Fan:

N/A

Frame cond.:

Good







Motor Mount Position:

Horizontal/Foot mount

Endbell type:

Endbell Image:

Single piece

Missing parts?

☐ J-Box cover

O-rings

☐ J-Box

☐ HH cover

Glands

✓ None

Other missing parts





Mechanical Inspection (Continued)

Air Gap Meaurements (N/A on Single Piece Endbell)

Does Air Gap Meet Customer or EASA spec(<10% variation)?

DE @ 0 ODE @ 0 -

DE @ 90 ODE @ 90

DE @ 180 ODE @ 180

DE @ 270 ODE @ 270

AC Electrical Inspection

Number of leads: 9 Terminal Markings:

Length of leads: 3" REF: NEMA Stds. MG 1-2009, Rev. 1-2010, 2.41-Terminal

Markings Identified By Color:

Size of leads: 12 1-Blue 5-Black P1-No color assigned

2-White 6-No color assigned P2-Brown
3-Orange 7-No color assigned

Lead condition: Good 4-Yellow 8-Red

Connections As Received: Low voltage

Lug type: N/A

Lug Condition: — Terminal Lugs

Lug size:

Lug Attachment: —



AC Electrical Inspection (Continued)

Rotor Type: Cast Aluminum

Ok

Num rotor bars: 45

Num broken bars: 0

Rotor



Rotor Test Results

Rotor Condition:

Visual: Pass Growler: Pass Single phase: Pass

Stator type: Factory If other, stator type:

Stator condition: Ground If other, stator condition: Insulation weak

Failure location: Other If other, stator failure: Insulation failure

Stator Image: Failure Image:







AC Electrical Inspection (Continued)


Winding color: Dull black Winding image Winding Thermal Protection: Yes

Winding condition: Solid

Winding Thermal ___ Protection DE:

Winding Thermal Protection ODE:

Stator test results: Rewind



Megs incoming: Bad Surge incoming: Good Hi-pot incoming: Good

Winding Resistance Incoming

Phases A to B Phases B to C Phases C to A Resistive imbalance

Incoming

Leads/jumpers: Ok Lead jumper Image. :

If other, leads/jumpers:





Conclusion

Component Failure

Megger failure.

Cause of Failure

Insulation failure

Comments

Service Tech name: Kelly Felts

Service Tech signature:

Fax 901-873-5301