

Job Information

Job #: 143043 Date: August 10, 2020

Priority: — Authorized OT: No Authorized by:

Customer Information

Name: Ktg Reason:

Contact: Motor#: PO#:

Application: – Special notes:

Name Plate Information

Manufacturer: Enclosure: Totally Enclosed Enclosure Type image

Fan Cooled

Serial#: Model#:

Service Factor: Frame:

Horsepower/kW: 75 Rated RPM: 1780

Rated Amps: 169/84.9 Rated Voltage: 230/460

Phase: 3 Cycles: 60

Special design: No

Nameplate DE ODE F1 F2 Top













Fax 901-873-5301



Mechanical Inspection

Type of grounding device:

Shaft runout(TIR-Inbound):

Bearings DE:

Worn

Inspect bolt holes and fasteners. Validate correct fasteners.

Does the shaft turn freely?: Yes Contaminant(s): Water

Shaft rotation: Bi-directional Contaminant(s) Amt: Full

Shaft grounding device No Contaminant Image:

present?:

Insulated: No Bearing DE Size: 6312 c3

Bearings ODE: Worn Bearings ODE make: NACHI

Bearing Type: Ball Bearing ODE Size: 6313 c3

Bearings Retainer: Yes Thermal Protection: No

Retainer condition: Good Thermal Protection Type: —

Bearing Type Image



Bearing Make Image



Bearing Retainer Image

Bearings DE make:

NACHI



Thermal Protection





Mechanical Inspection (Continued)

Lubrication Type: Grease Thermal Protection device DE: N/A

Lubrication brand inbound: Unknown Thermal Protection device ODE: N/A

Lubrication brand outbound: Mobile Polyrex EM

Grease Amt DE: Full Grease Cond. DE: Watery

Grease Amt ODE: Full Grease Cond. ODE: Watery

Seals DE type: N/A Seals Image:

Seals DE size:

Slinger

Seals Image 2:

Seals ODE size:

Seals ODE type:

Seals ODE (inbound) condition

Seals DE (inbound) condition:

Shaft damage cause: None Shaft Image:

Fax 901-873-5301

CENTRAL ARKANSAS




Mechanical Inspection (Continued)

Brg. Image:



Bushings/sleeves image:



Water jacket:


N/A



Ok

Frame cond.:

Good



-an:



Motor Mount Position:

Horizontal/Foot mount

Endbell type:

Endbell Image:

Single piece

Missing parts?

J-Box cover

O-rings

✓ J-Box

☐ HH cover

Glands

☐ None

Other missing parts



Mechanical Inspection (Continued)

Air Gap Meaurements (N/A on Single Piece Endbell)

Does Air Gap Meet Customer or EASA

spec(<10% variation)?

DE @ 0 ODE @ 0 -

DE @ 90 ODE @ 90

DE @ 180 ODE @ 180

DE @ 270 ODE @ 270

AC Electrical Inspection

Number of leads: 9 Terminal Markings: 1-9

Length of leads: 10" REF: NEMA Stds. MG 1-2009, Rev. 1-2010, 2.41-Terminal

Markings Identified By Color:

Size of leads: 2 1-Blue 5-Black P1-No color assigned

2-White 6-No color assigned P2-Brown

3-Orange 7-No color assigned

Lead condition: Worn 4-Yellow 8-Red

Connections As Received: High voltage Lug type:

Lug Condition: Good Terminal Lugs

Lug size:

Lug Attachment: —



AC Electrical Inspection (Continued)

Rotor Type: Cast Aluminum

Ok

Num rotor bars: 47

Num broken bars: 0

Rotor



Rotor Test Results

Rotor Condition:

Visual: Pass Growler: Pass Single phase: Pass

Stator type: Factory If other, stator type:

Stator condition: Ok If other, stator condition:

Failure location: Coil head If other, stator failure:

Stator Image: Failure Image:







AC Electrical Inspection (Continued)


Winding color: Still has color Winding image Winding Thermal Protection: No

Winding condition: Solid

Winding Thermal ___ Protection DE:

Winding Thermal Protection ODE:

Stator test results: Rewind



Megs incoming: Good Surge incoming: Good Hi-pot incoming: Good

Winding Resistance Incoming

Phases A to B Phases B to C Phases C to A Resistive imbalance

Incoming

Leads/jumpers: Ok Lead jumper Image. :

If other, leads/jumpers:





Conclusion

Winding

Cause of Failure

Water

Comments

Mother was full of water and the winding is blown

Service Tech name: Shawn

Service Tech signature:

1/2___