



AC Recondition Repair Report

FolderID: 97414
FormID: 9086774

Delta Plastics (11016)
8801 Frazier Pike
Little Rock, AR 72206

Priorities Found: 3 - High 5 - Good

General			
1. Job Number	97414		
2. Report Date			
3. Customer	DELTA PLASTICS LR		
Name Plate Information			
4. Manufacturer	BALDOR		
5. Model			
6. Serial Number	B9126122-020001 JQ		
7. Horsepower	150 HP		
8. KW			
9. Volts	460 Volts		
10. Amps	180		
11. RPM	1750		
12. Frame	URL2882Z		P12
13. Enclosure	DP		P13
14. Cycles	60		
15. Phase	3		
16. Service Factor	1.0		
17. Motor Mount Position			
Initial Inspection			
18. Number of Leads	6		P18
19. Lead Length	12 Inches		
20. Lead Size			
21. Lead Condition	(P) Pass		
22. Lead Markings	1,2,3		
23. Lug Size, Condition, and Type	N/a		
24. Winding RTD's			
25. Winding Rtd's Condition			
26. Shaft Run Out			
27. Does Shaft Turn Freely	no		P27
28. Does Shaft Have Visible Damage	yes		P28
29. Bearing Rtd's			
30. Bearing Rtd's Condition			
31. Contamination			P31
Yes			
32. Frame Condition	(P) Pass		

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

33.	Fan Condition	(NA) Not Applicable	
34.	Broken or missing components		
	None		
Initial Electric Test			
35.	Resistance to Ground	Mohm	
36.	Winding Resistance 1-2		
37.	Winding Resistance 2-3		
38.	Winding Resistance 1-3		
39.	Resistive Imbalance		
40.	Hi-Pot		
	41. Surge Test	(F) Fail	P41
42.	Stator Condition		
43.	Failure Location		P43
Initial Rotor Inspection			
44.	Rotor Type	squirrel cage	P44
45.	Air Gap <10% Variation		
46.	Number of Rotor Bars		
47.	Number of Broken Rotor Bars		
48.	Growler Test		
	49. Rotor Condition	(P) Pass	P49
Mechanical Inspection			
50.	Bearing Manufacture	nachi	
51.	Bearing DE Size	nu215/C3	P51
52.	Bearing DE Type		
53.	DE Bearing Qty.		
54.	Bearing ODE Size	6211/C3	P54
55.	Bearing ODE Type	ball bearing	
56.	ODE Bearing Qty.	1	
57.	Insulated Bearing	no	
58.	Lubrication Type	polyrex	
	59. Grease Condition	(F) Fail	P59
	60. Bearing Retainers	(Y) Yes	P60
61.	Shaft Grounding Device	(NA) Not Applicable	
62.	DE Seal	(NA) Not Applicable	
63.	DE Seal Type/Size		
64.	ODE Seal	(NA) Not Applicable	
65.	ODE Seal Type/Size		
Root Cause of Failure			
66.	Component Failure	D.e. bearing	
67.	Cause of Failure	<i>Lack of lubricant in D.E bearing caused excessive failure and contaminated grease in the O.d.e bearing contributed to premature failure of the bearings and is responsible for bearing pieces embedded in the motor windings.</i>	
68.	Comments		



Machine Fit Inspection Report



70.	Shaft Run Out		
71.	Initial Shaft Run Out		
72.	Final Shaft Run Out		
73.	DE Bearing Shaft Fit	(F) Fail	P73
74.	DE Initial Shaft Bearing Fit Size 1	"	
75.	DE Initial Shaft Bearing Fit Size 2		
76.	DE Initial Shaft Bearing Fit Size 3		
77.	DE Finial Shaft Bearing Fit Size 1	2.9537 "	P77
	<i>Belzona shaft fit</i>		
78.	DE Finial Shaft Bearing Fit Size 2	2.9537 "	
79.	DE Finial Shaft Bearing Fit Size 3	2.9538 "	
80.	ODE Bearing Shaft Fit		
81.	ODE Initial Shaft Bearing Fit Size 1	"	
82.	ODE Initial Shaft Bearing Fit Size 2		
83.	ODE Initial Shaft Bearing Fit Size 3		
84.	ODE Finial Shaft Bearing Fit Size 1		
85.	ODE Finial Shaft Bearing Fit Size 2		
86.	ODE Finial Shaft Bearing Fit Size 3		
87.	DE Air Seal Shaft Fit		
88.	DE Initial Air Seal Shaft Size		
89.	DE Final Air Seal Shaft Size		
90.	ODE Air Seal Shaft Fit		
91.	ODE Initial Air Seal Shaft Size		
92.	ODE Final Air Seal Shaft Size		
93.	DE Endbell Fit		
94.	DE Initial Endbell Fit Size 1		
95.	DE Initial Endbell Fit Size 2		
96.	DE Initial Endbell Fit Size 3		
97.	DE Final Endbell Fit Size 1		
98.	DE Finial Endbell Fit Size 2		
99.	DE Final Endbell Fit Size 3		
100.	DE Endbell Fit Insulated		
101.	DE Endbell Air Seal Fit		
102.	Initial Endbell Air Seal Fit Size		
103.	Finial Endbell Air Seal Fit Size		
104.	ODE Endbell Fit		
105.	ODE Initial Endbell Fit Size 1		
106.	ODE Initial Endbell Fit Size 2		
107.	ODE Initial Endbell Fit Size 3		
108.	ODE Final Endbell Fit Size 1		
109.	ODE Final Endbell Fit Size 2		

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

110.	ODE Final Endbell Fit Size 3		
111.	ODE Endbell Fit Insulated		
112.	ODE Endbell Air Seal Fit		
113.	ODE Initial Endbell Seal Fit Size		
114.	ODE Finial Endbell Seal Fit Size		
115.	Foot Flatness		
116.	Foot Condition		
117.	Flange Condition		
118.	Service Technician		
Balancing Report			
119.	Balance Type		P119
120.	Balance Operating Speed		
121.	Start Left End		
122.	Start Right End		
123.	Balancing Specification		
124.	Finish Left End		
125.	Finish Right End		
126.	Service Technician		
Assembly and Final Test			
127.	Meggar Testing Reading		
128.	Surge Test		
129.	Hi-Pot		
130.	Winding Resistance 1-2		
131.	Winding Resistance 2-3		
132.	Winding Resistance 1-3		
133.	Test Run Voltage Phase A	460 Volts	P133
134.	Test Run Amps A	44.9 Amps	
135.	Test Run Voltage Phase B	460 Volts	
136.	Test Run Amps B	44.1 Amps	
137.	Test Run Voltage Phase C	462 Volts	
138.	Test Run Amps C	44 Amps	
139.	DE Horizontal Vibration Reading	0.03 In/Sec	P139
140.	DE Vertical Vibration Reading	0.05 In/Sec	
141.	DE Axial Vibration Reading	0.06 In/Sec	
142.	ODE Horizontal Vibration Reading	0.06 In/Sec	
143.	ODE Vertical Vibration Reading	0.02 In/Sec	
144.	ODE Axial Vibration Reading	0.05 In/Sec	
145.	Ambient Temp at start of Test Run		
146.	Temp at 5 minutes		
147.	Temp at 10 minutes		
148.	Temp at 15 minutes		
149.	Temp at 20 minutes		
150.	Temp at 25 minutes		
151.	Temp at 30 minutes		
152.	Temp at 35 minutes		
153.	Temp at 40 minutes		
154.	Temp at 45 minutes		
155.	Temp at 50 minutes		

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

156. Temp at 55 minutes

157. Temp at 60 minutes

● 158. Motor Paint

159. Service Technician

(P) Pass

P158

Terrence Holland

Terrence Holland




P12.1



P13.2



P13.3



P18.4



P27.5



P28.6




P28.7



P31.8



P31.9



P31.10



P41.11



P43.12



P43.13



P43.14



P44.15



P44.16




P49.17



P51.18



P51.19



P51.20



P54.21



P54.22



P59.23



P59.24



P59.25



P60.26



P73.27



P77.28




P119.29



P119.30




P119.31



P133.32



P133.33



P139.34



P158.35



P158.36



P158.37