



## AC Recondition Repair Report

FolderID: 97537  
FormID: 9280246

### Process & Power

1625 East 145th Street  
Little Rock, AR 72206

Priorities Found: 4 - High 8 - Good

General			
1. Job Number	97537		
2. Report Date			
3. Customer	PROCESS AND POWER		
Name Plate Information			
4. Manufacturer	BALDOR	P5	
5. Model			
6. Serial Number			
7. Horsepower	200		
8. KW			
9. Volts	460		
10. Amps			
11. RPM			
12. Frame			
13. Enclosure			
14. Cycles			
15. Phase			
16. Service Factor			
17. Motor Mount Position			
Initial Inspection			
18. Number of Leads	6	P13	
19. Lead Length	90 Inches		
20. Lead Size	1		
21. Lead Condition	(P) Pass		
22. Lead Markings	1-6		
23. Lug Size, Condition, and Type			
24. Winding RTD's	(Y) Yes	P73	
6 at 108.7 ohms			
25. Winding Rtd's Condition	(F) Fail		
26. Shaft Run Out			
27. Does Shaft Turn Freely	no		
28. Does Shaft Have Visible Damage	yes	P94	
29. Bearing Rtd's	(NA) Not Applicable		
30. Bearing Rtd's Condition	(NA) Not Applicable		
31. Contamination			
32. Frame Condition	(P) Pass		
33. Fan Condition	(F) Fail	P109	
Replace			

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

34.	Broken or missing components <i>Fan</i>		
<b>Initial Electric Test</b>			
35.	Resistance to Ground	0 Mohm	P7
36.	Winding Resistance 1-2		
37.	Winding Resistance 2-3		
38.	Winding Resistance 1-3		
39.	Resistive Imbalance		
40.	Hi-Pot	Ua	
41.	Surge Test	(F) Fail	
42.	Stator Condition	Rewind	
43.	Failure Location		P68
<b>Initial Rotor Inspection</b>			
44.	Rotor Type		P4
45.	Air Gap <10% Variation		
46.	Number of Rotor Bars	58	
47.	Number of Broken Rotor Bars	0	
48.	Growler Test	(P) Pass	
49.	Rotor Condition	(P) Pass	
<b>Mechanical Inspection</b>			
50.	Bearing Manufacture	SKF	
51.	Bearing DE Size	NU222	
52.	Bearing DE Type	Roller	P23
53.	DE Bearing Qty.	1	
54.	Bearing ODE Size	6318	
55.	Bearing ODE Type	ball	P53
56.	ODE Bearing Qty.	1	P59
	<i>Frosted</i>		
57.	Insulated Bearing	no	
58.	Lubrication Type	grease	
59.	Grease Condition	(NA) Not Applicable	P74
60.	Bearing Retainers		
61.	Shaft Grounding Device	(NA) Not Applicable	
62.	DE Seal	(NA) Not Applicable	
63.	DE Seal Type/Size		
64.	ODE Seal		
65.	ODE Seal Type/Size		
<b>Root Cause of Failure</b>			
66.	Component Failure	Turn to turn short	
67.	Cause of Failure		
68.	Comments		
69.	Service Technician		
<b>Machine Fit Inspection Report</b>			
70.	Shaft Run Out		
71.	Initial Shaft Run Out		
72.	Final Shaft Run Out		
73.	DE Bearing Shaft Fit	(F) Fail	P39
74.	DE Initial Shaft Bearing Fit Size 1	4.3297 "	

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

75.	DE Initial Shaft Bearing Fit Size 2	4.3253 "	
76.	DE Initial Shaft Bearing Fit Size 3	4.3298 "	
77.	DE Finial Shaft Bearing Fit Size 1	4.3317 "	P71
	<i>Belzona bearing fit</i>		
78.	DE Finial Shaft Bearing Fit Size 2	4.3316 "	
79.	DE Finial Shaft Bearing Fit Size 3	4.3317 "	
80.	ODE Bearing Shaft Fit	(P) Pass	P93
81.	ODE Initial Shaft Bearing Fit Size 1	3.5436 "	
82.	ODE Initial Shaft Bearing Fit Size 2	3.5436 "	
83.	ODE Initial Shaft Bearing Fit Size 3	3.5436 "	
84.	ODE Finial Shaft Bearing Fit Size 1	"	
85.	ODE Finial Shaft Bearing Fit Size 2		
86.	ODE Finial Shaft Bearing Fit Size 3		
87.	DE Air Seal Shaft Fit		
88.	DE Initial Air Seal Shaft Size		
89.	DE Final Air Seal Shaft Size		
90.	ODE Air Seal Shaft Fit		
91.	ODE Initial Air Seal Shaft Size		
92.	ODE Final Air Seal Shaft Size		
93.	DE Endbell Fit	(P) Pass	
94.	DE Initial Endbell Fit Size 1	7.8741 "	
95.	DE Initial Endbell Fit Size 2	7.8741 "	
96.	DE Initial Endbell Fit Size 3	7.8741 "	
97.	DE Final Endbell Fit Size 1	"	
98.	DE Finial Endbell Fit Size 2		
99.	DE Final Endbell Fit Size 3		
100.	DE Endbell Fit Insulated		
101.	DE Endbell Air Seal Fit		
102.	Initial Endbell Air Seal Fit Size		
103.	Finial Endbell Air Seal Fit Size		
104.	ODE Endbell Fit	(P) Pass	P145
105.	ODE Initial Endbell Fit Size 1	7.4809 "	
106.	ODE Initial Endbell Fit Size 2	7.4809 "	
107.	ODE Initial Endbell Fit Size 3	7.4809 "	
108.	ODE Final Endbell Fit Size 1		
109.	ODE Final Endbell Fit Size 2		
110.	ODE Final Endbell Fit Size 3		
111.	ODE Endbell Fit Insulated		
112.	ODE Endbell Air Seal Fit		
113.	ODE Initial Endbell Seal Fit Size		
114.	ODE Finial Endbell Seal Fit Size		
115.	Foot Flatness		
116.	Foot Condition		
117.	Flange Condition		
118.	Service Technician	RW	
<b>Balancing Report</b>			
119.	Balance Type		
120.	Balance Operating Speed		

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

121.	Start Left End
122.	Start Right End
123.	Balancing Specification
124.	Finish Left End
125.	Finish Right End
126.	Service Technician
Assembly and Final Test	
127.	Meggar Testing Reading
128.	Surge Test
129.	Hi-Pot
130.	Winding Resistance 1-2
131.	Winding Resistance 2-3
132.	Winding Resistance 1-3
133.	Test Run Voltage Phase A
134.	Test Run Amps A
135.	Test Run Voltage Phase B
136.	Test Run Amps B
137.	Test Run Voltage Phase C
138.	Test Run Amps C
139.	DE Horizontal Vibration Reading
140.	DE Vertical Vibration Reading
141.	DE Axial Vibration Reading
142.	ODE Horizontal Vibration Reading
143.	ODE Vertical Vibration Reading
144.	ODE Axial Vibration Reading
145.	Ambient Temp at start of Test Run
146.	Temp at 5 minutes
147.	Temp at 10 minutes
148.	Temp at 15 minutes
149.	Temp at 20 minutes
150.	Temp at 25 minutes
151.	Temp at 30 minutes
152.	Temp at 35 minutes
153.	Temp at 40 minutes
154.	Temp at 45 minutes
155.	Temp at 50 minutes
156.	Temp at 55 minutes
157.	Temp at 60 minutes
158.	Motor Paint
159.	Service Technician

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.



P4.1



P5.2



P5.3



P5.4



P5.5



P5.6



P7.7



P7.8




P13.9



P23.10




P39.11



P53.12



P59.13



P68.14



P68.15




P68.16






P71.17



P71.18



P73.19



P74.20



P93.21



P94.22



P109.23



P109.24



P109.25



P145.26