

Job Information

Job #: 95012 Date: December 17,

2018

Priority: — Authorized OT: No Authorized by:

Customer Information

Name: Flake Board Reason:

Contact: Motor#: PO#:

Application: – Special notes:

Name Plate Information

Manufacturer: Siemens Enclosure: Totally Enclosed Enclosure Type image

Fan Cooled

Serial#: HT10T009EEI10 Model#: 1LAE22012CB2B2

16AA3

Service Factor: 1.15 Frame: 286T

Horsepower/kW: 30 Rated RPM: 1765

Rated Amps: 70/35 Rated Voltage: 230/460

Phase: 3 Cycles: 60

Special design: No

Nameplate DE ODE F1 F2 Top















Mechanical Inspection

Inspect bolt holes and fasteners. Validate correct fasteners.

Does the shaft turn freely?: Yes Contaminant(s): None

Shaft rotation: Bi-directional Contaminant(s) Amt: None

Shaft grounding device

present?:

No

Type of grounding device:

Shaft runout(TIR-Inbound):

Bearings DE: Worn Bearings DE make: Other

Insulated: No Bearing DE Size: 63101Z

Bearings ODE: Worn Bearings ODE make: Other

Bearing Type: Ball Bearing ODE Size: 62101Z

Bearings Retainer: Yes Thermal Protection: No

Retainer condition: — Thermal Protection Type: —

Bearing Type Image



Bearing Make Image



Bearing Retainer Image



Thermal Protection





Lubrication Type: Grease Thermal Protection device DE: -

Lubrication brand inbound: Mobile Polyrex EM Thermal Protection device ODE: —

Lubrication brand outbound: Mobile Polyrex EM

Grease Amt DE: Full Grease Cond. DE: New

Grease Amt ODE: Full Grease Cond. ODE: New

Seals DE type: N/A

Seals DE size:

Seals DE (inbound) condition:

Seals ODE type: N/A

Seals ODE size:

Seals ODE (inbound) condition

:

Shaft damage cause: None Shaft Image:







Brg. Image:



Bushings/sleeves image:

Not Available

Water jacket:

N/A

Fan:

Ok

Frame cond.:

Good

Not Available







Motor Mount Position:

Horizontal/Foot mount

Endbell type:

Single piece

Missing parts?

☐ J-Box cover

O-rings

☐ J-Box

☐ HH cover

Glands

✓ None

Endbell Image:





Other missing parts



Air Gap Meaurements (N/A on Single Piece Endbell)

Does Air Gap Meet Customer or EASA

spec(<10% variation)?

High voltage

DE @ 0 ODE @ 0 -

DE @ 90 ODE @ 90

DE @ 180 ODE @ 180

DE @ 270 ODE @ 270

AC Electrical Inspection

Number of leads: 9 Terminal Markings: 1-9

Length of leads: 13" REF: NEMA Stds. MG 1-2009, Rev. 1-2010, 2.41-Terminal

Markings Identified By Color:

Size of leads: 1-Blue 5-Black P1-No color assigned

Connections As Received:

2-White 6-No color assigned P2-Brown

3-Orange 7-No color assigned

Lead condition: — 4-Yellow 8-Red

Lug type:

Lug Condition: Good Terminal Lugs

Lug size:

Lug Attachment:



AC Electrical Inspection (Continued)

Rotor Type: Cast Aluminum

Rotor Condition: Ok

Num rotor bars:

Num broken bars:

Rotor



Rotor Test Results

Visual: Pass Growler: Pass Single phase: Pass

Stator type: Factory If other, stator type:

Stator condition: Ok If other, stator condition:

Failure location: In slot If other, stator failure:

Stator Image: Failure Image:







AC Electrical Inspection (Continued)

Winding color: Like new Winding image Winding Thermal Protection: No

Winding condition: Solid

Winding Thermal Protection DE:

Winding Thermal Protection ODE:

Stator test results: Salvageable

Not Available

Megs incoming: Good Surge incoming: Good Hi-pot incoming: Good

Winding Resistance Incoming

Phases A to B Phases B to C Phases C to A Resistive imbalance

Incoming 0.239 0.239 0.239 0.1

Leads/jumpers: Ok Lead jumper Image. :

If other, leads/jumpers:

Mechanical Inspection

Inspect bolt holes and fasteners. Validate correct fasteners.

Shaft Condition: Good Bearings Retainer: Yes

Type of grounding device: Bearing DE Size: 6310

Shaft runout(TIR-Inbound): Bearing ODE Size: 6210

Retainer condition: —

ax 901-873-5301



Seals DE condition: None Brg. Seats DE: Good

Seals DE type: N/A If DE undersized, amt.:

Seals DE size: Brg. Seats ODE: Good

Seals DE (inbound) condition: If ODE undersized, amt.:

Seals ODE condition: None Shaft damage: OK

Seals ODE type: N/A

Seals ODE size:

Bushings/sleeves DE: Ok

Seals ODE (inbound) condition : Bushings/sleeves ODE: Ok

Endbell fits/damage: Bad Foot/Flange condition: Ok

Endbell DE size: 4.3320 Foot flatness: Pass

Endbell DE insulated?: No

Does Air Gap Meet Customer or EASA spec(<10%

variation)?

Endbell ODE insulated?: No

Endbell ODE size:

3.5450



Conclusion

Component Failure

Cause of Failure

Comments

DE AND ODE BEARINGS HOUSING FITS BAD. FOUND METAL FATIGUE IN ODE Bearing

Hobers Wiles

Service Tech name: Robert Wiley

Service Tech signature:

Fax 901-873-5301