

#### **Job Information**

Job #: 95302 Date: March 12, 2019

Priority: — Authorized OT: No Authorized by:

#### **Customer Information**

Name: Welspun Reason:

Contact: Motor#: PO#:

Application: – Special notes:

#### **Name Plate Information**

Manufacturer: Crompton Greaves Enclosure: Totally Enclosed Enclosure Type image

Fan Cooled

Serial#: Model#:

Service Factor: Frame: ND100LD

Horsepower/kW: 3.7KW Rated RPM: 2840

Rated Amps: 7.25 Rated Voltage: 415

Phase: 3 Cycles: 60

Special design: No

Nameplate DE ODE F1 F2 Top













WEST TENNESSEE



# **Mechanical Inspection**

Inspect bolt holes and fasteners. Validate correct fasteners.

Does the shaft turn freely?: Yes Contaminant(s): None

Shaft rotation: CCW Contaminant(s) Amt: None

Shaft grounding device

present?:

No

Type of grounding device:

Shaft runout(TIR-Inbound):

Bearings DE: Worn Bearings DE make: Koyo

Insulated: No Bearing DE Size: 6206 ZZ

Bearings ODE: Worn Bearings ODE make: Koyo

Bearing Type: Ball Bearing ODE Size: 6205 ZZ

Bearings Retainer: Yes Thermal Protection: Yes

Retainer condition: — Thermal Protection Type: —

Bearing Type Image



Bearing Make Image



Bearing Retainer Image



Thermal Protection





Lubrication Type: Grease Thermal Protection device DE: N/A

Lubrication brand inbound: Mobile Polyrex EM Thermal Protection device ODE: N/A

Lubrication brand outbound: Mobile Polyrex EM

Grease Amt DE: Full Grease Cond. DE: New

Grease Amt ODE: Full Grease Cond. ODE: New

Seals DE type: N/A

Seals DE size:

Seals DE (inbound) condition:

Seals ODE type: N/A

Seals ODE size:

Seals ODE (inbound) condition

:

Shaft damage cause: None Shaft Image:





Brg. Image:



Bushings/sleeves image:



Water jacket:

N/A

Fan: (

Ok

Frame cond.:

Good



Endbell Image:

Motor Mount Position:

Horizontal/Foot mount

Endbell type:

Single piece

Missing parts?

☐ J-Box cover

O-rings

☐ J-Box

☐ HH cover

Glands

✓ None



Other missing parts



Air Gap Meaurements (N/A on Single Piece Endbell)

Does Air Gap Meet Customer or EASA spec(<10% variation)?

DE @ 0 ODE @ 0 -

DE @ 90 ODE @ 90

DE @ 180 ODE @ 180

DE @ 270 ODE @ 270

#### **AC Electrical Inspection**

Number of leads: 6 Terminal Markings: U1 V1 W1. U2 V2 W2

Length of leads: REF: NEMA Stds. MG 1-2009, Rev. 1-2010, 2.41-Terminal

Markings Identified By Color:

Size of leads: 1-Blue 5-Black P1-No color assigned

2-White 6-No color assigned P2-Brown 3-Orange 7-No color assigned

Lead condition: Good 4-Yellow 8-Red

Connections As Received: 460 Delt

Lug Condition: Good Terminal Lugs

Lug size:

Lug type:

Lug Attachment: Acceptable





Fax 901-873-5301



# **AC Electrical Inspection (Continued)**

Rotor Type: Cast Aluminum

Ok

Num rotor bars:

Num broken bars:

Rotor



#### **Rotor Test Results**

**Rotor Condition:** 

Single phase: Visual: **Pass** Growler: Pass Pass

Stator type: If other, stator type: Factory

Stator condition: Ok If other, stator condition:

Failure location: Other If other, stator failure: Stator Good

Stator Image:







# **AC Electrical Inspection (Continued)**

Winding color: Like new Winding image Winding Thermal Protection: Yes

Winding condition: Solid

Winding Thermal Protection DE:

Winding Thermal Protection ODE:

Stator test results: Salvageable

Megs incoming: Good Surge incoming: Good Hi-pot incoming: Good

**Winding Resistance Incoming** 

Phases A to B Phases B to C Phases C to A Resistive imbalance

Incoming 2.097 2.080 2.089 03

Leads/jumpers: Ok Lead jumper Image. :

If other, leads/jumpers:

# **Mechanical Inspection**

Inspect bolt holes and fasteners. Validate correct fasteners.

Shaft Condition: Good Bearings Retainer: Yes

Type of grounding device: Bearing DE Size: 6206

Shaft runout(TIR-Inbound): Bearing ODE Size: 6205

Retainer condition: —

ax 901-873-5301



Seals DE condition: None Brg. Seats DE: Good

Seals DE type: N/A If DE undersized, amt.: 1.1810 Good

Seals DE size: Brg. Seats ODE: Good

Seals DE (inbound) condition: If ODE undersized, amt.: .9847 Good

Seals ODE condition: None Shaft damage: OK

Seals ODE type: N/A

Seals ODE size:

Bushings/sleeves DE: Ok

Seals ODE (inbound) condition : Bushings/sleeves ODE: Ok

Endbell fits/damage: Good Foot/Flange condition: Ok

Endbell DE size: 2.4413 Foot flatness: Pass

Endbell DE insulated?: No

Does Air Gap Meet Customer or EASA spec(<10%

variation)?

Endbell ODE insulated?: No

Endbell ODE size:

2.0479



#### Conclusion

**Component Failure** 

**Cause of Failure** 

**Comments** 

Bearings and wash and bake

Service Tech name: Robert Wiley

Service Tech signature:

Robers Willey