

Job Information

Job #: 95998 Date: September 16,

2019

Priority: — Authorized OT: No Authorized by:

Customer Information

Name: Sage V Foods Reason:

Contact: Motor#: PO#:

Application: – Special notes:

Name Plate Information

Manufacturer: Baldor Enclosure: Totally Enclosed Enclosure Type image

Non-Ventilated Serial#: C1511130057 Model#:

Service Factor: 1.15 Frame: 284T

Horsepower/kW: 25 Rated RPM: 1770

Rated Amps: 60/30 Rated Voltage: 230/460

Phase: 3 Cycles: 60

No

Nameplate DE ODE F1 F2 Top



Special design:









Mechanical Inspection

Inspect bolt holes and fasteners. Validate correct fasteners.

Does the shaft turn freely?: Yes Contaminant(s): None

Shaft rotation: Bi-directional Contaminant(s) Amt: None

Shaft grounding device

present?:

No

Type of grounding device:

Shaft runout(TIR-Inbound):

Bearings DE: Worn Bearings DE make: Other

Insulated: No Bearing DE Size: 6311

Bearings ODE: Worn Bearings ODE make: NTN

Bearing Type: Ball Bearing ODE Size: 6309

Bearings Retainer: Yes Thermal Protection: No

Retainer condition: Good Thermal Protection Type: —

Bearing Type Image



Bearing Make Image



Bearing Retainer Image



Thermal Protection



Lubrication Type: Grease Thermal Protection device DE: —

Lubrication brand inbound: Unknown Thermal Protection device ODE: —

Lubrication brand outbound: Unknown

Grease Amt DE: Full Grease Cond. DE: Charred

Grease Amt ODE: Full Grease Cond. ODE: Charred

Seals DE type: N/A

Seals DE size:

Seals DE (inbound) condition:

Seals ODE type: N/A

Seals ODE size:

Seals ODE (inbound) condition

:

Shaft damage cause: None Shaft Image:





Brg. Image:



Water jacket: N/A Fan: N/A Frame cond.: Good



Motor Mount Position: Horizontal/Foot mount Endbell type: Single piece

Missing parts? Endbell Image:

☐ J-Box cover ☐ O-rings ☐ J-Box

☐ HH cover ☐ Glands ☑ None

Other missing parts







Air Gap Meaurements (N/A on Single Piece Endbell)

Does Air Gap Meet Customer or EASA spec(<10% variation)?

DE @ 0 ODE @ 0 -

DE @ 90 ODE @ 90

DE @ 180 ODE @ 180

DE @ 270 ODE @ 270

AC Electrical Inspection

Number of leads: 9 Terminal Markings:

Length of leads: 12 in REF: NEMA Stds. MG 1-2009, Rev. 1-2010, 2.41-Terminal

Markings Identified By Color:

Size of leads: 1-Blue 5-Black P1-No color assigned

2-White 6-No color assigned P2-Brown

3-Orange 7-No color assigned

Lead condition: Good 4-Yellow 8-Red

Connections As Received: Lug type:

Lug Condition: — Terminal Lugs

Lug size:

Lug Attachment: —

Fax 901-873-5301



AC Electrical Inspection (Continued)

Rotor Type: Cast Aluminum

Ok

Num rotor bars: 40

Num broken bars: 0

Rotor



Rotor Test Results

Rotor Condition:

Visual: Pass Growler: Pass Single phase: Pass

Stator type: Factory If other, stator type:

Stator condition: Ok If other, stator condition:

Failure location: Other If other, stator failure:

Stator Image: Failure Image:







AC Electrical Inspection (Continued)

Winding color: Still has color Winding image Winding Thermal Protection: No

Winding condition: Solid

Winding Thermal ____ Protection DE:

Winding Thermal Protection ODE:

Stator test results: Salvageable

Megs incoming: Good Surge incoming: Good Hi-pot incoming: Good

Winding Resistance Incoming

Phases A to B Phases B to C Phases C to A Resistive imbalance

Incoming 0.00 0.00 0.00

Leads/jumpers: Ok

If other, leads/jumpers:

Mechanical Inspection

Inspect bolt holes and fasteners. Validate correct fasteners.

Shaft Condition: Good Bearings Retainer: Yes

Type of grounding device: Bearing DE Size: 6311

Shaft runout(TIR-Inbound): 0.002 Bearing ODE Size: 6309

Retainer condition: Good

Fax 901-873-5301



Seals DE condition: None Brg. Seats DE: Good

Seals DE type: N/A If DE undersized, amt.:

Seals DE size: Brg. Seats ODE: Good

Seals DE (inbound) condition: If ODE undersized, amt.:

Seals ODE condition: None Shaft damage: OK

Seals ODE type: N/A

Seals ODE size:

Bushings/sleeves DE: Ok

Seals ODE (inbound) condition : Bushings/sleeves ODE: Ok

3.9390 BAD

Endbell fits/damage: Good Foot/Flange condition: Ok

Endbell DE size: 4.7243 Foot flatness: Pass

Endbell DE insulated?: —

Does Air Gap Meet Customer or EASA spec(<10%

variation)?

Endbell ODE insulated?: -

Endbell ODE size:



Conclusion

Component Failure

Cause of Failure

Comments

DE end bell is cracked around the outer lip. ODE endbell bearing seat is over sized. ODE bearing shows signs of heaving frosting recommend ajuis ring and the DE bearing shows signs of wear and moisture contamination

Chris Ellery

Service Tech name: Chris Wiley

Service Tech signature:

7030 Ryburn Drive Millington, TN 38053 Phone 901-873-5300 Fax 901-873-5301