

#### **Job Information**

97060 Job #: Date: July 20, 2020

Priority: Authorized OT: No Authorized by:

# **Customer Information**

Name: 26KW Reason:

Contact: Motor#: PO#:

Application: Special notes:

#### **Name Plate Information**

Manufacturer: **Bartec Varnost** Enclosure: Totally Enclosed **Enclosure Type image** 

Fan Cooled

3KTC180M-2 Serial#: 515 Model#:

Service Factor: 180M Frame:

Horsepower/kW: 26 Rated RPM: 3525

Rated Amps: 71/41 Rated Voltage: 278/480

Cycles: Phase: 3 60

Special design:

No

Nameplate DE ODE F1 F2 Top









WEST TENNESSEE



## **Mechanical Inspection**

Inspect bolt holes and fasteners. Validate correct fasteners.

Does the shaft turn freely?: Contaminant(s): Yes None

> Shaft rotation: Bi-directional Contaminant(s) Amt: None

Shaft grounding device No

Contaminant Image: present?:

Shaft runout(TIR-Inbound):

Type of grounding device:

Bearings DE: Worn Bearings DE make: **FAG** 

Insulated: Bearing DE Size: 6310 No

Bearings ODE: Worn Bearings ODE make: **FAG** 

Bearing Type: Bearing ODE Size: Ball 6310

Bearings Retainer: Yes Thermal Protection: Yes

Retainer condition: Good Thermal Protection Type:


Bearing Type Image



Bearing Make Image



Bearing Retainer Image



Thermal Protection



Lubrication Type: Grease Thermal Protection device DE: -

Lubrication brand inbound: Mobile Polyrex EM Thermal Protection device ODE: —

Lubrication brand outbound: Mobile Polyrex EM

Grease Amt DE: Full Grease Cond. DE: New

Grease Amt ODE: Full Grease Cond. ODE: New

Seals DE type: Slinger

Seals DE size:

Seals DE (inbound) condition:

Seals ODE type: Slinger

Seals ODE size:

Seals ODE (inbound) condition

:

Shaft damage cause: None Shaft Image:





Brg. Image:



Water jacket: N/A Fan: Ok Frame cond.: Good



Motor Mount Position: Horizontal/Foot mount Endbell type: Single piece

Missing parts?

J-Box cover O-rings J-Box

HH cover Glands None

Other missing parts



Air Gap Meaurements (N/A on Single Piece Endbell)

Does Air Gap Meet Customer or EASA spec(<10% variation)?

DE @ 0 ODE @ 0 -

DE @ 90 ODE @ 90

DE @ 180 ODE @ 180

DE @ 270 ODE @ 270

### **AC Electrical Inspection**

Number of leads: 6 Terminal Markings:

Length of leads: REF: NEMA Stds. MG 1-2009, Rev. 1-2010, 2.41-Terminal

Markings Identified By Color:

Size of leads: 1-Blue 5-Black P1-No color assigned

2-White 6-No color assigned P2-Brown

3-Orange 7-No color assigned

Lead condition: Good 4-Yellow 8-Red

Connections As Received: Lug type:

Lug Condition: Good Terminal Lugs

Lug size:

Lug Attachment: Acceptable



## **AC Electrical Inspection (Continued)**

Rotor Type: Cast Aluminum

Ok

Num rotor bars:

Num broken bars: 0

Rotor



#### **Rotor Test Results**

**Rotor Condition:** 

Visual: Pass Growler: Pass Single phase: Pass

Stator type: Factory If other, stator type:

Stator condition: Ok If other, stator condition:

Failure location: In slot If other, stator failure:

Stator Image:





## **AC Electrical Inspection (Continued)**

Winding color: Like new Winding image Winding Thermal Protection: Yes

Winding condition: Solid

Winding Thermal Protection DE:

Winding Thermal
Protection ODE:

Stator test results: Salvageable

Megs incoming: Good Surge incoming: Good Hi-pot incoming: Good

**Winding Resistance Incoming** 

Phases A to B Phases B to C Phases C to A Resistive imbalance

Incoming

Leads/jumpers: Ok

If other, leads/jumpers:

## **Mechanical Inspection**

Inspect bolt holes and fasteners. Validate correct fasteners.

Shaft Condition: Good Bearings Retainer: Yes

Type of grounding device: Aegis Bearing DE Size: 6310 2Z

Shaft runout(TIR-Inbound): .002 Bearing ODE Size: 6310 2Z

Retainer condition: Good

Fax 901-873-5301



Seals DE condition: Worn Brg. Seats DE: Good

Seals DE type: If DE undersized, amt.: Slinger

Seals DE size: Brg. Seats ODE: Good

Seals DE (inbound) condition: Good If ODE undersized, amt.:

Worn Seals ODE condition: Shaft damage: OK

Seals ODE type: Slinger

Bushings/sleeves DE: Ok Seals ODE size:

Bushings/sleeves ODE: Ok Seals ODE (inbound) condition: Good

> Endbell fits/damage: Foot/Flange condition: Good Ok

Endbell DE size: 4.3310 Foot flatness: **Pass** 

Endbell DE insulated?: No

> Does Air Gap Meet Customer or EASA spec(<10% variation)?

Endbell ODE insulated?:

Endbell ODE size:

4.3312



#### Conclusion

Com	ponent	<b>Failure</b>
-----	--------	----------------

#### **Cause of Failure**

#### **Comments**

Customer requests periodic maintenance and bearing time change on motor assembly.

Service Tech name: Terrence Holland

Service Tech signature: