

AC Recondition Repair Report

FolderID: 97505 FormID: 9215292

7030 Ryburn Dr Millington, Tn 38053 901-873-5300

Hi-Speed Industrial Service

SAGE 5901 SLOAN DRIVE LITTLE ROCK, AR 72206

| Genera | General | | | | |
|-----------|--------------------------------|------|--|--|--|
| 1. | Job Number 975 | 05 | | | |
| 2. | Report Date | | | | |
| 3. | Customer | GE . | | | |
| Name | Name Plate Information | | | | |
| 4. | Manufacturer BALDO | DR . | | | |
| 5. | Model | | | | |
| 6. | Serial Number z11052522 | 26 | | | |
| 7. | Horsepower | 20 | | | |
| 8. | KW | | | | |
| 9. | Volts 2304 | 60 | | | |
| 10. | Amps | | | | |
| - | 43/21.5 | | | | |
| 11. | RPM 35 | 25 | | | |
| 12. | Frame 256 | ГС | | | |
| 13. | Enclosure | FC . | | | |
| 14. | Cycles | 60 | | | |
| 15. | Phase | 3 | | | |
| 16. | Service Factor 1. | 15 | | | |
| 17. | Motor Mount Position | F1 | | | |
| Initial I | nspection | | | | |
| 18. | Number of Leads | | | | |
| 19. | Lead Length | | | | |
| 20. | Lead Size | | | | |
| 21. | Lead Condition | | | | |
| 22. | Lead Markings | | | | |
| 23. | Lug Size, Condition, and Type | | | | |
| 24. | Winding RTD's | | | | |
| 25. | Winding Rtd's Condition | | | | |
| 26. | Shaft Run Out | | | | |
| 27. | Does Shaft Turn Freely | | | | |
| 28. | Does Shaft Have Visible Damage | | | | |
| 29. | Bearing Rtd's | | | | |
| 30. | Bearing Rtd's Condition | | | | |
| 31. | Contamination | | | | |
| 32. | Frame Condition | | | | |
| 33. | Fan Condition | | | | |
| 34. | Broken or missing components | | | | |

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

| | Electric Test | | |
|-----------|-------------------------------------|--|--|
| 35. | Resistance to Ground | | |
| 36. | Winding Resistance 1-2 | | |
| 37. | Winding Resistance 2-3 | | |
| 38. | Winding Resistance 1-3 | | |
| 39. | Resistive Imbalance | | |
| 40. | Hi-Pot | | |
| 41. | Surge Test | | |
| 42. | Stator Condition | | |
| 43. | Failure Location | | |
| Initial I | Initial Rotor Inspection | | |
| 44. | Rotor Type | | |
| 45. | Air Gap <10% Variation | | |
| 46. | Number of Rotor Bars | | |
| 47. | Number of Broken Rotor Bars | | |
| 48. | Growler Test | | |
| 49. | Rotor Condition | | |
| Mecha | Mechanical Inspection | | |
| 50. | Bearing Manufacture | | |
| 51. | Bearing DE Size | | |
| 52. | Bearing DE Type | | |
| 53. | DE Bearing Qty. | | |
| 54. | Bearing ODE Size | | |
| 55. | Bearing ODE Type | | |
| 56. | ODE Bearing Qty. | | |
| 57. | Insulated Bearing | | |
| 58. | Lubrication Type | | |
| 59. | Grease Condition | | |
| 60. | Bearing Retainers | | |
| 61. | Shaft Grounding Device | | |
| 62. | DE Seal | | |
| 63. | DE Seal Type/Size | | |
| 64. | ODE Seal | | |
| 65. | ODE Seal Type/Size | | |
| Root C | cause of Failure | | |
| 66. | Component Failure | | |
| 67. | Cause of Failure | | |
| 68. | Comments | | |
| 69. | Service Technician | | |
| Machir | ne Fit Inspection Report | | |
| 70. | Shaft Run Out | | |
| 71. | Initial Shaft Run Out | | |
| 72. | Final Shaft Run Out | | |
| 73. | DE Bearing Shaft Fit | | |
| 74. | DE Initial Shaft Bearing Fit Size 1 | | |
| 75. | DE Initial Shaft Bearing Fit Size 2 | | |
| 76. | DE Initial Shaft Bearing Fit Size 3 | | |
| 77. | DE Finial Shaft Bearing Fit Size 1 | | |
| | · | | |

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

| 70 | DE Finial Obett Bearing & Fit Oire O |
|--------|--------------------------------------|
| | DE Finial Shaft Bearing Fit Size 2 |
| 79. | DE Finial Shaft Bearing Fit Size 3 |
| 80. | ODE Bearing Shaft Fit |
| 81. | ODE Initial Shaft Bearing Fit Size 1 |
| 82. | ODE Initial Shaft Bearing Fit Size 2 |
| 83. | ODE Initial Shaft Bearing Fit Size 3 |
| 84. | ODE Finial Shaft Bearing Fit Size 1 |
| 85. | ODE Finial Shaft Bearing Fit Size 2 |
| 86. | ODE Finial Shaft Bearing Fit Size 3 |
| 87. | DE Air Seal Shaft Fit |
| 88. | DE Initial Air Seal Shaft Size |
| 89. | DE Final Air Seal Shaft Size |
| 90. | ODE Air Seal Shaft Fit |
| 91. | ODE Initial Air Seal Shaft Size |
| 92. | ODE Final Air Seal Shaft Size |
| 93. | DE Endbell Fit |
| 94. | DE Initial Endbell Fit Size 1 |
| 95. | DE Initial Endbell Fit Size 2 |
| 96. | DE Initial Endbell Fit Size 3 |
| 97. | DE Final Endbell Fit Size 1 |
| 98. | DE Finial Endbell Fit Size 2 |
| 99. | DE Final Endbell Fit Size 3 |
| 100. | DE Endbell Fit Insulated |
| 101. | DE Endbell Air Seal Fit |
| 102. | Initial Endbell Air Seal Fit Size |
| 103. | Finial Endbell Air Seal Fit Size |
| 104. | ODE Endbell Fit |
| 105. | ODE Initial Endbell Fit Size 1 |
| 106. | ODE Initial Endbell Fit Size 2 |
| 107. | ODE Initial Endbell Fit Size 3 |
| 108. | ODE Final Endbell Fit Size 1 |
| 109. | ODE Final Endbell Fit Size 2 |
| 110. | ODE Final Endbell Fit Size 3 |
| 111. | ODE Endbell Fit Insulated |
| 112. | ODE Endbell Air Seal Fit |
| 113. | ODE Initial Endbell Seal Fit Size |
| 114. | ODE Finial Endbell Seal Fit Size |
| 115. | Foot Flatness |
| 116. | Foot Condition |
| 117. | Flange Condition |
| | Service Technician |
| Balanc | ing Report |
| | Balance Type |
| | Balance Operating Speed |
| | Start Left End |
| | Start Right End |
| | Balancing Specification |
| | Finish Left End |
| | |

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

| 125. | Finish Right End | |
|-------------------------|-----------------------------------|--|
| 126. | Service Technician | |
| Assembly and Final Test | | |
| 127. | Meggar Testing Reading | |
| 128. | Surge Test | |
| 129. | Hi-Pot | |
| 130. | Winding Resistance 1-2 | |
| 131. | Winding Resistance 2-3 | |
| 132. | Winding Resistance 1-3 | |
| 133. | Test Run Voltage Phase A | |
| 134. | Test Run Amps A | |
| 135. | Test Run Voltage Phase B | |
| 136. | Test Run Amps B | |
| 137. | Test Run Voltage Phase C | |
| 138. | Test Run Amps C | |
| 139. | DE Horizontal Vibration Reading | |
| 140. | DE Vertical Vibration Reading | |
| 141. | DE Axial Vibration Reading | |
| 142. | ODE Horizontal Vibration Reading | |
| 143. | ODE Vertical Vibration Reading | |
| 144. | ODE Axial Vibration Reading | |
| 145. | Ambient Temp at start of Test Run | |
| 146. | Temp at 5 minutes | |
| 147. | Temp at 10 minutes | |
| 148. | Temp at 15 minutes | |
| 149. | Temp at 20 minutes | |
| 150. | Temp at 25 minutes | |
| 151. | Temp at 30 minutes | |
| 152. | Temp at 35 minutes | |
| 153. | Temp at 40 minutes | |
| 154. | Temp at 45 minutes | |
| 155. | Temp at 50 minutes | |
| 156. | Temp at 55 minutes | |
| 157. | Temp at 60 minutes | |
| 158. | Motor Paint | |
| 159. | Service Technician | |

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.