



MILLINGTON, TN

LITTLE ROCK, AR

Job Information

Job #: 97033

Date: July 21, 2020

Priority: —

Authorized OT: No

Authorized by:

Customer Information

Name: Richland Foods

Motor#:

Name Plate Information

| | | | | | |
|---------------|-----------------|-------------|-----------------------|-----------------|------|
| Manufacturer: | Baldor/Reliance | Enclosure : | Open Drop Proof (ODP) | Horsepower/kW: | 300 |
| Serial#: | A1306072047 | Model#: | P44G3921 | Service Factor: | 1.15 |
| Frame: | 449TS | Rated RPM: | 3570 | Rated Voltage: | 460 |
| Phase: | 3 | Rated Amps: | 324 | Cycles: | 60 |

Special design: No

AC Electrical Inspection

Megs after rewind: Good Surge after rewind: Good Hi-pot after rewind: Good

Core loss: Good Thermistors: None Thermostat: None

RTD: None ohms at degrees C

Motor Heater(s) Present: Yes Qty: Voltage: Wattage:

WEST TENNESSEE
7030 Ryburn Drive
Millington, TN 38053
Phone 901-873-5300
Fax 901-873-5301

CENTRAL ARKANSAS
6812 Lindsey Rd.
Little Rock, AR 72206
Phone 501-375-9178
Fax 501-375-4254



MILLINGTON, TN

LITTLE ROCK, AR

AC Electrical Inspection (Continued)




Core Test Data

| | Flux | Watts | Watts loss per lb | Condition of iron |
|----------------|--------|-------|-------------------|-------------------|
| Before burnout | 84.015 | 0.505 | 1.737 | 257 |
| After burnout | 85.299 | 0.694 | 3.236 | 351 |

Conclusion

Service Tech name: RHR

Service Tech signature:



WEST TENNESSEE

7030 Ryburn Drive
Millington, TN 38053
Phone 901-873-5300
Fax 901-873-5301

CENTRAL ARKANSAS

6812 Lindsey Rd.
Little Rock, AR 72206
Phone 501-375-9178
Fax 501-375-4254

Polyphase AC Winding

Polyphase Date: July 21, 2020

Hp/kw: 300 RPM: 3570 Poles: 2 Manufacturer: Baldor/Reliance

Slots: 48 Type: P Volts: 460

Coils: 48 Model: P44G3921 Amps: 324

Serial#: A1306072047 Phase: 3

Lead marking: 1-1-2-2-3-3 Hertz: 60

6 Of 8
Grouping
Of

Turns/Coil: 4 Lead length: 2 C Rise: Frame: 449TS

Wire Size 16 17 Lead size: 20 Duty: Cont C AMB:

Wire Mult. 30 2 Num. Leads: 6 Eff.: Ins. Cls.:

Pitch 1 to: 18 ☐ DP ☐ TEFC ☐ XPRF ☐ TENV S.F.: 1.15

Connection: 2D

Jumper:

Core length: 16.125

Core ID: 10.75

Back iron: 2.5

Slot depth: 2.0

Slot/tooth w: 0.284

Wire weight: 360

Vents: Size

COIL


☒ Left

Connection End
(Facing Terminal Box)

☐ Right

Rotor bars:



MILLINGTON, TN

LITTLE ROCK, AR

Single Phase

Split Phase ☐
Capacitor: ☐ Start ☐ Start & Run ☐ Perm. Split

Hp/kw: 300

RPM: 3570

Manufacturer: Baldor/Reliance

Run

Start

Type:

Volts: 460

Model: P44G3921

Amps: 324

Style:

Hertz:

Form:

Frame:

No. Slots

No. Poles

Coils/pole

Dwg No.

C Rise:

Hrs.:

Cap. Mfd.:

Wire Size

Serial#: A1306072047

Wires in par.

Duty: —

☐ BB☐ SB

No. Circuits

Open: —

Coil Ext.

Sta.length:

Sta.b.i.:

Stator Bore

Running ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐

Slot No. 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18

Starting ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐

Customer: Richland Foods

(Please return a copy to EASA Headquarters, 1331 Baur Blvd., St. Louis, MO 63132)

WEST TENNESSEE
7030 Ryburn Drive
Millington, TN 38053
Phone 901-873-5300
Fax 901-873-5301

CENTRAL ARKANSAS
6812 Lindsey Rd.
Little Rock, AR 72206
Phone 501-375-9178
Fax 501-375-4254

AC Stator Form Coil Data

1. Core bore diameter
2. Total core length
3. Back iron
4. No. of vents
5. Width of vents
6. Finger plate width
7. Overall coil length
8. Connection end extension
9. Opposite Conn. End Ext.
10. Straight length bottom side
11. Straight length top side
12. Small knuckle drop. CE
13. Large knuckle drop. CE
14. Conn. Support Ring from core
15. Opp. Conn. Supp. Ring from core
16. Connection support ring ID
17. Opp. Conn. Supp. Ring ID
18. Total slot depth
19. Slot depth under wedge
20. Slot width

OCE

OCE



AC Stator Form Coil Data (Continued)

21. Lead location ☐ A ☐ B ☐ C ☐ D

22. Coil type ☐ Left hand ☐ Right hand

23. Coil leads Long# LG

Short# LG

☐ Out ☐ Down

24. Jumper —

25. Connection —

26. No. of circuits

27. No. of slots

28. Coil throw 1-

29. Turns per coil

30. Total wires in parallel

31. Bare wire sizes () x

() x

32. Strand insulation

☐ Film ☐ Glass ☐ Mica ☐ Bare ☐ Other

33. Coil weight Lbs.

34. Groups of Coils

Groups of Coils

35. Iron skewed ☐ Right ☐ Left in


AC Stator Form Coil Data (Continued)

Special Features Yes No

Data change ☐ ☐

Coil support ring steel ☐ ☐

Terrace wound ☐ ☐

Corona Protection ☐ ☐

RTDs ☐ ☐

Ohms Qty

Hermetic ☐ ☐

Slot paper used ☐ ☐

Insulation class ☐ B ☐ F ☐ H

☐ VPI ☐ Dip & Bake ☐ Sealed

☐ Leads taped ☐ Leads sleeved

Comments

