

# **Motor Shop Repairs**

## **Job Number 100046**

Prepared for ARKANSAS INDUSTRIAL MACHINERY

3804 N. NONA ST NORTH LITTLE ROCK AR 72118

### **Table of Contents**

AC Recondition As Found - Shop

AC Recondition - Rev. 2: 1061037868

1.0



FolderID: 100046

FormID: 14064234



#### **AC Recondition As Found ARKANSAS INDUSTRIAL MACHINERY**

**3804 N. NONA ST** NORTH LITTLE ROCK, AR 72118

AC Recondition - Rev. 2

Location:

Serial Number: 1061037868

Description:350HP WEG 1800RPM 447TS

Shop

Hi-Speed Job Number:	100046
Manufacturer:	WEG
Product Number:	350180T3G447/9TS-W40
Serial Number:	1061037868
HP/kW:	350 (HP)
RPM:	1780 (RPM)
Frame:	447TS
Voltage:	460
Current:	396
Phase:	Three
Hz:	60 (Hz)
Service Factor:	1.15
Repair Stage:	Teardown Inspection

Priorities Found: 1 - High



6 - Good

#### **Overall Condition**

Report Date

Nameplate Picture





Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.







































	3.	Describe the Overall Condition of the <i>Dirty</i>	Equipment as Received	
	4.	Distance from the end of the shaft to t	he Coupling/Sheave	
	5.	Photos of all six sides of the machine.		
In	itial	Mechanical/Electrical		
	6.	Does Shaft Turn Freely?		(Yes) Yes
	7.	Does Shaft Have Visible Damage?		(No) No
	8.	Assembled Shaft Runout		
	9.	Assembled Shaft End Play		
	10.	Air Gap Variation <10%		
	11.	Lead Condition		(P) Pass
	12.	Lead Length		18 Inches
	13.	Stator Temperature Detector Rating a	nd Function	
		Quantity	Rating	Quantity Passed
	_			
	•	Na		
	14.	Bearing Temperature Detector Rating		0 5
		Quantity	Rating	Quantity Passed
	-	Na		
	15.	Frame Condition		
	-	Good		
	16.	Fan Condition		(N) NA
	17.	Heater Quantity, Ratings		
		Quantity	Volts/Watts	Pass/Fail
	-	Na		
		Broken or Missing Components		na
Ir		Electrical Inspection		
		Insulation Resistance/Megger		
	20.	Winding Resistance		
		1-2	1-3	2-3
	04	Desferre Corner Test		(NIA) Niat Ampliant I
	21.	9		(NA) Not Applicable
		Blown windings		

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

### Drive End Bearing Number- 23. Drive End Bearing Number- 24. Drive End Bearing Oty. 25. Drive End Bearing Type 26. Drive End Bearing Type 37. Drive End Bearing Type 38. Drive End Lubrication Type 38. Drive End Bearing Installation or Grounding Device? 39. Drive End Bearing Condition 39. Drive End Bearing Condition 30. Opposite Drive End Bearing Number- 31. Opposite Drive End Bearing Number- 32. Drive End Bearing Condition 39. Opposite Drive End Bearing Number- 30. Opposite Drive End Bearing Number- 31. Opposite Drive End Bearing Type 39. (Ball) Ball Bearing 31. Opposite Drive End Bearing Type 30. Opposite Drive End Bearing Strype 31. (Ball) Ball Bearing 32. Opposite Drive End Bearing Insulation or Grounding Device? 33. Opposite Drive End Bearing Insulation or Grounding Device? 34. Opposite Drive End Bearing Insulation or Grounding Device? 36. Opposite Drive End Bearing Condition 37. Drive End Seal 38. Opposite Drive End Bearing Condition 39. DE Sleeve Bearing Inside Diameter 39. De Sleeve Bearing Inside Diameter 39. De Sleeve Bearing Housing Inside Diameter 40. De Sleeve Bearing Housing Inside Diameter 50. degrees 51.20 degrees 51.20 degrees 52.40 degrees	22.	Stator Condition			
24. Drive End Bearing Oty. 25. Drive End Bearing Type (Ball) Ball Bearing 26. Drive End Lubrication Type (Grease) Grease Lubricated 27. Drive End Bearing Insulation or Grounding Device? 28. Drive End Bearing Condition 29. Drive End Bearing Condition 30. Opposite Drive End Bearing Number- 31. Opposite Drive End Bearing Oty. 31. Opposite Drive End Bearing Type (Ball) Ball Bearing 32. Opposite Drive End Bearing Type (Ball) Ball Bearing 33. Opposite Drive End Bearing Type (Ball) Ball Bearing 34. Opposite Drive End Bearing Type (Grease) Grease Lubricated 35. Opposite Drive End Bearing Type (Grease) Grease Lubricated 36. Opposite Drive End Bearing Type (Grease) Grease Lubricated 37. Opposite Drive End Bearing Type (Grease) Grease Lubricated 38. Opposite Drive End Bearing Condition 39. De Sleeve Bearing Condition 39. De Sleeve Bearing Inside Diameter 0 degrees 120 degrees 120 degrees 240 degrees  120 degrees 240 degrees	Mecha	hanical Inspection			
26. Drive End Bearing Type (Grease) Grease Lubricated 26. Drive End Bearing Insulation or Grounding Device? 27. Drive End Bearing Insulation or Grounding Device? 38. Drive End Bearing Insulation or Grounding Device? 39. Drive End Bearing Condition 30. Opposite Drive End Bearing Number- 31. Opposite Drive End Bearing Other Retention Device? 31. Opposite Drive End Bearing Other Retention Device? 32. Opposite Drive End Bearing Number- 33. Opposite Drive End Bearing Type 34. Opposite Drive End Bearing Type 35. Opposite Drive End Bearing Insulation or Grounding Device? 36. Opposite Drive End Bearing Condition 37. Opposite Drive End Bearing Condition 38. Opposite Drive End Bearing Condition 39. DE Sleeve Bearing Inside Diameter 39. DE Sleeve Bearing Inside Diameter 39. DE Sleeve Bearing Outside Diameter 39. DE Sleeve Bearing Housing Inside Diameter 30. degrees 31.20 degrees 31.20 degrees 32.40 degrees	23.	Drive End Bearing Number-		6314	
26. Drive End Lubrication Type (Grease) Grease Lubricated 27. Drive End Bearing Insulation or Grounding Device? 28. Drive End Wavy Washer/Snap-Ring Other Retention Device? 30. Opposite Drive End Bearing Number- 31. Opposite Drive End Bearing Number- 32. Opposite Drive End Bearing Other Retention Device? 33. Opposite Drive End Bearing Type 34. Opposite Drive End Bearing Type 35. Opposite Drive End Bearing Type 36. Opposite Drive End Bearing Insulation or Grounding Device? 37. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? 38. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? 39. Opposite Drive End Bearing Condition 30. Opposite Drive End Bearing Condition 31. Drive End Seal 32. Opposite Drive End Seal 33. Opposite Drive End Seal 34. Ope Sleeve Bearing Inside Diameter 35. Obe Sleeve Bearing Utside Diameter 36. Odegrees 37. Drive End Seal 38. Opposite Drive End Seal 39. DE Sleeve Bearing Utside Diameter 39. DE Sleeve Bearing Housing Inside Diameter 39. DE Sleeve Bearing Housing Inside Diameter 39. Obe Sleeve Bearing Housing Inside Diameter 39. Obe Sleeve Bearing to Housing Clearance 39. Obe Sleeve Bearing Inside Diameter 39. Obe Sleeve Bearing Outside Diameter 39. Obe Sleeve Bearing Outside Diameter 39. Obe Sleeve Bearing Housing Inside Diameter	24.	Drive End Bearing Qty.		1	
27. Drive End Bearing Insulation or Grounding Device? 28. Drive End Wavy Washer/Snap-Ring Other Retention Device? 39. Drive End Bearing Condition 30. Opposite Drive End Bearing Number- 43. Opposite Drive End Bearing QIV. 41. Opposite Drive End Bearing QIV. 42. Opposite Drive End Bearing Type 43. Opposite Drive End Bearing Type 44. Opposite Drive End Bearing Insulation or Grounding Device? 45. Opposite Drive End Bearing Insulation or Grounding Device? 46. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? 47. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? 48. Opposite Drive End Bearing Insulation or Grounding Device? 49. Opposite Drive End Bearing Condition 40. Opposite Drive End Bearing Condition 40. Description End Seal 41. Description End Seal 42. Obes Sleeve Bearing Outside Diameter 43. Odegrees 44. Description End Searing Inside Diameter 44. Description End Searing Inside Diameter 45. ODE Sleeve Bearing Inside Diameter 46. Obes Sleeve Bearing Inside Diameter 47. Odegrees 48. As 49. Description End Searing Inside Diameter 40. Description End Searing End Diameter 41. Description End Searing End Diameter 42. Description End Searing End Diameter 43. Obes Sleeve Bearing Inside Diameter 44. ODE Sleeve Bearing Inside Diameter 45. ODE Sleeve Bearing Outside Diameter 46. ODE Sleeve Bearing Outside Diameter 47. Odegrees 48. As 49. ODE Sleeve Bearing Inside Diameter 40. Description End Searing End Diameter 41. Description End Searing End Diameter 42. Description End Searing End Diameter 43. Open End Searing End	25.	Drive End Bearing Type		(Ball) Ball Bearing	
28. Drive End Wavy Washer/Snap-Ring Other Retention Device?  29. Drive End Bearing Condition  30. Opposite Drive End Bearing Number-  31. Opposite Drive End Bearing Qty.  32. Opposite Drive End Bearing Type  33. Opposite Drive End Lubrication Type  34. Opposite Drive End Uubrication Type  35. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device?  36. Opposite Drive End Bearing Condition  37. Drive End Seal  38. Opposite Drive End Bearing Condition  39. Deposite Drive End Seal  39. DE Sleeve Bearing Inside Diameter  30. degrees  30. Opposite Drive End Seal  31. Drive End Seal  32. Opposite Drive End Seal  33. Opposite Drive End Seal  34. Opposite Drive End Seal  35. Opposite Drive End Seal  36. Opposite Drive End Seal  37. Drive End Seal  38. Opposite Drive End Seal  39. DE Sleeve Bearing Inside Diameter  30. degrees  30. DE Sleeve Bearing Outside Diameter  31. De Grees  32. De Sleeve Bearing Outside Diameter  33. Opposite Drive End Seal  34. DE Sleeve Bearing Housing Inside Diameter  35. degrees  36. Opposite Drive End Seal  37. Drive End Seal  38. Opposite Drive End Seal  39. DE Sleeve Bearing Housing Inside Diameter  39. DE Sleeve Bearing Housing Clearance  39. degrees  30. DE Sleeve Bearing to Housing Clearance  30. degrees  30. DE Sleeve Bearing Inside Diameter  30. degrees  31. De Sleeve Bearing Inside Diameter  32. De Sleeve Bearing Inside Diameter  33. Opposite Drive End Bearing Outside Diameter  34. ODE Sleeve Bearing Outside Diameter  36. Opposite Drive End Bearing Outside Diameter  37. Drive End Seal  38. Opposite Drive End Warter  39. De Sleeve Bearing Housing Inside Diameter  39. De Sleeve Bearing Housing Inside Diameter  39. De Sleeve Bearing Housing Inside Diameter  30. De Sleeve Bearing Housing Inside Diameter	26.	Drive End Lubrication Type		(Grease) Grease Lubricated	
29. Drive End Bearing Condition 6314 30. Opposite Drive End Bearing Number-6314 31. Opposite Drive End Bearing Qtv. 1 32. Opposite Drive End Bearing Type (Ball) Ball Bearing 33. Opposite Drive End Bearing Type (Grease) Grease Lubricated 34. Opposite Drive End Bearing Insulation or Grounding Device? na 35. Opposite Drive End Bearing Insulation or Grounding Device? bearing cap springs 36. Opposite Drive End Bearing Condition normal wear 37. Drive End Seal na 38. Opposite Drive End Bearing Condition normal wear 39. Drive End Seal na 39. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Wha 40. DE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees  Wha 41. DE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 240 degrees  Wha 42. DE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees  Wha 43. ODE Sleeve Bearing Inside Diameter 0 degrees 240 degrees  Wha 44. ODE Sleeve Bearing Inside Diameter 0 degrees 240 degrees  Wha 45. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees	27.	Drive End Bearing Insulation or Groun	nding Device?	na	
30. Opposite Drive End Bearing Number- 31. Opposite Drive End Bearing Qty. 31. Opposite Drive End Bearing Qty. 32. Opposite Drive End Bearing Type 33. Opposite Drive End Lubrication Type 34. Opposite Drive End Bearing Insulation or Grounding Device? 35. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? 36. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? 37. Drive End Seal 38. Opposite Drive End Seal 39. DE Sleeve Bearing Inside Diameter 39. Des Sleeve Bearing Outside Diameter 40. DE Sleeve Bearing Outside Diameter 50. degrees 40. DE Sleeve Bearing Housing Inside Diameter 60. degrees 41. Na 42. DE Sleeve Bearing to Housing Clearance 60. degrees 4240 degrees 43. ODE Sleeve Bearing Inside Diameter 60. degrees 44. ODE Sleeve Bearing Inside Diameter 60. degrees 44. ODE Sleeve Bearing Unside Diameter 60. degrees 44. ODE Sleeve Bearing Inside Diameter 60. degrees 44. ODE Sleeve Bearing Unside Diameter 60. degrees 44. ODE Sleeve Bearing Outside Diameter 60. degrees 44. ODE Sleeve Bearing Unside Diameter 60. degrees 44. ODE Sleeve Bearing Unside Diameter 60. degrees 44. ODE Sleeve Bearing Unside Diameter 70. degrees 44. ODE Sleeve Bearing Unside Diameter 70. degrees 44. ODE Sleeve Bearing Outside Diameter 70. degrees 44. ODE Sleeve Bearing Housing Inside Diameter 70. degrees 44. ODE Sleeve Bearing Unside Diameter 70. degrees 44. ODE Sleeve Bearing Housing Inside Diameter 70. degrees 44. ODE Sleeve Bearing Housing Inside Diameter 84. ODE Sleeve Bearing Housing Inside Diameter 84. ODE Sleeve Bearing Housing Inside Diameter 85. ODE Sleeve Bearing Housing Inside Diameter	28.	Drive End Wavy Washer/Snap-Ring C	Other Retention Device?	na	
31. Opposite Drive End Bearing Qty.  32. Opposite Drive End Bearing Type 33. Opposite Drive End Bearing Type 34. Opposite Drive End Bearing Type 35. Opposite Drive End Bearing Insulation or Grounding Device? 36. Opposite Drive End Bearing Insulation or Grounding Device? 37. Drive End Bearing Condition 38. Opposite Drive End Bearing Condition 39. Drive End Seal 39. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  140 degrees 120 degrees 240 degrees  140 degrees  150 degrees 240 degrees  240 degrees	29.	Drive End Bearing Condition		normal wear	
32. Opposite Drive End Bearing Type (Grease) Grease Lubricated na 33. Opposite Drive End Lubrication Type (Grease) Grease Lubricated na 34. Opposite Drive End Bearing Insulation or Grounding Device? na 35. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? bearing cap springs 36. Opposite Drive End Bearing Condition normal wear 37. Drive End Seal na 38. Opposite Drive End Seal na 38. Opposite Drive End Seal na 39. DE Sleeve Bearing Inside Diameter Odegrees 120 degrees 240 degrees  ## Ma  40. DE Sleeve Bearing Outside Diameter Odegrees 120 degrees 240 degrees  ## Ma  41. DE Sleeve Bearing Housing Inside Diameter Odegrees 120 degrees 240 degrees  ## Ma  42. DE Sleeve Bearing to Housing Clearance Odegrees 120 degrees 240 degrees  ## Ma  43. ODE Sleeve Bearing Inside Diameter Odegrees 240 degrees  ## Ma  44. ODE Sleeve Bearing Inside Diameter Odegrees 240 degrees	30.	Opposite Drive End Bearing Number-		6314	
33. Opposite Drive End Lubrication Type (Grease) Grease Lubricated na A Opposite Drive End Bearing Insulation or Grounding Device? na A 35. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? bearing cap springs A Opposite Drive End Searing Condition normal wear na A Norwe End Searing Condition normal wear na A 38. Opposite Drive End Seal na A 39. DE Sleeve Bearing Inside Diameter O degrees 120 degrees 240 degrees  **Na**  **Na**  **DE Sleeve Bearing Outside Diameter O degrees 120 degrees 240 degrees  **Na**  **Na**  **A1**  **DE Sleeve Bearing Housing Inside Diameter O degrees 120 degrees 240 degrees  **Na**  **Na**  **A2**  **DE Sleeve Bearing to Housing Clearance O degrees 120 degrees 240 degrees  **Na**  **Na**  **A3**  **A4**  **A5**  **A6**  **A6**  **A7**  **A7**  **A8**  **A8**  **A9**  **A	31.	Opposite Drive End Bearing Qty.		1	
34. Opposite Drive End Bearing Insulation or Grounding Device?  35. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device?  36. Opposite Drive End Bearing Condition  37. Drive End Seal  38. Opposite Drive End Seal  39. DE Sleeve Bearing Inside Diameter  0 degrees  120 degrees  240 degrees  140 degrees  140 degrees  140 degrees  140 degrees  140 degrees  140 degrees  150 degrees  160 degrees  170 degrees	32.	Opposite Drive End Bearing Type		(Ball) Ball Bearing	
35. Opposite Drive End Wavy Washer/Snap-Ring Other Retention Device? bearing cap springs 36. Opposite Drive End Bearing Condition normal wear 37. Drive End Seal na 38. Opposite Drive End Seal na 39. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Na 40. DE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees  Na 41. DE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 240 degrees  Na 42. DE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees  Na 43. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Na 44. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Na 45. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees	33.	Opposite Drive End Lubrication Type		(Grease) Grease Lubricated	
36. Opposite Drive End Bearing Condition na  37. Drive End Seal na  38. Opposite Drive End Seal na  39. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  40. DE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees  Na  41. DE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  42. DE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees  Na  43. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  44. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  45. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees	34.	Opposite Drive End Bearing Insulation	or Grounding Device?	na	
37. Drive End Seal na 38. Opposite Drive End Seal na 39. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Na 40. DE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees  Na 41. DE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 240 degrees  Na 42. DE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees  Na 42. DE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees  Na 43. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Na 44. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees	35.	Opposite Drive End Wavy Washer/Sn	ap-Ring Other Retention Device?	bearing cap springs	
38. Opposite Drive End Seal  39. DE Sleeve Bearing Inside Diameter  0 degrees 120 degrees 240 degrees   Na  40. DE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees   Na  41. DE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 240 degrees   Na  42. DE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees   Na  43. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees   Na  44. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees   Na  45. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees	36.	Opposite Drive End Bearing Condition	1	normal wear	
39. DE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  40. DE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees  Na  41. DE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  42. DE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees  Na  43. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  44. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees  Na  44. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees  Na  45. ODE Sleeve Bearing Housing Inside Diameter	37.	Drive End Seal		na	
0 degrees 120 degrees 240 degrees  Na  40. DE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees  Na  41. DE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  42. DE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees  Na  43. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  44. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees  Na  45. ODE Sleeve Bearing Housing Inside Diameter	38.	Opposite Drive End Seal		na	
Na  40. DE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees  Na  41. DE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  42. DE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees  Na  43. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  44. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees  Na  45. ODE Sleeve Bearing Housing Inside Diameter	39.	DE Sleeve Bearing Inside Diameter			
40. DE Sleeve Bearing Outside Diameter  0 degrees 120 degrees 240 degrees  Na  41. DE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  42. DE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees  Na  43. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  44. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees  Na  44. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees		0 degrees	120 degrees	240 degrees	
40. DE Sleeve Bearing Outside Diameter  0 degrees 120 degrees 240 degrees  Na  41. DE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  42. DE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees  Na  43. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  44. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees  Na  44. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees					
<ul> <li>0 degrees</li> <li>Na</li> <li>41. DE Sleeve Bearing Housing Inside Diameter</li> <li>0 degrees</li> <li>120 degrees</li> <li>240 degrees</li> <li>Na</li> <li>42. DE Sleeve Bearing to Housing Clearance</li> <li>0 degrees</li> <li>120 degrees</li> <li>240 degrees</li> <li>Na</li> <li>43. ODE Sleeve Bearing Inside Diameter</li> <li>0 degrees</li> <li>120 degrees</li> <li>240 degrees</li> <li>Na</li> <li>44. ODE Sleeve Bearing Outside Diameter</li> <li>0 degrees</li> <li>120 degrees</li> <li>240 degrees</li> <li>Na</li> <li>44. ODE Sleeve Bearing Outside Diameter</li> <li>0 degrees</li> <li>120 degrees</li> <li>240 degrees</li> <li>Na</li> <li>45. ODE Sleeve Bearing Housing Inside Diameter</li> </ul>	-				
<ul> <li>Na</li> <li>41. DE Sleeve Bearing Housing Inside Diameter</li></ul>	40.	•			
41. DE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  42. DE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees  Na  43. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  44. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees  Na  45. ODE Sleeve Bearing Housing Inside Diameter		0 degrees	120 degrees	240 degrees	
41. DE Sleeve Bearing Housing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  42. DE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees  Na  43. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  44. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees  Na  45. ODE Sleeve Bearing Housing Inside Diameter	_	Na			
0 degrees 120 degrees 240 degrees  Na  42. DE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees  Na  43. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  44. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees  Na  45. ODE Sleeve Bearing Housing Inside Diameter			amotor		
<ul> <li>Na</li> <li>42. DE Sleeve Bearing to Housing Clearance</li></ul>	41.			240 dogrado	
42. DE Sleeve Bearing to Housing Clearance 0 degrees 120 degrees 240 degrees  Na  43. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  44. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees  Na  45. ODE Sleeve Bearing Housing Inside Diameter		o degrees	120 degrees	240 degrees	
0 degrees 120 degrees 240 degrees  Na  43. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  44. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees  Na  45. ODE Sleeve Bearing Housing Inside Diameter	-	Na			
0 degrees 120 degrees 240 degrees  Na  43. ODE Sleeve Bearing Inside Diameter 0 degrees 120 degrees 240 degrees  Na  44. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees  Na  45. ODE Sleeve Bearing Housing Inside Diameter	42.	DE Sleeve Bearing to Housing Cleara	nce		
<ul> <li>Na</li> <li>43. ODE Sleeve Bearing Inside Diameter     0 degrees</li></ul>		•		240 degrees	
43. ODE Sleeve Bearing Inside Diameter  0 degrees 120 degrees 240 degrees  Na  44. ODE Sleeve Bearing Outside Diameter  0 degrees 120 degrees 240 degrees  Na  45. ODE Sleeve Bearing Housing Inside Diameter		<u> </u>	<u> </u>	Ŭ	
0 degrees 120 degrees 240 degrees  Na  44. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees  Na  45. ODE Sleeve Bearing Housing Inside Diameter	-	Na			
Na  44. ODE Sleeve Bearing Outside Diameter  0 degrees 120 degrees 240 degrees  Na  45. ODE Sleeve Bearing Housing Inside Diameter	43.	ODE Sleeve Bearing Inside Diameter			
<ul> <li>44. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees</li> <li>Na</li> <li>45. ODE Sleeve Bearing Housing Inside Diameter</li> </ul>		0 degrees	120 degrees	240 degrees	
<ul> <li>44. ODE Sleeve Bearing Outside Diameter 0 degrees 120 degrees 240 degrees</li> <li>Na</li> <li>45. ODE Sleeve Bearing Housing Inside Diameter</li> </ul>					
0 degrees 120 degrees 240 degrees  Na  45. ODE Sleeve Bearing Housing Inside Diameter					
<ul> <li>Na</li> <li>45. ODE Sleeve Bearing Housing Inside Diameter</li> </ul>	44.				
45. ODE Sleeve Bearing Housing Inside Diameter		0 degrees	120 degrees	240 degrees	
45. ODE Sleeve Bearing Housing Inside Diameter	_	Na			
			Diameter		
	45.			240 dograda	
0 degrees 120 degrees 240 degrees		o degrees	120 degrees	240 degrees	
■ Na	-	Na			

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

46.	46. ODE Sleeve Bearing to Housing Clearance				
10.	0 degrees	120 degrees	240 degrees		
	o degrees	120 4091000	210 dog.000		
•	Na				
Rotor Inspection					
47.	Rotor Type/Material		(Squirrel Aluminum) Squirrel Cage Aluminum Die Cast		
48.	Growler Test		(Pass) Pass		
49.	Number of Rotor Bars				
50.	Rotor Condition		pass		
51.	List the Parts needed for the Repair B 6314x2 bearings Wire for rewind	elow			
52.	Signature of Technician that Disassen	_	Cw		
lecha	anical Fits- Rotor				
53.	Shaft Runout		0.001 inches		
54.	Rotor Runout				
	Drive End Bearing Fit	Rotor Body	Opposite Drive End Bearing		
-	0.002				
55.	Coupling Fit Closest to Bearing Housi	ng			
	0 Degrees	90 Degrees	120 Degrees		
56	Counting Eit Classest to the and of the	Chaft			
56.	Coupling Fit Closest to the end of the		120 Dograps		
56.	Coupling Fit Closest to the end of the 0 Degrees	Shaft 60 Degrees	120 Degrees		
			120 Degrees		
	0 Degrees		120 Degrees 120 Degrees		
	0 Degrees  Drive End Bearing Shaft Fit	60 Degrees	·		
57.	0 Degrees  Drive End Bearing Shaft Fit  0 Degrees	60 Degrees	·		
57.	O Degrees  Drive End Bearing Shaft Fit O Degrees  2.7565x3  Drive End Bearing Shaft Fit Condition	60 Degrees	120 Degrees		
57. • 58.	0 Degrees  Drive End Bearing Shaft Fit 0 Degrees  2.7565x3  Drive End Bearing Shaft Fit Condition	60 Degrees	120 Degrees		
57. • 58.	O Degrees  Drive End Bearing Shaft Fit O Degrees  2.7565x3  Drive End Bearing Shaft Fit Condition Opposite Drive End Bearing Shaft Fit	60 Degrees 60 Degrees	120 Degrees (P) Pass		
57. 58. 59.	O Degrees  Drive End Bearing Shaft Fit O Degrees  2.7565x3  Drive End Bearing Shaft Fit Condition Opposite Drive End Bearing Shaft Fit O Degrees	60 Degrees 60 Degrees 60 Degrees	120 Degrees (P) Pass		
57. 58. 59.	O Degrees  Drive End Bearing Shaft Fit O Degrees  2.7565x3  Drive End Bearing Shaft Fit Condition Opposite Drive End Bearing Shaft Fit O Degrees  2.7564-2.7565x2	60 Degrees 60 Degrees 60 Degrees	120 Degrees  (P) Pass  120 Degrees		

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

**Mechanical Fits- Bearing Housings** 

6	62.	Drive End - Endbell Bearing Fit			
		0 Degrees	60 Degrees	120 Degrees	
-		5.9066-5.9067-5.9066			
6	3.	Drive End - Endbell Bearing Fit Condition	tion		(P) Pass
6	64.	Opposite Drive End - Endbell Bearing	Fit		
		0 Degrees	60 Degrees	120 Degrees	
-		5.9061-5.9062-5.9062			
6	65.	i. Opposite Drive End - Endbell Bearing Fit Condition			(P) Pass
6	66.	Bearing Cap Condition			
		Drive End Bearing Cap	Opposite Drive End Bearing Cap		
-		Pass			



67.	End Bell Air Seal Fits		
	Drive End Air Seal	Opposite Drive End Air Seal	
68.	List Machine Work Needed Below		
	Na		
69.	Technician		Cw
	lnh		
Root	Cause of Failure		
70.	Failure locations		
	Coil head of windings		
71.	Root cause of failure		

#### Mechanical Fits- Bearing Housings - Post Repair

72. DE Sleeve Bearing Inside ID Post Repair

Turn to turn short

Measure 1 Measure 2 Measure 3

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

73. DE Sleeve Bearing Outside ID Post Repair			
	Measure 1	Measure 2	Measure 3
74.	DE Sleeve Bearing Inside OD Post Repair		
	Measure 1	Measure 2	Measure 3
75.	DE Sleeve Bearing Outside OD Post Repair		
	Measure 1	Measure 2	Measure 3
76.	ODE Sleeve Bearing Inside ID Post R	epair	
	Measure 1	Measure 2	Measure 3
77.	ODE Sleeve Bearing Outside ID Post	Repair	
	Measure 1	Measure 2	Measure 3
78. ODE Sleeve Bearing Inside OD Post Repair			
	Measure 1	Measure 2	Measure 3
79.	ODE Sleeve Bearing Outside OD Pos	t Repair	
	Measure 1	Measure 2	Measure 3



#### STANDARD TERMS AND CONDITIONS FOR PURCHASE OF GOOD AND/OR SERVICES

- 1. APPLICABILITY. The sale of any and all goods and/or services by Mock, Inc. d/b/a Hi-Speed Industrial Service ("Hi-Speed") shall be specifically conditioned upon and subject to the following terms and conditions which are incorporated by reference into any contracts and purchase orders with Hi-Speed, and which shall form and become a part of any agreement related thereto. Buyer's acceptance of any offer or quotation made by Hi-Speed for sale of any goods or services is expressly made subject to the terms and conditions set forth herein and to be so effective, Buyer need not sign or approve these Terms and Conditions to be bound hereunder provided a copy of same is provided to Buyer through any means. None of the terms and conditions contained herein may be added to, expanded, changed, modified, superseded or otherwise altered except as revised in writing and duly executed by Hi-Speed, and all orders received by Hi-Speed shall be governed only by the terms and conditions contained herein, notwithstanding any terms, conditions or provisions of any purchase order, release order, authorization or any other form issued by the Buyer. Hi-Speed hereby objects to any additional, modified, changed, deleted, altered or other terms and conditions not contained herein and notifies Buyer that any such terms or provisions are expressly rejected by Hi-Speed.
- 2. PRICE. All quoted prices shall remain firm and binding for a period of thirty (30) days from the date of quotation or for the period specifically stated in the quotation. The price for any and all goods and/or services ordered or approved by Buyer after thirty (30) days from the date of any quotation are subject to any increase in price that may occur after the expiration of thirty (30) days from the issuance of the quotation and the date the Buyer releases any shipment.
- 3. SCOPE OF GOODS AND/OR SERVICES. The goods and/or services provided by Hi-Speed pursuant to any quotation shall be limited exclusively to those goods and/or services expressly identified therein. Hi-Speed does not assume any responsibility and/or liability for the failure to provide any other goods and/or services not identified in any quotation. Modifications, additions or deletions to or from the scope referenced in any quotation shall only bee effective if evidenced in writing and signed by Hi-Speed. The sale of any of all goods and/or services affected by such modification, addition or deletion shall be subject to these same Standard Terms and Conditions whether or not referenced therein.
- 4. <u>BILLING AND PAYMENT TERMS.</u> Hi-Speed shall invoice Buyer for all goods and/or services as same are rendered at the address listed on the quotation. Payments for all goods and/or services shall be due thirty (30) days from the date of the current invoice or as otherwise set forth in the quotation. Late payments are subject to a late fee of 5% of the total invoice amount. Recurring late payments may lead to a deposit requirement on future services or sale of goods. Buyer shall be liable to Hi-Speed for any and all fees and expenses incurred by Hi-Speed to collect any invoices or to enforce these Standard Terms and Conditions, including but not limited to, attorney's fees.
- 5. <u>DELIVERY OF GOODS AND/OR SERVICES.</u> Unless otherwise identified in the quotation, all shipments are F.O.B. Hi-Speed's warehouse and the title to and all risk of loss with respect to any goods shipped shall pass to Buyer when such goods are delivered to the carrier at Hi-Speed's warehouse. Hi-Speed will use its best efforts to affect delivery by the date or dates specified in the quotation. However, Hi-Speed shall not be liable for delay in or failure to make shipment, or to perform services, by any identified date for any reason whatsoever, including but not limited to, causes beyond its reasonable control, such as strikes, fires, floods, epidemics, quarantines, restrictions, severe weather, embargos, acts of God, or public enemy, war, riot, delays in transportation or the inability to obtain necessary labor, materials or manufacturing facilities.
- **DELIVERY SITE AND TIME FOR PERFORMANCE.** Hi-Speed and Buver agree that time is of the essence for the purchase order and that Buyer shall fully cooperate with Hi-Speed in order to allow Hi-Speed full access to prosecute its work diligently and in an orderly manner. Buyer shall assist Hi-Speed in every way possible to avoid delaying, disrupting or interfering with the progress of Hi-Speed's work at the project site. In the event Hi-Speed's work is delayed, hindered, suspended, disrupted, re-sequenced or interfered with or rendered less efficient or more costly or adversely affected in any way as a result of acts or omissions of Buyer or other contractors or employees of Buyer or by any other reason beyond Hi-Speed's control and without the fault of Hi-Speed, then, in such event, Buyer shall be liable to Hi-Speed for any damages, additional costs, expenses, labor, materials, man hours, acceleration costs, overtime, additional jobsite overhead, extended home office overhead, and any and all other direct and indirect expenses of whatsoever nature or kind, caused in whole or in part, as a result of any of the above-referenced occurrences. Hi-Speed's project records will be the basis for computing the additional costs and damages of Hi-Speed's labor, materials, expenses and overhead related to such changes. BUYER WARRANTS THAT THE SITE FOR DELIVERY OR INSTALLATION OF ANY GOODS AND/OR FOR THE PERFORMANCE OF ANY SERVICES SHALL BE READY AND ADEQUATE FOR HI-SPEED'S DELIVERY OF GOODS AND/OR PERFORMANCE OF SERVICES AND THAT HI-SPEED SHALL HAVE FULL ACCESS THERETO, FREE OF ALL OBSTRUCTIONS. BUYER SHALL ASSUME ALL EXTRA COSTS ASSOCIATED WITH HI-SPEED'S INABILITY TO INSTALL ANY GOODS OR PERFORM ANY SERVICES AS A RESULT OF BUYER'S FAILURE TO COMPLY WITH THIS PROVISION. HI-SPEED MAY NOT INSPECT THE SITE PRIOR TO DELIVERY AND/OR INSTALLATION OF GOODS AND/OR PERFORMANCE OF SERVICES AND MAKES NO WARRANTY AS TO THE SUFFICIENCY OF THE SITE FOR THE DELIVERY AND/OR INSTALLATION OF GOODS AND/OR THE PERFORMANCE OF SERVICES AT SUCH SITE.
- 7. INSPECTION/ACCEPTANCE. All goods and services ordered pursuant to any quotation shall be subject to inspection by Buyer after delivery or performance to determine conformity with the quotation and/or purchase order and Hi-Speed's advertised or published specifications. Buyer shall have a period of thirty (30) days from shipment of goods at the delivery destination specified in the quotation within which to inspect the goods for conformity with the quotation, order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. Buyer shall have a period of thirty (30) days following completion of any services within which to inspect the services for conformity with the quotation, purchase order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. If the goods delivered or services performed do not so conform, upon delivery of notice to Hi-Speed of any discrepancy, nonconformance or rejection, Hi-Speed shall have sixty (60) days to cure the alleged discrepancy and/or nonconformance. If Hi-Speed fails to cure in this time period, Buyer shall have the right to reject such goods or services. After the cure period, goods that have been delivered and rejected, in whole or in part, shall be returned to Hi-Speed. Buyer shall notify Hi-Speed and arrange for the return of the goods as required. Should such non-conforming services be rejected Hi-Speed shall, at its sole cost, re-perform the non-conforming services. Inspection or failure to inspect on any occasion shall not affect Buyer's rights under the warranty provisions herein.
- 8. WARRANTIES. Hi-Speed warrants that all goods shall conform in all material aspects to the goods identified in the quotation to Buyer and/or purchase order, and Hi-Speed makes to Buyer the manufacturer's express warranty for any goods sold to Buyer, which is offered by the manufacturer at the time of acceptance of any quotation by Buyer. This warranty is conditioned upon the installation, operation, and maintenance of the goods in accordance with the manufacturer's recommendations and/or standard industry practice and the goods at all times being operated or used under normal operating conditions for which they were designed. Hi-Speed, at its sole option, will repair or

replace any defective or non-conforming goods in accordance with the applicable manufacturer's warranty. Warranty for any defective or incorrect parts is limited to the repair or replacement of those parts. Hi-Speed warrants that all services will conform in all material respects to the description of services identified in the quotation and will be performed in a good and workmanlike manner in accordance with industry practices and standards. Should the services be reasonably rejected or not conform with the foregoing warranties, Hi-Speed shall, at its sole cost, re-perform the defective or nonconforming services. Notwithstanding the foregoing, these warranties do not extend to goods or services to the extent that such goods have been subject to misuse, neglect or abuse not caused by Hi-Speed or have been used in violation of the approved written instructions furnished to Buyer. THE FOREGOING REPRESENTS THE SOLE AND EXCLUSIVE WARRANTY GIVEN BY HI-SPEED WITH RESPECT TO ALL GOODS SOLD AND IS IN LIEU OF ALL OTHER WARRANTIES EITHER EXPRESS OR IMPLIED. HI-SPEED EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICLAR USE OR PURPOSE. BUYER WAIVES ANY CLAIM THAT THESE EXCLUSIONS OR LIMITATIONS DEPRIVE IT OF AN ADEQUATE REMEDY AT EQUITY OR LAW OR CAUSE THIS AGREEMENT TO FAIL IN ITS ESSENTIAL PURPOSE. BUYER SHALL BE ENTITLED TO NO OTHER REMEDY OTHER THAN AS SET FORTH HEREIN, REGARDLESS OF THE CLAIM OR CAUSE OF ACTION, WHETHER BASED IN CONTRACT, TORT, NEGLIGENCE, GOODS LIABILITY, STRICT LIABILITY OR OTHERWISE.

- 9. <u>LIMITATION OF DAMAGES.</u> HI-SPEED SHALL HAVE NO LIABILITY TO BUYER WITH RESPECT TO THE SALE OR DELIVERY OF ANY GOODS OR THE REPAIR THEREOF OR WITH RESPECT TO THE SALE OR PERFORMANCE OF ANY SERVICES, FOR LOST PROFITS, SPECIAL, CONSEQUENTIAL, EXEMPLARY, PUNITIVE OR INCIDENTAL DAMAGES OF ANY KIND OR NATURE WHETHER ARISING IN CONTRACT, TORT, GOODS LIABILITY OR OTHERWISE, EVEN IF HI-SPEED WAS ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGES. HI-SPEED SHALL NOT BE LIABLE FOR ANY DAMAGES OR DELAYS CAUSED BY ANY FAILURE TO MAKE ANY DELIVERY OF GOODS BY ANY EXPECTED TIME OR DATE OR THE FAILURE TO PROVIDE OR COMPLETE ANY SERVICES BY ANY EXPECTED DATE OR TIME. IN NO EVENT SHALL HI-SPEED BE LIABLE TO BUYER FOR ANY DAMAGES WHATSOEVER IN EXCESS OF THE TOTAL PRICE PAID FOR ALL GOODS AND/OR SERVICES HEREUNDER OR REFERENCED IN ANY QUOTATION OR THE PURCHASE ORDER.
- 10. <u>SEVERABILITY.</u> The partial or complete invalidity of any provision of these Standard Terms and Conditions shall not affect the enforceability of the remainder of these Standard Terms and Conditions. If any provision is found to be invalid or unenforceable, that portion shall be modified to make it enforceable or shall be stricken and the remainder of these Standard Terms and Conditions shall enforced.
- 11. **GOVERNING LAW AND JURISDICTION.** Any controversy arising out of any quotation, the purchase order, the goods sold or delivered, repair or replacement thereof, or any services provided pursuant to any quotation or any purchase order, or these Standard Terms and Conditions shall be governed by the laws of the state of Tennessee without regard to any choice of law provisions and any cause of action related in any manner thereto shall be brought only in the state or federal courts of Shelby County, Tennessee.
- 12. ABANDONED EQUIPMENT. Hi-Speed requires that Buyer promptly pick up or provide shipment instructions for Buyer equipment or other Buyer property in Hi-Speed's possession. If equipment or other Buyer property is left with Hi-Speed and not picked up within six (6) months after Hi-Speed's final action related to the applicable property (e.g. evaluation, teardown, estimate, completion of services), Hi-Speed will consider such property abandoned and may dispose of it in accordance with applicable law. Buyer agrees to hold Hi-Speed harmless for any damage or claim for such abandoned property and acknowledges that Hi-Speed may discard or recycle it at Hi-Speed's sole and absolute discretion. Specifically, Hi-Speed may sell Buyer's abandoned property at a private or public sale and retain the proceeds to offset Hi-Speed's storage, inspection and servicing costs. For the avoidance of doubt, Hi-Speed reserves its statutory and other lawful liens for unpaid charges related to abandoned property.
- 13. FORCE MAJEURE. Neither party shall be responsible for any delay or failure in performance of any party of the quotation, purchase order or these Standard Terms and Conditions to the extent that such delays or failures are caused by fire, flood, earth quake, explosion, war, embargo, government requirement, civil or military authority, acts of God, or any other circumstances beyond its reasonable control and not involving any fault or negligence on the party affected ("Condition"). If any such Condition occurs, the party delayed or unable to perform shall promptly give written notice to the other party and, if such Condition remains at the end of thirty (30) days, the party affected by the other party's delay and inability to perform may elect to (i) terminate such order or part thereof, or (ii) suspend the order for the duration of the Condition, if the Buyer is the suspending party, buy elsewhere comparable material to be sold under the order and apply to any commitment the purchase price of such purchase, and resume performance of the order once the Condition ceases, with an option in the affected party to extend the period of this order up to the length of the time the Condition endures.
- 14. <u>NONWAIVER.</u> No course of dealing or failure of either party to strictly enforce any term, right, or condition of these Standard Terms and Conditions will be construed as a waiver of such term, right or condition. Any waiver by Hi-Speed will only be in writing and will waive no succeeding breach of a term, right or condition.
- 15. **ASSIGNMENT.** The rights and obligations of the parties shall neither be assigned nor delegated without the prior written consent of the other party. However, any party may assign or delegate its respective rights and obligations, in whole or in part, (i) to any subsidiary, (ii) pursuant to other financing, merger or reorganization or (iii) pursuant to any sale or transfer of substantially all of the assets of the assigning party. These Standard Terms and Conditions shall bind the heirs, successors and assigns of the parties hereto.
- 16. NO INDIVIDUAL LIABILITY. Notwithstanding any other agreement to the contrary, the Buyer agrees that in no event will the Buyer hold and HI-Speed owner, director, officer or employee personally liable for unintentional tortious conduct or conduct that constitutes the breach of any contract between HI-Speed and the Buyer, even if the HI-Speed owner, director, officer or employee is or could be construed to be a party to such contract.