

# EVERY DAY SINCE 1946

**Motor Shop Repairs** 

## Job Number 98002

Prepared for Kordsmeier (10022)

118 Harkrider Conway AR 72032

### Table of Contents

AC Recondition Repair Report



Hi-Speed Industrial Service 7030 Ryburn Dr Millington, Tn 38053 901-873-5300

BALDOR

FolderID: 98002

FormID: 10259844

#### **AC Recondition Repair Report**

#### Kordsmeier (10022)

118 Harkrider Conway, AR 72032

#### Priorities Found: **17 - Good**

General				
1. Job Number	98002			
2. Report Date	3/18/2021			
3. Customer	KORDSMEIR			
Name Plate Information				

4. Manufacturer

















5.	Model	
6.	Serial Number	Z0601230240
7.	Horsepower	60
8.	KW	
9.	Volts	460
10.	Amps	72
11.	RPM	1770
12.	Frame	364TC
13.	Enclosure	ODP
14.	Cycles	60
15.	Phase	3
16.	Service Factor	1.15
17.	Motor Mount Position	
Initial	Inspection	
18.	Number of Leads	9
19.	Lead Length	12 Inches
20.	Lead Size	6
21.	Lead Condition	(P) Pass
22.	Lead Markings	printed
23.	Lug Size, Condition, and Type	
24.	Winding RTD's	(NA) Not Applicable
25.	Winding Rtd's Condition	

26.	Shaft Run Out	
20.		201
	Does Shaft Have Visible Damage	yes
	-	(NA) Net Applicable
	Bearing Rtd's	(NA) Not Applicable
30.	5	
31.		
32.	Frame Condition	(P) Pass
33.	Fan Condition	(NA) Not Applicable
34.	Broken or missing components	
Initial	Electric Test	
35.	Resistance to Ground	
36.	Winding Resistance 1-2	
37.	Winding Resistance 2-3	
38.	Winding Resistance 1-3	
39.		
40.	Hi-Pot	
41.		(P) Pass
-	Stator Condition	grease contamination
	Failure Location	groupe containination
	Rotor Inspection	
	-	cast aluminum
	Rotor Type	cast auminum
	Air Gap <10% Variation	<i>(</i> 0)
	Number of Rotor Bars	48
	Number of Broken Rotor Bars	
48.		(P) Pass
-	Rotor Condition	(P) Pass
Mecha	anical Inspection	
50.	Bearing Manufacture	FAG
51.	Bearing DE Size	6313
52.	Bearing DE Type	bell
53.	DE Bearing Qty.	1
54.	Bearing ODE Size	6311
55.	-	ball
56.		1
57.	Insulated Bearing	
58.	Lubrication Type	
59.	Grease Condition	(P) Pass
<b>6</b> 0.	Bearing Retainers	(Y) Yes
61.	-	(1) Tes (Y) Yes
62.	DE Seal	(NA) Not Applicable
63.	DE Seal Type/Size	
	ODE Seal	(NA) Not Applicable
65.		
	Cause of Failure	
66.	Component Failure	ODE bearing false brinelling
67.	Cause of Failure	
	None	

<b>/achine F</b> 70. Sha 71. Initia 72. Fina	vice Technician <b>Fit Inspection Report</b> aff Run Out al Shaft Run Out	David Maclin
<ul><li>70. Sha</li><li>71. Initia</li><li>72. Fina</li></ul>	aft Run Out	
<ul><li>70. Sha</li><li>71. Initia</li><li>72. Fina</li></ul>	aft Run Out	
<ul><li>70. Sha</li><li>71. Initia</li><li>72. Fina</li></ul>	aft Run Out	
<ul><li>70. Sha</li><li>71. Initia</li><li>72. Fina</li></ul>	aft Run Out	
<ul><li>70. Sha</li><li>71. Initia</li><li>72. Fina</li></ul>	aft Run Out	
71. Initia 72. Fina		
72. Fina	al Shaft Run Out	
73. DE	al Shaft Run Out	
	Bearing Shaft Fit	(P) Pass
74. DE	Initial Shaft Bearing Fit Size 1	2.5595 "
75. DE	Initial Shaft Bearing Fit Size 2	2.5595 "
	Initial Shaft Bearing Fit Size 3	2.5595 "
	Finial Shaft Bearing Fit Size 1	
	Finial Shaft Bearing Fit Size 2	
	Finial Shaft Bearing Fit Size 3	
	E Bearing Shaft Fit	(P) Pass
	E Initial Shaft Bearing Fit Size 1	2.166 "
	E Initial Shaft Bearing Fit Size 2	2.166 "
	E Initial Shaft Bearing Fit Size 3	2.166 "
	E Finial Shaft Bearing Fit Size 1	
	E Finial Shaft Bearing Fit Size 2	
	E Finial Shaft Bearing Fit Size 3	
	Air Seal Shaft Fit	
	Initial Air Seal Shaft Size	
	Final Air Seal Shaft Size	
	E Air Seal Shaft Fit	
	E Initial Air Seal Shaft Size	
	E Final Air Seal Shaft Size	(=) =
	Endbell Fit	(P) Pass
• · · ·	Initial Endbell Fit Size 1	5.512 "
	Initial Endbell Fit Size 2	5.512 "
	Initial Endbell Fit Size 3	5.512 "
-	Final Endbell Fit Size 1	
	Finial Endbell Fit Size 2	
	Final Endbell Fit Size 3	
	Endbell Fit Insulated	
-	Endbell Air Seal Fit al Endbell Air Seal Fit Size	
	al Endbell Air Seal Fit Size	
	E Endbell Fit E Initial Endbell Fit Size 1	(P) Pass
		4.725 "
	E Initial Endbell Fit Size 2 E Initial Endbell Fit Size 3	4.725 "
	E Initial Endbell Fit Size 3 E Final Endbell Fit Size 1	4.725 "
	E Final Enddell Fit Size 1 E Final Endbell Fit Size 2	

110. ODE Final Endbell Fit Size 3	
111. ODE Endbell Fit Insulated	
112. ODE Endbell Air Seal Fit	
113. ODE Initial Endbell Seal Fit Size	
114. ODE Finial Endbell Seal Fit Size	
115. Foot Flatness	(NA) Not Applicable
116. Foot Condition	(NA) Not Applicable
117. Flange Condition	(P) Pass
118. Service Technician	David Maclin
Balancing Report 119. Balance Type	
120. Balance Operating Speed	
121. Start Left End	
122. Start Right End	
123. Balancing Specification	
124. Finish Left End	
125. Finish Right End	
126. Service Technician	David Maclin

#### 127. Meggar Testing Reading

mer;	KORDSMI AR	ER			Contact: Phone: Date:	3/30/2021
Number: Al No: afacturer: el: r: ne: losure: ni:	98002 206012303 BALDOR 42H074W 3-Phase M OPEN 4	39042			Voltage: Current Horsepower: RPM: Power Factor: Efficiency: Field V: Field A:	460 72 60 1770
- A-8	(V) B-C (V	) CA (V	A (A)	8.(A)	C (A)	
ted By	450	459	27.6	29.6	27	Date

128. Surge Test         129. HI-Pot         130. Winding Resistance 1-2         131. Winding Resistance 2-3         132. Winding Resistance 2-3         133. Test Run Voltage Phase A         134. Test Run Voltage Phase A         135. Test Run Voltage Phase B         136. Test Run Amps A         137. Test Run Voltage Phase C         138. Test Run Voltage Phase C         139. DE Horizontal Vibration Reading       0.0375 In/Sec         140. DE Vertical Vibration Reading       0.0675 In/Sec         141. DE Axial Vibration Reading       0.03265 In/Sec         142. ODE Horizontal Vibration Reading       0.0325 In/Sec         143. ODE Vertical Vibration Reading       0.0325 In/Sec         144. ODE Horizontal Vibration Reading       0.0321 In/Sec         145. Ambient Temp at start of Test Run       146. Temp at 5 minutes         147. Temp at 10 minutes       149. Temp at 20 minutes         148. Temp at 20 minutes       150. Temp at 25 minutes         150. Temp at 35 minutes       151. Temp at 30 minutes         151. Temp at 30 minutes       153. Temp at 40 minutes         152. Temp at 35 minutes       151. Temp at 35 minutes         153. Temp at 40 minutes       155. Temp at 45 minutes         154. Temp at 50 minutes       155. Temp at 60 minutes			
130. Winding Resistance 1-2         131. Winding Resistance 1-3         132. Winding Resistance 1-3         133. Test Run Voltage Phase A         134. Test Run Amps A         135. Test Run Voltage Phase B         136. Test Run Voltage Phase C         137. Test Run Voltage Phase C         138. Test Run Voltage Phase C         139. DE Horizontal Vibration Reading       0.0375 in/Sec         140. DE Vertical Vibration Reading       0.0375 in/Sec         141. DE Axial Vibration Reading       0.0433 in/Sec         142. ODE Horizontal Vibration Reading       0.0325 in/Sec         144. ODE Vertical Vibration Reading       0.0325 in/Sec         145. Ambient Temp at start of Test Run       0.0321 in/Sec         146. Temp at 5 minutes       147. Temp at 10 minutes         147. Temp at 20 minutes       148. Temp at 20 minutes         150. Temp at 20 minutes       151. Temp at 30 minutes         152. Temp at 35 minutes       151. Temp at 40 minutes         153. Temp at 40 minutes       155. Temp at 40 minutes         155. Temp at 45 minutes       155. Temp at 60 minutes         155. Temp at 60 minutes       155. Temp at 60 minutes	128.	Surge Test	
131. Winding Resistance 2-3         132. Winding Resistance 1-3         133. Test Run Voltage Phase A         134. Test Run Amps A         135. Test Run Voltage Phase B         136. Test Run Amps B         137. Test Run Voltage Phase C         138. Test Run Amps C         139. DE Horizontal Vibration Reading       0.0375 In/Sec         140. DE Vertical Vibration Reading       0.0675 In/Sec         141. DE Axial Vibration Reading       0.0265 In/Sec         142. ODE Horizontal Vibration Reading       0.0433 In/Sec         143. ODE Vertical Vibration Reading       0.032299999999999999999999999999999 In/Sec         144. ODE Axial Vibration Reading       0.0321 In/Sec         144. ODE Axial Vibration Reading       0.0321 In/Sec         145. Ambient Temp at start of Test Run       146. Temp at 5 minutes         147. Temp at 10 minutes       148. Temp at 20 minutes         148. Temp at 20 minutes       150. Temp at 30 minutes         150. Temp at 35 minutes       151. Temp at 30 minutes         152. Temp at 35 minutes       153. Temp at 45 minutes         154. Temp at 40 minutes       155. Temp at 55 minutes         155. Temp at 55 minutes       155. Temp at 55 minutes         155. Temp at 55 minutes       155. Temp at 55 minutes         155. Temp at 55 minutes	129.	Hi-Pot	
132. Winding Resistance 1-3         133. Test Run Voltage Phase A         134. Test Run Amps A         135. Test Run Voltage Phase B         136. Test Run Amps B         137. Test Run Voltage Phase C         138. Test Run Amps C         139. DE Horizontal Vibration Reading       0.0375 In/Sec         140. DE Vertical Vibration Reading       0.0675 In/Sec         141. DE Axial Vibration Reading       0.04675 In/Sec         142. ODE Horizontal Vibration Reading       0.04251 In/Sec         144. DE Axial Vibration Reading       0.0321 In/Sec         145. Ambient Temp at start of Test Run       0.0321 In/Sec         146. Temp at 5 minutes       0.0321 In/Sec         147. Temp at 10 minutes       148. Temp at 20 minutes         148. Temp at 20 minutes       150. Temp at 25 minutes         150. Temp at 35 minutes       151. Temp at 30 minutes         152. Temp at 35 minutes       153. Temp at 45 minutes         153. Temp at 40 minutes       155. Temp at 55 minutes         155. Temp at 55 minutes       155. Temp at 55 minutes         155. Temp at 55 minutes       155. Temp at 56 minutes         155. Temp at 55 minutes       155. Temp at 56 minutes         155. Temp at 50 minutes       155. Temp at 56 minutes         155. Temp at 50 minutes       155.	130.	Winding Resistance 1-2	
133. Test Run Voltage Phase A         134. Test Run Amps A         135. Test Run Voltage Phase B         136. Test Run Amps B         137. Test Run Voltage Phase C         138. Test Run Voltage Phase C         139. DE Horizontal Vibration Reading       0.0375 In/Sec         140. DE Vertical Vibration Reading       0.0675 In/Sec         141. DE Axial Vibration Reading       0.0265 In/Sec         142. ODE Horizontal Vibration Reading       0.0321 In/Sec         143. ODE Vertical Vibration Reading       0.0922999999999999 In/Sec         144. ODE Axial Vibration Reading       0.0321 In/Sec         145. Ambient Temp at start of Test Run       0.0321 In/Sec         146. Temp at 5 minutes       147. Temp at 10 minutes         148. Temp at 20 minutes       148. Temp at 20 minutes         149. Temp at 20 minutes       150. Temp at 30 minutes         151. Temp at 30 minutes       152. Temp at 35 minutes         152. Temp at 35 minutes       153. Temp at 40 minutes         153. Temp at 50 minutes       155. Temp at 50 minutes         155. Temp at 50 minutes       155. Temp at 50 minutes         155. Temp at 50 minutes       156. Temp at 50 minutes	131.	Winding Resistance 2-3	
134. Test Run Amps A135. Test Run Voltage Phase B136. Test Run Amps B137. Test Run Voltage Phase C138. Test Run Amps C139. DE Horizontal Vibration Reading0.0375 In/Sec140. DE Vertical Vibration Reading0.0675 In/Sec141. DE Axial Vibration Reading0.0433 In/Sec142. ODE Horizontal Vibration Reading0.0433 In/Sec143. ODE Vertical Vibration Reading0.0321 In/Sec144. ODE Axial Vibration Reading0.0321 In/Sec145. Ambient Temp at start of Test Run0.0321 In/Sec146. Temp at 5 minutes147. Temp at 10 minutes147. Temp at 20 minutes148. Temp at 20 minutes150. Temp at 35 minutes152. Temp at 36 minutes153. Temp at 40 minutes155. Temp at 50 minutes154. Temp at 50 minutes155. Temp at 50 minutes155. Temp at 50 minutes156. Temp at 50 minutes156. Temp at 50 minutes156. Temp at 50 minutes	132.	Winding Resistance 1-3	
135. Test Run Voltage Phase B136. Test Run Amps B137. Test Run Voltage Phase C138. Test Run Amps C139. DE Horizontal Vibration Reading0.0375 In/Sec140. DE Vertical Vibration Reading0.0675 In/Sec141. DE Axial Vibration Reading0.0265 In/Sec142. ODE Horizontal Vibration Reading0.0433 In/Sec143. ODE Vertical Vibration Reading0.0922999999999999999999999999999999999	133.	Test Run Voltage Phase A	
136. Test Run Amps B137. Test Run Voltage Phase C138. Test Run Amps C139. DE Horizontal Vibration Reading0.0375 In/Sec140. DE Vertical Vibration Reading0.0675 In/Sec141. DE Axial Vibration Reading0.0265 In/Sec142. ODE Horizontal Vibration Reading0.0433 In/Sec143. ODE Vertical Vibration Reading0.092299999999999999 In/Sec144. ODE Axial Vibration Reading0.09229999999999999999999 In/Sec145. Ambient Temp at start of Test Run0.0321 In/Sec146. Temp at 5 minutes147. Temp at 10 minutes148. Temp at 15 minutes148. Temp at 20 minutes150. Temp at 25 minutes151. Temp at 30 minutes152. Temp at 36 minutes153. Temp at 40 minutes155. Temp at 50 minutes155. Temp at 50 minutes156. Temp at 50 minutes155. Temp at 50 minutes157. Temp at 60 minutes157. Temp at 60 minutes	134.	Test Run Amps A	
137. Test Run Voltage Phase C138. Test Run Amps C139. DE Horizontal Vibration Reading0.0375 In/Sec140. DE Vertical Vibration Reading0.0675 In/Sec141. DE Axial Vibration Reading0.0265 In/Sec142. ODE Horizontal Vibration Reading0.0433 In/Sec143. ODE Vertical Vibration Reading0.0922999999999999999999999999999999999	135.	Test Run Voltage Phase B	
138. Test Run Amps C139. DE Horizontal Vibration Reading0.0375 In/Sec140. DE Vertical Vibration Reading0.0675 In/Sec141. DE Axial Vibration Reading0.0265 In/Sec142. ODE Horizontal Vibration Reading0.0433 In/Sec143. ODE Vertical Vibration Reading0.09229999999999999999999999999999999144. ODE Axial Vibration Reading0.0321 In/Sec145. Ambient Temp at start of Test Run0.0321 In/Sec146. Temp at 5 minutes147. Temp at 10 minutes148. Temp at 15 minutes148. Temp at 20 minutes150. Temp at 20 minutes151. Temp at 30 minutes152. Temp at 30 minutes153. Temp at 40 minutes154. Temp at 45 minutes154. Temp at 45 minutes155. Temp at 50 minutes155. Temp at 50 minutes156. Temp at 55 minutes156. Temp at 55 minutes157. Temp at 60 minutes157. Temp at 60 minutes	136.	Test Run Amps B	
139. DE Horizontal Vibration Reading0.0375 In/Sec140. DE Vertical Vibration Reading0.0675 In/Sec141. DE Axial Vibration Reading0.0265 In/Sec142. ODE Horizontal Vibration Reading0.0433 In/Sec143. ODE Vertical Vibration Reading0.09229999999999999999999999999999999144. ODE Axial Vibration Reading0.0321 In/Sec145. Ambient Temp at start of Test Run0.0321 In/Sec146. Temp at 5 minutes147. Temp at 10 minutes148. Temp at 15 minutes148. Temp at 20 minutes150. Temp at 20 minutes151. Temp at 30 minutes152. Temp at 30 minutes152. Temp at 35 minutes153. Temp at 40 minutes154. Temp at 45 minutes155. Temp at 50 minutes155. Temp at 50 minutes156. Temp at 55 minutes156. Temp at 55 minutes157. Temp at 60 minutes157. Temp at 60 minutes	137.	Test Run Voltage Phase C	
140. DE Vertical Vibration Reading0.0675 In/Sec141. DE Axial Vibration Reading0.0265 In/Sec142. ODE Horizontal Vibration Reading0.0433 In/Sec143. ODE Vertical Vibration Reading0.0922999999999999999999999999999999999	138.	Test Run Amps C	
141. DE Axial Vibration Reading0.0265 In/Sec142. ODE Horizontal Vibration Reading0.0433 In/Sec143. ODE Vertical Vibration Reading0.0922999999999999999999999999999999999	139.	DE Horizontal Vibration Reading	0.0375 In/Sec
142. ODE Horizontal Vibration Reading0.0433 In/Sec143. ODE Vertical Vibration Reading0.0922999999999999999999999999999999999	140.	DE Vertical Vibration Reading	0.0675 In/Sec
143. ODE Vertical Vibration Reading0.0922999999999999999999999999999999999	141.	DE Axial Vibration Reading	0.0265 In/Sec
144. ODE Axial Vibration Reading0.0321 In/Sec145. Ambient Temp at start of Test Run146. Temp at 5 minutes147. Temp at 10 minutes148. Temp at 15 minutes149. Temp at 20 minutes150. Temp at 20 minutes151. Temp at 30 minutes152. Temp at 35 minutes153. Temp at 40 minutes154. Temp at 45 minutes155. Temp at 50 minutes156. Temp at 55 minutes157. Temp at 60 minutes	142.	ODE Horizontal Vibration Reading	0.0433 In/Sec
145. Ambient Temp at start of Test Run146. Temp at 5 minutes147. Temp at 10 minutes148. Temp at 15 minutes149. Temp at 20 minutes150. Temp at 20 minutes151. Temp at 30 minutes152. Temp at 35 minutes153. Temp at 40 minutes154. Temp at 45 minutes155. Temp at 50 minutes156. Temp at 55 minutes157. Temp at 60 minutes	143.	ODE Vertical Vibration Reading	0.0922999999999999 In/Sec
146. Temp at 5 minutes147. Temp at 10 minutes148. Temp at 15 minutes149. Temp at 20 minutes150. Temp at 25 minutes151. Temp at 30 minutes152. Temp at 35 minutes153. Temp at 40 minutes154. Temp at 45 minutes155. Temp at 50 minutes156. Temp at 55 minutes157. Temp at 60 minutes	144.	ODE Axial Vibration Reading	0.0321 In/Sec
147. Temp at 10 minutes148. Temp at 15 minutes149. Temp at 20 minutes150. Temp at 25 minutes151. Temp at 30 minutes152. Temp at 35 minutes153. Temp at 40 minutes154. Temp at 45 minutes155. Temp at 50 minutes156. Temp at 55 minutes157. Temp at 60 minutes	145.	Ambient Temp at start of Test Run	
148. Temp at 15 minutes149. Temp at 20 minutes150. Temp at 25 minutes151. Temp at 30 minutes152. Temp at 35 minutes153. Temp at 40 minutes154. Temp at 45 minutes155. Temp at 50 minutes156. Temp at 55 minutes157. Temp at 60 minutes	146.	Temp at 5 minutes	
149. Temp at 20 minutes150. Temp at 25 minutes151. Temp at 30 minutes152. Temp at 35 minutes153. Temp at 40 minutes154. Temp at 45 minutes155. Temp at 50 minutes156. Temp at 55 minutes157. Temp at 60 minutes	147.	Temp at 10 minutes	
150. Temp at 25 minutes151. Temp at 30 minutes152. Temp at 35 minutes153. Temp at 40 minutes154. Temp at 45 minutes155. Temp at 50 minutes156. Temp at 55 minutes157. Temp at 60 minutes	148.	Temp at 15 minutes	
<ul> <li>151. Temp at 30 minutes</li> <li>152. Temp at 35 minutes</li> <li>153. Temp at 40 minutes</li> <li>154. Temp at 45 minutes</li> <li>155. Temp at 50 minutes</li> <li>156. Temp at 55 minutes</li> <li>157. Temp at 60 minutes</li> </ul>	149.	Temp at 20 minutes	
152. Temp at 35 minutes153. Temp at 40 minutes154. Temp at 45 minutes155. Temp at 50 minutes156. Temp at 55 minutes157. Temp at 60 minutes	150.	Temp at 25 minutes	
153. Temp at 40 minutes154. Temp at 45 minutes155. Temp at 50 minutes156. Temp at 55 minutes157. Temp at 60 minutes	151.	Temp at 30 minutes	
154. Temp at 45 minutes         155. Temp at 50 minutes         156. Temp at 55 minutes         157. Temp at 60 minutes	152.	Temp at 35 minutes	
155. Temp at 50 minutes         156. Temp at 55 minutes         157. Temp at 60 minutes	153.	Temp at 40 minutes	
156. Temp at 55 minutes     157. Temp at 60 minutes	154.	Temp at 45 minutes	
157. Temp at 60 minutes	155.	Temp at 50 minutes	
	156.	Temp at 55 minutes	
158. Motor Paint     (P) Pass	157.	Temp at 60 minutes	
	158.	Motor Paint	(P) Pass











#### STANDARD TERMS AND CONDITIONS FOR PURCHASE OF GOOD AND/OR SERVICES

- 1. <u>APPLICABILITY.</u> The sale of any and all goods and/or services by Mock, Inc. d/b/a Hi-Speed Industrial Service ("Hi-Speed") shall be specifically conditioned upon and subject to the following terms and conditions which are incorporated by reference into any contracts and purchase orders with Hi-Speed, and which shall form and become a part of any agreement related thereto. Buyer's acceptance of any offer or quotation made by Hi-Speed for sale of any goods or services is expressly made subject to the terms and conditions set forth herein and to be so effective, Buyer need not sign or approve these Terms and Conditions to be bound hereunder provided a copy of same is provided to Buyer through any means. None of the terms and conditions contained herein may be added to, expanded, changed, modified, superseded or otherwise altered except as revised in writing and duly executed by Hi-Speed, and all orders received by Hi-Speed shall be governed only by the terms and conditions contained herein, notwithstanding any terms, conditions or provisions of any purchase order, release order, authorization or any other form issued by the Buyer. Hi-Speed hereby objects to any additional, modified, changed, deleted, altered or other terms and conditions not contained herein and notifies Buyer that any such terms or provisions are expressly rejected by Hi-Speed.
- 2. PRICE. All quoted prices shall remain firm and binding for a period of thirty (30) days from the date of quotation or for the period specifically stated in the quotation. The price for any and all goods and/or services ordered or approved by Buyer after thirty (30) days from the date of any quotation are subject to any increase in price that may occur after the expiration of thirty (30) days from the issuance of the quotation and the date the Buyer releases any shipment.
- 3. <u>SCOPE OF GOODS AND/OR SERVICES.</u> The goods and/or services provided by Hi-Speed pursuant to any quotation shall be limited exclusively to those goods and/or services expressly identified therein. Hi-Speed does not assume any responsibility and/or liability for the failure to provide any other goods and/or services not identified in any quotation. Modifications, additions or deletions to or from the scope referenced in any quotation shall only be effective if evidenced in writing and signed by Hi-Speed. The sale of any of all goods and/or services affected by such modification, addition or deletion shall be subject to these same Standard Terms and Conditions whether or not referenced therein.
- 4. <u>BILLING AND PAYMENT TERMS.</u> Hi-Speed shall invoice Buyer for all goods and/or services as same are rendered at the address listed on the quotation. Payments for all goods and/or services shall be due thirty (30) days from the date of the current invoice or as otherwise set forth in the quotation. Late payments are subject to a late fee of 5% of the total invoice amount. Recurring late payments may lead to a deposit requirement on future services or sale of goods. Buyer shall be liable to Hi-Speed for any and all fees and expenses incurred by Hi-Speed to collect any invoices or to enforce these Standard Terms and Conditions, including but not limited to, attorney's fees.
- 5. DELIVERY OF GOODS AND/OR SERVICES. Unless otherwise identified in the quotation, all shipments are F.O.B. Hi-Speed's warehouse and the title to and all risk of loss with respect to any goods shipped shall pass to Buyer when such goods are delivered to the carrier at Hi-Speed's warehouse. Hi-Speed will use its best efforts to affect delivery by the date or dates specified in the quotation. However, Hi-Speed shall not be liable for delay in or failure to make shipment, or to perform services, by any identified date for any reason whatsoever, including but not limited to, causes beyond its reasonable control, such as strikes, fires, floods, epidemics, quarantines, restrictions, severe weather, embargos, acts of God, or public enemy, war, riot, delays in transportation or the inability to obtain necessary labor, materials or manufacturing facilities.
- 6. DELIVERY SITE AND TIME FOR PERFORMANCE. Hi-Speed and Buver agree that time is of the essence for the purchase order and that Buyer shall fully cooperate with Hi-Speed in order to allow Hi-Speed full access to prosecute its work diligently and in an orderly manner. Buyer shall assist Hi-Speed in every way possible to avoid delaying, disrupting or interfering with the progress of Hi-Speed's work at the project site. In the event Hi-Speed's work is delayed, hindered, suspended, disrupted, re-sequenced or interfered with or rendered less efficient or more costly or adversely affected in any way as a result of acts or omissions of Buyer or other contractors or employees of Buyer or by any other reason beyond Hi-Speed's control and without the fault of Hi-Speed, then, in such event, Buyer shall be liable to Hi-Speed for any damages, additional costs, expenses, labor, materials, man hours, acceleration costs, overtime, additional jobsite overhead, extended home office overhead, and any and all other direct and indirect expenses of whatsoever nature or kind, caused in whole or in part, as a result of any of the above-referenced occurrences. Hi-Speed's project records will be the basis for computing the additional costs and damages of Hi-Speed's labor, materials, expenses and overhead related to such changes. BUYER WARRANTS THAT THE SITE FOR DELIVERY OR INSTALLATION OF ANY GOODS AND/OR FOR THE PERFORMANCE OF ANY SERVICES SHALL BE READY AND ADEQUATE FOR HI-SPEED'S DELIVERY OF GOODS AND/OR PERFORMANCE OF SERVICES AND THAT HI-SPEED SHALL HAVE FULL ACCESS THERETO, FREE OF ALL OBSTRUCTIONS. BUYER SHALL ASSUME ALL EXTRA COSTS ASSOCIATED WITH HI-SPEED'S INABILITY TO INSTALL ANY GOODS OR PERFORM ANY SERVICES AS A RESULT OF BUYER'S FAILURE TO COMPLY WITH THIS PROVISION. HI-SPEED MAY NOT INSPECT THE SITE PRIOR TO DELIVERY AND/OR INSTALLATION OF GOODS AND/OR PERFORMANCE OF SERVICES AND MAKES NO WARRANTY AS TO THE SUFFICIENCY OF THE SITE FOR THE DELIVERY AND/OR INSTALLATION OF GOODS AND/OR THE PERFORMANCE OF SERVICES AT SUCH SITE.
- 7. INSPECTION/ACCEPTANCE. All goods and services ordered pursuant to any quotation shall be subject to inspection by Buyer after delivery or performance to determine conformity with the quotation and/or purchase order and Hi-Speed's advertised or published specifications. Buyer shall have a period of thirty (30) days from shipment of goods at the delivery destination specified in the quotation within which to inspect the goods for conformity with the quotation, order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. Buyer shall have a period of thirty (30) days following completion of any services within which to inspect the services for conformity with the quotation, purchase order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. If the goods delivered or services performed do not so conform, upon delivery of notice to Hi-Speed of any discrepancy, nonconformance or rejection, Hi-Speed shall have the right to reject such goods or services. After the cure period, goods that have been delivered and rejected, in whole or in part, shall be returned to Hi-Speed shall, at its sole cost, re-perform the non-conforming services. Inspection or failure to inspect on any occasion shall not affect Buyer's rights under the warranty provisions herein.
- 8. WARRANTIES. Hi-Speed warrants that all goods shall conform in all material aspects to the goods identified in the quotation to Buyer and/or purchase order, and Hi-Speed makes to Buyer the manufacturer's express warranty for any goods sold to Buyer, which is offered by the manufacturer at the time of acceptance of any quotation by Buyer. This warranty is conditioned upon the installation, operation, and maintenance of the goods in accordance with the manufacturer's recommendations and/or standard industry practice and the goods at all times being operated or used under normal operating conditions for which they were designed. Hi-Speed, at its sole option, will repair or

**TermsAndConditions** 

replace any defective or non-conforming goods in accordance with the applicable manufacturer's warranty. Warranty for any defective or incorrect parts is limited to the repair or replacement of those parts. Hi-Speed warrants that all services will conform in all material respects to the description of services identified in the quotation and will be performed in a good and workmanlike manner in accordance with industry practices and standards. Should the services be reasonably rejected or not conform with the foregoing warranties, Hi-Speed shall, at its sole cost, re-perform the defective or nonconforming services. Notwithstanding the foregoing, these warranties do not extend to goods or services to the extent that such goods have been subject to misuse, neglect or abuse not caused by Hi-Speed or have been used in violation of the approved written instructions furnished to Buyer. THE FOREGOING REPRESENTS THE SOLE AND EXCLUSIVE WARRANTY GIVEN BY HI-SPEED WITH RESPECT TO ALL GOODS SOLD AND IS IN LIEU OF ALL OTHER WARRANTIES EITHER EXPRESS OR IMPLIED. HI-SPEED EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICLAR USE OR PURPOSE. BUYER WAIVES ANY CLAIM THAT THESE EXCLUSIONS OR LIMITATIONS DEPRIVE IT OF AN ADEQUATE REMEDY AT EQUITY OR LAW OR CAUSE THIS AGREEMENT TO FAIL IN ITS ESSENTIAL PURPOSE. BUYER SHALL BE ENTITLED TO NO OTHER REMEDY OTHER THAN AS SET FORTH HEREIN, REGARDLESS OF THE CLAIM OR CAUSE OF ACTION, WHETHER BASED IN CONTRACT, TORT, NEGLIGENCE, GOODS LIABILITY, STRICT LIABILITY OR OTHERWISE.

- 9. LIMITATION OF DAMAGES. HI-SPEED SHALL HAVE NO LIABILITY TO BUYER WITH RESPECT TO THE SALE OR DELIVERY OF ANY GOODS OR THE REPAIR THEREOF OR WITH RESPECT TO THE SALE OR PERFORMANCE OF ANY SERVICES, FOR LOST PROFITS, SPECIAL, CONSEQUENTIAL, EXEMPLARY, PUNITIVE OR INCIDENTAL DAMAGES OF ANY KIND OR NATURE WHETHER ARISING IN CONTRACT, TORT, GOODS LIABILITY OR OTHERWISE, EVEN IF HI-SPEED WAS ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGES. HI-SPEED SHALL NOT BE LIABLE FOR ANY DAMAGES OR DELAYS CAUSED BY ANY FAILURE TO MAKE ANY DELIVERY OF GOODS BY ANY EXPECTED TIME OR DATE OR THE FAILURE TO PROVIDE OR COMPLETE ANY SERVICES BY ANY EXPECTED DATE OR TIME. IN NO EVENT SHALL HI-SPEED BE LIABLE TO BUYER FOR ANY DAMAGES WHATSOEVER IN EXCESS OF THE TOTAL PRICE PAID FOR ALL GOODS AND/OR SERVICES HEREUNDER OR REFERENCED IN ANY QUOTATION OR THE PURCHASE ORDER.
- 10. <u>SEVERABILITY</u>. The partial or complete invalidity of any provision of these Standard Terms and Conditions shall not affect the enforceability of the remainder of these Standard Terms and Conditions. If any provision is found to be invalid or unenforceable, that portion shall be modified to make it enforceable or shall be stricken and the remainder of these Standard Terms and Conditions shall enforced.
- 11. <u>GOVERNING LAW AND JURISDICTION.</u> Any controversy arising out of any quotation, the purchase order, the goods sold or delivered, repair or replacement thereof, or any services provided pursuant to any quotation or any purchase order, or these Standard Terms and Conditions shall be governed by the laws of the state of Tennessee without regard to any choice of law provisions and any cause of action related in any manner thereto shall be brought only in the state or federal courts of Shelby County, Tennessee.
- 12. <u>ABANDONED EQUIPMENT.</u> Hi-Speed requires that Buyer promptly pick up or provide shipment instructions for Buyer equipment or other Buyer property in Hi-Speed's possession. If equipment or other Buyer property is left with Hi-Speed and not picked up within six (6) months after Hi-Speed's final action related to the applicable property (e.g. evaluation, teardown, estimate, completion of services), Hi-Speed will consider such property abandoned and may dispose of it in accordance with applicable law. Buyer agrees to hold Hi-Speed harmless for any damage or claim for such abandoned property and acknowledges that Hi-Speed may discard or recycle it at Hi-Speed's sole and absolute discretion. Specifically, Hi-Speed may sell Buyer's abandoned property at a private or public sale and retain the proceeds to offset Hi-Speed's storage, inspection and servicing costs. For the avoidance of doubt, Hi-Speed reserves its statutory and other lawful liens for unpaid charges related to abandoned property.
- 13. FORCE MAJEURE. Neither party shall be responsible for any delay or failure in performance of any party of the quotation, purchase order or these Standard Terms and Conditions to the extent that such delays or failures are caused by fire, flood, earth quake, explosion, war, embargo, government requirement, civil or military authority, acts of God, or any other circumstances beyond its reasonable control and not involving any fault or negligence on the party affected ("Condition"). If any such Condition occurs, the party delayed or unable to perform shall promptly give written notice to the other party and, if such Condition remains at the end of thirty (30) days, the party affected by the other party's delay and inability to perform may elect to (i) terminate such order or part thereof, or (ii) suspend the order for the duration of the Condition, if the Buyer is the suspending party, buy elsewhere comparable material to be sold under the order and apply to any commitment the purchase price of such purchase, and resume performance of the order once the Condition ceases, with an option in the affected party to extend the period of this order up to the length of the time the Condition endures.
- 14. <u>NONWAIVER</u>. No course of dealing or failure of either party to strictly enforce any term, right, or condition of these Standard Terms and Conditions will be construed as a waiver of such term, right or condition. Any waiver by Hi-Speed will only be in writing and will waive no succeeding breach of a term, right or condition.
- 15. <u>ASSIGNMENT.</u> The rights and obligations of the parties shall neither be assigned nor delegated without the prior written consent of the other party. However, any party may assign or delegate its respective rights and obligations, in whole or in part, (i) to any subsidiary, (ii) pursuant to other financing, merger or reorganization or (iii) pursuant to any sale or transfer of substantially all of the assets of the assigning party. These Standard Terms and Conditions shall bind the heirs, successors and assigns of the parties hereto.
- 16. <u>NO INDIVIDUAL LIABILITY</u>. Notwithstanding any other agreement to the contrary, the Buyer agrees that in no event will the Buyer hold and HI-Speed owner, director, officer or employee personally liable for unintentional tortious conduct or conduct that constitutes the breach of any contract between HI-Speed and the Buyer, even if the HI-Speed owner, director, officer or employee is or could be construed to be a party to such contract.