

EVERY DAY SINCE 1946 ——

Motor Shop Repairs

Job Number 97631

Prepared for Kroger

20820 interstate 30 N Benton AR 72019

Table of Contents



Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

Printed on 1/7/2021 Powered by INSPECTALL Table of Contents



FolderID: 97631

FormID: 9504607



AC Recondition Repair Report

Kroger

20820 interstate 30 N Benton, AR 72019

Priorities Found: 6 5 - High

4 - Good

	_ · · · · · · · · · · · · · · · · · · ·	
General		
1.	Job Number	97631
2.	Report Date	
3.	Customer	KROGER
Name	Plate Information	
4.	Manufacturer	ILG









5.	Model	
6.	Serial Number	
7.	Horsepower	6. HP
8.	KW	
9.	Volts	200

11. RPM 855 12. Frame 32 13. Enclosure 32 15. Phase 54 15. Phase 54 15. Phase 54 17. Motor Mount Position 54 18. Number of Leads 54 19. Lead Length 54 20. Lead Markings 54 21. Lead Condition 54 22. Lead Markings 54 23. Lig Size, Condition, and Type 54 24. Winding RtD'S 54 25. Winding Rtd's Condition 54 26. Shaft Tum Freely 54 27. Does Shaft Tum Freely 54 28. Bearing Rtd's Condition 54 31. Contamination 54 32. Frame Condition 54 33. Fan Condition 54 34. Broken or missing components 54 18tal Electric Test 9 35. Resistance to Ground 9 36. Winding Resistance 3 9 37. Winding Resistance 3 9 38. Resistive Imbalance 9 <	10.	Amps	18
13. Enclosure 14. Cycles 15. Phase 16. Service Factor 17. Motor Mount Position 18. Number of Leads 19. Lead Length 20. Lead Size 21. Lead Condition 22. Lead Markings 23. Lug Size, Condition, and Type 24. Winding RTD's 25. Winding RTD's 26. Shaft Run Out 27. Does Shaft Turn Freely 28. Does Shaft Turn Freely 29. Bearing Rtd's 30. Bearing Rtd's 31. Contamination 31. Contamination 32. Frame Condition 33. False Condition 34. Broken or missing components 15. Winding Resistance 1-3 36. Winding Resistance 1-3 37. Winding Resistance 1-3 38. Winding Resistance 1-3 39. Resister to Found 30. Surge Test 31. Surge Test 32. Surge Test 33. Surge Test 34. Surge Test 35. Residen or Ground 36. Winding Resistance 1-3 37. Winding Resistance 1-3 38. Winding Resistance 1-3 39. Resister Lendition 31. Surge Test 31. Surge Test 32. Surge Test 33. Faller Location 34. Surge Test 35. Residen or Ground 36. Winding Resistance 1-3 37. Winding Resistance 1-3 38. Winding Resistance 1-3 39. Resister Lendition 31. Surge Test 31. Surge Test 32. Surge Test 33. Faller Location 34. Surge Test 35. Air Cap +10% Variation 36. Winding Resistance 1-3 36. Winding Resistance 1-3 37. Winding Resistance 1-3 38. Winding Resistance 1-3 39. Winding Resistance 1-3 39. Winding Resistance 1-3 30. Winding Resistance 1-3 31. Winding Resistance 1-3 32. Winding Resistance 1-3 33. Winding Resistance 1-3 34. Winding Resistance 1-3 35. Resister Lendition 36. Winding Resistance 1-3 37. Winding Resistance 1-3 38. Winding Resistance 1-3 39. Winding Resistance 1-3 30. Wind			
1.4. Cycles 1.5. Phase 1.6. Service Factor 1.7. Motor Mount Position Itial Inspection 1.8. Number of Leads 2.0. Lead Size 2.1. Lead Condition 2.2. Lead Markings 2.3. Lug Size, Condition, and Type 2.4. Winding RTD's 2.5. Winding RTD's 2.5. Winding RtD's Condition 2.7. Does Shaft Run Out 2.8. Shaft Run Out 2.9. Bearing Rtd's Condition 3.0. Shaft Have Visible Damage 3.0. Bearing Rtd's Condition 3.1. Contamination 3.2. Frame Condition 3.3. Fan Condition 3.4. Prame Condition 3.5. Resistance to Ground Montan 3.6. Resistance to Ground Montan 3.7. Winding Resistance 2-3 Multing Resistance 2-3 3.8. Resister Imbalance % 4.0 Hi-Pot Ua 4.1 Surge Test (F) Fail 4.2 Stator Condition (F) Fail 4.3 Failure Location (F) Fail 4.4 Roor Type cast aluminum w fine	12.	Frame	32
1.4. Cycles 1.5. Phase 1.6. Service Factor 1.7. Motor Mount Position Itial Inspection 1.8. Number of Leads 2.0. Lead Size 2.1. Lead Condition 2.2. Lead Markings 2.3. Lug Size, Condition, and Type 2.4. Winding RTD's 2.5. Winding RTD's 2.5. Winding RtD's Condition 2.7. Does Shaft Run Out 2.8. Shaft Run Out 2.9. Bearing Rtd's Condition 3.0. Shaft Have Visible Damage 3.0. Bearing Rtd's Condition 3.1. Contamination 3.2. Frame Condition 3.3. Fan Condition 3.4. Prame Condition 3.5. Resistance to Ground Montan 3.6. Resistance to Ground Montan 3.7. Winding Resistance 2-3 Multing Resistance 2-3 3.8. Resister Imbalance % 4.0 Hi-Pot Ua 4.1 Surge Test (F) Fail 4.2 Stator Condition (F) Fail 4.3 Failure Location (F) Fail 4.4 Roor Type cast aluminum w fine			
15. Phase 16. Service Factor 17. Motor Mount Position itial Inspection 18. Number of Leads 19. Lead Length 20. Lead Size 21. Lead Markings 22. Lead Markings 23. Lug Size, Condition, and Type 24. Winding RTD's 25. Winding Rtd's Condition 26. Shaft Run Out 27. Does Shaft Turn Freely 28. Does Shaft Turn Freely 29. Bearing Rtd's Condition 30. Bearing Rtd's Condition 31. Contamination 32. Frame Condition 33. Fan Condition 34. Roken or missing components 35. Resistance to Ground O Mohn 36. Winding Resistance 1-2 O Mohn 37. Winding Resistance 2-3 O Mohn 38. Ry Winding Resistance 1-2 O Mohn 39. Resistive Imbalance Ø 40. Hi-Pot Ua 41. Surge Test Ø 42. Stalor Condition Winding Resistance 1-3 43. Faiture Location O 44. Rot Type O 45. Af C			
16. Service Factor 17. Motor Mount Position 18. Number of Leads 19. Lead Length 20. Lead Size 21. Lead Condition 22. Lead Markings 23. Lug Size, Condition, and Type 24. Winding RtD's 25. Winding Rtd's Condition 26. Shaft Turn Freely 27. Does Shaft Turn Freely 28. Does Shaft Have Visible Damage 30. Bearing Rtd's Condition 31. Contamination 32. Frame Condition 33. Fan Condition 34. Broken or missing components 35. Resistance to Ground O Mohm 36. Winding Resistance 1-2 37. Winding Resistance 2-3 38. Winding Resistance 1-3 O Mohm 39. Resistive Imbalance Winding Resistance 2-1 40. Hi-Pot Ua 41. Surge Test (F) Fail 42. Staft Condition (F) Fail 43. Failure Location T 44. Notor Type Cast aluminum wins 45. Air Gap +10% Variation T 46. Number of Rotor Bars 72 47. Number of			
17. Motor Mount Position itial Inspection 18. Number of Leads 20. Lead Size 21. Lead Condition 22. Lead Markings 23. Lug Size, Condition, and Type 24. Winding RTD's 25. Winding Rtd's Condition 27. Does Shaft Turn Freely 28. Does Shaft Turn Freely 29. Bearing Rtd's 29. Bearing Rtd's Condition 31. Contamination 32. Frame Condition 33. Fan Condition 34. Broken or missing components tital Electric Test tital Electric Test tital Electric Test dividing Resistance 1-2 dividing Resistance 1-2 dividing Resistance 1-3 Minding Resistance 1-3 Ohm's 39. Resistive Imbalance % 40. Hi-Pot Und 41. Surge Test (F) Fall 42. Stator Condition (F) Fall 43. Fallure Location (F) Fall 44. Rotor Type Cast aluminum w fins 45. Ali Gap < 10% Varia			
Number of Leads			
18. Number of Leads 19. Lead Length 20. Lead Size 21. Lead Condition 22. Lead Markings 23. Lyg Size, Condition, and Type 24. Winding Rtd's Condition 25. Winding Rtd's Condition 26. Shaft Run Out 27. Does Shaft Turn Freely 28. Does Shaft Ave Visible Damage 30. Bearing Rtd's Condition 31. Contamination 32. Frame Condition 33. Frame Condition 34. Broken or missing components Itial Electric Test 35. Resistance to Ground 0 Mohn 36. Winding Resistance 1-2 0 Mohn 37. Winding Resistance 2-3 % 38. Winding Resistance 1-3 Ohn's 39. Resistive Imbalance % 40. LiPot Quality 41. Surge Test (F) Fail 42. Stator Condition (F) Fail 43. Fallure Location To 44. Rotor Type cast aluminum wfins 45. Ali Gap < 10% Variation			
19. Lead Length 20. Lead Size 21. Lead Condition 22. Lead Markings 23. Lug Size, Condition, and Type 24. Winding RTD's 25. Winding Rtd's Condition 26. Shaft Run Out 27. Does Shaft Turn Freely 28. Does Shaft Turn Freely 29. Bearing Rtd's 30. Bearing Rtd's 30. Bearing Rtd's Condition 31. Contamination 32. Frame Condition 33. Fan Condition 34. Broken or missing components 35. Resistance to Ground 36. Winding Resistance 1-2 37. Winding Resistance 1-2 38. Winding Resistance 1-2 39. Winding Resistance 1-2 40. Winding Resistance 1-2 41. Surger Test 42. Stafor Condition 43. Sirger September 1-2 44. Surger September 1-2 45. Resistive Imbalance 46. Hi-Pot 47. Lug Test 48. Ground Condition 49. Hi-Pot 40. Hi-Pot 41. Surger Test 42. Stafor Condition 43. Winding Resistance 1-3 44. Stafor Condition 45. Air Gap <			
20. Lead Size 21. Lead Condition 22. Lead Markings 23. Lug Size, Condition, and Type 24. Winding RTD's 25. Winding Rtd's Condition 26. Shaft Run Out 27. Does Shaft Have Visible Damage 28. Dearing Rtd's 30. Bearing Rtd's Condition 31. Contamination 32. Frame Condition 33. Fan Condition 34. Broken or missing components Itial Electric Test 36. Winding Resistance 1-2 37. Winding Resistance 1-3 38. Winding Resistance 2-3 39. Winding Resistance 1-2 40. Hi-Pot 40. Hi-Pot 41. Surge Test 42. Stator Condition 43. Fillure Location 44. Rotor Inspection 45. Ali Gap < 10% Variation			
21. Lead Condition 22. Lead Markings 23. Lug Size, Condition, and Type 24. Winding RtD's 25. Winding Rtd's Condition 26. Shaft Run Out 27. Does Shaft Tum Freely 28. Does Shaft Have Visible Damage 29. Bearing Rtd's Condition 30. Bearing Rtd's Condition 31. Contamination 32. Frame Condition 33. Fan Condition 34. Rocken or missing components Itial Electric Test 35. Resistance to Ground 0 Mohm 36. Winding Resistance 1-2 0 Mohms 37. Winding Resistance 2-3 0 Mm's 38. Resistive Imbalance % 40. Hi-Pot Ua 41. Surge Test (F) Fail 42. Stator Condition (F) Fail 43. Failure Location (F) Fail 44. Rotor Type cast aluminum w fins 45. Air Gap <10% Variation			
22. Lead Markings 23. Lug Size, Condition, and Type 24. Winding RTD's 25. Winding Rtd's Condition 26. Shaft Run Out 27. Does Shaft Turn Freely 28. Does Shaft Have Visible Damage 29. Bearing Rtd's 30. Bearing Rtd's Condition 31. Contamination 32. Frame Condition 33. Fan Condition 34. Prime Condition 35. Resistance to Ground 0 Mohm 36. Winding Resistance 1-2 37. Winding Resistance 2-3 0 Mohm 38. Resistance to Ground 0 Mohm 39. Resistance 2-3 0 Mohms 30. Resistance 1-2 0 Mohms 31. Vinding Resistance 2-3 0 Mms 32. Resistive Imbalance % 40. Hi-Pot Ua 41. Surge Test (F) Fail 42. Stator Condition (F) Fail 43. Failure Location (F) Fail 44. Rotor Type cast aluminum w fins 45. Air Gap <10% Variation			
23. Lug Size, Condition, and Type 24. Winding RTD'S 25. Winding Rtd's Condition 27. Des Shaft Run Out 28. Does Shaft Turn Freely 29. Bearing Rtd's 30. Bearing Rtd's Condition 31. Contamination 32. Fane Condition 33. Fan Condition 34. Broken or missing components Itial Electric Test 35. Resistance to Ground 0 Mohn 36. Winding Resistance 1-2 0 Mohn 37. Winding Resistance 1-2 0 Mohn 38. Winding Resistance 1-3 0 Mohn's 39. Resistive Imbalance 0 Mon's 40. Hi-Pot Ua 41. Surge Test (F) Fail 42. Stator Condition (F) Fail 43. Fallure Location (F) Fail 44. Rotor Type cast aluminum w fins 45. Air Gay <			
24. Winding RTD's 25. Winding Rtd's Condition 26. Shaft Run Out 27. Does Shaft Turn Freely 28. Does Shaft Have Visible Damage 29. Bearing Rtd's 30. Bearing Rtd's Condition 31. Contamination 32. Frame Condition 33. Fan Condition 34. Pictoric Test 35. Resistance to Ground 0 Mohm 36. Winding Resistance 1-2 37. Winding Resistance 2-3 0 Mohm's 38. Winding Resistance 1-3 0 hm's 39. Resistive Imbalance % 40. Li-Pot Ua 41. Suge Test (F) Fail 42. Stator Condition (F) Fail 43. Failure Location (F) Fail 44. Rotor Type cast aluminum w fins 45. Air Gap < 10 World Wirdition			
25. Winding Rtd's Condition 26. Shaft Run Out 27. Does Shaft Turn Freely 28. Does Shaft Turn Freely 29. Bearing Rtd's 30. Bearing Rtd's Condition 31. Contamination 32. Frame Condition 33. Fan Condition 34. Broken or missing components 35. Resistance to Ground 0 Mohm 36. Winding Resistance 1-2 37. Winding Resistance 1-2 0 Mohm 38. Winding Resistance 1-3 0 hms 39. Resistive Imbalance % 40. Hi-Pot Ua 41. Surge Test (F) Fail 42. Stator Condition (F) Fail 43. Failure Location (F) Fail 44. Rotor Type cast aluminum w fins 45. Ali Gap <10% Variation			
26. Shaft Run Out 27. Does Shaft Turn Freely 28. Does Shaft Have Visible Damage 29. Bearing Rtd's 30. Bearing Rtd's Condition 31. Contamination 32. Frame Condition 33. Fan Condition 34. Broken or missing components itial Electric Test 35. Resistance to Ground 0 Mohm 36. Winding Resistance 1-2 0 Mohm 37. Winding Resistance 2-3 0 Mm's 38. Winding Resistance 1-2 0 Mm's 39. Resistive Imbalance 0 Mm's 40. Hi-Pot Ua 41. Surge Test (F) Fail 42. Stator Condition (F) Fail 43. Failure Location (F) Fail 44. Rotor Type cast aluminum w fins 45. Air Gay = 10% Variation 72 46. Number of Rotor Bars 72 47. Umber of Broken Rotor Bars (P) Pass 48. Growler Test (P) Pass 49. Rotor Condition (P) Pass			
27. Does Shaft Turn Freely 28. Does Shaft Have Visible Damage 29. Bearing Rtd's 30. Bearing Rtd'S Condition 31. Contamination 32. Frame Condition 33. Fan Condition 34. Broken or missing components Itial Electric Test 35. Resistance to Ground 0 Mohm 36. Winding Resistance 1-2 0 Mohm 37. Winding Resistance 2-3 0 Minding Resistance 2-3 38. Winding Resistance 1-3 0 hm's 40. H-Pot Ua 41. Surge Test (F) Fail 42. Stator Condition (F) Fail 43. Failure Location (F) Fail 44. Rotor Type cast aluminum w fins 45. Air Gap < 10% Variation		-	
28. Does Shaft Have Visible Damage 29. Bearing Rtd's 30. Bearing Rtd's Condition 31. Contamination 32. Frame Condition 33. Fan Condition 34. Broken or missing components Itial Electric Test 35. Resistance to Ground 0 Mohm 36. Winding Resistance 1-2 Vinding Resistance 2-3 37. Winding Resistance 2-3 Ohm's 38. Winding Resistance 1-3 Ohm's 40. Hi-Pot Ua 41. Surge Test (F) Fail 42. Stator Condition (F) Fail 43. Failure Location E 44. Rotor Type Cast aluminum w fins 45. Air Gap < 10% Variation			
29. Bearing Rtd's 30. Bearing Rtd's Condition 31. Contamination 32. Frame Condition 33. Fan Condition 34. Broken or missing components tital Electric Test 35. Resistance to Ground 0 Mohm 36. Winding Resistance 1-2 0 Mohm 37. Winding Resistance 2-3 0 Mohm's 38. Winding Resistance 1-3 0 Mm's 40. Hi-Pot Ua 41. Surge Test (F) Fail 42. Stator Condition (F) Fail 43. Failure Location cast aluminum w fins 44. Rotor Type cast aluminum w fins 45. Air Gap <10% Variation		·	
30. Bearing Rtd's Condition 31. Contamination 32. Frame Condition 33. Fan Condition 34. Broken or missing components itial Electric Test 35. Resistance to Ground 0 Mohm 36. Winding Resistance 1-2 0 Mohm's 37. Winding Resistance 2-3 0 Mohm's 38. Winding Resistance 1-3 0 Mohm's 39. Resistive Imbalance % 40. Hi-Pot Ua 41. Surge Test (F) Fail 42. Stator Condition (F) Fail 43. Failure Location (E) Fail 44. Rotor Inspection cast aluminum w fins 45. Air Gap < 10% Variation		-	
31. Contamination 32. Frame Condition 33. Fan Condition 34. Broken or missing components itial Electric Test 35. Resistance to Ground 0 Mohm 36. Winding Resistance 1-2 0 Mohm 37. Winding Resistance 2-3 0 Mm's 38. Winding Resistance 1-3 0 hm's 39. Resistive Imbalance % 40. Hi-Pot Ua 41. Surge Test (F) Fail 42. Stator Condition (F) Fail 43. Failure Location (E) Fail 44. Rotor Type cast aluminum w fins 45. Air Gap < 10% Variation			
33. Fan Condition 34. Broken or missing components itial Electric Test 35. Resistance to Ground 0 Mohnm 36. Winding Resistance 1-2 37. Winding Resistance 1-3 Ohm's 38. Winding Resistance 1-3 Ohm's 39. Resistive Imbalance % 40. Hi-Pot Ua 41. Surge Test (F) Fail 42. Stator Condition 43. Failure Location itial Rotor Inspection 44. Rotor Type cast aluminum w fins 45. Air Gap <10% Variation 46. Number of Rotor Bars 72 47. Number of Broken Rotor Bars 48. Growler Test (P) Pass 49. Rotor Condition (P) Pass 49. Rotor Condition (P) Pass 49. Rotor Condition (P) Pass			
34. Broken or missing components itial Electric Test 35. Resistance to Ground 0 Mohm 36. Winding Resistance 1-2 37. Winding Resistance 1-3 Ohm's 39. Resistive Imbalance % 40. Hi-Pot Ua 41. Surge Test (F) Fail 42. Stator Condition 43. Failure Location tital Rotor Inspection 44. Rotor Type cast aluminum w fins 45. Air Gap < 10% Variation 46. Number of Rotor Bars 72 47. Number of Broken Rotor Bars (P) Pass 49. Rotor Condition (P) Pass 49. Rotor Condition (P) Pass	32.	Frame Condition	
itial Electric Test 35. Resistance to Ground 0 Mohm 36. Winding Resistance 1-2	33.	Fan Condition	
itial Electric Test 35. Resistance to Ground 0 Mohm 36. Winding Resistance 1-2	34.	Broken or missing components	
35. Resistance to Ground 0 Mohm 36. Winding Resistance 1-2 37. Winding Resistance 2-3 38. Winding Resistance 1-3 39. Resistive Imbalance 40. Hi-Pot 41. Surge Test (F) Fail 42. Stator Condition 43. Failure Location Itial Rotor Inspection 44. Rotor Type cast aluminum w fins 45. Air Gap <10% Variation 46. Number of Rotor Bars 72 47. Number of Broken Rotor Bars 72 48. Growler Test (P) Pass 49. Rotor Condition (P) Pass			
37. Winding Resistance 2-3 38. Winding Resistance 1-3 Ohm's 39. Resistive Imbalance % 40. Hi-Pot Ua 41. Surge Test (F) Fail 42. Stator Condition Failure Location 43. Failure Location Cast aluminum w fins 44. Rotor Type cast aluminum w fins 45. Air Gap <10% Variation			0 Mohm
37. Winding Resistance 2-3 38. Winding Resistance 1-3 Ohm's 39. Resistive Imbalance % 40. Hi-Pot Ua 41. Surge Test (F) Fail 42. Stator Condition Failure Location 43. Failure Location Cast aluminum w fins 44. Rotor Type cast aluminum w fins 45. Air Gap <10% Variation	36.	Winding Resistance 1-2	
38. Winding Resistance 1-3 Ohm's 39. Resistive Imbalance % 40. Hi-Pot Ua 41. Surge Test (F) Fail 42. Stator Condition Failure Location 43. Failure Location Cast aluminum w fins 44. Rotor Type cast aluminum w fins 45. Air Gap <10% Variation			
39.Resistive Imbalance%40.Hi-PotUa41.Surge Test(F) Fail42.Stator Condition43.Failure Locationitial Rotor Inspection44.Rotor Typecast aluminum w fins45.Air Gap <10% Variation			Ohm's
41. Surge Test 42. Stator Condition 43. Failure Location itial Rotor Inspection 44. Rotor Type cast aluminum w fins 45. Air Gap <10% Variation 46. Number of Rotor Bars 47. Number of Broken Rotor Bars 48. Growler Test 49. Rotor Condition (P) Pass	39.	Resistive Imbalance	%
42. Stator Condition 43. Failure Location itial Rotor Inspection 44. Rotor Type cast aluminum w fins 45. Air Gap <10% Variation 46. Number of Rotor Bars 72 47. Number of Broken Rotor Bars 48. Growler Test (P) Pass 49. Rotor Condition (P) Pass	40.	Hi-Pot	Ua
43. Failure Location itial Rotor Inspection 44. Rotor Type cast aluminum w fins 45. Air Gap <10% Variation 46. Number of Rotor Bars 47. Number of Broken Rotor Bars 48. Growler Test 49. Rotor Condition (P) Pass	41.	Surge Test	(F) Fail
itial Rotor Inspection44. Rotor Typecast aluminum w fins45. Air Gap <10% Variation46. Number of Rotor Bars7247. Number of Broken Rotor Bars(P) Pass48. Growler Test(P) Pass49. Rotor Condition(P) Pass	42.	Stator Condition	
44.Rotor Typecast aluminum w fins45.Air Gap <10% Variation	43.	Failure Location	
44.Rotor Typecast aluminum w fins45.Air Gap <10% Variation	Initial	Rotor Inspection	
46.Number of Rotor Bars7247.Number of Broken Rotor Bars48.Growler Test(P) Pass49.Rotor Condition(P) Pass			cast aluminum w fins
46.Number of Rotor Bars7247.Number of Broken Rotor Bars48.Growler Test(P) Pass49.Rotor Condition(P) Pass	45.	Air Gap <10% Variation	
48. Growler Test 49. Rotor Condition (P) Pass (P) Pass			72
49. Rotor Condition (P) Pass	47.	Number of Broken Rotor Bars	
. ,	48.	Growler Test	(P) Pass
echanical Inspection	49.	Rotor Condition	(P) Pass
	vlecha	anical Inspection	



51.	Bearing DE Size	6208 2Z
52.	Bearing DE Type deep	groove ball
53.	DE Bearing Qty.	1
54.	Bearing ODE Size 633	206 C3 2RS
55.	Bearing ODE Type deep groove heav	/y duty ball
56.	ODE Bearing Qty.	1
57.	Insulated Bearing	
58.	Lubrication Type	
59.	Grease Condition	(F) Fail
60.	Bearing Retainers	
61.	Shaft Grounding Device	
62.	DE Seal	
63.	DE Seal Type/Size	
64.	ODE Seal	
65.	ODE Seal Type/Size	
Root	Cause of Failure	
66.	Component Failure O	DE bearing
67.	Cause of Failure	
68.	Comments	
	Rewind. Machine and sleeve both end bells. Braze crack in ODE end bell. Weld and machine ODE rotor	





David Maclin

N	/lachi	ine Fit Inspection Report	
	70.	Shaft Run Out	
	71.	Initial Shaft Run Out	
	72.	Final Shaft Run Out	
	73.	DE Bearing Shaft Fit (P) Pa	ss
	74.	DE Initial Shaft Bearing Fit Size 1 1.5751	"
	75.	DE Initial Shaft Bearing Fit Size 2 1.575	5 "
	76.	DE Initial Shaft Bearing Fit Size 3 1.5749) "
	77.	DE Finial Shaft Bearing Fit Size 1	
	78.	DE Finial Shaft Bearing Fit Size 2	
	79.	DE Finial Shaft Bearing Fit Size 3	
	80.	ODE Bearing Shaft Fit (F) Fa	ail
	-	Deep groves and large damage pit	



81.	ODE Initial Shaft Bearing Fit Size 1	
82.	ODE Initial Shaft Bearing Fit Size 2	
83.	ODE Initial Shaft Bearing Fit Size 3	
84.	ODE Finial Shaft Bearing Fit Size 1	
85.	ODE Finial Shaft Bearing Fit Size 2	
86.	ODE Finial Shaft Bearing Fit Size 3	
87.	DE Air Seal Shaft Fit	
88.	DE Initial Air Seal Shaft Size	
89.	DE Final Air Seal Shaft Size	
90.	ODE Air Seal Shaft Fit	
91.	ODE Initial Air Seal Shaft Size	
92.	ODE Final Air Seal Shaft Size	
93.	DE Endbell Fit	(F) Fail
94.	DE Initial Endbell Fit Size 1	3.1505 "
95.	DE Initial Endbell Fit Size 2	3.1503 "
96.	DE Initial Endbell Fit Size 3	3.1504 "

9	7. DE Final Endbell Fit Size 1	
98	3. DE Finial Endbell Fit Size 2	
99	9. DE Final Endbell Fit Size 3	
10	DE Endbell Fit Insulated	
10	1. DE Endbell Air Seal Fit	
10	2. Initial Endbell Air Seal Fit Size	
10	3. Finial Endbell Air Seal Fit Size	
10	4. ODE Endbell Fit	(F) Fail
-	Extreme pitting	



105. ODE Initial Endbell Fit Size 1
106. ODE Initial Endbell Fit Size 2
107. ODE Initial Endbell Fit Size 3
108. ODE Final Endbell Fit Size 1
109. ODE Final Endbell Fit Size 2
110. ODE Final Endbell Fit Size 3
111. ODE Endbell Fit Insulated
112. ODE Endbell Air Seal Fit
113. ODE Initial Endbell Seal Fit Size
114. ODE Finial Endbell Seal Fit Size
115. Foot Flatness
116. Foot Condition
117. Flange Condition
118. Service Technician
Balancing Report
119. Balance Type
120. Balance Operating Speed
121. Start Left End
122. Start Right End
123. Balancing Specification
124. Finish Left End
125. Finish Right End
126. Service Technician
Assembly and Final Test



128. Surge Test	(P) Pass
129. Hi-Pot	
130. Winding Resistance 1-2	
131. Winding Resistance 2-3	
132. Winding Resistance 1-3	
133. Test Run Voltage Phase A	226 Volts



134. Test Run Amps A	7.2 Amps
135. Test Run Voltage Phase B	225 Volts



136. Test Run Amps B 7.1 Amps



138. Test Run Amps C	7.1 Amps
139. DE Horizontal Vibration Reading	
140. DE Vertical Vibration Reading	
141. DE Axial Vibration Reading	
142. ODE Horizontal Vibration Reading	
143. ODE Vertical Vibration Reading	
144. ODE Axial Vibration Reading	
145. Ambient Temp at start of Test Run	
146. Temp at 5 minutes	
147. Temp at 10 minutes	
148. Temp at 15 minutes	
149. Temp at 20 minutes	
150. Temp at 25 minutes	
151. Temp at 30 minutes	
152. Temp at 35 minutes	
153. Temp at 40 minutes	
154. Temp at 45 minutes	
155. Temp at 50 minutes	
156. Temp at 55 minutes	
157. Temp at 60 minutes	
158. Motor Paint	







159. Service Technician RW



STANDARD TERMS AND CONDITIONS FOR PURCHASE OF GOOD AND/OR SERVICES

- 1. APPLICABILITY. The sale of any and all goods and/or services by Mock, Inc. d/b/a Hi-Speed Industrial Service ("Hi-Speed") shall be specifically conditioned upon and subject to the following terms and conditions which are incorporated by reference into any contracts and purchase orders with Hi-Speed, and which shall form and become a part of any agreement related thereto. Buyer's acceptance of any offer or quotation made by Hi-Speed for sale of any goods or services is expressly made subject to the terms and conditions set forth herein and to be so effective, Buyer need not sign or approve these Terms and Conditions to be bound hereunder provided a copy of same is provided to Buyer through any means. None of the terms and conditions contained herein may be added to, expanded, changed, modified, superseded or otherwise altered except as revised in writing and duly executed by Hi-Speed, and all orders received by Hi-Speed shall be governed only by the terms and conditions contained herein, notwithstanding any terms, conditions or provisions of any purchase order, release order, authorization or any other form issued by the Buyer. Hi-Speed hereby objects to any additional, modified, changed, deleted, altered or other terms and conditions not contained herein and notifies Buyer that any such terms or provisions are expressly rejected by Hi-Speed.
- 2. PRICE. All quoted prices shall remain firm and binding for a period of thirty (30) days from the date of quotation or for the period specifically stated in the quotation. The price for any and all goods and/or services ordered or approved by Buyer after thirty (30) days from the date of any quotation are subject to any increase in price that may occur after the expiration of thirty (30) days from the issuance of the quotation and the date the Buyer releases any shipment.
- 3. SCOPE OF GOODS AND/OR SERVICES. The goods and/or services provided by Hi-Speed pursuant to any quotation shall be limited exclusively to those goods and/or services expressly identified therein. Hi-Speed does not assume any responsibility and/or liability for the failure to provide any other goods and/or services not identified in any quotation. Modifications, additions or deletions to or from the scope referenced in any quotation shall only bee effective if evidenced in writing and signed by Hi-Speed. The sale of any of all goods and/or services affected by such modification, addition or deletion shall be subject to these same Standard Terms and Conditions whether or not referenced therein.
- 4. <u>BILLING AND PAYMENT TERMS.</u> Hi-Speed shall invoice Buyer for all goods and/or services as same are rendered at the address listed on the quotation. Payments for all goods and/or services shall be due thirty (30) days from the date of the current invoice or as otherwise set forth in the quotation. Late payments are subject to a late fee of 5% of the total invoice amount. Recurring late payments may lead to a deposit requirement on future services or sale of goods. Buyer shall be liable to Hi-Speed for any and all fees and expenses incurred by Hi-Speed to collect any invoices or to enforce these Standard Terms and Conditions, including but not limited to, attorney's fees.
- 5. <u>DELIVERY OF GOODS AND/OR SERVICES.</u> Unless otherwise identified in the quotation, all shipments are F.O.B. Hi-Speed's warehouse and the title to and all risk of loss with respect to any goods shipped shall pass to Buyer when such goods are delivered to the carrier at Hi-Speed's warehouse. Hi-Speed will use its best efforts to affect delivery by the date or dates specified in the quotation. However, Hi-Speed shall not be liable for delay in or failure to make shipment, or to perform services, by any identified date for any reason whatsoever, including but not limited to, causes beyond its reasonable control, such as strikes, fires, floods, epidemics, quarantines, restrictions, severe weather, embargos, acts of God, or public enemy, war, riot, delays in transportation or the inability to obtain necessary labor, materials or manufacturing facilities.
- **DELIVERY SITE AND TIME FOR PERFORMANCE.** Hi-Speed and Buver agree that time is of the essence for the purchase order and that Buyer shall fully cooperate with Hi-Speed in order to allow Hi-Speed full access to prosecute its work diligently and in an orderly manner. Buyer shall assist Hi-Speed in every way possible to avoid delaying, disrupting or interfering with the progress of Hi-Speed's work at the project site. In the event Hi-Speed's work is delayed, hindered, suspended, disrupted, re-sequenced or interfered with or rendered less efficient or more costly or adversely affected in any way as a result of acts or omissions of Buyer or other contractors or employees of Buyer or by any other reason beyond Hi-Speed's control and without the fault of Hi-Speed, then, in such event, Buyer shall be liable to Hi-Speed for any damages, additional costs, expenses, labor, materials, man hours, acceleration costs, overtime, additional jobsite overhead, extended home office overhead, and any and all other direct and indirect expenses of whatsoever nature or kind, caused in whole or in part, as a result of any of the above-referenced occurrences. Hi-Speed's project records will be the basis for computing the additional costs and damages of Hi-Speed's labor, materials, expenses and overhead related to such changes. BUYER WARRANTS THAT THE SITE FOR DELIVERY OR INSTALLATION OF ANY GOODS AND/OR FOR THE PERFORMANCE OF ANY SERVICES SHALL BE READY AND ADEQUATE FOR HI-SPEED'S DELIVERY OF GOODS AND/OR PERFORMANCE OF SERVICES AND THAT HI-SPEED SHALL HAVE FULL ACCESS THERETO, FREE OF ALL OBSTRUCTIONS. BUYER SHALL ASSUME ALL EXTRA COSTS ASSOCIATED WITH HI-SPEED'S INABILITY TO INSTALL ANY GOODS OR PERFORM ANY SERVICES AS A RESULT OF BUYER'S FAILURE TO COMPLY WITH THIS PROVISION. HI-SPEED MAY NOT INSPECT THE SITE PRIOR TO DELIVERY AND/OR INSTALLATION OF GOODS AND/OR PERFORMANCE OF SERVICES AND MAKES NO WARRANTY AS TO THE SUFFICIENCY OF THE SITE FOR THE DELIVERY AND/OR INSTALLATION OF GOODS AND/OR THE PERFORMANCE OF SERVICES AT SUCH SITE.
- 7. INSPECTION/ACCEPTANCE. All goods and services ordered pursuant to any quotation shall be subject to inspection by Buyer after delivery or performance to determine conformity with the quotation and/or purchase order and Hi-Speed's advertised or published specifications. Buyer shall have a period of thirty (30) days from shipment of goods at the delivery destination specified in the quotation within which to inspect the goods for conformity with the quotation, order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. Buyer shall have a period of thirty (30) days following completion of any services within which to inspect the services for conformity with the quotation, purchase order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. If the goods delivered or services performed do not so conform, upon delivery of notice to Hi-Speed of any discrepancy, nonconformance or rejection, Hi-Speed shall have sixty (60) days to cure the alleged discrepancy and/or nonconformance. If Hi-Speed fails to cure in this time period, Buyer shall have the right to reject such goods or services. After the cure period, goods that have been delivered and rejected, in whole or in part, shall be returned to Hi-Speed. Buyer shall notify Hi-Speed and arrange for the return of the goods as required. Should such non-conforming services be rejected Hi-Speed shall, at its sole cost, re-perform the non-conforming services. Inspection or failure to inspect on any occasion shall not affect Buyer's rights under the warranty provisions herein.
- 8. WARRANTIES. Hi-Speed warrants that all goods shall conform in all material aspects to the goods identified in the quotation to Buyer and/or purchase order, and Hi-Speed makes to Buyer the manufacturer's express warranty for any goods sold to Buyer, which is offered by the manufacturer at the time of acceptance of any quotation by Buyer. This warranty is conditioned upon the installation, operation, and maintenance of the goods in accordance with the manufacturer's recommendations and/or standard industry practice and the goods at all times being operated or used under normal operating conditions for which they were designed. Hi-Speed, at its sole option, will repair or

replace any defective or non-conforming goods in accordance with the applicable manufacturer's warranty. Warranty for any defective or incorrect parts is limited to the repair or replacement of those parts. Hi-Speed warrants that all services will conform in all material respects to the description of services identified in the quotation and will be performed in a good and workmanlike manner in accordance with industry practices and standards. Should the services be reasonably rejected or not conform with the foregoing warranties, Hi-Speed shall, at its sole cost, re-perform the defective or nonconforming services. Notwithstanding the foregoing, these warranties do not extend to goods or services to the extent that such goods have been subject to misuse, neglect or abuse not caused by Hi-Speed or have been used in violation of the approved written instructions furnished to Buyer. THE FOREGOING REPRESENTS THE SOLE AND EXCLUSIVE WARRANTY GIVEN BY HI-SPEED WITH RESPECT TO ALL GOODS SOLD AND IS IN LIEU OF ALL OTHER WARRANTIES EITHER EXPRESS OR IMPLIED. HI-SPEED EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICLAR USE OR PURPOSE. BUYER WAIVES ANY CLAIM THAT THESE EXCLUSIONS OR LIMITATIONS DEPRIVE IT OF AN ADEQUATE REMEDY AT EQUITY OR LAW OR CAUSE THIS AGREEMENT TO FAIL IN ITS ESSENTIAL PURPOSE. BUYER SHALL BE ENTITLED TO NO OTHER REMEDY OTHER THAN AS SET FORTH HEREIN, REGARDLESS OF THE CLAIM OR CAUSE OF ACTION, WHETHER BASED IN CONTRACT, TORT, NEGLIGENCE, GOODS LIABILITY, STRICT LIABILITY OR OTHERWISE.

- 9. <u>LIMITATION OF DAMAGES.</u> HI-SPEED SHALL HAVE NO LIABILITY TO BUYER WITH RESPECT TO THE SALE OR DELIVERY OF ANY GOODS OR THE REPAIR THEREOF OR WITH RESPECT TO THE SALE OR PERFORMANCE OF ANY SERVICES, FOR LOST PROFITS, SPECIAL, CONSEQUENTIAL, EXEMPLARY, PUNITIVE OR INCIDENTAL DAMAGES OF ANY KIND OR NATURE WHETHER ARISING IN CONTRACT, TORT, GOODS LIABILITY OR OTHERWISE, EVEN IF HI-SPEED WAS ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGES. HI-SPEED SHALL NOT BE LIABLE FOR ANY DAMAGES OR DELAYS CAUSED BY ANY FAILURE TO MAKE ANY DELIVERY OF GOODS BY ANY EXPECTED TIME OR DATE OR THE FAILURE TO PROVIDE OR COMPLETE ANY SERVICES BY ANY EXPECTED DATE OR TIME. IN NO EVENT SHALL HI-SPEED BE LIABLE TO BUYER FOR ANY DAMAGES WHATSOEVER IN EXCESS OF THE TOTAL PRICE PAID FOR ALL GOODS AND/OR SERVICES HEREUNDER OR REFERENCED IN ANY QUOTATION OR THE PURCHASE ORDER.
- 10. <u>SEVERABILITY.</u> The partial or complete invalidity of any provision of these Standard Terms and Conditions shall not affect the enforceability of the remainder of these Standard Terms and Conditions. If any provision is found to be invalid or unenforceable, that portion shall be modified to make it enforceable or shall be stricken and the remainder of these Standard Terms and Conditions shall enforced.
- 11. **GOVERNING LAW AND JURISDICTION.** Any controversy arising out of any quotation, the purchase order, the goods sold or delivered, repair or replacement thereof, or any services provided pursuant to any quotation or any purchase order, or these Standard Terms and Conditions shall be governed by the laws of the state of Tennessee without regard to any choice of law provisions and any cause of action related in any manner thereto shall be brought only in the state or federal courts of Shelby County, Tennessee.
- 12. <u>ABANDONED EQUIPMENT.</u> Hi-Speed requires that Buyer promptly pick up or provide shipment instructions for Buyer equipment or other Buyer property in Hi-Speed's possession. If equipment or other Buyer property is left with Hi-Speed and not picked up within six (6) months after Hi-Speed's final action related to the applicable property (e.g. evaluation, teardown, estimate, completion of services), Hi-Speed will consider such property abandoned and may dispose of it in accordance with applicable law. Buyer agrees to hold Hi-Speed harmless for any damage or claim for such abandoned property and acknowledges that Hi-Speed may discard or recycle it at Hi-Speed's sole and absolute discretion. Specifically, Hi-Speed may sell Buyer's abandoned property at a private or public sale and retain the proceeds to offset Hi-Speed's storage, inspection and servicing costs. For the avoidance of doubt, Hi-Speed reserves its statutory and other lawful liens for unpaid charges related to abandoned property.
- 13. FORCE MAJEURE. Neither party shall be responsible for any delay or failure in performance of any party of the quotation, purchase order or these Standard Terms and Conditions to the extent that such delays or failures are caused by fire, flood, earth quake, explosion, war, embargo, government requirement, civil or military authority, acts of God, or any other circumstances beyond its reasonable control and not involving any fault or negligence on the party affected ("Condition"). If any such Condition occurs, the party delayed or unable to perform shall promptly give written notice to the other party and, if such Condition remains at the end of thirty (30) days, the party affected by the other party's delay and inability to perform may elect to (i) terminate such order or part thereof, or (ii) suspend the order for the duration of the Condition, if the Buyer is the suspending party, buy elsewhere comparable material to be sold under the order and apply to any commitment the purchase price of such purchase, and resume performance of the order once the Condition ceases, with an option in the affected party to extend the period of this order up to the length of the time the Condition endures.
- 14. <u>NONWAIVER.</u> No course of dealing or failure of either party to strictly enforce any term, right, or condition of these Standard Terms and Conditions will be construed as a waiver of such term, right or condition. Any waiver by Hi-Speed will only be in writing and will waive no succeeding breach of a term, right or condition.
- 15. **ASSIGNMENT.** The rights and obligations of the parties shall neither be assigned nor delegated without the prior written consent of the other party. However, any party may assign or delegate its respective rights and obligations, in whole or in part, (i) to any subsidiary, (ii) pursuant to other financing, merger or reorganization or (iii) pursuant to any sale or transfer of substantially all of the assets of the assigning party. These Standard Terms and Conditions shall bind the heirs, successors and assigns of the parties hereto.
- 16. NO INDIVIDUAL LIABILITY. Notwithstanding any other agreement to the contrary, the Buyer agrees that in no event will the Buyer hold and HI-Speed owner, director, officer or employee personally liable for unintentional tortious conduct or conduct that constitutes the breach of any contract between HI-Speed and the Buyer, even if the HI-Speed owner, director, officer or employee is or could be construed to be a party to such contract.