

EVERY DAY SINCE 1946

Motor Shop Repairs

Job Number 97468

Prepared for SAGE

5901 SLOAN DRIVE LITTLE ROCK AR 72206

Table of Contents

AC Recondition Repair Report



Hi-Speed Industrial Service 7030 Ryburn Dr Millington, Tn 38053 901-873-5300

FolderID: 97468

FormID: 9157602

AC Recondition Repair Report

SAGE

5901 SLOAN DRIVE LITTLE ROCK, AR 72206 Performed By: Motor Shop LR Date Completed: 10/26/2020

Priorities Found: **12 - Good**

General 97468 P9 1. Job Number 97468 P9 2. Report Date SAGE SAGE Name Plate Information Image: Sage Sage Sage Sage Sage Sage Sage Sage	-	· · ·		
2. Report Date SAGE 3. Customer SAGE Name Plate Information Image: Same Plate Information 4. Manufacturer US 5. Model G29316 6. Serial Number 20 7. Horsapower 20 8. KW 30460 10. Amps 230460 10. Amps 230460 10. Amps 230460 11. RPM 1770 12. Frame 256JM 13. Enclosure TE 14. Cycles 60 15. Phase 3 16. Service Factor 1.25 7. Motor Mount Position F1 Initial Inspection Imitial Inspection 18. Number of Leads 9 P13 19. Lead Length 12 Inches 20. Lead Size 10 10 21. Lead Condition (P) Pass 12 22. Lead Markings Printed leads 12 23. Lug Size, Condition, and Type None 20 24. Winding RTD's (NA) Not Applicable 12 25. Winding Rtd's Condition 12 </th <th>Gene</th> <th></th> <th></th> <th></th>	Gene			
3. Customer SAGE Name Plate Information Image: Comparison of Casa and Casa a	1.		97468	P9
Name Plate Information Image: Second	2.	Report Date		
4. Manufacturer US P5 5. Model G29316 6. Serial Number 20 7. Horsepower 20 8. KW 230460 9. Volts 230460 10. Amps 49.0024.50 11. RPM 1770 12. Frame 256JM 13. Enclosure TE 14. Cycles 60 15. Phase 3 16. Service Factor 1.25 17. Motor Mount Position F1 Initial Inspection 18. Number of Leads 9 19. Lead Length 12 Inchese 20. Lead Size 10 21. Lead Condition (P) Pass 22. Lead Markings Printed leads 23. Lug Size, Condition, and Type None (NA) Not Applicable 24. Winding RTD's (NA) Not Applicable 25. Winding Rtd's Condition 9 26. Shaft Run Out 0.0005 27. Does Shaft Turn Freely yes 28. Does Shaft Rure Visible Damage no 29. Bearing Rtd's (NA) Not Applicable	3.	Customer	SAGE	
5. Model G29316 6. Serial Number 20 7. Horsepower 20 8. KW 230460 9. Volts 230460 10. Amps 230460 11. RPM 230460 12. Frame 256JM 13. Enclosure 1770 14. Cycles 60 15. Phase 3 16. Service Factor 1.25 17. Motor Mount Position F1 Initial Inspection 1 18. Number of Leads 9 20. Lead Size 10 21. Lead Condition, and Type 10 None 0.0005 22. Lead Markings Printed leads 23. Lug Size, Condition, and Type yes None 0.0005 24. Winding RTD's (NA) Not Applicable 25. Winding Rtd's Condition 9 26. Shaft Run Out 0.0005 27. Does Shaft Tum Freely yes 28. Does Shaft Run Visible Damage no 29. Bearing Rtd's (NA) Not Applicable	Name	Plate Information		Ο
6. Serial Number 20 7. Horsepower 20 8. KW 230460 9. Volts 230460 10. Amps 230460 49.0024.50 11770 11. RPM 17770 12. Frame 256JM 13. Enclosure TE 14. Cycles 60 15. Phase 3 16. Service Factor 1.25 17. Motor Mount Position F1 Initial Inspection 18. Number of Leads 9 19. Lead Length 12 Inches 20. Lead Size 10 21. Lead Condition (P) Pass 22. Lead Markings Printed leads 23. Lug Size, Condition, and Type None 24. Winding RTD's (NA) Not Applicable 25. Winding RTD's 0.0005 27. Does Shaft Run Out 0.0005 27. Does Shaft Tum Freely yes 28. Does Shaft Tum Visible Damage no 29. Bearing Rtd's (NA) Not Applicable	4.	Manufacturer	US	P5
7. Horsepower 20 8. KW 230460 9. Volts 230460 10. Amps 230460 • 49.00/24.50 1770 11. RPM 1770 12. Frame 256JM 13. Enclosure TE 14. Cycles 60 15. Phase 3 16. Service Factor 1.25 17. Motor Mount Position F1 Initial Inspection 1 18. Number of Leads 9 19. Lead Length 12 Inches 20. Lead Size 10 • 21. Lead Condition (P) Pass 22. Lead Markings Printed leads 23. Lug Size, Condition, and Type None 24. Winding RTD's (NA) Not Applicable 25. Winding RTD's 0.0005 27. Does Shaft Run Out 0.0005 27. Does Shaft Turn Freely yes 28. Does Shaft Ruro Visible Damage no 29. Bearing Rtd's (NA) Not Applicable	5.	Model	G29316	
8. KW 9. Voits 230460 10. Amps 49.0024.50 11. RPM 1770 12. Frame 256JM 13. Enclosure TE 14. Cycles 60 15. Phase 3 16. Service Factor 1.25 17. Motor Mount Position F1 Initial Inspection 0 0 18. Number of Leads 9 P13 19. Lead Length 12 Inches 0 20. Lead Size 10 0 21. Lead Condition (P) Pass 0 22. Lead Markings Printed leads 0 23. Lug Size, Condition, and Type None 0 24. Winding Rtd's Condition 0.00005 0 25. Shaft Run Out 0.00005 0 26. Shaft Run Out 0.00005 0 27. Does Shaft Turn Freely yes 0 28. Does Shaft Have Visible	6.	Serial Number		
9. Volts 230460 10. Amps 49.00/24.50 11. RPM 1770 12. Frame 256JM 13. Enclosure TE 14. Cycles 60 15. Phase 3 16. Service Factor 1.25 17. Motor Mount Position F1 Initial Inspection 1 18. Number of Leads 9 20. Lead Length 12 Inches 20. Lead Size 10 21. Lead Condition (P) Pass 22. Lead Markings Printed leads 23. Lug Size, Condition, and Type None (NA) Not Applicable 24. Winding Rtd's Condition 0.0005 27. Does Shaft Turn Freely yes 28. Does Shaft Have Visible Damage no 29. Bearing Rtd's (NA) Not Applicable	7.	Horsepower	20	
10. Amps 49.00/24.50 11. RPM 1770 12. Frame 256JM 13. Enclosure TE 14. Cycles 60 15. Phase 3 16. Service Factor 1.25 17. Motor Mount Position F1 Initial Inspection 0 18. Number of Leads 9 19. Lead Length 12 Inches 20. Lead Size 10 21. Lead Condition (P) Pass 22. Lead Markings Printed leads 23. Lug Size, Condition, and Type None 24. Winding RtD's (NA) Not Applicable 25. Winding Rtd's Condition 20. 26. Shaft Run Out 0.0005 27. Does Shaft Turn Freely yes 28. Does Shaft Have Visible Damage no 29. Bearing Rtd's (NA) Not Applicable	8.	KW		
49.0024.50 11. RPM 1770 12. Frame 256JM 13. Enclosure TE 14. Cycles 60 15. Phase 3 16. Service Factor 1.25 17. Motor Mount Position F1 Initial Inspection 60 18. Number of Leads 9 20. Lead Length 12 Inches 20. Lead Size 10 21. Lead Condition (P) Pass 22. Lead Markings Printed leads 23. Lug Size, Condition, and Type None (NA) Not Applicable 24. Winding RTD's (NA) Not Applicable 25. Winding Rtd's Condition 9 26. Shaft Run Out 0.0005 27. Dees Shaft Turn Freely yes 28. Does Shaft Have Visible Damage no 29. Bearing Rtd's (NA) Not Applicable	9.	Volts	230460	
11. RPM 1770 12. Frame 256JM 13. Enclosure TE 14. Cycles 60 15. Phase 3 16. Service Factor 1.25 17. Motor Mount Position F1 Initial Inspection 18. Number of Leads 9 19. Lead Length 12 Inches 20. Lead Size 10 21. Lead Condition (P) Pass 22. Lead Markings Printed leads 23. Lug Size, Condition, and Type None None 0.00005 23. Winding RTD's (NA) Not Applicable 24. Winding RTD's 0.00005 27. Does Shaft Turn Freely yes 28. Does Shaft Turn Freely yes 28. Does Shaft Have Visible Damage no 29. Bearing Rtd's (NA) Not Applicable	10.	Amps		
12. Frame 256JM 13. Enclosure TE 14. Cycles 60 15. Phase 3 16. Service Factor 1.25 17. Motor Mount Position F1 Initial Inspection 18. Number of Leads 9 19. Lead Length 12 Inches 20. Lead Size 10 21. Lead Condition (P) Pass 22. Lead Markings Printed leads 23. Lug Size, Condition, and Type None (NA) Not Applicable 24. Winding RTD's (NA) Not Applicable 25. Winding Rtd's Condition 2 26. Shaft Run Out 0.00005 27. Does Shaft Turn Freely yes 28. Does Shaft Have Visible Damage no 29. Bearing Rtd's (NA) Not Applicable		49.00/24.50		
13. Enclosure TE 14. Cycles 60 15. Phase 3 16. Service Factor 1.25 17. Motor Mount Position F1 Initial Inspection 18. Number of Leads 9 19. Lead Length 12 Inches 20. Lead Size 10 21. Lead Condition (P) Pass 22. Lead Markings Printed leads 23. Lug Size, Condition, and Type None (NA) Not Applicable 24. Winding RTD's (NA) Not Applicable 25. Winding Rtd's Condition 2 26. Shaft Run Out 0.00005 27. Does Shaft Turn Freely yes 28. Does Shaft Have Visible Damage no 29. Bearing Rtd's (NA) Not Applicable	11.	RPM	1770	
14.Cycles6015.Phase316.Service Factor1.2517.Motor Mount PositionF1Initial InspectionImitial Inspection18.Number of Leads919.Lead Length12 Inches20.Lead Size1021.Lead Condition(P) Pass22.Lead MarkingsPrinted leads23.Lug Size, Condition, and Type None(NA) Not Applicable24.Winding RTD's(NA) Not Applicable25.Winding RtD's0.000527.Does Shaft Turn Freely Seasyes28.Does Shaft Turn Freelyyes29.Bearing Rtd's(NA) Not Applicable	12.	Frame	256JM	
15. Phase 3 16. Service Factor 1.25 17. Motor Mount Position F1 Initial Inspection 18. Number of Leads 9 19. Lead Length 12 Inches 20. Lead Size 10 21. Lead Condition (P) Pass 22. Lead Markings Printed leads 23. Lug Size, Condition, and Type None 24. Winding RTD's (NA) Not Applicable 25. Winding RtD's Condition 0.0005 27. Does Shaft Turn Freely yes 28. Does Shaft Have Visible Damage no 29. Bearing Rtd's (NA) Not Applicable	13.	Enclosure	TE	
16. Service Factor 1.25 17. Motor Mount Position F1 Initial Inspection 18. Number of Leads 9 19. Lead Length 12 Inches 20. Lead Size 10 21. Lead Condition (P) Pass 22. Lead Markings Printed leads 23. Lug Size, Condition, and Type None 24. Winding RTD's (NA) Not Applicable 25. Winding Rtd's Condition 0.0005 27. Does Shaft Turn Freely yes 28. Does Shaft Have Visible Damage no 29. Bearing Rtd's (NA) Not Applicable	14.	Cycles	60	
17. Motor Mount Position F1 Initial Inspection Imitial Inspection 18. Number of Leads 9 19. Lead Length 12 Inches 20. Lead Size 10 21. Lead Condition (P) Pass 22. Lead Markings Printed leads 23. Lug Size, Condition, and Type None 24. Winding RTD's (NA) Not Applicable 25. Winding Rtd's Condition 0.0005 27. Does Shaft Run Out 0.0005 27. Does Shaft Turn Freely yes 28. Does Shaft Have Visible Damage no 29. Bearing Rtd's (NA) Not Applicable	15.	Phase	3	
Initial InspectionImage: Constraint of LeadsPis18. Number of Leads9Pis19. Lead Length12 Inches20. Lead Size1021. Lead Condition(P) Pass22. Lead MarkingsPrinted leads23. Lug Size, Condition, and Type None(NA) Not Applicable24. Winding RTD's(NA) Not Applicable25. Winding Rtd's Condition0.000526. Shaft Run Out0.000527. Does Shaft Turn Freelyyes28. Does Shaft Have Visible Damageno29. Bearing Rtd's(NA) Not Applicable	16.	Service Factor	1.25	
18.Number of Leads9P1319.Lead Length12 Inches20.Lead Size1021.Lead Condition(P) Pass22.Lead MarkingsPrinted leads23.Lug Size, Condition, and Type None(NA) Not Applicable24.Winding RTD's(NA) Not Applicable25.Winding RtD's Condition0.000526.Shaft Run Out0.000527.Does Shaft Turn Freelyyes28.Does Shaft Have Visible Damageno29.Bearing Rtd's(NA) Not Applicable	17.	Motor Mount Position	F1	
19. Lead Length12 Inches20. Lead Size1021. Lead Condition(P) Pass22. Lead MarkingsPrinted leads23. Lug Size, Condition, and Type None(NA) Not Applicable24. Winding RTD's(NA) Not Applicable25. Winding RtD's Condition0.000526. Shaft Run Out0.000527. Does Shaft Turn Freelyyes28. Does Shaft Have Visible Damageno29. Bearing Rtd's(NA) Not Applicable	Initial	Inspection		Ο
20. Lead Size1021. Lead Condition(P) Pass22. Lead MarkingsPrinted leads23. Lug Size, Condition, and Type None(NA) Not Applicable24. Winding RTD's(NA) Not Applicable25. Winding Rtd's Condition0.000526. Shaft Run Out0.000527. Does Shaft Turn Freelyyes28. Does Shaft Have Visible Damageno29. Bearing Rtd's(NA) Not Applicable	18.	Number of Leads	9	P13
 21. Lead Condition (P) Pass (P) Pass 22. Lead Markings Printed leads 23. Lug Size, Condition, and Type None (NA) Not Applicable 24. Winding RTD's (NA) Not Applicable 25. Winding Rtd's Condition 26. Shaft Run Out 0.0005 27. Does Shaft Turn Freely yes 28. Does Shaft Have Visible Damage no 29. Bearing Rtd's (NA) Not Applicable 	19.	Lead Length	12 Inches	
22. Lead MarkingsPrinted leads23. Lug Size, Condition, and Type None(NA) Not Applicable24. Winding RTD's(NA) Not Applicable25. Winding Rtd's Condition0.000526. Shaft Run Out0.000527. Does Shaft Turn Freelyyes28. Does Shaft Have Visible Damageno29. Bearing Rtd's(NA) Not Applicable	20.	Lead Size	10	
23. Lug Size, Condition, and Type None 24. Winding RTD's (NA) Not Applicable 25. Winding Rtd's Condition 26. Shaft Run Out 0.0005 27. Does Shaft Turn Freely yes 28. Does Shaft Have Visible Damage no 29. Bearing Rtd's (NA) Not Applicable	21.	Lead Condition	(P) Pass	
None24.Winding RTD's(NA) Not Applicable25.Winding Rtd's Condition26.Shaft Run Out0.000527.Does Shaft Turn Freelyyes28.Does Shaft Have Visible Damageno29.Bearing Rtd's(NA) Not Applicable	22.	Lead Markings	Printed leads	
24. Winding RTD's(NA) Not Applicable25. Winding Rtd's Condition0.000526. Shaft Run Out0.000527. Does Shaft Turn Freelyyes28. Does Shaft Have Visible Damageno29. Bearing Rtd's(NA) Not Applicable	23.	Lug Size, Condition, and Type		
25. Winding Rtd's Condition26. Shaft Run Out0.000527. Does Shaft Turn Freelyyes28. Does Shaft Have Visible Damageno29. Bearing Rtd's(NA) Not Applicable		None		
26.Shaft Run Out0.000527.Does Shaft Turn Freelyyes28.Does Shaft Have Visible Damageno29.Bearing Rtd's(NA) Not Applicable	24.	Winding RTD's	(NA) Not Applicable	
27. Does Shaft Turn Freelyyes28. Does Shaft Have Visible Damageno29. Bearing Rtd's(NA) Not Applicable	25.	Winding Rtd's Condition		
28. Does Shaft Have Visible Damage no 29. Bearing Rtd's (NA) Not Applicable	26.	Shaft Run Out	0.0005	
29. Bearing Rtd's (NA) Not Applicable	27.	Does Shaft Turn Freely	yes	
29. Bearing Rtd's (NA) Not Applicable	28.	Does Shaft Have Visible Damage	no	
30. Bearing Rtd's Condition	29.	Bearing Rtd's	(NA) Not Applicable	
	30.	Bearing Rtd's Condition		

	0.4			
	31.	Contamination None		
	22	Frame Condition	(P) Pass	
		Fan Condition	(P) Pass (P) Pass	
		Broken or missing components	(г) газз	
	54.	Fan cover damaged		
In	itial	Electric Test		
		Resistance to Ground	Mohm	D Pž
		Winding Resistance 1-2	WORM	
		Winding Resistance 2-3		
		Winding Resistance 1-3		
		Resistive Imbalance		
		Hi-Pot		
		Surge Test	(P) Pass	
		Stator Condition	good	
		Failure Location	good	
In				
		Rotor Inspection Rotor Type	cast aluminum	
		Air Gap <10% Variation	Cast auminum	
		Number of Rotor Bars	40	
		Number of Roken Rotor Bars		
		Growler Test	•	
		Rotor Condition	(P) Pass (P) Pass	
			(г) газэ	
IVI		anical Inspection	Deve	о Р'
		Bearing Manufacture	Peer	Р
		Bearing DE Size	6310ZZ	
		Bearing DE Type	Deep groove ball	
		DE Bearing Qty.	1	
		Bearing ODE Size	6207ZZ	
		Bearing ODE Type	Deep Groove ball	
		ODE Bearing Qty.		
	57.	Insulated Bearing	- ·	
		Lubrication Type	Polyrex	
•	59.	Grease Condition	(P) Pass	
	60.	Bearing Retainers	00 M.	
	61.	Shaft Grounding Device	(Y) Yes	
	•	Aegis 193836	00 M.	
	62.	DE Seal	(Y) Yes	
	63.	DE Seal Type/Size	1 1/2 * 2 1/8 CAR/CER Mechanical	
	64.	ODE Seal		
	65.			
R		Cause of Failure		
	66.			
		Cause of Failure		
	5	Mechanical seal failure		
	68	Comments		
	00.	oommonto		

Machi	ine Fit Inspection Report		Ο
	Shaft Run Out		
71.	Initial Shaft Run Out		
72.	Final Shaft Run Out		
73.	DE Bearing Shaft Fit		P39
74.	DE Initial Shaft Bearing Fit Size 1	1.969 "	
75.	DE Initial Shaft Bearing Fit Size 2	1.969 "	
76.	DE Initial Shaft Bearing Fit Size 3	1.969 "	
77.	DE Finial Shaft Bearing Fit Size 1		
78.	DE Finial Shaft Bearing Fit Size 2		
79.	DE Finial Shaft Bearing Fit Size 3		
80.	ODE Bearing Shaft Fit	(P) Pass	P93
81.	ODE Initial Shaft Bearing Fit Size 1	1.3785 "	
82.	ODE Initial Shaft Bearing Fit Size 2	1.3784 "	
83.	ODE Initial Shaft Bearing Fit Size 3	1.3783 "	
84.	ODE Finial Shaft Bearing Fit Size 1		
85.	ODE Finial Shaft Bearing Fit Size 2		
86.	ODE Finial Shaft Bearing Fit Size 3		
87.	DE Air Seal Shaft Fit		
88.	DE Initial Air Seal Shaft Size		
89.	DE Final Air Seal Shaft Size		
90.	ODE Air Seal Shaft Fit		
91.	ODE Initial Air Seal Shaft Size		
92.	ODE Final Air Seal Shaft Size		
93.	DE Endbell Fit	(P) Pass	
94.	DE Initial Endbell Fit Size 1	4.3308 "	
95.	DE Initial Endbell Fit Size 2	4.3307 "	
96.	DE Initial Endbell Fit Size 3	4.3309 "	
97.	DE Final Endbell Fit Size 1		
98.	DE Finial Endbell Fit Size 2		
	DE Final Endbell Fit Size 3		
	DE Endbell Fit Insulated		
	DE Endbell Air Seal Fit		
-	Initial Endbell Air Seal Fit Size		
	Finial Endbell Air Seal Fit Size		
	ODE Endbell Fit	(P) Pass	
	ODE Initial Endbell Fit Size 1	2.8348 "	
	ODE Initial Endbell Fit Size 2	2.8348 "	
-	ODE Initial Endbell Fit Size 3	2.8349 "	
	ODE Final Endbell Fit Size 1		
	ODE Final Endbell Fit Size 2		
-	ODE Final Endbell Fit Size 3		
	ODE Endbell Fit Insulated		
	ODE Endbell Air Seal Fit		
-	ODE Initial Endbell Seal Fit Size		
114.	ODE Finial Endbell Seal Fit Size		

1115. Foot Condition 116. Foot Condition 117. Flange Condition 118. Service Technician Balancing Report 120. Balance Type 120. Balance Operating Speed 121. Start Left End 122. Start Right End 123. Balancing Specification 124. Finish Laft End 125. Finish Right End 126. Service Technician Assembly and Final Test 127. Meggar Testing Reading 128. Surgice Technician Assembly and Final Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 1-2 132. Winding Resistance 1-2 133. Test Run Voltage Phase A 134. Test Run Amps A 135. Test Run Voltage Phase A 136. Test Run Voltage Phase A 137. Test Run Voltage Phase G 138. DE Vertical Vibration Reading 144. ODE Vertical Vibration Reading 145. DE Vertical Vibration Reading 146. DE Vertical Vibration Reading 147. Temp at 10 minutes 148. Temp at 25 minutes 149. DE Vertical Vibration Reading 141. DE Kavial Vibration Reading </th
117. Flange Condition 118. Service Technician Balancing Report 119. Balance Type 120. Balance Operating Speed 121. Start Left End 122. Start Right End 123. Balancing Specification 124. Finish Left End 125. Finish Right End 126. Service Technician Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Po 130. Winding Resistance 1-2 131. Winding Resistance 1-3 132. Winding Resistance 1-3 133. Test Run Voltage Phase A 134. Test Run Amps A 135. Test Run Voltage Phase C 138. Test Run Voltage Phase C 139. De Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. De Kaial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Vertical Vibration Reading 145. Temp at 15 minutes 146. Temp at 15 minutes 147. Temp at 10 minutes 148. Temp at 15 minutes 149. Temp at 20 minutes 140. Temp at 20 minutes
118. Service Technician Balancing Report 119. Balance Type 120. Balance Operating Speed 121. Start Left End 122. Start Right End 123. Balancing Specification 124. Finish Left End 125. Finish Right End 126. Service Technician Assembly and Final Test 127. Meggar Testing Reading 128. Surge Testing Reading 128. Winding Resistance 1-2 131. Winding Resistance 2-3 132. Winding Resistance 2-3 133. Test Run Voltage Phase A 134. Test Run Voltage Phase A 135. Test Run Voltage Phase B 136. Test Run Amps B 137. Test Run Amps C 138. DE Vertical Vibration Reading 144. DD E Vertical Vibration Reading 144. DD E Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Amber Term at start of Test Run 146. Temp at Sminutes 147. Temp at 30 minutes 148. Temp at 35 minutes 149. DE Axial Vibration Reading 144. ODE Axial Vibration Reading 145. Amber Temp at at start of Test Run 146. Temp at 30 minutes
Balancing Report 119. Balance Type 120. Balance Operating Speed 121. Start Left End 122. Start Right End 123. Balancing Specification 124. Finish Left End 125. Finish Right End 126. Service Technician Assembly and Final Test 127. Meggar Testing Reading 128. Hirbert Net Start S
119. Balance Type 120. Balance Operating Speed 121. Start Left End 122. Start Right End 123. Balancing Specification 124. Finish Right End 125. Finish Right End 126. Service Technician Assembly and Final Test 127. Meggar Testing Reading 128. Hink Hoft 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3 132. Winding Resistance 1-3 133. Test Run Voltage Phase A 134. Test Run Amps A 135. Test Run Voltage Phase B 136. Test Run Voltage Phase C 137. Test Run Voltage Phase C 138. Test Run Voltage Phase C 139. DE Horizontal Vibration Reading 140. DE Varical Vibration Reading 141. DE Xaid Vibration Reading 142. ODE Horizontal Vibration Reading 143. DE Varical Vibration Reading 144. ODE Varical Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at Sminutes 147. Temp at 30 minutes 148. Temp at 15 minutes 149. Temp at 30 minutes 141. DE Varid Vibration Reading
120. Balance Operating Speed 121. Start Left End 122. Start Right End 123. Balancing Specification 124. Finish Left End 125. Finish Right End 126. Service Technician Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 1-3 132. Winding Resistance 1-3 133. Winding Resistance 1-3 134. Test Run Voltage Phase A 135. Test Run Voltage Phase A 136. Test Run Amps A 137. Test Run Voltage Phase B 138. Test Run Voltage Phase C 138. Test Run Voltage Phase C 138. Test Run Voltage Phase C 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Avial Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Avial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 11 minutes 149. Temp at 20 minutes
121. Start Left End 122. Start Right End 123. Balancing Specification 124. Finish Left End 125. Finish Right End 126. Service Technician Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3 132. Winding Resistance 2-3 133. Test Run Voltage Phase A 134. Test Run Voltage Phase A 135. Test Run Voltage Phase A 136. Test Run Voltage Phase B 137. Test Run Voltage Phase C 138. Del Horizontal Voration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 25 minutes 149. Temp at 35 minutes 141. Temp at 35 minutes 142. ODE Horizontal Vibration Reading 143. DE Axial Vibration Reading 144. ODE Axial Vibration Reading 145. Temp at 5 minutes
122. Start Right End 123. Balancing Specification 124. Finish Right End 125. Finish Right End 126. Service Technician Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 1-2 133. Test Run Voltage Phase A 134. Test Run Voltage Phase A 135. Test Run Voltage Phase B 136. Test Run Maps A 137. Test Run Voltage Phase C 138. Test Run Voltage Phase C 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Avial Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 0 minutes 148. Temp at 25 minutes 149. Temp at 30 minutes 141. Temp at 30 minutes 142. Temp at 45 minutes 143. ODE Avial Vibration Reading 144. Temp at 16 minutes 145. Temp at 30 minutes <t< th=""></t<>
123. Balancing Specification 124. Finish Left End 125. Finish Right End 126. Service Technician Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 1-3 132. Winding Resistance 1-3 133. Test Run Voltage Phase A 134. Test Run Voltage Phase B 135. Test Run Voltage Phase C 136. Test Run Voltage Phase C 137. Test Run Voltage Phase C 138. Test Run Voltage Phase C 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Xaial Vibration Reading 145. Test Run Pat 15 minutes 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Term pat 20 minutes 149. Temp at 20 minutes 140. DE Varial Vibration Reading 141. Temp at 10 minutes 142. ODE Taxial Vibration Reading 144. Temp at 15 minutes 145. Temp at 20 minutes
124. Finish Left End 125. Finish Right End 126. Service Technician Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3 132. Winding Resistance 1-3 133. Test Run Voltage Phase A 134. Test Run Voltage Phase A 135. Test Run Voltage Phase B 136. Test Run Amps A 137. Test Run Voltage Phase C 138. Test Run Voltage Phase B 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Kaiki Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Avial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 2 minutes 147. Term at 10 minutes 148. Temp at 20 minutes 149. Temp at 20 minutes 150. Temp at 30 minutes 151. Temp at 30 minutes 152. Temp at 30 minutes 153. Temp at 40 minutes 154. Temp at 55 minutes 155. Temp at 60 minutes
125. Finish Right End 126. Service Technician Assembly and Final Test 127. Megaz Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3 132. Winding Resistance 1-3 133. Test Run Yoltage Phase A 134. Test Run Amps A 135. Test Run Voltage Phase B 136. Test Run Aups A 137. Test Run Aups A 138. Test Run Aups B 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Vertical Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Ambient Temp at start of Test Run 147. Temp at 10 minutes 148. Temp at 20 minutes 149. Temp at 20 minutes 150. Temp at 20 minutes 151. Term pat 40 minutes 152. Temp at 35 minutes 153. Term pat 40 minutes 154. Temp at 40 minutes 155. Temp at 50 minutes 156. Temp at 50 minutes 156. Temp a
128. Service Technician Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 1-3 132. Winding Resistance 1-3 133. Test Run Voltage Phase A 134. Test Run Amps A 135. Test Run Voltage Phase B 136. Test Run Amps A 137. Test Run Voltage Phase C 138. Test Run Amps C 139. DE Horizontal Vibration Reading 140. DE Verical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Verical Vibration Reading 144. ODE Avial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 20 minutes 149. Temp at 30 minutes 150. Temp at 35 minutes 151. Temp at 40 minutes 152. Temp at 35 minutes 153. Temp at 40 minutes 154. Temp at 40 minutes 155. Temp at 40 minutes 156. Temp at 55 minutes 156. Temp at 50 minutes
Assembly and Final Test 127. Meggar Testing Reading 128. Surge Test 129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3 132. Winding Resistance 1-3 133. Test Run Voltage Phase A 134. Test Run Amps A 135. Test Run Amps A 136. Test Run Amps B 137. Test Run Amps B 138. Test Run Amps C 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. DE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 20 minutes 149. Temp at 20 minutes 150. Temp at 30 minutes 152. Temp at 35 minutes 153. Temp at 40 minutes 154. Temp at 40 minutes 155. Temp at 45 minutes 156. Temp at 55 minutes 157. Temp at 60 minutes
127. Meggar Testing Reading128. Surge Test129. Hi-Pot130. Winding Resistance 1-2131. Winding Resistance 2-3132. Winding Resistance 1-3133. Test Run Voltage Phase A134. Test Run Voltage Phase B135. Test Run Voltage Phase B136. Test Run Voltage Phase C137. Test Run Voltage Phase C138. Test Run Voltage Phase C139. DE Horizontal Vibration Reading140. DE Vertical Vibration Reading141. DE Axial Vibration Reading142. ODE Horizontal Vibration Reading144. ODE Vertical Vibration Reading145. Ambient Temp at start of Test Run146. Temp at 5 minutes147. Temp at 10 minutes148. Temp at 15 minutes150. Temp at 36 minutes151. Temp at 40 minutes155. Temp at 45 minutes156. Temp at 56 minutes157. Temp at 60 minutes
128. Surge Test129. Hi-Pot130. Winding Resistance 1-2131. Winding Resistance 2-3132. Winding Resistance 1-3133. Test Run Voltage Phase A134. Test Run Amps A135. Test Run Voltage Phase B136. Test Run Voltage Phase C138. Test Run Voltage Phase C139. DE Horizontal Vibration Reading140. DE Vertical Vibration Reading141. DE Axial Vibration Reading142. ODE Horizontal Vibration Reading144. ODE Vertical Vibration Reading145. Ambient Temp at star for the standing146. Temp at 5 minutes147. Temp at 10 minutes148. Temp at 15 minutes151. Temp at 30 minutes152. Temp at 35 minutes153. Temp at 40 minutes154. Temp at 45 minutes155. Temp at 45 minutes156. Temp at 55 minutes157. Temp at 60 minutes156. Temp at 55 minutes
129. Hi-Pot 130. Winding Resistance 1-2 131. Winding Resistance 2-3 132. Winding Resistance 1-3 133. Test Run Voltage Phase A 134. Test Run Amps A 135. Test Run Voltage Phase B 136. Test Run Amps B 137. Test Run Voltage Phase C 138. Test Run Amps C 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 10 minutes 147. Temp at 10 minutes 148. Temp at 20 minutes 149. Temp at 20 minutes 150. Temp at 35 minutes 151. Temp at 36 minutes 152. Temp at 36 minutes 153. Temp at 40 minutes 154. Temp at 40 minutes 155. Temp at 50 minutes 156. Temp at 50 minutes 156. Temp at 50 minutes 156. Temp at 60 minutes 156. Temp at 60 minutes
130. Winding Resistance 1-2131. Winding Resistance 2-3132. Winding Resistance 1-3133. Test Run Voltage Phase A134. Test Run Amps A135. Test Run Voltage Phase B136. Test Run Voltage Phase C137. Test Run Voltage Phase C138. Test Run Voltage Phase C139. DE Horizontal Vibration Reading140. DE Vertical Vibration Reading141. DE Axial Vibration Reading142. ODE Horizontal Vibration Reading144. ODE Vertical Vibration Reading145. Ambient Temp at start of Test Run146. Temp at 5 minutes147. Temp at 10 minutes148. Temp at 20 minutes150. Temp at 23 minutes151. Temp at 30 minutes152. Temp at 40 minutes153. Temp at 40 minutes154. Temp at 40 minutes155. Temp at 40 minutes155. Temp at 50 minutes156. Temp at 50 minutes157. Temp at 60 minutes
131. Winding Resistance 2-3132. Winding Resistance 1-3133. Test Run Voltage Phase A134. Test Run Amps A135. Test Run Voltage Phase B136. Test Run Amps B137. Test Run Voltage Phase C138. Test Run Amps C139. DE Horizontal Vibration Reading140. DE Vertical Vibration Reading141. DE Axial Vibration Reading142. ODE Horizontal Vibration Reading144. ODE Vertical Vibration Reading145. Ambient Temp at start of Test Run146. Temp at 5 minutes147. Temp at 10 minutes148. Temp at 20 minutes150. Temp at 25 minutes151. Temp at 30 minutes152. Temp at 35 minutes153. Temp at 46 minutes154. Temp at 46 minutes155. Temp at 55 minutes156. Temp at 55 minutes157. Temp at 60 minutes
132. Winding Resistance 1-3133. Test Run Voltage Phase A134. Test Run Amps A135. Test Run Voltage Phase B136. Test Run Amps B137. Test Run Voltage Phase C138. Test Run Voltage Phase C139. DE Horizontal Vibration Reading140. DE Vertical Vibration Reading141. DE Axial Vibration Reading142. ODE Horizontal Vibration Reading144. ODE Vertical Vibration Reading145. Ambient Temp at start of Test Run146. Temp at 5 minutes147. Temp at 10 minutes148. Temp at 20 minutes150. Temp at 25 minutes151. Temp at 30 minutes152. Temp at 35 minutes153. Temp at 46 minutes154. Temp at 55 minutes155. Temp at 55 minutes156. Temp at 55 minutes157. Temp at 60 minutes
133. Test Run Voltage Phase A134. Test Run Amps A135. Test Run Voltage Phase B136. Test Run Amps B137. Test Run Voltage Phase C138. Test Run Amps C139. DE Horizontal Vibration Reading140. DE Vertical Vibration Reading141. DE Axial Vibration Reading142. ODE Horizontal Vibration Reading144. ODE Axial Vibration Reading145. Ambient Temp at start of Test Run146. Temp at 3 minutes147. Temp at 10 minutes148. Temp at 15 minutes150. Temp at 35 minutes151. Temp at 30 minutes152. Temp at 30 minutes153. Temp at 40 minutes154. Temp at 45 minutes155. Temp at 55 minutes156. Temp at 55 minutes157. Temp at 60 minutes
134. Test Run Amps A135. Test Run Voltage Phase B136. Test Run Amps B137. Test Run Voltage Phase C138. Test Run Amps C139. DE Horizontal Vibration Reading140. DE Vertical Vibration Reading141. DE Axial Vibration Reading142. ODE Horizontal Vibration Reading143. ODE Vertical Vibration Reading144. ODE Axial Vibration Reading145. Ambient Temp at start of Test Run146. Temp at S minutes147. Temp at 10 minutes148. Temp at 15 minutes150. Temp at 35 minutes151. Temp at 30 minutes152. Temp at 35 minutes153. Temp at 46 minutes154. Temp at 46 minutes155. Temp at 55 minutes156. Temp at 55 minutes157. Temp at 60 minutes
135. Test Run Voltage Phase B136. Test Run Amps B137. Test Run Voltage Phase C138. Test Run Amps C139. DE Horizontal Vibration Reading140. DE Vertical Vibration Reading141. DE Axial Vibration Reading142. ODE Horizontal Vibration Reading143. ODE Vertical Vibration Reading144. ODE Axial Vibration Reading145. Ambient Temp at start of Test Run146. Temp at 5 minutes147. Temp at 10 minutes148. Temp at 20 minutes150. Temp at 20 minutes151. Temp at 30 minutes152. Temp at 35 minutes153. Temp at 40 minutes154. Temp at 50 minutes155. Temp at 50 minutes156. Temp at 55 minutes157. Temp at 60 minutes
136. Test Run Amps B137. Test Run Voltage Phase C138. Test Run Amps C139. DE Horizontal Vibration Reading140. DE Vertical Vibration Reading141. DE Axial Vibration Reading142. ODE Horizontal Vibration Reading143. ODE Vertical Vibration Reading144. ODE Axial Vibration Reading145. Ambient Temp at start of Test Run146. Temp at 5 minutes147. Temp at 10 minutes148. Temp at 20 minutes150. Temp at 25 minutes151. Temp at 35 minutes152. Temp at 40 minutes153. Temp at 40 minutes154. Temp at 50 minutes155. Temp at 50 minutes156. Temp at 50 minutes157. Temp at 60 minutes
 137. Test Run Voltage Phase C 138. Test Run Amps C 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 20 minutes 150. Temp at 25 minutes 151. Temp at 30 minutes 152. Temp at 40 minutes 153. Temp at 50 minutes 154. Temp at 50 minutes 155. Temp at 50 minutes 156. Temp at 50 minutes 157. Temp at 60 minutes
138. Test Run Amps C139. DE Horizontal Vibration Reading140. DE Vertical Vibration Reading141. DE Axial Vibration Reading142. ODE Horizontal Vibration Reading143. ODE Vertical Vibration Reading144. ODE Axial Vibration Reading145. Ambient Temp at start of Test Run146. Temp at 5 minutes147. Temp at 10 minutes148. Temp at 15 minutes149. Temp at 20 minutes150. Temp at 35 minutes151. Temp at 30 minutes152. Temp at 40 minutes153. Temp at 40 minutes154. Temp at 50 minutes155. Temp at 50 minutes156. Temp at 50 minutes157. Temp at 60 minutes
 139. DE Horizontal Vibration Reading 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 15 minutes 149. Temp at 20 minutes 150. Temp at 25 minutes 151. Temp at 30 minutes 152. Temp at 35 minutes 153. Temp at 40 minutes 154. Temp at 50 minutes 155. Temp at 50 minutes 156. Temp at 55 minutes 157. Temp at 60 minutes
 140. DE Vertical Vibration Reading 141. DE Axial Vibration Reading 142. ODE Horizontal Vibration Reading 143. ODE Vertical Vibration Reading 144. ODE Axial Vibration Reading 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 15 minutes 149. Temp at 20 minutes 150. Temp at 25 minutes 151. Temp at 30 minutes 152. Temp at 35 minutes 153. Temp at 40 minutes 154. Temp at 45 minutes 155. Temp at 50 minutes 156. Temp at 50 minutes 157. Temp at 60 minutes
141. DE Axial Vibration Reading142. ODE Horizontal Vibration Reading143. ODE Vertical Vibration Reading144. ODE Axial Vibration Reading145. Ambient Temp at start of Test Run146. Temp at 5 minutes147. Temp at 10 minutes148. Temp at 15 minutes149. Temp at 20 minutes150. Temp at 25 minutes151. Temp at 30 minutes152. Temp at 35 minutes153. Temp at 40 minutes154. Temp at 45 minutes155. Temp at 50 minutes156. Temp at 55 minutes157. Temp at 60 minutes
142. ODE Horizontal Vibration Reading143. ODE Vertical Vibration Reading144. ODE Axial Vibration Reading145. Ambient Temp at start of Test Run146. Temp at 5 minutes147. Temp at 10 minutes148. Temp at 15 minutes149. Temp at 20 minutes150. Temp at 25 minutes151. Temp at 30 minutes152. Temp at 35 minutes153. Temp at 40 minutes154. Temp at 55 minutes155. Temp at 50 minutes156. Temp at 55 minutes157. Temp at 60 minutes
143. ODE Vertical Vibration Reading144. ODE Axial Vibration Reading145. Ambient Temp at start of Test Run146. Temp at 5 minutes147. Temp at 10 minutes148. Temp at 15 minutes148. Temp at 20 minutes150. Temp at 20 minutes151. Temp at 30 minutes152. Temp at 35 minutes153. Temp at 40 minutes154. Temp at 50 minutes155. Temp at 50 minutes157. Temp at 50 minutes
144. ODE Axial Vibration Reading145. Ambient Temp at start of Test Run146. Temp at 5 minutes147. Temp at 10 minutes148. Temp at 15 minutes149. Temp at 20 minutes150. Temp at 20 minutes151. Temp at 30 minutes152. Temp at 35 minutes153. Temp at 40 minutes154. Temp at 45 minutes155. Temp at 50 minutes156. Temp at 50 minutes157. Temp at 60 minutes
 145. Ambient Temp at start of Test Run 146. Temp at 5 minutes 147. Temp at 10 minutes 148. Temp at 15 minutes 149. Temp at 20 minutes 149. Temp at 20 minutes 150. Temp at 25 minutes 151. Temp at 30 minutes 152. Temp at 35 minutes 153. Temp at 40 minutes 154. Temp at 45 minutes 155. Temp at 50 minutes 156. Temp at 55 minutes 157. Temp at 60 minutes
146. Temp at 5 minutes147. Temp at 10 minutes148. Temp at 15 minutes149. Temp at 20 minutes150. Temp at 25 minutes151. Temp at 30 minutes152. Temp at 35 minutes153. Temp at 40 minutes154. Temp at 45 minutes155. Temp at 50 minutes156. Temp at 55 minutes157. Temp at 60 minutes
147. Temp at 10 minutes148. Temp at 15 minutes149. Temp at 20 minutes150. Temp at 25 minutes151. Temp at 30 minutes152. Temp at 35 minutes153. Temp at 40 minutes154. Temp at 45 minutes155. Temp at 50 minutes156. Temp at 55 minutes157. Temp at 60 minutes
148. Temp at 15 minutes149. Temp at 20 minutes150. Temp at 25 minutes151. Temp at 30 minutes152. Temp at 35 minutes153. Temp at 40 minutes154. Temp at 45 minutes155. Temp at 50 minutes156. Temp at 55 minutes157. Temp at 60 minutes
 149. Temp at 20 minutes 150. Temp at 25 minutes 151. Temp at 30 minutes 152. Temp at 35 minutes 153. Temp at 40 minutes 154. Temp at 45 minutes 155. Temp at 50 minutes 156. Temp at 55 minutes 157. Temp at 60 minutes
 150. Temp at 25 minutes 151. Temp at 30 minutes 152. Temp at 35 minutes 153. Temp at 40 minutes 154. Temp at 45 minutes 155. Temp at 50 minutes 156. Temp at 55 minutes 157. Temp at 60 minutes
 151. Temp at 30 minutes 152. Temp at 35 minutes 153. Temp at 40 minutes 154. Temp at 45 minutes 155. Temp at 50 minutes 156. Temp at 55 minutes 157. Temp at 60 minutes
 152. Temp at 35 minutes 153. Temp at 40 minutes 154. Temp at 45 minutes 155. Temp at 50 minutes 156. Temp at 55 minutes 157. Temp at 60 minutes
 153. Temp at 40 minutes 154. Temp at 45 minutes 155. Temp at 50 minutes 156. Temp at 55 minutes 157. Temp at 60 minutes
 154. Temp at 45 minutes 155. Temp at 50 minutes 156. Temp at 55 minutes 157. Temp at 60 minutes
155. Temp at 50 minutes156. Temp at 55 minutes157. Temp at 60 minutes
156. Temp at 55 minutes 157. Temp at 60 minutes
157. Temp at 60 minutes
158. Motor Paint

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

159. Service Technician





P5.2



P5.3



P5.4



P5.8



P5.12





P9.16

Hi-Speed Industrial Service disclaims all warranties, both express and implied, relating to the information, reports, opinions and analysis disclosed to the Customer by Hi-Speed. Hi-Speed shall not be liable for any errors or omissions, or any losses, injury or damages arising from the use of such information, reports, opinions and analysis by the Customer.

Printed on 10/26/2020







P9.15

Powered by INSPECTALL

1.4



P5.9

P7.13







P5.6



















P39.20

P9.17

P9.18



P39.21

P93.22



P93.23

P13.19



STANDARD TERMS AND CONDITIONS FOR PURCHASE OF GOOD AND/OR SERVICES

- 1. <u>APPLICABILITY.</u> The sale of any and all goods and/or services by Mock, Inc. d/b/a Hi-Speed Industrial Service ("Hi-Speed") shall be specifically conditioned upon and subject to the following terms and conditions which are incorporated by reference into any contracts and purchase orders with Hi-Speed, and which shall form and become a part of any agreement related thereto. Buyer's acceptance of any offer or quotation made by Hi-Speed for sale of any goods or services is expressly made subject to the terms and conditions set forth herein and to be so effective, Buyer need not sign or approve these Terms and Conditions to be bound hereunder provided a copy of same is provided to Buyer through any means. None of the terms and conditions contained herein may be added to, expanded, changed, modified, superseded or otherwise altered except as revised in writing and duly executed by Hi-Speed, and all orders received by Hi-Speed shall be governed only by the terms and conditions contained herein, notwithstanding any terms, conditions or provisions of any purchase order, release order, authorization or any other form issued by the Buyer. Hi-Speed hereby objects to any additional, modified, changed, deleted, altered or other terms and conditions not contained herein and notifies Buyer that any such terms or provisions are expressly rejected by Hi-Speed.
- 2. PRICE. All quoted prices shall remain firm and binding for a period of thirty (30) days from the date of quotation or for the period specifically stated in the quotation. The price for any and all goods and/or services ordered or approved by Buyer after thirty (30) days from the date of any quotation are subject to any increase in price that may occur after the expiration of thirty (30) days from the issuance of the quotation and the date the Buyer releases any shipment.
- 3. <u>SCOPE OF GOODS AND/OR SERVICES.</u> The goods and/or services provided by Hi-Speed pursuant to any quotation shall be limited exclusively to those goods and/or services expressly identified therein. Hi-Speed does not assume any responsibility and/or liability for the failure to provide any other goods and/or services not identified in any quotation. Modifications, additions or deletions to or from the scope referenced in any quotation shall only be effective if evidenced in writing and signed by Hi-Speed. The sale of any of all goods and/or services affected by such modification, addition or deletion shall be subject to these same Standard Terms and Conditions whether or not referenced therein.
- 4. <u>BILLING AND PAYMENT TERMS.</u> Hi-Speed shall invoice Buyer for all goods and/or services as same are rendered at the address listed on the quotation. Payments for all goods and/or services shall be due thirty (30) days from the date of the current invoice or as otherwise set forth in the quotation. Late payments are subject to a late fee of 5% of the total invoice amount. Recurring late payments may lead to a deposit requirement on future services or sale of goods. Buyer shall be liable to Hi-Speed for any and all fees and expenses incurred by Hi-Speed to collect any invoices or to enforce these Standard Terms and Conditions, including but not limited to, attorney's fees.
- 5. DELIVERY OF GOODS AND/OR SERVICES. Unless otherwise identified in the quotation, all shipments are F.O.B. Hi-Speed's warehouse and the title to and all risk of loss with respect to any goods shipped shall pass to Buyer when such goods are delivered to the carrier at Hi-Speed's warehouse. Hi-Speed will use its best efforts to affect delivery by the date or dates specified in the quotation. However, Hi-Speed shall not be liable for delay in or failure to make shipment, or to perform services, by any identified date for any reason whatsoever, including but not limited to, causes beyond its reasonable control, such as strikes, fires, floods, epidemics, quarantines, restrictions, severe weather, embargos, acts of God, or public enemy, war, riot, delays in transportation or the inability to obtain necessary labor, materials or manufacturing facilities.
- 6. DELIVERY SITE AND TIME FOR PERFORMANCE. Hi-Speed and Buver agree that time is of the essence for the purchase order and that Buyer shall fully cooperate with Hi-Speed in order to allow Hi-Speed full access to prosecute its work diligently and in an orderly manner. Buyer shall assist Hi-Speed in every way possible to avoid delaying, disrupting or interfering with the progress of Hi-Speed's work at the project site. In the event Hi-Speed's work is delayed, hindered, suspended, disrupted, re-sequenced or interfered with or rendered less efficient or more costly or adversely affected in any way as a result of acts or omissions of Buyer or other contractors or employees of Buyer or by any other reason beyond Hi-Speed's control and without the fault of Hi-Speed, then, in such event, Buyer shall be liable to Hi-Speed for any damages, additional costs, expenses, labor, materials, man hours, acceleration costs, overtime, additional jobsite overhead, extended home office overhead, and any and all other direct and indirect expenses of whatsoever nature or kind, caused in whole or in part, as a result of any of the above-referenced occurrences. Hi-Speed's project records will be the basis for computing the additional costs and damages of Hi-Speed's labor, materials, expenses and overhead related to such changes. BUYER WARRANTS THAT THE SITE FOR DELIVERY OR INSTALLATION OF ANY GOODS AND/OR FOR THE PERFORMANCE OF ANY SERVICES SHALL BE READY AND ADEQUATE FOR HI-SPEED'S DELIVERY OF GOODS AND/OR PERFORMANCE OF SERVICES AND THAT HI-SPEED SHALL HAVE FULL ACCESS THERETO, FREE OF ALL OBSTRUCTIONS. BUYER SHALL ASSUME ALL EXTRA COSTS ASSOCIATED WITH HI-SPEED'S INABILITY TO INSTALL ANY GOODS OR PERFORM ANY SERVICES AS A RESULT OF BUYER'S FAILURE TO COMPLY WITH THIS PROVISION. HI-SPEED MAY NOT INSPECT THE SITE PRIOR TO DELIVERY AND/OR INSTALLATION OF GOODS AND/OR PERFORMANCE OF SERVICES AND MAKES NO WARRANTY AS TO THE SUFFICIENCY OF THE SITE FOR THE DELIVERY AND/OR INSTALLATION OF GOODS AND/OR THE PERFORMANCE OF SERVICES AT SUCH SITE.
- 7. INSPECTION/ACCEPTANCE. All goods and services ordered pursuant to any quotation shall be subject to inspection by Buyer after delivery or performance to determine conformity with the quotation and/or purchase order and Hi-Speed's advertised or published specifications. Buyer shall have a period of thirty (30) days from shipment of goods at the delivery destination specified in the quotation within which to inspect the goods for conformity with the quotation, order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. Buyer shall have a period of thirty (30) days following completion of any services within which to inspect the services for conformity with the quotation, purchase order and/or Hi-Speed's advertised and published specifications and to provide Hi-Speed with written notice of any discrepancy or rejection. If the goods delivered or services performed do not so conform, upon delivery of notice to Hi-Speed of any discrepancy, nonconformance or rejection, Hi-Speed shall have the right to reject such goods or services. After the cure period, goods that have been delivered and rejected, in whole or in part, shall be returned to Hi-Speed shall, at its sole cost, re-perform the non-conforming services. Inspection or failure to inspect on any occasion shall not affect Buyer's rights under the warranty provisions herein.
- 8. WARRANTIES. Hi-Speed warrants that all goods shall conform in all material aspects to the goods identified in the quotation to Buyer and/or purchase order, and Hi-Speed makes to Buyer the manufacturer's express warranty for any goods sold to Buyer, which is offered by the manufacturer at the time of acceptance of any quotation by Buyer. This warranty is conditioned upon the installation, operation, and maintenance of the goods in accordance with the manufacturer's recommendations and/or standard industry practice and the goods at all times being operated or used under normal operating conditions for which they were designed. Hi-Speed, at its sole option, will repair or

TermsAndConditions

replace any defective or non-conforming goods in accordance with the applicable manufacturer's warranty. Warranty for any defective or incorrect parts is limited to the repair or replacement of those parts. Hi-Speed warrants that all services will conform in all material respects to the description of services identified in the quotation and will be performed in a good and workmanlike manner in accordance with industry practices and standards. Should the services be reasonably rejected or not conform with the foregoing warranties, Hi-Speed shall, at its sole cost, re-perform the defective or nonconforming services. Notwithstanding the foregoing, these warranties do not extend to goods or services to the extent that such goods have been subject to misuse, neglect or abuse not caused by Hi-Speed or have been used in violation of the approved written instructions furnished to Buyer. THE FOREGOING REPRESENTS THE SOLE AND EXCLUSIVE WARRANTY GIVEN BY HI-SPEED WITH RESPECT TO ALL GOODS SOLD AND IS IN LIEU OF ALL OTHER WARRANTIES EITHER EXPRESS OR IMPLIED. HI-SPEED EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICLAR USE OR PURPOSE. BUYER WAIVES ANY CLAIM THAT THESE EXCLUSIONS OR LIMITATIONS DEPRIVE IT OF AN ADEQUATE REMEDY AT EQUITY OR LAW OR CAUSE THIS AGREEMENT TO FAIL IN ITS ESSENTIAL PURPOSE. BUYER SHALL BE ENTITLED TO NO OTHER REMEDY OTHER THAN AS SET FORTH HEREIN, REGARDLESS OF THE CLAIM OR CAUSE OF ACTION, WHETHER BASED IN CONTRACT, TORT, NEGLIGENCE, GOODS LIABILITY, STRICT LIABILITY OR OTHERWISE.

- 9. LIMITATION OF DAMAGES. HI-SPEED SHALL HAVE NO LIABILITY TO BUYER WITH RESPECT TO THE SALE OR DELIVERY OF ANY GOODS OR THE REPAIR THEREOF OR WITH RESPECT TO THE SALE OR PERFORMANCE OF ANY SERVICES, FOR LOST PROFITS, SPECIAL, CONSEQUENTIAL, EXEMPLARY, PUNITIVE OR INCIDENTAL DAMAGES OF ANY KIND OR NATURE WHETHER ARISING IN CONTRACT, TORT, GOODS LIABILITY OR OTHERWISE, EVEN IF HI-SPEED WAS ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGES. HI-SPEED SHALL NOT BE LIABLE FOR ANY DAMAGES OR DELAYS CAUSED BY ANY FAILURE TO MAKE ANY DELIVERY OF GOODS BY ANY EXPECTED TIME OR DATE OR THE FAILURE TO PROVIDE OR COMPLETE ANY SERVICES BY ANY EXPECTED DATE OR TIME. IN NO EVENT SHALL HI-SPEED BE LIABLE TO BUYER FOR ANY DAMAGES WHATSOEVER IN EXCESS OF THE TOTAL PRICE PAID FOR ALL GOODS AND/OR SERVICES HEREUNDER OR REFERENCED IN ANY QUOTATION OR THE PURCHASE ORDER.
- 10. <u>SEVERABILITY</u>. The partial or complete invalidity of any provision of these Standard Terms and Conditions shall not affect the enforceability of the remainder of these Standard Terms and Conditions. If any provision is found to be invalid or unenforceable, that portion shall be modified to make it enforceable or shall be stricken and the remainder of these Standard Terms and Conditions shall enforced.
- 11. <u>GOVERNING LAW AND JURISDICTION.</u> Any controversy arising out of any quotation, the purchase order, the goods sold or delivered, repair or replacement thereof, or any services provided pursuant to any quotation or any purchase order, or these Standard Terms and Conditions shall be governed by the laws of the state of Tennessee without regard to any choice of law provisions and any cause of action related in any manner thereto shall be brought only in the state or federal courts of Shelby County, Tennessee.
- 12. <u>ABANDONED EQUIPMENT.</u> Hi-Speed requires that Buyer promptly pick up or provide shipment instructions for Buyer equipment or other Buyer property in Hi-Speed's possession. If equipment or other Buyer property is left with Hi-Speed and not picked up within six (6) months after Hi-Speed's final action related to the applicable property (e.g. evaluation, teardown, estimate, completion of services), Hi-Speed will consider such property abandoned and may dispose of it in accordance with applicable law. Buyer agrees to hold Hi-Speed harmless for any damage or claim for such abandoned property and acknowledges that Hi-Speed may discard or recycle it at Hi-Speed's sole and absolute discretion. Specifically, Hi-Speed may sell Buyer's abandoned property at a private or public sale and retain the proceeds to offset Hi-Speed's storage, inspection and servicing costs. For the avoidance of doubt, Hi-Speed reserves its statutory and other lawful liens for unpaid charges related to abandoned property.
- 13. FORCE MAJEURE. Neither party shall be responsible for any delay or failure in performance of any party of the quotation, purchase order or these Standard Terms and Conditions to the extent that such delays or failures are caused by fire, flood, earth quake, explosion, war, embargo, government requirement, civil or military authority, acts of God, or any other circumstances beyond its reasonable control and not involving any fault or negligence on the party affected ("Condition"). If any such Condition occurs, the party delayed or unable to perform shall promptly give written notice to the other party and, if such Condition remains at the end of thirty (30) days, the party affected by the other party's delay and inability to perform may elect to (i) terminate such order or part thereof, or (ii) suspend the order for the duration of the Condition, if the Buyer is the suspending party, buy elsewhere comparable material to be sold under the order and apply to any commitment the purchase price of such purchase, and resume performance of the order once the Condition ceases, with an option in the affected party to extend the period of this order up to the length of the time the Condition endures.
- 14. <u>NONWAIVER</u>. No course of dealing or failure of either party to strictly enforce any term, right, or condition of these Standard Terms and Conditions will be construed as a waiver of such term, right or condition. Any waiver by Hi-Speed will only be in writing and will waive no succeeding breach of a term, right or condition.
- 15. <u>ASSIGNMENT.</u> The rights and obligations of the parties shall neither be assigned nor delegated without the prior written consent of the other party. However, any party may assign or delegate its respective rights and obligations, in whole or in part, (i) to any subsidiary, (ii) pursuant to other financing, merger or reorganization or (iii) pursuant to any sale or transfer of substantially all of the assets of the assigning party. These Standard Terms and Conditions shall bind the heirs, successors and assigns of the parties hereto.
- 16. <u>NO INDIVIDUAL LIABILITY</u>. Notwithstanding any other agreement to the contrary, the Buyer agrees that in no event will the Buyer hold and HI-Speed owner, director, officer or employee personally liable for unintentional tortious conduct or conduct that constitutes the breach of any contract between HI-Speed and the Buyer, even if the HI-Speed owner, director, officer or employee is or could be construed to be a party to such contract.